

Package ‘ffaframework’

June 6, 2025

Title Flood Frequency Analysis Framework
Version 0.1.0
Author Riley Wheadon [aut, cre]
Maintainer Riley Wheadon <rileywheadon@gmail.com>
Description Tools for exploratory data analysis and flood frequency analysis using L-moments, statistical tests, and model assessment. Implements several methods for distribution selection, trend detection, and uncertainty quantification.
License CC BY 4.0
Encoding UTF-8
LazyData true
Imports lmom,
parallel,
stats,
graphics,
utils,
ggplot2,
aTSA,
randtests
Suggests testthat,
covr
Roxygen list(markdown = TRUE)
RoxygenNote 7.3.2

Contents

mk.test	1
Index	3

mk.test	<i>Mann–Kendall Test for Monotonic Trends</i>
---------	---

Description

Performs the Mann–Kendall trend test on a numeric vector to detect the presence of a monotonic trend (increasing or decreasing) over time. The test is non-parametric and accounts for tied observations in the data.

Usage

```
mk.test(data, alpha = 0.05, quiet = TRUE)
```

Arguments

<code>data</code>	A numeric vector of AMS values or their variances. Must not contain NA values.
<code>alpha</code>	A numeric value specifying the significance level (default is 0.05).
<code>quiet</code>	Logical. If FALSE, prints a summary of the test result to the console.

Details

The statistic (S) is computed as the sum over all pairs $(i < j)$ of the sign of the difference $(x_j - x_i)$. Ties are explicitly accounted for when calculating the variance of (S) , using grouped frequencies of tied observations.

The test statistic (Z) is then computed based on the sign and magnitude of (S) , and the p-value is derived from the standard normal distribution.

Value

A named list with the following components:

s.statistic The raw Mann–Kendall test statistic (S) .

s.variance The variance of the test statistic under the null hypothesis.

p.value The p-value associated with the two-sided hypothesis test.

reject Logical. TRUE if the null hypothesis of no trend is rejected at `alpha`.

See Also

[bbmk_test](#) for a bootstrap-based variant of this test.

Index

`bbmk_test`, [2](#)

`mk.test`, [1](#)