Answers to the exercise #3 on Computer Networks

Christian Rinderknecht

11 April 2008

Question. Design a protocol to be used between an automatic teller machine (ATM) and a bank's centralised computer. Your protocol should allow a user's card and password to be verified, the account balance (which is maintained at the bank) to be queried, and an account withdrawal to be made (money is given to the customer). 1. Specify your protocol by listing the messages exchanged and the action taken by the ATM or the bank's centralised computer on transmission or receipt of each message:

From ATM to Bank				
Message name and arguments	Meaning/Action			

From Bank to ATM				
Message name and arguments	Meaning/Action			

2. Sketch the operation of your protocol, using a diagram, for the cases of a simple withdrawal (a) with no errors, (b) with one error.

Answer. One example is as follows.

Messages from ATM to server:

Message name	Purpose
HELO <userid></userid>	Let server know that there is a card
	in the ATM, then transmits user ID
	to server
PASSWD <passwd></passwd>	User enters PIN, which is sent
	to server
BALANCE	User requests balance
${\rm WITHDRAWAL} < {\rm amount} >$	User asks to withdraw money
BYE	User all done

Messages from server to ATM (display):

Message name	Purpose	
PASSWD	Ask user for PIN (password)	
OK	Last requested operation	
	(PASSWD, WITHDRAWAL) OK	
ERR	Last requested operation	
	(PASSWD, WITHDRAWAL)	
	resulted in error	
AMOUNT <amount></amount>	Sent in response to BALANCE request	
BYE	User done, display welcome	
	screen at ATM	

A correct withdrawal looks like this:

HELO <userid></userid>	>	(Check if valid userid)
	<	PASSWD
PASSWD <passwd></passwd>	>	(Check password)
	<	OK (password is OK)
BALANCE	>	
	<	AMOUNT <amount></amount>
WITHDRAWAL <amount></amount>	>	(Check if enough money)
	<	OK
ATM dispenses money		
BYE	>	
	<	BYE