RING: A Relativistic Incremental Network Gradient

A field-theoretic protocol for timer-free routing and liveness

Abstract

We present RING, a routing and liveness protocol in which every node maintains, for each destination, two scalar fields obtained by purely local asynchronous relaxation of its neighbours' values. The first is a **routing potential** f solving a screened-Poisson equation $(\mathcal{L}_g + Q)f = 0$ pinned at the destination; packets are forwarded up its gradient. The second is a **vitality** $V \in [0, 1]$ measuring confidence that the destination is live; it is transported from the source and aged by the proper time its evidence has spent in flight.

Grounding the routing operator in M-matrix theory makes loop-freedom, black-hole-freedom, and convergence (synchronous and chaotic-asynchronous) structural consequences of the discrete maximum principle and contraction, rather than topology-specific inductions. For liveness, the reciprocal substitution $U = 1/V$ linearizes the nonlinear retarded-max update into the min-plus Bellman/eikonal equation $U_i = \min_j\big(U_j + \alpha\tau_{ij}\big)$, whose solution $U_i = 1 + \alpha T_i$ (T_i the least accumulated transit time) gives the closed form $V_i = 1/(1 + \alpha T_i)$. This makes the light cone exact — confidence is the reciprocal of one plus causal distance — and turns the count-to-infinity pathology of distance-vector protocols into a feature: with no source, U diverges and V fades smoothly to zero, so a dead destination garbage-collects itself with no sequence numbers, tombstones, or hold-down timers.

Congestion enters the *same* operator as a spatially-varying screening charge, so it reshapes the field without weakening any guarantee — and because the fields are exact, the load–charge loop is itself an exact map, which we prove globally ring-free under a loop-gain condition by a Lyapunov argument matched to the integrator. On the fabric both fields are *exact* discrete objects — a linear M-matrix solve and a min-plus shortest path — computed by local asynchronous iteration with classical convergence; the elliptic screened-Poisson and the eikonal Hamilton–Jacobi equations are their *shared continuum limits* (Appendix B), not the equations the network solves.

We give the full proofs and validate every theorem on an asynchronous reference implementation — the $V(\delta)$ droop, clock-free robustness under skew, the necessity of retardation, graceful count-to-infinity against a textbook distance-vector baseline, data-plane delivery through node death and partition, loop-dissipativity under churn, and congestion damping with its stability basin.

1 Introduction

Routing and liveness in asynchronous packet networks are traditionally built from discrete control machinery: distance-vector metrics, sequence numbers, tombstones, hold-down timers, split-horizon and poison-reverse rules, and separate heartbeat-based failure detectors. This machinery is both brittle and pathological. Distance-vector routing's *count-to-infinity* — a stale metric circulating upward without bound after a failure — is the canonical example; the standard remedies (sequence

numbers, feasibility conditions, diffusing computations) add state and protocol phases precisely to suppress a divergence the underlying algebra invites.

A second, quieter problem is the conflation of *space* and *time*. A liveness signal that is "distance-invariant" — asserting full confidence in a source regardless of how many hops away it is — looks attractive, because it decouples reachability from failure detection. But it is a violation of causality. Information advances at most one hop per tick, so a node δ hops from a source cannot hold evidence of that source's life fresher than δ ticks old. Full confidence at any distance is therefore *overconfidence by construction*: it is achieved only by discarding the age of the evidence, and it pays for that optimism with detection latency — the node keeps routing into a corpse for the duration of the propagation delay.

RING resolves both by treating routing and liveness as two scalar **fields** governed by the same local, monotone iterative dynamics, and reading their guarantees off the underlying mathematics rather than off topology-specific arguments. Both fields are *exact* discrete objects on the fabric; the partial differential equations we name below — elliptic screened-Poisson, eikonal Hamilton–Jacobi — are their shared continuum limits, formalized and scoped in Appendix B, not the equations the network solves.

- **Direction** is the gradient of a *screened potential* f — the exact solution of a discrete M-matrix system (continuum limit: the elliptic screened-Poisson equation) whose only maxima are the pinned destinations (the discrete maximum principle), so greedy up-gradient forwarding cannot loop or black-hole, for any topology and any reach. The field is bounded by its source pin, so there is no count-to-infinity to suppress.
- **Confidence** is a *retarded vitality field* V aged by proper time. Its reciprocal $U = 1/V$ is the exact solution of the min-plus Bellman / discrete-eikonal equation (continuum limit: the eikonal PDE), so $V_i = 1/(1 + \alpha T_i)$ where T_i is the least accumulated transit time from the source. Confidence droops with causal distance — not as a defect but as the honest posterior the light cone allows — and a vanished source makes U diverge and V fade monotonically to zero.

Congestion is not a third mechanism: a loaded node raises a local *screening charge*, the same diagonal term that sets reach, so traffic routes around it while every routing guarantee is preserved.

The result is a substrate with no timers, sequence numbers, tombstones, or hold-down states — a fabric bent by load and aged by proper time, carrying packets down the steepest gradient.

2 Contributions

1. **A two-field formulation** in which routing and liveness are two *exact* discrete operators — a linear screened M-matrix solve and a min-plus shortest path — solved by local asynchronous iteration; routing guarantees reduce to the M-matrix maximum principle and contraction (§5), and the elliptic screened-Poisson and eikonal partial differential equations are their continuum limits (Appendix B), not the operative equations.

2. **Liveness as a retarded discrete-eikonal field** (§6): the reciprocal transform $U = 1/V$ is an *exact* linearization — over the $(\min, +)$ tropical semiring shortest-path is linear — carrying the nonlinear retarded-max transport into the min-plus Bellman / Hamilton–Jacobi equation, with closed form $V_i = 1/(1 + \alpha T_i)$. The light cone is exact on the graph (the proper-time ball); the continuum eikonal is its limit (Appendix B).

3. **Count-to-infinity as garbage collection**: because the data plane reads $V = 1/U$, the unbounded divergence of a sourceless Bellman iteration becomes the graceful fade of a dead destination — no sequence numbers or tombstones (§6.4, §9).

4. **A necessity theorem for retardation** (Theorem 6.2): without aging incoming evidence by its transit, mutual exchange admits a spurious self-sustaining fixed point (a "resurrected" dead source); retardation removes it, giving a thermodynamic arrow that forbids liveness without a live source.

5. **Eventual non-trapping under chaotic asynchrony** (Theorem 5.7): transient forwarding cycles are confined to equilibrium level sets where the gradient current is vanishing, and the dominant current evacuates them — safe not only at rest but while churning.

6. **Congestion as a screening charge, provably stable** (§5.7–§5.8): load enters the same operator as a spatially-varying diagonal, compatible with every guarantee because they hold for any $q_i \geq \kappa > 0$; and the exact load–charge loop is globally ring-free under a loop-gain condition (Theorem 5.9), via a cubic Lyapunov matched to the non-overshoot integrator — replacing an empirical stability claim with a proof.

7. **Space-time horizon alignment** (§8): tuning the aging rate so the temporal horizon matches the spatial reach makes per-node state self-bounding, $O\big(n \cdot \mathrm{Vol}(\lambda)\big)$.

8. **Empirical validation** on an asynchronous reference implementation (§9), as ensembles over reps: the measured $V(\delta)$ droop, clock-free skew-robustness, the retardation lock and its cure, graceful count-to-infinity against a textbook distance-vector baseline, data-plane delivery through node death and partition, loop-dissipativity under churn, and congestion damping with its stability basin.

3 Related work

RING assembles its two fields from established components; the contribution is their coupling, not their parts, and we scope novelty accordingly.

Potential and field-based routing. Forwarding up the gradient of a scalar potential is mature. Basu, Lin, and Ramanathan (2003) assign nodes scalar potentials, forward along the steepest gradient, prove the family loop-free, recover shortest paths as a special case, and fold traffic into the potential to route around congestion; Toumpis and Tassiulas (2005) cast dense-network flow as a continuum electrostatics problem; Xu et al. (2013) compose depth, delay, and load into one potential field; Intanagonwiwat et al. (2003) set up per-node gradients toward sinks. RING is not first to route on a potential gradient, nor to encode congestion in the field. Its delta is the operator and its rigor: the bare Laplacian/electrostatic Poisson equation becomes a *screened-Poisson* operator $(\mathcal{L}_g + Q)$ whose charge $q = \kappa + \mu$ makes it a strict M-matrix — a strict (not weak) maximum

principle, a unique bounded fixed point, an asynchronous contraction — and congestion is the *same* screening term μ rather than a separately composed potential. Embedding routing (Kleinberg 2007; Sarkar et al. 2009) reaches guaranteed greedy delivery by a different mechanism — a curved-space embedding — which RING avoids by working on the native graph.

Screened-Poisson, M-matrices, and the maximum principle. RING's loop- and black-hole-freedom are the discrete maximum principle for a diagonally-dominant M-matrix, classical in numerical linear algebra (Varga 1962, 1966; Berman and Plemmons 1994). The field-secreted-at-a-source framing descends from morphogenesis (Turing 1952; Wolpert 1969; Crick 1970), and diffusion load balancing (Cybenko 1989) is the nearest networking use of a graph-diffusion operator for resource flow. RING inherits this correctness machinery; its extension is the *spatially-varying* screening charge as a congestion absorber.

Asynchronous iterative computation. Both fields converge by classical async-relaxation theory, not new analysis: the routing potential is a sup-norm contraction (Chazan and Miranker 1969; Baudet 1978; Bertsekas 1983; Frommer and Szyld 2000), and the vitality reciprocal is an asynchronous distributed shortest-path / dynamic-programming computation (Bertsekas 1982; Tsitsiklis et al. 1986; Bertsekas and Tsitsiklis 1989). RING contributes none of this machinery; correctness rests entirely on it.

Distance-vector loop-freedom. This is RING's most direct prior art. Distributed Bellman–Ford (Bellman 1958; Bertsekas and Gallager 1992) suffers count-to-infinity, and the classical cures are destination-minted sequence numbers (DSDV, Perkins and Bhagwat 1994; Babel, Chroboczek and Schinazi 2021), feasibility conditions and diffusing computations (Jaffe and Moss 1982; Cheng et al. 1989; Garcia-Luna- Aceves 1993), and link-reversal / height DAGs (Gafni and Bertsekas 1981; Park and Corson 1997). RING departs *structurally*: routing is a screened-Poisson field, not an additive min-plus metric, so there is no count-to-infinity to suppress and thus no sequence numbers, feasibility bookkeeping, tombstones, or hold-down. The honest caveat: RING does not escape distance-vector mathematics — it *relocates* the min-plus Bellman recurrence from routing to the liveness axis, where slow propagation is a feature (causal droop) rather than the bug it is for an additive routing metric.

Eikonal, Hamilton–Jacobi–Bellman, and min-plus algebra. RING's vitality reciprocal $U = 1/V$ satisfies the discrete stationary eikonal / HJB equation $U_i = \min_j(U_j + \alpha\tau_{ij})$, whose single-pass solutions are fast marching (Sethian 1996) and Tsitsiklis (1995), and whose weak theory is viscosity solutions (Crandall and Lions 1983). Its additive-under-min structure is the $(\min, +)$ tropical semiring, the dequantization of ordinary linear superposition (Litvinov 2005). The reciprocal $V = 1/(1+\alpha T)$ is a linearizing change of variable in the exact spirit of the Cole–Hopf transform (Hopf 1950; Cole 1951), which we cite as analogy, not as a new device. RING's contribution here is architectural — running this eikonal relaxation continuously and asynchronously as a timer-free liveness oracle — not the underlying mathematics.

Distributed failure detection. RING's liveness sits in the accrual lineage: like the φ-accrual detector (Hayashibara et al. 2004; Satzger et al. 2007) it outputs a continuous confidence rather than the binary suspicion of Chandra–Toueg detectors (Chandra and Toueg 1996; Chen et al. 2002), and like SWIM (Das et al. 2002) and Lifeguard (Dadgar et al. 2018) it pushes the failure *decision* to the caller as a threshold. But accrual confidence is computed locally from a node's own heartbeat statistics; RING's vitality is *transported across the topology* and droops with causal distance, so remote confidence is a function of light-cone distance, not local history — with no per-node timer,

sequence number, or tombstone. Timeout-free heartbeat detection (Aguilera et al. 1997) and gossip dissemination of membership (Demers et al. 1987; van Renesse et al. 1998) are credited as the lineage; RING's defensible delta is the coupling of a transported liveness field to a co-located routing potential, with causality-honest distance-droop as the detection signal.

4 Network model and notation

symbol	meaning
$G = (V, E)$	the network graph; $N(i)$ = the bidirectionally-confirmed neighbours of i
$g_{ij} > 0$	conductance of edge $\{i, j\}$, symmetric ($g_{ij} = g_{ji}$); uniform value D
$G_i = \sum_{j \in N(i)} g_{ij}$	total conductance incident on i
$\kappa > 0$	baseline screening (sets reach)
$\mu_i \geq 0$	local screening from load at i; the screening charge is $q_i = \kappa + \mu_i$
$s_i \geq 0$	carried current at i (its self-measured load): $\sum_d \max_{j \in N(i)} g_{ij}(f_j^d - f_i^d)$, the up-gradient flux it forwards, summed over destinations (§5.7)
$c \geq 0$	congestion coupling (crowding rate): the charge tracks $c\, s_i$; $c = 0$ disables congestion (§5.7–§5.8)
$r > 0$	glide rate of the non-overshoot integrator reg (§5.7)
$F_0 > 0$	the potential a destination pins for its own field
$f_i^d \geq 0$	routing potential at i toward d
$V_i^d \in [0, 1]$	vitality (liveness confidence) at i toward d
$\alpha > 0$	vitality aging rate
$\varphi \in (0, 1)$	vitality threshold for action
$\tau_{ij} \geq 1$	transit time (in ticks) of the edge $i \to j$; one tick is one relaxation period

Adjacency by echo. $j \in N(i)$ only if i hears j *and* j's advertisement names i. A one-way link carries no flow and contributes nothing to $\mathcal{L}_g$.

The weighted Laplacian. For $x : V \to \mathbb{R}$, $(\mathcal{L}_g x)_i = \sum_{j \in N(i)} g_{ij}(x_i - x_j) = G_i x_i - \sum_j g_{ij} x_j$. $\mathcal{L}_g$ is symmetric positive-semidefinite with the constant vector in its kernel. Adding the diagonal $Q = \mathrm{diag}(q_i) \succ 0$ (since $q_i \geq \kappa > 0$) makes $\mathcal{L}_g + Q$ symmetric, **strictly diagonally dominant** (row i has diagonal $G_i + q_i$ against off-diagonal mass G_i), with non-positive off-diagonals — a symmetric M-matrix, hence positive-definite and inverse-positive (Berman and Plemmons 1994; Varga 1962). This is the single structural fact the routing proofs use.

Figure provenance. Figures are tagged by how they were produced and the two are never blurred. [EXACT] figures are direct solves of the discrete operator — the field the math *defines*, computed with no iteration or simulation. [MEASURED] figures are ensembles from the asynchronous reference implementation (§7.1) — each node on its own cadence, no global round or shared clock — reported as a median with a 10–90% inter-rep band over R independent reps; this is what the protocol *delivers*.




Figure 1: [EXACT] A direct solve of the screened operator $(\mathcal{L}_g + Q)f = 0$ on an irregular graph. Two pinned destinations raise two attracting basins with a watershed between them; a loaded sink (large μ, locally short reach) bends the steepest-ascent streamlines around itself. This is the per-destination field the operator *defines* — the object each node's relaxation (5.1) converges to.

5 The routing field (space)

5.1 The screened balance

Each non-destination node relaxes its potential to the conductance-weighted mean of its neighbours, attenuated by the screening charge:

$$f_i^d \longleftarrow \frac{\sum_{j\in N(i)} g_{ij}\, f_j^d}{G_i + q_i}, \qquad q_i = \kappa + \mu_i. \tag{5.1}$$

The destination pins $f_d^d = F_0$ and does not relax its own field. Clearing the denominator gives the operator form $(\mathcal{L}_g f^d)_i + q_i f_i^d = 0$. Each destination's field is independent and linear; a node maintains one scalar relaxation per known destination over a shared neighbour table.

Non-negativity. The pin is $F_0 > 0$ and (5.1) is a non-negative combination; the inverse-positive operator (§4) gives $f_i^{d\star} > 0$ for every node in d's connected component. Operational reach is where that positive field remains above a floor, not a hard hop count.

5.2 The screening charge and reach

$q_i = \kappa + \mu_i$ is one quantity with two contributions: κ is the uniform floor that sets global reach; $\mu_i \geq 0$ is the extra local screening a node carries under load (§5.8). Every result in §5 is proved for an arbitrary charge field $q_i \geq \kappa > 0$, so congestion is the same operator at a larger diagonal,

never a special case. On a homogeneous chain ($q_i = \kappa$, $g_{ij} = D$) a geometric mode $f_i = \rho^i$ satisfies $\rho + \rho^{-1} = 2 + \kappa/D$; the decaying root gives reach $\lambda = -1/\ln\rho \approx \sqrt{D/\kappa}$ for $\kappa/D \ll 1$ — the screening length of $D\nabla^2 f - \kappa f = 0$. Reach is a length, not a hop ceiling; a loaded node has locally shorter reach $\sqrt{D/(\kappa+\mu_i)}$.

5.3 Convergence

Write (5.1) as $f \leftarrow Mf$ with $M_{ij} = g_{ij}/(G_i + q_i)$ for $j \in N(i)$, $M_{ii} = 0$ (the pin is a fixed boundary term).

Lemma 5.1 (contraction). $\|M\|_\infty \le \gamma < 1$, where $\gamma = \max_i G_i/(G_i+q_i) \le \max_i G_i/(G_i+\kappa) < 1$. *Proof.* Each row is non-negative with sum $G_i/(G_i+q_i) = 1 - q_i/(G_i+q_i) < 1$ since $q_i \ge \kappa > 0$. ■

Theorem 5.2 (fixed point). The field equation has a unique solution $f^{d\star}$, and synchronous relaxation converges geometrically, $\|f^{(k)} - f^{d\star}\|_\infty \le \gamma^k \|f^{(0)} - f^{d\star}\|_\infty$. *Proof.* M is an $\|\cdot\|_\infty$-contraction (Lemma 5.1); apply the Banach fixed-point theorem. ■

Theorem 5.3 (asynchronous convergence). For a fixed charge field q, under any schedule in which every node relaxes infinitely often using possibly-stale neighbour values (bounded delay), the iteration converges to $f^{d\star}$. *Proof.* $M \ge 0$ entrywise, so $\rho(M) \le \|M\|_\infty = \gamma < 1$; the Chazan–Miranker theorem on chaotic relaxation gives convergence of $x \leftarrow Mx$ whenever $\rho(M) < 1$ (Chazan and Miranker 1969). ■

When the charge drifts (a node's μ_i moving under load) the field tracks a moving target; the relevant property is stability. Every M_t satisfies $\|M_t\|_\infty \le \bar\gamma < 1$ with $\bar\gamma = \max_i G_i/(G_i+\kappa)$ — a uniform contraction in one fixed norm. The homogeneous error contracts at rate $\bar\gamma$ under every schedule, so the field cannot diverge while μ moves, and if μ settles the iteration converges to the corresponding fixed point (Theorems 5.2/5.3).

5.4 The maximum principle

Theorem 5.4 (no interior maximum). At the fixed point, every non-destination node i with $f_i^{d\star} > 0$ satisfies $f_i^{d\star} < \max_{j\in N(i)} f_j^{d\star}$. *Proof.* From (5.1), $f_i^{d\star} = \gamma_i \langle f^{d\star}\rangle_{N(i)}$ with $\gamma_i = G_i/(G_i+q_i) < 1$ and $\langle\cdot\rangle$ the conductance-weighted neighbour mean $\le \max_j f_j^{d\star}$. With $f_i^{d\star} > 0$, $\max_j f_j^{d\star} > 0$, so $f_i^{d\star} \le \gamma_i \max_j f_j^{d\star} < \max_j f_j^{d\star}$. ■

The field's only maxima are the pinned destinations; the gradient has no interior sink.

5.5 Forwarding — the current split

A node forwards along the discrete current $J_{ij} = g_{ij}(f_j^d - f_i^d)$. The active next hops are the strictly-uphill neighbours, split in proportion to the current:

$$N^\uparrow(i) = \{\, j \in N(i) : f_j^d > f_i^d \,\}, \qquad w_{ij} = g_{ij}(f_j^d - f_i^d), \qquad \text{via} = \arg\max_j w_{ij}. \tag{5.2}$$




Figure 2: [EXACT] The maximum principle (Theorem 5.4), by counterexample. *Left:* the field the operator produces toward a corner source — every interior node sits strictly below its largest neighbour, so steepest-ascent arrows all escape to the source (no trap). *Right:* a hand-drawn *forbidden* configuration with a spurious interior maximum — every nearby arrow points into it, a black hole. The screened M-matrix can never produce the right panel (Theorems 5.4, 5.6); it is an impossibility, not a measurement.

Forwarding to all uphill neighbours is a current-proportional spread (a generalisation of equal-cost multipath); the dominant edge is the maximum-current hop. Conductance biases the split toward high-quality links without changing which neighbours qualify.

5.6 Loop-freedom, black-hole-freedom, dissipativity

Theorem 5.5 (loop-freedom). For any single field configuration f, the active-edge relation $\{i \to j : f_j > f_i\}$ is acyclic. *Proof.* A directed walk along active edges strictly increases f; a cycle would force a value to exceed itself. The active edges are the strict-ascent relation of a real labeling — a DAG — for the equilibrium field and every relaxation iterate alike. ■

Theorem 5.6 (black-hole-freedom). At equilibrium, ascent from any node with $f_i^{d\star} > 0$ reaches d in finitely many hops. *Proof.* By Theorem 5.4 every positive non-destination has an uphill neighbour, so $N^{\uparrow}(i) \neq \varnothing$; each hop strictly increases a quantity bounded above by F_0, and on a finite graph a strictly-increasing walk terminates at the maximum, d. ■

When every forwarding comparison reads one field configuration — the common case, each node re-advertising every tick — the active edges are that configuration's strict-ascent relation, acyclic at every round by Theorem 5.5. Under bounded-delay asynchrony a comparison may mix values from different relaxation steps, and a transient cycle can momentarily appear. It cannot persist:

Theorem 5.7 (eventual non-trapping). Fix the graph and charge field after the last disturbance. Under bounded-delay fair asynchrony there is a finite time after which the dominant forwarding hop is acyclic and no packet is trapped. *Proof.* By Theorem 5.3 every advertised potential converges to $f^{d\star}$, so the bounded-delay samples any node compares are eventually within any $\varepsilon > 0$ of equilibrium. Let $g_{\min}$ be the smallest *nonzero* equilibrium gap. Once samples are within $g_{\min}/2$, every edge with $f_i^{d\star} \neq f_j^{d\star}$ is compared with the correct sign, so the active relation restricted to such edges is the




Figure 3: [MEASURED] The forwarding map on a converged grid: at each node the dominant up-gradient hop (5.2), coloured by the log of the current $g_{ij}(f_j^d - f_i^d)$ it carries. Every arrow climbs to the single source basin — the active-edge relation is acyclic (Theorem 5.5) with no interior sink (Theorem 5.6).

equilibrium strict-ascent DAG (Theorems 5.5, 5.4). A *level-set* edge ($f_i^{d\star} = f_j^{d\star}$) carries current $O(\varepsilon) \to 0$, while by Theorem 5.4 every non-destination node — including one on a level set — has a strictly-higher *exterior* neighbour, so its dominant current leaves the set and climbs the equilibrium gradient. The via-map therefore follows the equilibrium ascent and is acyclic; the only circulation not excluded is the vanishing $O(\varepsilon)$ flow on a flat level set, which makes no potential progress and decays to zero. ■

Under *continuing* forcing (load that keeps μ in motion) the corresponding property is a bounded non-equilibrium steady state: circulation stays confined to near-flat level sets and carries vanishing current, rather than exact acyclicity.

5.7 Congestion as a screening charge

Congestion is *endogenous*: a node measures the current it carries and screens itself accordingly — no externally injected load, no separate congestion protocol. The carried current at i is

$$s_i \;=\; \sum_d \max_{j \in N(i)} g_{ij}\big(f_j^d - f_i^d\big),$$

the sum over destinations d of the up-gradient flux it forwards on its chosen (max-flux) edge — the very quantity the current split of §5.6 already computes, read off the node's own field state each relax. A loaded node (large s_i) raises its screening charge μ_i, which by (5.1) flattens its potential — a shorter local reach (§5.2). The current split then steers flow around it: it advertises a depressed potential, so fewer neighbours find it uphill. Because $\mu_i \geq 0$ keeps $q_i \geq \kappa > 0$, every guarantee of §5.3–§5.6 holds unchanged.

The load-to-charge map is closed *internally*, through a **non-overshoot integrator**: with coupling c (the crowding rate) and glide rate r, the charge glides toward its own carried-current target, $\mu_i \leftarrow \mathrm{reg}(\mu_i,\, c\,s_i,\, r)$, where $\mathrm{reg}(v, T, r) = T + (v - T)/(1 + r|v - T|)$. (A deployment may add an externally-offered demand to s_i; the base signal is self-measured.)

Lemma 5.8 (non-overshoot). $\mathrm{reg}(v, T, r)$ lies strictly between v and T for $r > 0$, $v \neq T$, reaching T only in the limit. *Proof.* The factor $1/(1+r|v-T|) \in (0, 1)$ shrinks the gap $v-T$ without changing its sign. ■

The charge update is therefore itself non-overshooting and bounded — it removes the explicit-Euler overshoot mechanism a proportional update would introduce and damps the load↔field feedback. The target $c\,s_i$ moves as routing shifts load, so freedom from *closed-loop* ringing is not a consequence of Lemma 5.8 alone; §5.8 proves it.

5.8 Congestion stability

Because both fields are exact (§4, §5.1), the load-to-charge loop is an *exact* discrete map: $\mu \leftarrow G(\mu)$ with $G(\mu)_i = \mathrm{reg}\big(\mu_i,\, c\,s_i(\mu),\, r\big)$, where $s(\mu)$ is the load carried under the current-split flow of the exact field $f(\mu)$. Its stability is therefore a theorem, not a simulation outcome. Write the loop Jacobian $J(\mu) = c\,Ds(\mu)$ and loop gain $\Gamma = \sup_\mu \|J(\mu)\|$.

Two structural facts (Appendix C). First, the non-overshoot integrator has **no linear ringing mode**: because reg approaches its target *algebraically*, the Jacobian of G at the fixed point is exactly I (marginal), so no small-signal mode can amplify — the proportional-control ringing an additive charge suffers is structurally absent. Second, stability is settled by the operator's own cubic potential.

Theorem 5.9 (congestion stability). Let $\delta(\mu) = \mu - c\,s(\mu)$, $\Psi(\delta)_i = \delta_i|\delta_i|$, and $V(\mu) = \frac{1}{3}\sum_i |\delta_i|^3$. Along the residual flow,

$$\dot{V} = -r\,\Psi(\delta)^\top \big(I - \mathrm{Sym}\, J(\mu)\big)\Psi(\delta).$$

If $\sup_\mu \lambda_{\max}\big(\mathrm{Sym}\, J(\mu)\big) < 1$, then V is a strict global Lyapunov function and the congestion loop converges to its unique fixed point with no oscillation. *(Proof: Appendix C.)*

The condition is implied by loop gain $\Gamma < 1$ and holds *trivially* when the feedback is dissipative, $\mathrm{Sym}\, J \preceq 0$. It gives a **design rule**: hold the load coupling c (the crowding rate) below $1/\|Ds\|$ — finite because the field-sensitivity is itself the M-matrix, $\partial f/\partial \mu_i = -f_i(\mathcal{L}_g + Q)^{-1}e_i \leq 0$ (§4) — and the loop is provably ring-free for any glide rate r. The bound is conservative: the discrete non-overshoot adds damping, so the realized stable basin extends past $\Gamma = 1$ (§9, Appendix C).

6 The vitality field (proper time)

Reach screens the routing field in space; vitality screens liveness in time. For a destination d each node carries $V_i^d \in [0, 1]$ — its confidence that d is live — transported from the source and aged by

the proper time its evidence has spent in flight.

6.1 Causal structure and the aging law

A relayed value is evidence about its source as of the moment it left. Information advances at most one hop per tick, so a node at hop-distance δ holds evidence no fresher than δ ticks old: liveness lies on a light cone. A relay therefore ages a value by the proper time it carried it.

Vitality decays toward 0 by the integrator of §5.8 with target 0 and rate α; one tick of aging is $A(v) = \mathrm{reg}(v, 0, \alpha) = v/(1 + \alpha v)$.

Lemma 6.1 (Lorentzian decay). $A^k(1) = 1/(1 + \alpha k)$. *Proof.* $1/A(v) = 1/v + \alpha$, so $1/A^k(1) = 1 + k\alpha$. ■

6.2 Retardation is necessary

A value arriving after $\tau \geq 1$ ticks in flight is evidence from τ ticks ago and is aged by τ before use: $\tilde{v} = A^\tau(v)$. This is forced by causal consistency.

Theorem 6.2 (necessity of retardation). Adopting a neighbour's vitality without aging it by transit admits a spurious fixed point: on any edge whose endpoints exchange vitality, $V \equiv v$ is fixed for any v, even after the source dies. *Proof.* With the source gone, suppose each endpoint ages its own value and takes the max with the neighbour's last value: $V_a \leftarrow \max(A(V_a), V_b)$. If $V_a = V_b = v$ then $A(v) < v$, so $\max(A(v), v) = v$ — fixed at any v, in particular 1: the un-aged exchange refreshes each endpoint above its own decay. Retardation replaces the neighbour's value with $A^\tau(V_b)$; at $V_a = V_b = v$ and minimal transit $\tau = 1$, $A^\tau(v) = A(v)$ equals the self-aged value, so $\max(A(V_a), A^\tau(V_b)) = A(v) < v$ (strictly smaller still for $\tau \geq 2$). The max no longer exceeds the self-aging, the spurious fixed point is gone, and the only fixed point is the source-pinned one. A relayed value spends at least one tick in flight, so $\tau \geq 1$ always holds. ■

Retardation is a thermodynamic arrow: a liveness eddy cannot sustain itself without the continuous energy of a live source pin.

6.3 The reciprocal transform: vitality is a proper-time eikonal

The destination pins $V_d^d = 1$. Each node ages its held value and adopts the retarded value of any port offering a higher one:

$$V_i^d \longleftarrow \max\Big(A(V_i^d),\ \max_{j \in N(i)} A^{\tau_{ij}}(V_j^d)\Big). \tag{6.1}$$

Theorem 6.3 (steady state). For a continuously-live source, the converged vitality is




Figure 4: [MEASURED] Retardation is load-bearing (Theorem 6.2). A source is killed at $t = 0$ and a far observer's vitality toward it is tracked. Removing the transit-aging — the un-retarded recurrence ($\tau = 0$) — locks V at the spurious resurrection fixed point $V = 1$: a dead source the protocol can never let die. The retarded protocol (median + 10–90% band over reps) ages monotonically through the action threshold φ to zero — a clean severance.

$$\boxed{V_i^d = \frac{1}{1 + \alpha\, T_i^d}}$$

where T_i^d is the least accumulated transit time from d to i; with unit per-hop transit $T_i^d = \delta$ (hop-distance) and $V^d(\delta) = 1/(1 + \alpha\delta)$. *Proof.* Substitute the **reciprocal vitality** $U_i^d = 1/V_i^d$. Since $1/A^\tau(v) = 1/v + \alpha\tau$ (Lemma 6.1), a max over V is a min over U, and (6.1) becomes, away from the source,

$$U_i^d \;\longleftarrow\; \min\Big(U_i^d + \alpha,\; \min_{j \in N(i)} \big(U_j^d + \alpha\, \tau_{ij}\big)\Big), \qquad U_d^d = 1. \tag{6.2}$$

This is the Bellman optimality equation for least-cost paths with strictly positive edge weights $\alpha\tau_{ij}$ ($\tau_{ij} \geq 1$) and source value 1 — a *discrete* Hamilton–Jacobi–Bellman (eikonal) fixed point solved **exactly** on the graph, not a discretization of a PDE. Its unique finite solution is $U_i^d = 1 + \alpha T_i^d$ (the self-term $U_i^d + \alpha$ is dominated wherever a live path exists), and the min-iteration converges to it from any initialisation under synchronous or bounded-delay asynchronous updates (the asynchronous shortest-path theorem: Bertsekas 1982; Tsitsiklis 1995). Inverting, $V_i^d = 1/(1 + \alpha T_i^d)$. The continuum eikonal $|\nabla U| = \alpha$ is the conditional continuum limit of this exact graph object, scoped in Appendix B. ■

The exact object makes the light cone exact: $U_i^d - 1 = \alpha T_i^d$ is proper-time distance, so the iso-vitality level sets $\{V^d = \text{const}\}$ are the proper-time balls — the *discrete* light cones — around d. A node whose freshest evidence is T_i^d proper-time old reports exactly the confidence the decay law assigns to evidence of that age — no more.




Figure 5: [EXACT] The reciprocal transform (Theorem 6.3). On a grid with a centre source the hop-distance T is the exact min-plus shortest path. *Top:* $V = 1/(1+\alpha T)$ over the grid; its iso-T level sets are the discrete light cones (proper-time balls), the red ring the $V = \varphi$ horizon. *Bottom:* along a ray the Bellman metric $U = 1+\alpha T$ climbs without bound (the count-to-infinity), while the data plane reads $V = 1/U$, bounded in $[0, 1]$ and fading through φ.




Figure 6: The count-to-infinity contrast on the same line *A–B–C–D–E* after the far destination dies; both routers obey the identical min-plus recurrence and differ only in what they read off it. *Top* [MEASURED]: RING's far observer reads $V = 1/U$ — graceful monotone severance through φ to 0 (median + 10–90% band), even though its reciprocal U genuinely diverges. *Bottom* [TEXTBOOK]: a plain distance-vector router (no split-horizon, no poison reverse) circulates its hop metric upward toward the cap — the count-to-infinity RING converts into a bounded fade.

6.4 Death and garbage collection

When the source stops asserting life, every held value ages toward 0 (Lemma 6.1) and, by Theorem 6.2, nothing lifts it back. In reciprocal terms the source-pin disappears, so the Bellman recursion (6.2) has no finite boundary value and U_i^d increases without bound — the *count-to-infinity* of distance-vector routing. But the data plane reads $V = 1/U$, so divergence in U is convergence to zero in V:

$$U_i^d \to \infty \iff V_i^d \to 0.$$

The exact pathology that forces sequence numbers and tombstones into RIP and BGP is, under the reciprocal, the smooth monotone fade of a ghost — the destination garbage-collects itself with no discrete withdrawal, hold-down, or version counter.




Figure 7: [MEASURED] The vitality field over a grid toward the corner source, with the marginal CDF of V below. The far corner droops below φ — field-*known* but not vouched for: the vitality horizon R_V. On the CDF the φ cut splits the horizon tail (left) from the actionable fraction $1 - \mathrm{CDF}(\varphi)$ (right).

6.5 The horizon

Acting only above a threshold φ bounds the distance at which liveness can be asserted: $V^d(\delta) \geq \varphi \iff \delta \leq R_V = (1/\varphi - 1)/\alpha$. R_V is the radius within which the source's life is known to tolerance φ, set by the aging rate α — the rate at which stale evidence is discounted.

7 Direction and confidence

A node's routing state for d is the pair it offers a packet: a **direction** (the dominant uphill hop of f^d, defined where the field is above the floor and an uphill neighbour exists) and a **confidence** (the vitality V_i^d). A consumer acts on the direction when the confidence clears its threshold:

$$\mathrm{route}(d, \varphi) = \big(\mathrm{via},\ V_i^d \geq \varphi\big), \qquad \mathrm{known} \equiv \big(f_i^d \geq \mathrm{floor}\ \wedge\ \mathrm{via\ defined}\big).$$

The one hard precondition is **known**: a destination is routable only where its field has been received




Figure 8: RING node cycle. Message arrival and local cadence are independent event sources; the Tick is an emission/aging cadence, not a route-expiry timer.

above the floor. Confidence below φ does not erase the direction — it reports that the source's life is no longer vouched for — so the threshold is the consumer's to choose, per packet. Severance is a caller decision, never a substrate deletion.

7.1 Operational realization

The protocol realization is deliberately smaller than the field theory: a node keeps private adjacency state and a per-destination routing information base (RIB), and it exports only advertisements. There is one base message type. The message header carries the sender and the set of neighbours the sender currently hears; the body is a list of destination entries,

$$(\text{Dest}, \text{Pot}, \text{Vit}) = (d, f^d, V^d).$$

Every emission includes the sender's self-pin $(\text{self}, F_0, 1)$, which is the only assertion of life. The base message carries no sequence number, metric version, hop count, route age, tombstone, or timestamp.

field	**type**	**meaning**
From	node id	the emitter
Hears	list of node ids	neighbours the emitter currently hears, used as the bidirectional echo
Delta	list of entries	one advertised entry per destination retained above the field floor
Dest	node id	destination described by an entry
Pot	real ≥ 0	advertised routing potential f toward Dest
Vit	real in $[0, 1]$	advertised vitality V toward Dest

Each node runs independently on its own cadence. Reception only records neighbour advertisements and performs the retarded vitality adopt-max; emission happens only on the node's local relaxation cadence. There is no global round, no barrier, and no shared clock.

Adjacency is admitted only by echo: neighbour p contributes to the relaxation set $N^{\leftrightarrow}(i)$ when i hears p and p's advertisement lists i in Hears. A small link-layer freshness window may remove stale




Figure 9: Forwarding decision. Low vitality severs confidence, not direction; the caller chooses what to do with a known but no-longer-vouched-for destination.

adjacencies, but it is confined to the link layer; routing and liveness do not use per-route expiry timers. A received vitality is aged before adoption, using one Tick of staleness per relay in the clock-free base protocol,

$$V_i^d \leftarrow \max\Big(V_i^d, \mathrm{age}(V_p^d, 1)\Big),$$

while a node's held vitality is aged by its own elapsed local time. A clock-synchronized deployment may replace the fixed one-Tick relay cost by a measured transit time, but the base protocol never compares clocks across nodes.

The data plane reads the RIB as a policy decision over two levels: the field floor says whether a direction is known, and the vitality threshold says whether that direction is vouched for.

8 Space–time horizon alignment and bounded state

The two horizons can be made to coincide. The routing field carries direction out to the spatial reach $\lambda = \sqrt{D/\kappa}$; the vitality field certifies liveness out to the temporal horizon $R_V = (1/\varphi - 1)/\alpha$.

Proposition 8.1 (bounded state). If α is chosen so $R_V \asymp \lambda$, each node maintains non-negligible state only for destinations within an $O(\lambda)$ ball, so total fabric state is $O\big(n \cdot \mathrm{Vol}(\lambda)\big)$. *Sketch.* Beyond λ the screened field falls below the floor and the destination is *unknown* (§5.1); aligning R_V with λ ensures vitality has likewise decayed below φ there, so no node retains liveness for destinations it cannot route to. Each node's working set is its reach ball, of volume $\mathrm{Vol}(\lambda)$; summing over n nodes gives the bound. □

This is the payoff of unifying space and time: the protocol natively snuffs out state for distant destinations rather than carrying global tables, and the locality radius is a single tunable, λ. (Sub-$\mathrm{Vol}(\lambda)$ state would require hierarchy/landmarks, §10.)

9 Empirical validation

We validate the theory on the *asynchronous* reference implementation: each node runs on its own cadence with no global round, barrier, or shared clock (§7.1), and every measured figure is an




Figure 10: [MEASURED] Vitality lifecycle at a far observer: the field converges, the source is killed (vertical mark), and the held vitality ages through the action threshold φ to zero — graceful severance, no flap.

ensemble of R independent reps reported as a median with a 10–90% inter-rep band. The exact-solve figures of §§5–6 ([EXACT]) show what the operator *defines*; the figures here ([MEASURED]) show what the running protocol *realizes*. This is a simulation study, not a deployment (§10); its purpose is to exercise each theorem on the live protocol.

Lifecycle and the $V(\delta)$ droop. A far observer converges, the source is killed, and its vitality severs gracefully through φ to zero (Fig. 10). Along a line the steady live V tracks the law $1/(1+\alpha\delta)$ (Theorem 6.3) but ages slightly *faster* than unit-transit predicts (Fig. 11): a route also dwells in the RIB between refreshes, spending extra proper time. The measured-below-theory gap is that dwell, not error — the protocol is honest about evidence it has held longer than one hop's transit.

Clock-free robustness. Under unsynchronized clocks — per-node offsets up to s ticks, either sign — the two retardation modes diverge (Fig. 12). The clock-free hop-age (one tick of staleness per relay, never a cross-node clock read) is skew-invariant: it becomes routable while the source is live and severs after it dies in 100% of reps at every skew. Reading a measured cross-clock transit instead — the NTP-dependent variant — degrades as the skew dwarfs the true sub-tick transit, over-ageing a live source below φ or under-ageing a dead one: correctness falls to 0.71 at $s = 14$ and 0.48 at $s = 16$. Causal honesty needs no synchronized clock.

Count-to-infinity, made graceful. The headline contrast (Fig. 6, §6.4): on a dead line a textbook distance-vector metric counts upward to its cap while RING's reciprocal fade keeps the read V bounded and monotone — the same diverging metric, read two ways. Retardation is what forbids the alternative pathology, the spurious resurrection that locks a dead source at $V = 1$ (Fig. 4, §6.2).

Data-plane delivery through failure. On a converged grid every packet is delivered; a lossy fabric (4%/hop) plateaus at 0.67 delivered, the gap to one being physically lost mass, not a routing failure (Fig. 13a). When the chokepoint directly above the destination is killed, delivery collapses to 0.09 for one reconvergence window as stale routes forward into the corpse, and the black-hole ratio mirror-spikes to 0.91 (Fig. 13b). Then vitality ages the dead route past φ: forwarding cleanly




Figure 11: [MEASURED] The $V(\delta)$ droop along a line: measured live vitality vs. hop distance tracks the unit-transit law $1/(1+\alpha\delta)$ (Theorem 6.3); the shaded gap is the protocol ageing V slightly faster because a route also dwells in the RIB between refreshes — extra proper time, not error.




Figure 12: [MEASURED] Skew-robustness sweep ($R = 21$ reps/point). *Top:* fraction of reps that are correct (routable while live *and* severed after death); clock-free hop-age holds at 1 across all skew, measured cross-clock transit degrades as skew dwarfs the true sub-tick transit. *Bottom:* steady live V at the observer (median, 10–90% band) — skew-invariant for hop-age, scattered for measured-transit.




Figure 13: [MEASURED] The data-plane payoff. (a) Delivery-latency CDF by hop count on a converged grid: nominal reaches 1 (every packet delivered); the lossy fabric (4%/hop) plateaus at 0.67, the gap being physically lost mass, distinct from any routing failure. (b) A steady stream is injected and the chokepoint above the destination is killed at t_0: delivery collapses to 0.09 and the black-hole ratio mirror-spikes to 0.91 for one reconvergence window (they sum to ≈ 1 over the injected packets), then vitality severs the dead route and delivery snaps back to 1.

severs rather than black-holing, the field reconverges around the gap, and delivery snaps back to one.

Partition and recovery. Cutting the only bridge on a line collapses delivery (Fig. 14). The black-hole fraction spikes first — stale field routing packets into the dead edge — then hands off to correct severance as vitality ages below φ: the protocol declining to forward, not a black hole. After the heal the field reconverges and delivery recovers within $\sim$100 ms.

Loop-dissipativity under churn. Snapshotting the forwarding via-graph on a skewed, thrice-churned mesh and DFS-counting its directed cycles, transient via-cycles flicker as the field regrows on stale advertisements — at most three at once, mean length ≈ 1.2 hops — and every one dissipates to zero within a few rounds; none persists (Theorem 5.7, Fig. 15). Kills collapse the field monotonically and raise no loop; only revives spark a transient.

Congestion damping and the stability basin. On a barbell whose single bridge carries all cross-cluster current, the hub self-measures that load and glides its screening charge μ toward $c\,s$ with no injected stress (Fig. 16). At the operating couplings the charge climbs monotonically to equilibrium with no overshoot — the damped settle the non-overshoot integrator guarantees (Lemma 5.8) inside the basin. A wide coupling sweep then locates the basin boundary empirically: overshoot holds at the floor ($< 0.3\%$ through $c = 2$) and lifts off only once the gain amplifies the convergence load-spike, the median reaching $\sim$ 13–18% near $c = 16$–20. The realized basin extends well past the conservative $\Gamma < 1$ bound (Theorem 5.9, Appendix C).

Together these exercise every theorem of §§5–6 on the running protocol. The exact fields of §§5–6 are what the operator defines; the ensembles here are what an asynchronous, clock-free implementation delivers.




Figure 14: [MEASURED] Partition and recovery on a line ($R = 21$ reps). The bridge edge is cut, then relinked. Data-plane delivery (top) collapses at the cut and recovers $\sim$100 ms after the heal; the black-hole fraction spikes first, then hands off to correct severance (routable$\rightarrow$ 0, bottom) as vitality ages below φ. Markers are the measured cut / heal / recovered instants.




Figure 15: [MEASURED] Loop-dissipativity under async churn (Theorem 5.7). At each sample the forwarding via-graph is snapshotted and its directed cycles DFS-counted, read-only over a skewed, thrice-churned mesh. Transient via-cycles flicker as the field re-grows on stale advertisements (at most three at once, mean length ≈ 1.2 hops) and dissipate to zero within a few rounds; none persists. Kills raise no loop — only revives spark a transient. Median + envelope over $R = 21$ reps.




Figure 16: [MEASURED] The self-driven load/charge loop and its stability basin (Theorem 5.9) on a barbell bridge. *Top:* the hub's charge trajectory at three couplings, each normalised to its own equilibrium μ_∞; every curve climbs monotonically to 1 with no overshoot — the damped settle inside the basin (Lemma 5.8). *Bottom:* a wide coupling sweep of the transient overshoot (median + 10–90% band); flat through the operating couplings (wide basin) and lifting into ringing only once the gain amplifies the convergence load-spike — the basin boundary made empirical.

10 Discussion and limitations

Idealizations. The clean $V(\delta) = 1/(1 + \alpha\delta)$ assumes unit per-hop transit; the general result is $V = 1/(1 + \alpha T)$ with T the least accumulated transit time, which is what a deployment with heterogeneous link delay realizes. Closed-loop congestion stability is *proven*, not empirical (Theorem 5.9): because the fields are exact, the load–charge loop is an exact map, globally ring-free whenever the loop gain stays below one — and the only open quantitative question is the worst-case basin when the gain exceeds one (Appendix C gives a conservative sufficient bound; the realized basin is larger).

Control-plane cost. Liveness requires the source's assertion to be refreshed; a per-tick keepalive of the live working set is the simplest realization and is not silent at rest. It can be slowed to a lazy pulse at the cost of detection latency — a bandwidth/latency trade governed by α and the keepalive period.

Scope. Proposition 8.1 bounds state to a reach ball; genuinely sub-Vol(λ) routing (internet-scale diameters) needs hierarchy or landmarks layered above the field, which we do not address. The asynchronous shortest-path convergence of (6.2) is invoked, not reproved. The relationship between the discrete operators and the continuum PDEs — formerly stated by analogy — is made precise in Appendix B: on the fabric both fields are *exact* discrete objects (a linear M-matrix solve and a min-plus shortest path), and the elliptic screened-Poisson and eikonal equations govern them only under a monotone–consistent–stable manifold-discretization limit (Barles and Souganidis 1991; Calder and Ettehad 2022) whose sampling hypotheses a logical fabric does not satisfy — and against which a naive graph distance is metrication-biased. We therefore do *not* claim the deployed network is governed by a PDE, only that its discrete fields are the exact combinatorial objects those PDEs idealize.

Future work. A kernel data plane carrying the two scalars as the only per-destination state — programming the forwarding table over netlink and forwarding in eBPF, exposed as a CNI plugin for container fabrics — with conductance and transit measured from the link rather than assumed uniform; hierarchical aggregation beyond the reach ball; and a sharp characterization of the congestion basin when the loop gain exceeds one (Theorem 5.9 gives a conservative sufficient bound; the exact threshold is open).

11 Conclusion

RING maps the heuristic machinery of distributed routing — metrics, timers, sequence numbers, tombstones, hold-downs — onto two *exact* discrete fields solved by local asynchronous iteration. Direction is the exact solution of a screened M-matrix system whose maximum principle makes forwarding loop- and black-hole-free; confidence is the exact proper-time shortest path whose reciprocal turns count-to-infinity into graceful death. The two share one screening charge that also absorbs congestion, and the elliptic and eikonal equations a physicist would write for them are their continuum shadows (Appendix B), not the equations the fabric solves. What remains is a fabric bent by load and aged by proper time, carrying packets down the steepest gradient — no telecom algorithms left.

A Supplementary detail

A.1 The M-matrix properties (§4). $\mathcal{L}_g$ has non-positive off-diagonals $-g_{ij}$ and row sums zero; adding $Q \succ 0$ yields strict row diagonal dominance $G_i + q_i > G_i = \sum_j |-g_{ij}|$. A symmetric, strictly diagonally dominant matrix with non-positive off-diagonals and positive diagonal is a Stieltjes (symmetric M-) matrix: positive-definite, with real positive eigenvalues and an entrywise non-negative inverse (Berman and Plemmons 1994; Varga 1962). Inverse-positivity gives $f^{d\star} \geq 0$ for the non-negative boundary data of (5.1), and strict positivity on d's connected component.

A.2 Domination of the self-term in (6.2). The reciprocal update carries a self-term $U_i^d + \alpha$ (the node aging in the absence of fresher news). Since $U_i^d + \alpha > U_i^d \geq \min_j(U_j^d + \alpha\tau_{ij})$ whenever a live path exists, the self-term never attains the min at a live destination and the fixed point is the pure Bellman value $1 + \alpha T_i^d$. With *no* live source the self-term is the only term and drives $U \to \infty$ — the death dynamics of §6.4.

A.3 Asynchronous shortest-path convergence of (6.2). The min-plus operator $T(U)_i = \min_j(U_j^d + \alpha\tau_{ij})$ is monotone and a (weighted) contraction toward the unique solution with non-negative weights and a fixed source value; the asynchronous convergence of such Bellman iterations under bounded communication and computation delay is classical (Bertsekas 1982; Bertsekas and Tsitsiklis 1989). The reciprocal $V = 1/U$ inherits convergence by continuity away from $U = \infty$.

A.4 Loop-dissipativity round bound. In Theorem 5.7, the convergence rate fixes the window: samples fall within $g_{\min}/2$ of equilibrium after $O\big(\log(C/g_{\min})/\log(1/\gamma)\big)$ rounds, with C the initial discrepancy and $g_{\min}$ the least nonzero equilibrium gap; thereafter only level-set circulation (vanishing current) remains.

B The exact discrete fields and their continuum limits

The body names f an "elliptic screened-Poisson potential" and $U = 1/V$ an "eikonal" field. This appendix makes both names precise and, equally, bounds them. On the fabric *both* fields are **exact** discrete objects, computed with no limit; the named partial differential equations are their *shared continuum limits*, which a logical fabric is not built to take. We state the exact claims (B.1, B.2), the limit (B.3), and the scope (B.4).

B.1 The vitality field is an exact discrete eikonal. Fix a live destination d ($U_d = 1$), transit times $\tau_{ij} \geq 1$, aging rate $\alpha > 0$, weights $w_{ij} = \alpha\tau_{ij} > 0$. The min-plus relation (6.2) is the Bellman optimality equation of the shortest-path problem with these weights; on the component that can reach d, the strictly positive weights forbid zero/negative cycles, so it has the **unique finite solution**

$$U_i^d = 1 + \alpha\, T_i^d, \qquad T_i^d = \min_{P:\, d \rightsquigarrow i} \sum_{(j,k)\in P} \tau_{jk},$$

the least-accumulated-proper-time metric (Bellman 1958; Bertsekas 1982; Bertsekas and Tsitsiklis 1989). This is exact — a combinatorial optimum, no mesh and no limit. The operator

$(\mathsf{T}U)_i = \min_{j \in N(i)}(U_j + \alpha\tau_{ij})$ is **monotone** (order-preserving), and its iteration is asynchronous Bellman–Ford; it converges by monotone dynamic programming, *not* by a sup-norm contraction (that is the routing field's mechanism, §5.3). Over the $(\min, +)$ tropical (idempotent) semiring the operator is **linear** — the fixed point is the Kleene star $U = W^* \otimes b$, finite because $\tau_{ij} \geq 1$ excludes non-positive cycles (Litvinov 2005). The reciprocal $V = 1/U$ is thus an *exact* linearization of the nonlinear retarded-max update (6.1) into this tropically-linear problem; the Cole–Hopf transform (Hopf 1950; Cole 1951) is its continuum analogue, not its mechanism.

B.2 The routing field is an exact discrete screened operator. The relation (5.1) is the row equation of the finite linear system $(\mathcal{L}_g + Q)f^d = 0$ with $f^d_d = F_0$. Because $\mathcal{L}_g + Q$ is a symmetric M-matrix (§4), it is invertible with a non-negative inverse, so f^d is the **exact, unique** solution — again no mesh, no limit — and the reach λ, the maximum principle, and the contraction (Lemma 5.1) are exact statements about this discrete operator. The "screened-Poisson" / Helmholtz *PDE* $-D\nabla^2 f + \kappa f = 0$ is its continuum limit (B.3), not its definition.

B.3 The continuum limits, and their hypotheses. Both PDEs are recovered only when the graph discretizes an underlying length space or manifold, with edge data approximating the metric and a sampling/bandwidth scale driven to zero. The abstract bridge is Barles and Souganidis (1991): a *monotone, consistent, stable* scheme converges locally uniformly to the unique *viscosity solution* of the limiting equation (Crandall and Lions 1983), provided that equation enjoys a comparison principle. The min-plus update is monotone (B.1) and stable ($U = 1 + \alpha T$ is bounded on a finite live component); **consistency is the one hypothesis that is not free.** A naive graph shortest path is *not* eikonal-consistent: it is a path-restricted, anisotropic over-estimate of the geodesic — the documented **metrication / grid-anisotropy bias** — which is exactly why fast marching solves a *local* eikonal update instead of taking the graph min (Sethian 1996; Tsitsiklis 1995). Convergence to the geodesic eikonal therefore needs an eikonal-consistent solver or, for sampled data, random-geometric graphs with the right scaling, where it has been established with rates for graph Hamilton–Jacobi equations (Calder and Ettehad 2022; cf. Bernstein et al. 2000 for graph-geodesic convergence). The elliptic side is the parallel statement: the graph Laplacian $\mathcal{L}_g$ converges to the continuum Laplace–Beltrami operator under the analogous manifold-sampling hypotheses (García Trillos et al. 2020), so $(\mathcal{L}_g + Q)f = 0$ converges to the screened-Poisson PDE in the same limit.

B.4 Scope. A RING fabric is a *logical* graph — its edges are links, not a sample of any fixed manifold; there is no $n \to \infty$ embedding and no bandwidth driven to zero. The hypotheses of B.3 are therefore not met by the deployed network, and neither PDE is the equation it solves. What it solves exactly are the two discrete operators of B.1–B.2. The continuum PDEs earn their keep here as *clarifying idealizations* — they explain why iso-vitality sets behave like causal wavefronts and why the screened field decays with a reach length — and we invoke them strictly as limits, never as definitions. The protocol's guarantees rest only on the exact discrete statements.

C Congestion-loop stability

C.1 The exact map. Because $f(\mu)$ (the M-matrix solve) and the induced load $s(\mu)$ are *exact* functions of the charge field (§4–§5), the congestion loop is an exact discrete map $\mu \leftarrow G(\mu)$, $G(\mu)_i = \mathrm{reg}(\mu_i, c\, s_i(\mu), r)$. Stability is a property of this map, computed, not sampled. Let $\mu^\star$ be

the fixed point ($\mu_i^\star = c\, s_i(\mu^\star)$), $e = \mu - \mu^\star$, $J = c\, Ds$, and $\delta = \mu - c\, s(\mu)$ the residual (so $\delta = (I - J)e$ to first order in s).

C.2 No linear ringing mode. Since $\mathrm{reg}(v, T, r) = T + (v - T)/(1 + r|v - T|)$ approaches its target *algebraically*, $\partial_v \,\mathrm{reg}\,|_{v=T} = 1$ and $\partial_T \,\mathrm{reg}\,|_{v=T} = 0$, so the Jacobian of G at $\mu^\star$ is exactly I. There is no eigenvalue of modulus > 1: a small perturbation cannot ring. (An *additive* charge $\mu_i = c\, s_i$ is a proportional controller whose Jacobian is J itself, with no such marginality — it rings when $\|J\| > 1$. This is the analytic difference between the denominator charge that damps and the numerator charge that oscillates, §9.) Stability is thus decided by the nonlinear terms, which only damp.

C.3 The exact one-dimensional multiplier. For a single node with $T(\mu) = c\, s(\mu)$, $s' < 0$ and gain $\Gamma = c|s'|$, carrying the coupled linearization to nonlinear order gives the exact per-step error map $e^{k+1} = M(e^k)\, e^k$ with

$$M(e) = \frac{1 - \Gamma\rho}{1 + \rho}, \qquad \rho = r(1 + \Gamma)|e|.$$

Then $M(e) \to 1^-$ as $e \to 0$ (algebraic, monotone approach — the marginal mode of C.2, nonlinearly damped), and $|M(e)| \le 1$ for all e **iff** $\Gamma \le 1$. For $\Gamma > 1$, $|M| > 1$ only beyond a displacement $|e| > 2/\big(r(1 + \Gamma)(\Gamma - 1)\big)$, so the fixed point is always locally stable and the ringing basin shrinks as the glide slows ($r \downarrow$).

C.4 The cubic Lyapunov (proof of Theorem 5.9). The multi-node result follows from the Lyapunov function *matched to the operator*: reg is the time-1 flow of the cubic drag $\dot{x} = -r(x - T)|x - T|$, i.e. gradient descent on $\frac{r}{3}|x - T|^3$, so take $V(\mu) = \frac{1}{3}\sum_i |\delta_i|^3$. With $\Psi(\delta)_i = \delta_i|\delta_i|$, the residual flow $\dot{\mu} = -r\,\Psi(\delta)$ gives $\dot{\delta} = (I - J)\dot{\mu} = -r(I - J)\Psi(\delta)$, hence

$$\dot{V} = \sum_i \Psi(\delta_i)\,\dot{\delta}_i = \Psi(\delta)^\top \dot{\delta} = -r\,\Psi(\delta)^\top (I - J)\,\Psi(\delta) = -r\,\Psi(\delta)^\top \big(I - \mathrm{Sym}\, J\big)\Psi(\delta),$$

the last step because a quadratic form sees only the symmetric part. If $\lambda_{\max}(\mathrm{Sym}\, J(\mu)) < 1$ for all μ, then $I - \mathrm{Sym}\, J \succ 0$ and $\dot{V} \le -r\,\lambda_{\min}(I - \mathrm{Sym}\, J)\,\|\Psi(\delta)\|^2 < 0$ for $\delta \neq 0$. V is positive-definite and radially unbounded in δ, with $V = 0 \Leftrightarrow \delta = 0 \Leftrightarrow \mu = \mu^\star$; by Lyapunov's direct method $\mu^\star$ is globally asymptotically stable, without oscillation. The cubic potential is what diagonalizes $\dot{V}$ into a bare quadratic form — a quadratic Lyapunov $\|e\|^2$ fails, because the $|\delta|$ of the cubic drag breaks that form. The discrete map is the frozen-target time-1 integrator of this flow; its leading-order decrement is $\Delta V \approx -r\,\Psi^\top (I - \mathrm{Sym}\, J)\Psi$, and the non-overshoot factor $1/(1 + r|\delta_i|) \preceq I$ adds strictly more damping, so the realized stable region extends past $\lambda_{\max}(\mathrm{Sym}\, J) = 1$ (numerically, monotone decay of V persists to ≈ 1.3, divergence only near 2). Thus the gain condition is a *conservative* sufficient bound for the deployed protocol. ■

References

Aguilera, M. K., Chen, W., and Toueg, S. 1997. Heartbeat: A Timeout-Free Failure Detector for Quiescent Reliable Communication. *Distributed Algorithms (WDAG '97)*, LNCS 1320, 126–140.

Barles, G., and Souganidis, P. E. 1991. Convergence of Approximation Schemes for Fully Nonlinear Second Order Equations. *Asymptotic Analysis* 4(3), 271–283.

Basu, A., Lin, A., and Ramanathan, S. 2003. Routing Using Potentials: A Dynamic Traffic-Aware Routing Algorithm. *Proc. ACM SIGCOMM 2003*, 37–48.

Baudet, G. M. 1978. Asynchronous Iterative Methods for Multiprocessors. *Journal of the ACM* 25(2), 226–244.

Bellman, R. 1958. On a Routing Problem. *Quarterly of Applied Mathematics* 16(1), 87–90.

Berman, A., and Plemmons, R. J. 1994. *Nonnegative Matrices in the Mathematical Sciences*. SIAM Classics in Applied Mathematics 9 (reprint of the 1979 Academic Press edition).

Bernstein, M., de Silva, V., Langford, J. C., and Tenenbaum, J. B. 2000. Graph Approximations to Geodesics on Embedded Manifolds. Technical Report, Stanford University.

Bertsekas, D. P. 1982. Distributed Dynamic Programming. *IEEE Transactions on Automatic Control* 27(3), 610–616.

Bertsekas, D. P. 1983. Distributed Asynchronous Computation of Fixed Points. *Mathematical Programming* 27(1), 107–120.

Bertsekas, D. P., and Gallager, R. G. 1992. *Data Networks*, 2nd ed. Prentice-Hall (Ch. 5, Routing).

Bertsekas, D. P., and Tsitsiklis, J. N. 1989. *Parallel and Distributed Computation: Numerical Methods*. Prentice-Hall (reissued 1997, Athena Scientific).

Calder, J., and Ettehad, M. 2022. Hamilton–Jacobi Equations on Graphs with Applications to Semi-Supervised Learning and Data Depth. *Journal of Machine Learning Research* 23(318), 1–62.

Chandra, T. D., and Toueg, S. 1996. Unreliable Failure Detectors for Reliable Distributed Systems. *Journal of the ACM* 43(2), 225–267.

Chen, W., Toueg, S., and Aguilera, M. K. 2002. On the Quality of Service of Failure Detectors. *IEEE Transactions on Computers* 51(1), 13–32.

Chazan, D., and Miranker, W. 1969. Chaotic Relaxation. *Linear Algebra and its Applications* 2(2), 199–222.

Cheng, C., Riley, R., Kumar, S. P. R., and Garcia-Luna-Aceves, J. J. 1989. A Loop-Free Extended Bellman–Ford Routing Protocol Without Bouncing Effect. *Proc. ACM SIGCOMM '89*, 224–236.

Chroboczek, J., and Schinazi, D. 2021. The Babel Routing Protocol. IETF RFC 8966 (obsoletes RFC 6126).

Cole, J. D. 1951. On a Quasi-Linear Parabolic Equation Occurring in Aerodynamics. *Quarterly of Applied Mathematics* 9(3), 225–236.

Crandall, M. G., and Lions, P.-L. 1983. Viscosity Solutions of Hamilton–Jacobi Equations. *Transactions of the American Mathematical Society* 277(1), 1–42.

Crick, F. 1970. Diffusion in Embryogenesis. *Nature* 225(5231), 420–422.

Cybenko, G. 1989. Dynamic Load Balancing for Distributed Memory Multiprocessors. *Journal of Parallel and Distributed Computing* 7(2), 279–301.

Dadgar, A., Phillips, J., and Currey, J. 2018. Lifeguard: Local Health Awareness for More Accurate Failure Detection. *48th IEEE/IFIP DSN Workshops*.

Das, A., Gupta, I., and Motivala, A. 2002. SWIM: Scalable Weakly-Consistent Infection-Style Process Group Membership Protocol. *Proc. IEEE DSN 2002*, 303–312.

Demers, A., Greene, D., Hauser, C., Irish, W., et al. 1987. Epidemic Algorithms for Replicated Database Maintenance. *Proc. 6th ACM PODC*, 1–12.

Frommer, A., and Szyld, D. B. 2000. On Asynchronous Iterations. *Journal of Computational and Applied Mathematics* 123(1–2), 201–216.

Gafni, E. M., and Bertsekas, D. P. 1981. Distributed Algorithms for Generating Loop-Free Routes in Networks with Frequently Changing Topology. *IEEE Transactions on Communications* 29(1), 11–18.

Garcia-Luna-Aceves, J. J. 1993. Loop-Free Routing Using Diffusing Computations. *IEEE/ACM Transactions on Networking* 1(1), 130–141.

García Trillos, N., Gerlach, M., Hein, M., and Slepčev, D. 2020. Error Estimates for Spectral Convergence of the Graph Laplacian on Random Geometric Graphs Toward the Laplace–Beltrami Operator. *Foundations of Computational Mathematics* 20(4), 827–887.

Hayashibara, N., Défago, X., Yared, R., and Katayama, T. 2004. The φ Accrual Failure Detector. *Proc. 23rd IEEE SRDS*, 66–78.

Hopf, E. 1950. The Partial Differential Equation $u_t + uu_x = \mu u_{xx}$. *Communications on Pure and Applied Mathematics* 3(3), 201–230.

Intanagonwiwat, C., Govindan, R., Estrin, D., Heidemann, J., and Silva, F. 2003. Directed Diffusion for Wireless Sensor Networking. *IEEE/ACM Transactions on Networking* 11(1), 2–16.

Jaffe, J. M., and Moss, F. H. 1982. A Responsive Distributed Routing Algorithm for Computer Networks. *IEEE Transactions on Communications* 30(7), 1758–1762.

Kleinberg, R. 2007. Geographic Routing Using Hyperbolic Space. *Proc. IEEE INFOCOM 2007*, 1902–1909.

Litvinov, G. L. 2005. The Maslov Dequantization, Idempotent and Tropical Mathematics: A Brief Introduction. In *Idempotent Mathematics and Mathematical Physics*, Contemp. Math. 377, AMS.

Park, V. D., and Corson, M. S. 1997. A Highly Adaptive Distributed Routing Algorithm for Mobile Wireless Networks (TORA). *Proc. IEEE INFOCOM '97*, vol. 3, 1405–1413.

Perkins, C. E., and Bhagwat, P. 1994. Highly Dynamic Destination-Sequenced Distance-Vector Routing (DSDV) for Mobile Computers. *Proc. ACM SIGCOMM '94*, 234–244.

Sarkar, R., Yin, X., Gao, J., Luo, F., and Gu, X. D. 2009. Greedy Routing with Guaranteed Delivery Using Ricci Flows. *Proc. IPSN 2009*, 121–132.

Satzger, B., Pietzowski, A., Trumler, W., and Ungerer, T. 2007. A New Adaptive Accrual Failure Detector for Dependable Distributed Systems. *Proc. ACM SAC 2007*, 551–555.

Sethian, J. A. 1996. A Fast Marching Level Set Method for Monotonically Advancing Fronts. *Proceedings of the National Academy of Sciences* 93(4), 1591–1595.

Toumpis, S., and Tassiulas, L. 2005. Packetostatics: Deployment of Massively Dense Sensor Networks as an Electrostatics Problem. *Proc. IEEE INFOCOM 2005*, vol. 4, 2290–2301.

Tsitsiklis, J. N. 1995. Efficient Algorithms for Globally Optimal Trajectories. *IEEE Transactions on Automatic Control* 40(9), 1528–1538.

Tsitsiklis, J. N., Bertsekas, D. P., and Athans, M. 1986. Distributed Asynchronous Deterministic and Stochastic Gradient Optimization Algorithms. *IEEE Transactions on Automatic Control* 31(9), 803–812.

Turing, A. M. 1952. The Chemical Basis of Morphogenesis. *Philosophical Transactions of the Royal Society B* 237(641), 37–72.

van Renesse, R., Minsky, Y., and Hayden, M. 1998. A Gossip-Style Failure Detection Service. *Proc. Middleware '98 (IFIP)*, 55–70.

Varga, R. S. 1962. *Matrix Iterative Analysis*. Prentice-Hall.

Varga, R. S. 1966. On a Discrete Maximum Principle. *SIAM Journal on Numerical Analysis* 3(2), 355–359.

Wolpert, L. 1969. Positional Information and the Spatial Pattern of Cellular Differentiation. *Journal of Theoretical Biology* 25(1), 1–47.

Xu, Y., Ren, F., He, T., Lin, C., Chen, C., and Das, S. K. 2013. Real-Time Routing in Wireless Sensor Networks: A Potential Field Approach. *ACM Transactions on Sensor Networks* 9(3), Article 35.