

User API

api/v1/active_polls/

Methods: GET

Get active polls

Response example:

```
{
  {
    "poll_id": 1,
    "name": "poll-1",
    "start_date": 2020-04-24,
    "end_date": 2020-05-24,
    "description": "...",
  },
  ...
}
```

api/v1/completed_polls_by_user/

Method: POST

Get polls completed by user

Request example:

```
{
  "user_id": 1
}
```

Response example:

```
{
  {
    "poll_id": 2,
    "user_id": 1
  },
  ...
}
```

api/v1/questions_by_poll/

Method: POST

Get all of the poll's questions

Request example:

```
{
  "poll_id": 1
}
```

Response example:

```
{
  {
    "question_id": 1,
    "poll_id": 2,
    "text": 1,
    "many_answers": true,
  },
  ...
}
```

api/v1/answers_by_question/

Method: POST

Get the question answers

Request example:

```
{
  "question_id": 1
}
```

Response example:

```
{
  {
    "answer_id": 1,
    "question_id": 2,
    "text": 1,
  },
  ...
}
```

api/v1/submit_answers/

Method: POST

Sumbit answers to the poll

Request example:

```
{
  "poll_id": 1,
  "answered_questions": [
    {
      "question_id": 1,
      "answers": [
        { "answer_id": 1 }
      ]
    },
    {
      "question_id": 2,
      "answers": [
        { "answer_id": 4 },
        { "answer_id": 5 }
      ]
    }
  ]
}
```

Response example:

```
{}
```

Admin API

api/v1/add_poll/

Method: POST

Add a new poll

Request example:

```
{
  "poll_name": "some-name",
  "start_date": "2020-12-24",
  "end_date": "2020-12-24",
  "description": "..."
```

Response example:

```
{}
```

api/v1/change_poll/

Method: POST

Change existing poll

Request example:

```
{
  "poll_id": 10,
  "updated_pars": {
    "name": "new_name",
    "end_date": "2020-12-25",
    "description": "...?"
  }
}
```

Response example:

```
{}
```

api/v1/delete_poll/

Method: POST

Delete existion poll

Request example:

```
{
  "poll_id": 10
}
```

Response example:

```
{}
```

api/v1/add_question/

Method: POST

Add a new question to the poll

Request example:

```
{
  "poll_id": 10,
  "text": "Be or not to be?",
  "answers": [
    "be",
    "not to be"
  ],
  "many_answers": false
}
```

Response example:

```
{}
```

api/v1/change_question/

Method: POST

Change existing question

```
Request example:
{
  "question_id": 2,
  "updated_pars": {
    "text": "new text",
    "many_answers": true
  }
}

Response example:
{}
```

api/v1/delete_question/

Method: POST

Delete existing question

```
Request example:
{
  "question_id": 2
}

Response example:
{}
```