Gated replans in a study planner with BKT tracing

Rohit Saji[1*] and Ramesh Prakash Guledgudd[1]

[1*]Department of Data Science and Artificial Intelligence, PES University, 100 Feet Ring Road, Banashankari 3rd Stage, Bengaluru, 560085, Karnataka, India.

*Corresponding author(s). E-mail(s): iam.rohitsaji@gmail.com;
Contributing authors: rameshpg1988@gmail.com;

Abstract

Fixed study plans fail within days. Time logs record hours without measuring understanding. This paper closes the loop with assessment-based proof of learning. The system generates grounded practice from learner materials in one family per call. A server grades each family with its own arm. Bayesian Knowledge Tracing tracks mastery.

Reranked retrieval grounds each question in cited chunks. A verdict gate replans only when proof holds. The gate uses JEV with approve at 0.7. Retrieval on the frozen 754-chunk corpus increases from 0.60 to 0.67 at r@1 and from 0.80 to 0.90 at r@3 with rerank. Groundedness reaches 0.867 with near-duplicate rate 0.004. Live BKT reaches AUC 0.74 and ties the baseline rank while it halves calibration error.

The gated loop converts 4 of 4 synthetic longitudinal cases to replans. The stack runs Qwen3 embeddings plus rerank on demand with Piston grading. Fixed budgets appear in the Methods section with frozen evidence. Live runs show zero console errors across objectives, rubrics, coding grades, guides, practice runs, feedback copy, mastery reads, and ingestion. The scope stays single-learner with synthetic validation. Split-conformal prediction, change detection, and difficulty calibration stay unshipped.

Keywords: Closed-loop tutoring, Bayesian Knowledge Tracing (BKT), reranked retrieval, grounded generation, verdict-gated replanning

1 Introduction

Self-directed learners commit to a fixed plan and leave the plan within days. The plan does not adapt. Logged hours do not prove that study produced understanding. Phase I of this work built an open-loop planner that estimates true pace from session history. It regenerates the plan when the projection diverges from the deadline. The open loop adapts to pace but never checks learning.

Phase II closes the loop with assessment-based proof. The system generates grounded practice from learner materials. An authoritative arm grades each answer, Bayesian Knowledge Tracing tracks mastery, and a Socratic ladder guides the learner before the loop verdict replans. This paper reports the deployable loop and its measured proof.

The Methods section shows fixed budgets and frozen evidence. The Results section shows coherent tables on one corpus. The conclusion repeats the best system with its metric and names limits with numbered next steps. One-to-one tutoring sets the standard, and group methods chase it [1]. Three points set scope.

Every number traces to frozen evidence or live code. Synthetics replace a classroom study, and the text says so wherever it matters. Rejected arms and nulls appear beside positive results.

2 Literature Review

Each entry below names the source, its mechanism, its metric, and the gap it leaves. Table 1 shows the selected and rejected options per stream. A short note on sourcing and a 3-gap summary ends the section.

2.1 Tracing and mastery

BKT tracks a per-skill mastery chance through four fitted terms: prior $P(L_0)$, learn rate T, guess G, and slip S [2]. After each answer the posterior updates from the response and then moves toward mastery by the fitted rate:

$$\begin{aligned} P_{\text{correct}}(L_n) &= \frac{P(L_{n-1})(1-S)}{P(L_{n-1})(1-S) + (1-P(L_{n-1}))G}, \\ P(L_n) &= P_{\text{obs}}(L_n) + (1 - P_{\text{obs}}(L_n))T. \end{aligned} \tag{1}$$

The first term changes the estimate from the observed response. The second term moves the learner toward mastery by the fitted rate.

Chen et al. test a hierarchical Bayesian teaching model in two online experiments with 312 adults [3]. Hierarchical priors show learner-to-learner variation without overfit on sparse data. Their model selects the teacher's next example and leaves the learner's tested skill unselected. It supplies prior structure. BKT supplies the updater.

Zanellati et al. review hybrid tracers that combine Bayesian posteriors with machine learning [4]. Their taxonomy finds hybrids give better results than pure BKT and pure deep learning on correctness prediction. The surveyed hybrids predict answers on large logs. They do not guide what the learner sees next.

Our bake-off places bkt-v1 at AUC 0.888 against 0.889 for the baseline. That shows parity. The control module on top is this project's step.

Mai et al. combine deep temporal models with a probabilistic layer for calibrated, readable estimates [5]. The limit here is cold start. One self-directed learner arrives with almost no graded history. We keep the Bayesian updater with an informed setting from onboarding data, and mastery then drives difficulty.

Deep tracing gives less accuracy for less clarity and needs much data [6]. We reject it here. The loop needs few-shot updates a learner can read, and bkt-v1 already matches the baseline.

2.2 Generation and ranking

The STEM prompting study generates items across subjects and checks them per subject [7]. Coverage is the claim. No record ties a question to its chunk, so you cannot trace a wrong item to its source. Our harness shows groundedness 0.867 with near-duplicate rate 0.004 on cited chunks.

The lecture-to-quiz study generates local multiple-choice items with deterministic shape checks [8]. Shape checks find malformed items, but miss well-formed questions on wrong passages. Each call here makes one single-family question and records its chunk citations.

Tagging work generates knowledge-component tags from items [9]. Tags let us keep per-skill histories. The study ends with the tag and never guides practice. Each problem here has its family label from generation into the run.

Generation uses retrieved passages as its source [10]. The dense arm encodes 754 chunks at 768 dimensions [11]. The lexical arm scores the terms [12]. Reciprocal fusion combines the arms with pool 25 [13].

The reranker reorders the top 50 and increases r@1 by 7 and r@3 by 10 [14].

2.3 Grading authority

The EDUCON study grades short answers with a rubric-driven model [15]. Rubrics make judgments repeatable. Our live matrix grades written runs 4 of 4 with real rubric grades. A rubric cannot run code, so code answers execute in a hidden-test sandbox [16].

The grade-prediction study shows about 0.73 before scheduling [17]. Prediction guides planning. Grading stays separate. Objective runs here succeed in 2 of 2 cases with exact match on authored answers. The server grade stays approved while client checks stay advisory.

2.4 Guidance without answers

Alhazbi et al. review 25 studies and find most valid trace indicators cover time management [18]. That establishes adherence as a metric. It does not guide a learner in a hard problem. Our ladder guides learners from nudge to hint to targeted help to gated reveal.

Uzun et al. connect feedback engagement to self-regulation and course results [19]. Readable feedback helps learning. Each ungated hint tends to give answers, so the system locks the reveal until the learner confirms.

Think-aloud work separates genuine attempts from answer-extracting moves [20]. Our replay converts 4 of 4 verdict-triggered replans after the fix and converts 4 of 4 before it. Feedback copy stays advisory for the same reason and never changes a grade.

2.5 Sourcing note

We built this survey through advisor-guided curation and citation chaining, not a fresh database search. We started with the tracing trio and the loop anchors: single-family generation, per-family arms, the gated ladder, and advisory feedback. One representative work covers each sub-theme. We ran no hundred-scale screening, and we claim none.

Table 1 Phase 2 literature map with selected and rejected options

Stream	Selected	Rejected	Gap it closes
Tracing	BKT bkt-v1	DKT hybrid	Mastery-blind plan
Generation	Single family grounded	Multi-family ungrounded	Untraceable gen
Ranking	Hybrid plus rerank	Dense only	Ungrounded rank
Grading	Server arm per family	Client-side grade	Single signal
Guidance	Gated ladder	Answer-giving tutor	Reveal control
Loop	JEV gate fail-closed	Raw LLM choice	Ungated replan

Generation is fluent but untraceable, and tags guide nothing, so questions cannot support per-skill practice. Grades use one signal or the client, so they cannot support plan decisions. Guidance measures adherence or reveals answers, so attempts stop being evidence.

This loop addresses all three. The system cites sources for generation, and each family has its own approved grade. Difficulty follows mastery, the ladder stays gated, feedback stays advisory, and the verdict triggers regeneration.

3 Materials and Methods

3.1 Closed loop

The loop runs five stages. Generation makes practice from learner materials. Grading scores each answer with the arm that handles the family. Tracing updates mastery, and guidance guides with a ladder and a gated reveal.

The verdict gate decides between 'hold' and 'suggest replan'. 'Keep' writes no event. 'Suggest replan' copies an exact verdict pair onto the new roadmap.

3.2 Server gate and grading arms

One call has one family and one question. A run expands to N calls with bounded concurrency. Objective grading uses exact rules, written grading uses a rubric, and coding grades in a sandbox.

Client checks stay advisory and never change the grade. The coding arm refuses material it cannot ground and marks the attempt honestly.

3.3 Tracing and guidance

BKT bkt-v1 tracks mastery with released parameters. The Adaptive module uses the BKT band and stays advisory. We leave the module uncalibrated by design in this draft. The guide ladder guides learners from nudge to hint to targeted help to gated reveal. Feedback copy uses updated content only with a static fallback. Advisory text never changes a grade.

3.4 Verdict gate

JEV scores. The router applies the 0.7 rule. The loop changes JEV failure to 'hold' through a fail-closed path. The gate approves a replan at 0.7.

The sweep across 0.5 to 0.7 shows agreement at 0.857. The 0.8 setting failed during a live 0.79 dip and we reject it. Each decision records an exact verdict pair for audit.

3.5 Comparison design

The design uses two parts. The offline part uses frozen golds with fold hashes and a fail-closed gate. The longitudinal part runs four synthetic archetypes with held-out separation and scores conversion from verdict to replan and rebound in adherence. The live browser test set stays a deployment check and never adds a number to results.

3.6 Datasets

The retrieval corpus is the frozen ACCA set of 754 chunks with 768-d vectors and zero nulls. OULAD was the Phase-1 calibration source with real-learner logs, and we keep those logs reserved [21]. The 788-chunk split remains a frozen precedent only. Generation golds contain 30 objective plus 6 written plus 4 coding items with an attempt gate of 5. The longitudinal set contains four archetypes named steady, crammer, struggling, and returning. This draft uses no new live-user dataset.

3.7 Tool stack and fixed budgets

Table 2 shows the pinned stack. Fixed budgets appear here as the honesty note. Generation and judging use one provider service [22]. A transformer encoder gives dense vectors [23]. The Qwen3 pair supplies embeddings and rerank from one container [14, 24].

We run reranked-754 on 30 questions times 3 arms. We run the endpoint on 30 questions times 2 flags. The second corpus contains 1094 chunks with 30 verified golds.

The probe uses 395 calls at 0.099 dollars. JEV uses at most 15 calls for the dip replay. Generation uses reasoning off with temperature 0.3 and a 30 s timeout.

Table 2 Pinned tool stack (v0 with versions from live config)

Part	Pin
Generation	OpenRouter flash, reasoning off, T 0.3, 30 s
Feedback	muse-spark low via OpenRouter
Judge	JEV 1.13 hosted API, separate key
Retrieval	Qwen3 pair on demand at :8200
Grading	Piston sandbox at :2000
Client	CodeMirror plus Pyodide advisory

3.8 Reproducibility

Three facts allow reruns. Gates fail closed by default. Each logical call has one request id from frontend to backend logs. We version evidence beside the draft with golds, harness scripts, seeds, and replay outputs.

4 Results and Discussion

4.1 Retrieval and ranking

Table 3 and Figure 1 show the coherent 754 set. Hybrid plus rerank increases r@1 from 0.60 to 0.67 and r@3 from 0.80 to 0.90. MRR increases from 0.720 to 0.797. Dense and hybrid arms reproduce baselines exactly, which confirms the rerank arm. The retired 788 split remains a precedent note below the table and never changes the headline results.

Table 3 Retrieval on the frozen 754-chunk corpus (30Q coherent headline)

Arm	r@1	r@3	r@5	MRR
Dense	0.60	0.77	0.87	0.706
Hybrid	0.60	0.80	0.87	0.720
Hybrid plus rerank	0.67	0.90	0.93	0.797

Note: frozen 788-split precedent is 0.70/0.83/0.90/0.788 dense, 0.73/0.90/0.93/0.816 hybrid, and 0.77/0.97/0.97/0.858 reranked. It is superseded for the headline.

Endpoint numbers match the offline results. Plain search shows 0.60/0.73/0.87/0.703 on the live route. Reranked endpoint shows 0.70/0.90/0.93/0.813. The second DDIA corpus shows the same trend with gains of +16 at r@1, +17 at r@3, and +0.139 MRR.

Title-prefix gives no improvement. We reject INT8 collapse to 0.10 as an arm.




Fig. 1 Retrieval on the frozen 754-chunk corpus (30Q): hybrid plus rerank lifts r@1 from 0.60 to 0.67 and r@3 from 0.80 to 0.90. DDIA second corpus (1094 chunks) confirms the direction with gains of +16 at r@1, +17 at r@3, and +0.139 MRR.

4.2 Generation quality

Table 4 shows the harness. The S-layer over 180 items maintains schema validity at 0.9611 and citation validity at 0.9133. Gold support is 0.7803 and measures a different fact from groundedness.

Near-duplicate rate is 0.0044. The fresh live judge shows groundedness at 0.8667. Coding derivability is 0.5349 and passes the 0.5 gate. Gold agreement is 3 of 3.

Table 4 Generation quality (S-layer n=180 with judge n=30 fresh live)

Metric	Value
Schema valid	0.9611
Citation valid	0.9133
Gold support	0.7803
Near duplicate	0.0044
Cost	$0.061289
Groundedness judge	0.8667 (26/30)
Coding derivable	0.5349 passes 0.5

4.3 Knowledge tracing

Table 5 shows three populations with their scope. The released comparison establishes the prior. Live harness measures real attempts. External anchor establishes the 0.6 baseline. Thesis-safe result shows parity. We leave difficulty calibration unmeasured and the module remains advisory.

Table 5 BKT tracing by population (cite scope with each use)

Population	AUC	ECE
Synthetic bake-off	0.785	0.057
Live harness (282 obs, 139 seqs)	0.7397	0.1401
Running proportion live	0.7368	0.2679
External anchor	0.60–0.61	–

4.4 Closed loop verdicts

Table 6 shows the verdict table. The post-fix replay changes 4 of 4 'suggest replan' verdicts to roadmaps. All four use extend-deadline with an exact verdict copy. Pre-fix showed 4 of 4 at low confidence on span-zero inputs. The dip replay shows 4 of 4 at the September setting and blocks the struggling case at the September-12 setting. The change from low to high shows the intended trend.

Table 6 Verdict-gated replans across four archetypes (all extend-deadline)

Archetype	Verdict	Conf	Sufficiency	Converted
Steady	suggest replan	1.00	0.66–0.77	Yes
Crammer	suggest replan	1.00	0.66–0.77	Yes
Struggling	suggest replan	1.00	0.66–0.77	Yes
Returning	suggest replan	1.00	0.66–0.77	Yes

We select the verdict-gated loop as the reported system. It connects grounded generation, server grading, BKT tracing, and reranked retrieval to a measured replan decision. The live test set allows deployment only. It shows zero console errors across objectives, written rubrics, coding grades, guides, practice runs, feedback copy, mastery reads, and ingestion.

4.5 Architecture figures

We draw all figures to single-column width. Figure 2 shows the deployment with its sidecars, Figure 3 shows the five-stage loop with its gate, and Figure 4 shows the two-part comparison and we keep the check outside.




Fig. 2 Deployment map adapted to single-column width




Fig. 3 Closed loop with verdict gate




Fig. 4 Two-leg comparison pipeline with the deployment check kept separate

4.6 Ablation honesty

Rejected arms follow. Title-prefix gives no improvement on the frozen split. INT8 quantization reduces retrieval to 0.10 at a 2.45x speedup and we reject it. The 0.8 approve gate fails during a live 0.79 dip and we keep 0.7. We reject deep tracing, multi-family calls, client-side grades, and answer-giving tutors (see Table 1). Each rejection shows the limits of the loop.

4.7 Parity and nulls

BKT matches the baseline on rank order and halves its calibration error. That is an equal result with better calibration, not an improvement. Change detection remains a robust null result from Phase I. We leave split-conformal intervals unshipped. We leave difficulty calibration unmeasured, so the Adaptive module remains advisory. Each null limits what the evidence supports.

4.8 Deployment check

The live test set is a deployment check that never adds a number to results. Objective runs succeed in 2 of 2 cases and written rubrics succeed in 4 of 4 cases. Coding grades succeed in 3 of 3 cases and guides succeed in 2 of 2 cases. Practice runs succeed in 2 of 2 cases, feedback checks succeed in 3 of 3 cases, and mastery checks succeed in 2 of 2 cases.

Ingestion completes and the system logs skips. Zero console errors appear across viewports, and the full-book run becomes ready in about 88 seconds and we verify cleanup. The loop uses a managed stack with the sidecar on demand.

5 Conclusion

The verdict-gated loop connects grounded generation at 0.867, BKT at parity with AUC 0.74, and reranked retrieval at 0.67/0.90 to 4 of 4 measured replans. The limits

are compute budget, single-learner scope, synthetic-only validation, honest refusals for coding items, and unshipped refinements.

Numbered next steps are (1) a real-learner study, (2) real-log validation, (3) released conformal intervals, and (4) per-account scale. Code is available at https://github.com/rings0fsaturn/study-planner.

Supplementary information. Supplementary files contain versioned evidence for reranked-754, endpoint retrieval, and the second DDIA corpus. They also cover synthetic data generation, the fresh generation arms, the difficulty baseline, dip replay, and full-book timing.

Acknowledgments. Prof. Ramesh Prakash Guledgudd guides this work.

Declarations

- Funding: Not applicable.
- Conflict of interest/Competing interests: The authors declare no competing interests.
- Ethics approval: Not applicable.
- Consent to participate: Not applicable.
- Consent for publication: Not applicable.
- Availability of data and materials: The frozen 754-chunk corpus with golds plus four synthetic seeds allows reruns.
- Code availability: Code is available at https://github.com/rings0fsaturn/study-planner.
- Authors' contributions: R.S. built the loop and collected the evidence. R.P.G. guided the work.

Appendix A Evidence index

Appendix A lists frozen evidence by table. Retrieval maps to reranked-754 and endpoint maps to live routes. The second corpus maps to DDIA. Generation maps to the harness plus live runs. The loop maps to synthetic data generation plus dip replay.

References

[1] Bloom, B.S.: The 2 sigma problem: The search for methods of group instruction as effective as one-to-one tutoring. Educational Researcher **13**(6), 4–16 (1984)

[2] Corbett, A.T., Anderson, J.R.: Knowledge tracing: Modeling the acquisition of procedural knowledge. User Modeling and User-Adapted Interaction **4**(4), 253–278 (1994)

[3] Chen, A.M., Palacci, A., Vélez, N., Hawkins, R.D., Gershman, S.J.: A hierarchical Bayesian model of adaptive teaching. Cognitive Science **48**(7), 13477 (2024) https://doi.org/10.1111/cogs.13477

[4] Zanellati, A., Di Mitri, D., Gabbrielli, M., Levrini, O.: Hybrid models for knowledge tracing: A systematic literature review. IEEE Transactions on Learning Technologies **17**, 1021–1036 (2024) https://doi.org/10.1109/TLT.2023.3348690

[5] Mai, N.T., Cao, W., Liu, W.: Interpretable knowledge tracing via transformer–bayesian hybrid networks: Learning temporal dependencies and causal structures in educational data. Applied Sciences **15**(17), 9605 (2025) https://doi.org/10.3390/app15179605

[6] Piech, C., Bassen, J., Huang, J., Ganguli, S., Sahami, M., Guibas, L.J., Sohl-Dickstein, J.: Deep knowledge tracing. In: Advances in Neural Information Processing Systems, vol. 28 (2015)

[7] Chan, K.W., Ali, F., Park, J., Sham, K.S.B., Tan, E.Y.T., Chong, F.W.C., Qian, K., Sze, G.K.: Automatic item generation in various STEM subjects using large language model prompting. Computers and Education: Artificial Intelligence **8**, 100344 (2025) https://doi.org/10.1016/j.caeai.2024.100344

[8] Shintani, S.A.: Self-hosted Lecture-to-Quiz: Local LLM MCQ Generation with Deterministic Quality Control. arXiv:2603.08729 (2026)

[9] Moore, S., Schmucker, R., Mitchell, T., Stamper, J.: Automated generation and tagging of knowledge components from multiple-choice questions. In: Proc. ACM Learning @ Scale (L@S), pp. 122–133 (2024). https://doi.org/10.1145/3657604.3662030

[10] Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., Küttler, H., Lewis, M., Yih, W., Rocktäschel, T., Riedel, S., Kiela, D.: Retrieval-augmented generation for knowledge-intensive NLP tasks. In: Advances in Neural Information Processing Systems, vol. 33 (2020)

[11] Karpukhin, V., Oguz, B., Min, S., Lewis, P., Wu, L., Edunov, S., Chen, D., Yih, W.: Dense passage retrieval for open-domain question answering. In: Proc. EMNLP, pp. 6769–6781 (2020). https://doi.org/10.18653/v1/2020.emnlp-main.550

[12] Robertson, S., Zaragoza, H.: The probabilistic relevance framework: BM25 and beyond. Foundations and Trends in Information Retrieval **3**(4), 333–389 (2009)

[13] Cormack, G.V., Clarke, C.L.A., Buettcher, S.: Reciprocal rank fusion outperforms Condorcet and individual rank learning methods. In: Proc. 32nd Int. ACM SIGIR Conf. on Research and Development in Information Retrieval, pp. 75–82 (2009). https://doi.org/10.1145/1571941.1571951

[14] Qwen Team: Qwen3-Reranker-0.6B. Model card, Hugging Face. Cross-encoder reranker in this work; 0.6B parameters, 32k context (2025)

[15] Duong, T.N.B., Meng, C.: Automatic grading of short answers using large language models in software engineering courses. In: Proc. IEEE Global Engineering Education Conference (EDUCON), pp. 1–10 (2024). https://doi.org/10.1109/EDUCON60312.2024.10578839

[16] EngineerMan: Piston: A high performance general purpose code execution engine. GitHub repository, https://github.com/engineer-man/piston. Sandbox used for the coding grading arm (2018)

[17] Islam, M.S., Mukaddes, A.M.M., Uddin, M.: Predict students' performance and optimize preparatory leave: An integrated deep learning and dynamic programming approach. In: Proc. International Conference on Computer and Information Technology (ICCIT) (2024). https://doi.org/10.1109/ICCIT64611.2024.11021881

[18] Alhazbi, S., Al-Ali, A., Tabassum, A., Al-Ali, A.K., Al-Emadi, A., Khattab, T.M., Hasan, M.A.: Using learning analytics to measure self-regulated learning: A systematic review of empirical studies in higher education. Journal of Computer Assisted Learning **40**(4), 1658–1674 (2024) https://doi.org/10.1111/jcal.12982

[19] Uzun, Y., Suraworachet, W., Zhou, Q., Gauthier, A., Cukurova, M.: Engagement with analytics feedback and its relationship to self-regulated learning competence and course performance. International Journal of Educational Technology in Higher Education **22**(1), 17 (2025) https://doi.org/10.1186/s41239-025-00515-3

[20] Zhang, J., Borchers, C., Wang, C., Kumar, V., Teffera, L., McLaren, B.M., Baker, R.S.: Understanding gaming the system by analyzing self-regulated learning in think-aloud protocols. In: Proc. International Learning Analytics and Knowledge Conference (LAK) (2026). https://doi.org/10.1145/3785022.3785025

[21] Kuzilek, M., Hlosta, M., Zdrahal, Z.: Open University Learning Analytics dataset. Scientific Data **4**, 170171 (2017)

[22] OpenRouter: OpenRouter: Unified API for language models. Provider documentation, https://openrouter.ai/docs. Generation and judging run through this provider (2025)

[23] Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, L., Polosukhin, I.: Attention is all you need. In: Advances in Neural Information Processing Systems, vol. 30 (2017)

[24] Qwen Team: Qwen3-Embedding-0.6B. Model card, Hugging Face. Dense encoder in this work; 0.6B parameters, 32k context, up to 1024 dimensions with MRL (2025)