Contents

AWS Migration Plan **1**
1. Summary . . . 1
2. Target architecture . . . 2
   Why two instances . . . 2
   What I'd leave out at this size . . . 2
3. Region choice (M-02) . . . 3
4. Costs . . . 3
   4.1 Unit prices (AWS price list, fetched 2026-11-11) . . . 3
   4.2 Annual cost of the recommended setup . . . 4
   4.3 Other options, per year (on-demand) . . . 4
   4.4 Costs outside AWS (not included above) . . . 5
5. Changes needed in the code . . . 5
6. Migration steps . . . 7
   Rollback . . . 8
7. Operations on AWS . . . 8
8. Risks . . . 8
9. Decisions for the customer . . . 9


AWS Migration Plan

- **Status:** plan, 2026-11-11, for the customer to review. Nothing has been provisioned.
- **Scope:** move `ABCDE-Web-EU`, `RimiScraper-v2` and `BarboraScraper-v1` from Replit to AWS. The databases can stay on Neon or move to Amazon RDS (decision M-01).
- **Prices:** AWS public price list files for `eu-central-1` (Frankfurt) and `eu-north-1` (Stockholm), fetched 2026-11-11. They were published 2026-10-29 (RDS) and 2026-11-05 (VPC). All amounts are in USD and exclude VAT. Annual figures use 8,760 hours.
- **Related:** `PROPOSAL_architecture_consolidation.md` Part B ("always-on worker host"). This plan provides that host. If the plan is accepted, decision D-05 of that proposal becomes "one EC2 instance for both workers" instead of "one Replit Reserved VM".

1. Summary

	Recommendation
Instances	**2 × EC2**: `t4g.small` for the website, `t4g.medium` for both scrapers
Database	Keep Neon at first (M-01). Optionally move later to **1 × RDS PostgreSQL** `db.t4g.small`, Single-AZ, holding all three databases
Region	Same region as the Neon databases while Neon is kept, probably Frankfurt (M-02). Stockholm if everything moves to RDS.
Cost per year	**$661** (Frankfurt, keep Neon, on-demand) up to **$1,067** (Frankfurt, with RDS, on-demand). About **$453–744** with 1-year reserved instances. Full breakdown in §4.

2. Target architecture



Why two instances

- **The workloads are small.**
  - The scrapers make plain HTTP requests (`requests` + BeautifulSoup, no headless browser), and their speed is limited by deliberate crawl delays, not CPU.
  - The Replit plan for a worker was 0.5 vCPU and 2 GB (`BarboraScraper-v1/replit.md`), and a chunk of products uses about 58 MB of memory.
  - The Streamlit admin pages have only one or two users.
  - The site's catalogue is about 5,000+ products.
- **Keeping the scrapers away from the website.** A scraper running out of memory or a stuck worker can't take down the public site. The Streamlit admin pages have no login of their own, so they run on a server with **no open inbound ports**, reached only through AWS Systems Manager.
- **Why `t4g` (Graviton, burstable).** It's the cheapest current-generation option. Both Node 24 and Python 3.11 run on ARM64, and `sharp` and `psycopg2-binary` ship ARM64 builds. Burstable CPU fits a website that is mostly idle and scrapers that are busy at 02:00.
- **Why `t4g.medium` for the scrapers.** It runs two Streamlit apps (around 200–400 MB each), two workers with three threads each, and two schedulers. 4 GB leaves room. `t4g.small` (2 GB) would likely work but leaves little headroom while both nightly runs are active.

What I'd leave out at this size

Service	Why not now
Application Load Balancer	Adds a fixed hourly charge plus usage charges for one backend server. Caddy on the instance handles TLS with Let's Encrypt. Add one when the website runs on more than one server.
NAT Gateway	About $0.05/h plus data charges, which would be more than both instances together. The scraper server uses a public IP with no inbound rules instead.
ECS Fargate / EKS	More expensive than EC2 for services that run around the clock, and more to operate. Reconsider after Part E of the proposal, when there is a single scraper image.
Lambda	Doesn't fit long-running Streamlit apps and jobs that scrape whole categories.
Multi-AZ RDS	Doubles the database price (§4.3). The site is read-only on the store data and can tolerate a short outage. Revisit if it becomes business-critical.

3. Region choice (M-02)

Region	For	Against
Frankfurt (`eu-central-1`)	Neon offers this AWS region. Keeping the servers next to a Neon database there keeps query latency low and avoids cross-region transfer charges.	About 10–14 % more expensive than Stockholm (§4)
Stockholm (`eu-north-1`)	Closest AWS region to Latvia, and the cheapest of the two	Use it only if the databases move to RDS, or if Neon is in a nearby region

First step: check which region the current Neon projects are in. The Neon console shows it, and it's also part of each connection string's hostname. Put the EC2 instances in the same AWS region.

4. Costs

4.1 Unit prices (AWS price list, fetched 2026-11-11)

Item	Unit	Frankfurt	Stockholm
EC2 `t4g.small`, Linux, on-demand	per hour	$0.0192	$0.0172
EC2 `t4g.small`, 1-yr standard RI, all upfront	per year	$99	$89
EC2 `t4g.medium`, Linux, on-demand	per hour	$0.0384	$0.0344
EC2 `t4g.medium`, 1-yr standard RI, all upfront	per year	$198	$178
EBS gp3	per GB-month	$0.0952	$0.0836
EBS snapshot	per GB-month	$0.054	$0.0475

Item	Unit	Frankfurt	Stockholm
Public IPv4 address, in use	per hour	$0.005	$0.005
RDS PostgreSQL `db.t4g.micro`, Single-AZ, on-demand	per hour	$0.019	$0.016
RDS PostgreSQL `db.t4g.small`, Single-AZ, on-demand	per hour	$0.037	$0.033
RDS PostgreSQL `db.t4g.small`, Multi-AZ, on-demand	per hour	$0.074	$0.065
RDS PostgreSQL `db.t4g.small`, 1-yr RI, all upfront	per year	$209	$188
RDS gp3 storage	per GB-month	$0.137	$0.120
RDS backup storage beyond the free allowance	per GB-month	$0.103	$0.090

4.2 Annual cost of the recommended setup

Assumptions: - 30 GB gp3 disk per instance - 2 public IPv4 addresses - 50 GB RDS storage - RDS backups within the free allowance, which equals the provisioned storage

Line	Frankfurt on-demand	Frankfurt 1-yr RI	Stockholm on-demand	Stockholm 1-yr RI
EC2 web `t4g.small`	$168.19	$99.00	$150.67	$89.00
EC2 scrapers `t4g.medium`	$336.38	$198.00	$301.34	$178.00
EBS gp3, 2 × 30 GB	$68.54	$68.54	$60.19	$60.19
Public IPv4 × 2	$87.60	$87.60	$87.60	$87.60
Subtotal: compute (keep Neon)	**$660.71**	**$453.14**	**$599.80**	**$414.79**
RDS `db.t4g.small` Single-AZ	$324.12	$209.00	$289.08	$188.00
RDS gp3, 50 GB	$82.20	$82.20	$72.00	$72.00
Total with RDS	**$1,067.03**	**$744.34**	**$960.88**	**$674.79**

Small extras not in the table: - **EBS snapshots:** about $10–20/year for weekly snapshots. - **CloudWatch Logs:** a few dollars per year at this volume. - **Internet data transfer out:** AWS's free allowance (100 GB/month) should cover a site of this size. Check it against actual traffic, especially from `/api/image-proxy`.

4.3 Other options, per year (on-demand)

Option	Frankfurt	Stockholm	Note
One `t4g.medium` for everything, 1 disk, 1 IP (no RDS)	$414.46	$375.24	Saves about $225–245/year but loses the separation between website and scrapers
Scrapers on `t4g.small` instead of `t4g.medium`	−$168.19	−$150.67	Possible. Watch memory during the 02:00 runs first.
RDS `db.t4g.micro` (1 GB) instead of `small`	−$157.68	−$148.92	Tight for three databases plus the scrapers' concurrent writes
RDS Multi-AZ instead of Single-AZ	+$324.12	+$280.32	Only if a database outage of a few minutes is unacceptable

4.4 Costs outside AWS (not included above)


Service	Used by	Note
Neon PostgreSQL	all, while M-01 = keep	The current Neon bill continues. It goes away if the databases move to RDS.
Google Gemini 2.5 Flash	both scrapers	Probably provided through Replit until now (`AI_INTEGRATIONS_GEMINI_*`). After the move it needs a **Google AI Studio or Vertex AI key and its own billing.**
Google Cloud Vision	website photo scans	Already a direct Google key (`GOOGLE_CLOUD_API_KEY`)
Google Translate	both scrapers	Already a direct key (`GOOGLE_TRANSLATE_API_KEY`)
USDA FoodData Central	both scrapers	Free key
abcde-mcp	website `/mcp` proxy	A separate Replit project (`abcde-mcp.replit.app`). Migrate it as well, or leave it on Replit (M-04).
Domain and DNS	website	Move DNS to Route 53 ($0.50/month per hosted zone) or keep the current DNS provider.

5. Changes needed in the code

Changes needed to run outside Replit:

Repository	Change	Where
all	Replace `.replit` and `replit.nix` with a `Dockerfile` (or systemd units) and a `docker-compose.yml` per server	repo root
all	Load secrets from SSM Parameter Store or Secrets Manager into environment variables at start-up, instead of Replit Secrets	deploy scripts
both scrapers	Gemini: replace `AI_INTEGRATIONS_GEMINI_API_KEY` and `AI_INTEGRATIONS_GEMINI_BASE_URL` with a direct key. With no base URL set, `genai.Client` uses Google's default endpoint.	Rimi: `combined_ingredient_analyzer.py`, `ingredient_ai_categorizer.py`, `suspicion_analyzer.py`. Barbora: `combined_ingredient_analyzer.py`, `food_translator.py`. 14 references in total.
both scrapers	The `ENVIRONMENT`/`DEV_MODE` and `PROD_DATABASE_URL` conventions stay. Set them explicitly in each server's environment.	`database_config.py`
RimiScraper-v2	`combined_startup.sh` runs Streamlit and `worker_with_scheduler.py`. Keep it as the container entrypoint, or split it into two systemd services.	`combined_startup.sh`
BarboraScraper-v1	Add `barbora_worker.py` as its own long-running service. The current startup script runs only the UI and the scheduler. Run it in a loop, because it has no daemon mode (it has `--exit-when-empty`).	new service unit
ABCDE-Web-EU	Remove the `replit.dev` origin from the scan CORS check	`artifacts/api-server/src/routes/routes.ts:`
ABCDE-Web-EU	The `REPLIT_DEV_DOMAIN` branches are only for development. Leave them unset in production, or remove them.	`app.ts`, `mcpMachineProxy.ts`, `mcpPageProxy.ts`
ABCDE-Web-EU	Remove the unused `@replit/object-storage` dependency	`artifacts/api-server/package.json`
ABCDE-Web-EU	Set `SCAN_TOKEN_SECRET` explicitly. Without it, a random secret is created at every restart.	environment
ABCDE-Web-EU	Serve the built SPA and API from one Node process behind Caddy. `pnpm run build`, then `node dist/index.mjs`.	deploy script

6. Migration steps



1. **Prepare.**
   - Find the region of the Neon databases (M-02).
   - Create the AWS account structure, with an IAM user or SSO for the admin and a **budget alert** at, for example, $120/month.
   - Get a Gemini API key.
   - Write Dockerfiles or systemd units.
   - List every secret currently set in the three Replit projects.
2. **Build.**
   - Create one VPC with a public subnet, and two EC2 instances using Amazon Linux 2023 ARM64 and an IAM role allowing SSM and CloudWatch.
   - Security groups: **web-1** accepts 80/443 from anywhere. **scraper-1** accepts no inbound traffic.
   - Give web-1 an Elastic IP. Use Caddy for HTTPS.
3. **Test the website in parallel.** Deploy it to web-1 using the **same Neon connection strings** in read-only use, so both deployments serve the same data. Test it on a temporary hostname: SEO pages, scan, extension endpoint and MCP proxy.
4. **Hand over the scrapers.**
   - Deploy them to scraper-1 with workers and schedulers **stopped**.
   - Stop the workers and schedulers on Replit, then start them on AWS. **Never run both at once.** Two schedulers would queue duplicate jobs, and the Barbora worker doesn't reclaim stale jobs (`THINGS_TO_LOOK_AT.md` §4).
5. **Switch DNS.**
   - Lower the TTL of `abcde.lv`, `www.abcde.lv`, `nutri-score.lv` and `nutriscore.lv` a day ahead.
   - Point them at web-1's Elastic IP.
   - Keep the Replit website running until DNS has propagated.
6. **Watch two nightly runs.** Compare `daily_update_logs` and `lightweight_update_runs` with the previous Replit runs: the number of categories, price changes and errors.
7. **Optional: move the databases** (M-01).
   - Create the RDS instance with three databases.
   - Copy the data with `pg_dump`/`pg_restore` from Neon during a short write freeze, with the workers stopped.
   - Re-create the `product_ingredient_cards` materialized views, and check that the `pg_trgm` extension exists (`schema.sql` uses `gin_trgm_ops`).
   - Switch the connection strings.

8. **Shut down Replit**, after a week without problems.

Rollback

Until step 8 the Replit deployments stay available:

- **Website:** point DNS back to Replit.
- **Scrapers:** stop the AWS services and start the Replit ones again.
- **Databases:** while Neon is kept, there is nothing to roll back. After a move to RDS, keep Neon read-only for a week so you can switch back.

7. Operations on AWS

Concern	Setup
Process supervision	systemd (`Restart=always`) or Docker Compose (`restart: unless-stopped`). This replaces Replit's supervision and `combined_startup.sh`'s restart loop.
Logs	CloudWatch agent sending the systemd/container logs, retained for 30 days
Alarms	EC2 status check failed. CPU credit balance low on scraper-1. A daily check that `daily_update_logs` has a row for today.
Backups	Weekly EBS snapshots through Data Lifecycle Manager. RDS automated backups (7 days) if M-01 = RDS. Neon's own history while M-01 = keep.
Patching	`dnf upgrade` monthly through SSM Patch Manager, or rebuild containers from updated base images
Admin access	SSM Session Manager only: no SSH keys and no open port 22. Streamlit through `aws ssm start-session --document-name AWS-StartPortForwardingSession`.
Cost control	AWS Budgets alert. Buy 1-year RIs or a Compute Savings Plan after a month of stable use.

8. Risks

Risk	Mitigation
Rimi or Barbora rate-limit or block requests from AWS IP ranges, which they may treat differently from Replit's	Test a full category scrape from scraper-1 before cutover (step 4). Keep the existing delays. Contact the retailers if blocked.
CPU credits run out on `t4g` during long nightly runs	`t4g` runs in Unlimited mode by default, so the risk is a small extra charge, not slowdown. Alarm on credit balance. Move to `m7g.medium` if usage is high all the time.
Gemini behaves differently with a direct key (quotas, model access)	Re-run a sample of ingredient analyses before cutover (step 1)
Duplicate jobs while Replit and AWS workers overlap	Strict order in step 4. Never run both.
A secret is left behind on Replit	List the secrets in step 1 and check them off. Rotate the database passwords after cutover.

9. Decisions for the customer

ID	Decision
M-01	**Keep Neon** for now and move the servers only (recommended: no data migration, smallest change, easy rollback). The alternative is to **move to RDS** at the same time (one vendor and roughly $400/year more on AWS, but one more risky step during cutover). This can be done later as step 7.
M-02	**Same region as Neon**, probably Frankfurt (recommended: low latency, no cross-region transfer). The alternative is Stockholm, cheaper and closer to Latvia, but only sensible once the databases are on RDS.
M-03	**Two instances** (recommended: the public site is separated from the scrapers, and admin pages aren't exposed). The alternative is **one `t4g.medium`** (about $225–245/year cheaper, but a single point of failure).
M-04	**Leave `abcde-mcp` on Replit** for now (recommended: it's a separate service behind a fixed URL, and the website only proxies to it). The alternative is to migrate it too, as a third small service on web-1.
M-05	**On-demand for the first month, then 1-year reserved instances or a Savings Plan** (recommended: confirm the sizing before committing, then save about 30–40 %). The alternative is to commit on day one.