



```
$ mortgage-calculator --help
```

Introduction to Software Engineering in the Age of AI ■

```
# A hands-on introduction,  
# built one system at a time
```



```
<mortgage_calculator />
```

Introduction to Software Engineering in the Age of AI

A hands-on introduction, built one working system at a time

Robert Ioffe

2026

Contents

Introduction to Software Engineering in the Age of AI	1
Chapter 0 — Orientation	5
Chapter 1 — Meet Your Coding Agent	19
Chapter 2 — Writing SPEC.md	31
Chapter 3 — Holding the Agent to a Standard	39
Chapter 4 — The Domain: Fixed Mortgages	45
Chapter 5 — Tests & Test-Driven Development	55
Chapter 6 — Mathematical Core Library	69
Chapter 7 — Validation	77
Chapter 8 — Command Line Interface	87
Chapter 9 — Calculator UI	101
Chapter 10 — Tool Interface	111
Chapter 11 — LLM Interface: Enter A Second Model	119
Chapter 12 — Evaluation	129
Chapter 13 — Hardening	141
Appendix — Where to Go Next	151
Closing	157
License	163

Introduction to Software Engineering in the Age of AI

To my wife, Ellen, for her patience and support.

Who This Book Is For

This book is written for first-year students and casual learners — people who are curious about software engineering and willing to sit down and build something real, but who don't yet have a professional engineering background to draw on.

Here's what we assume you *do* have: comfort using a computer (you can find a file, open a terminal, install something), and enough curiosity about numbers to follow a formula when it's explained rather than just handed to you. Here's what we assume you *don't* have: prior experience with Python, git, or any of the tools this book introduces. If you've never opened a terminal before, Chapter 0 starts there, on purpose.

We should also say plainly who this book is *not* for. If you're already a working software engineer looking for advanced patterns in agentic development — multi-agent orchestration, production-grade evaluation infrastructure, enterprise deployment — you'll outgrow this book quickly, and that's fine. This is a first book, not a deep one. We'd rather tell you that now than have you discover it forty pages in.

What “Hybrid” Means in This Book

You’ll see the word *hybrid* a lot in the chapters ahead, so it’s worth defining before we use it for the first time.

A hybrid system, as this book means it, has two parts: a core that you design, write, and verify yourself — and an AI-assisted layer built around that core, where an agent drafts and a model reasons, but neither one gets to decide what “correct” means. That decision stays with you, and it gets written down, in three different forms, at three different points in the book: first as a plain-language spec, then as executable tests, then as a formal schema a language model can call. Same contract, three altitudes. You’ll notice this pattern recur — we’ve flagged it with a callout box each time it shows up, because it’s the actual idea this book is trying to teach, more than any individual tool.

This split — human-verified core, AI-assisted layer — isn’t a compromise or a hedge. It’s the whole point. A book that taught you to let an agent write everything would be teaching you to trust something you can’t yet evaluate. A book that banned AI assistance entirely would be pretending the tools in Chapter 1 don’t exist, or don’t matter. This book tries to do something more useful than either: show you exactly where the boundary between “yours” and “assisted” belongs, and give you enough practice drawing that line yourself that you can keep drawing it correctly long after you’ve finished the last chapter.

How This Book Is Structured

Two threads run through this book side by side, braided rather than stacked.

The first is **tools of the trade** — the terminal, git, Python, a coding agent, local and hosted language models, and everything in between. We introduce each tool right before the chapter that needs it, not all at once up front. You won’t get a 300-page tools reference before you’re allowed to write a line of code.

The second is **one system, built in stages**: a hybrid mortgage calculator, extended chapter by chapter from an empty repository to a working application with three different front ends — a command line, a graphical interface, and a language model that can operate it on your behalf. Every chapter leaves that system a little more complete, and a little more trustworthy, than it found it.

Most build chapters follow the same shape: a goal, the design decisions behind it, a test-driven development cycle, an implementation (often agent-assisted), an honest look at what the agent’s role actually was, and a checkpoint — a clear statement of what should be true about your system right now. We’re naming that shape once, here, so that by Chapter 3 it feels familiar instead of repetitive. Alongside it, you’ll see two recurring devices: a **definition of done** checklist that grows a line or two with each chapter, and **process concept** callout boxes marking ideas — like TDD, or “the spec was wrong, not the code” — that matter well beyond the chapter they first appear in.

How to Use This Book

This book is meant to be built along with, not just read. You’ll get more out of every chapter by actually typing the commands, running the tests, and reading the diffs an agent proposes than by reading a description of someone else doing it. That said, if you want to read it straight through first to get the shape of the thing before building anything, that works too — just know that the “definition of done” checklists and worked examples are written for someone with a terminal open.

Before Chapter 0, you need one thing: a computer capable of running a local language model. We’ll help you figure out whether yours qualifies in Chapter 1, with a plain hardware gut-check rather than a spec sheet you have to interpret yourself. If your setup turns out not to be enough, or gives you trouble, Chapter 1 also includes an escape hatch — a path to a hosted model that keeps you moving without derailing the rest of the book. You can come back to running things locally later, once the pressure’s off.

A note on pacing: every chapter ends at a checkpoint, and every checkpoint describes exactly what should be true about your project at that point. If something’s not working, that checkpoint is there so you can compare against a known-good state instead of debugging in isolation, wondering how far back the problem goes. Use it.

Finally, permission to skip things: the Appendix covers tools and practices — Docker, CI/CD, type checking, and a few others — that are genuinely useful but not required to finish this book. Skip it entirely on your first pass. It’ll still be there when a future project actually needs it.

A Note on What This Book Doesn’t Cover

In the interest of finishing a book you’ll actually complete, we left some real, valuable things out on purpose: Docker, continuous integration, static type checking, pre-commit automation, and a couple of others. None of them are missing by accident, and none of them are things we think you shouldn’t eventually learn — they’re just overhead this particular project, at this particular level, doesn’t need yet. Each one gets a short, honest description in the Appendix: what it does, what it would have added here, and where to go looking when you’re ready for it.

That’s the scope discipline this whole book tries to model, starting now, before Chapter 0 even begins: know what you’re building, know what you’re deliberately leaving out, and write both of those things down.

— *Robert Ioffe*

Portland, Oregon

September 1, 2026

4 *INTRODUCTION TO SOFTWARE ENGINEERING IN THE AGE OF AI*

Chapter 0 — Orientation

Contents

0.1 Why This Chapter Exists	7
0.2 The Terminal	7
0.2.1 Opening a Terminal	7
0.2.2 Navigation	7
0.2.3 File Basics	8
0.2.4 Why the Terminal Matters More Now, Not Less	8
0.3 Git Basics	8
0.3.1 What Version Control Is Actually For	8
0.3.2 Installing and Configuring Git	8
0.3.3 The Core Loop	9
0.3.4 Reading a Commit Log	9
0.4 GitHub.com	9
0.4.1 Creating an Account	9
0.4.2 Installing and Authenticating gh	9
0.4.3 SSH Keys, Briefly	10
0.4.4 Creating and Connecting the Repository	10
0.4.5 Reading a Diff	11
0.4.6 Branches	11
0.4.7 A First Look at a Pull Request	12
0.5 vi, Just Enough	12
0.5.1 Why Bother	12
0.5.2 Modes	12
0.5.3 The Commands You Actually Need	12
0.5.4 When to Reach for It	13
0.6 Python 3.12	13
0.6.1 Installing	13
0.6.2 Checking Your Install	13
0.6.3 What’s Relevant Here	13
0.7 uv & Good Project Structure	14
0.7.1 What uv Is	14
0.7.2 Initializing the Project	14
0.7.3 Project Layout	15
0.7.4 Adding a Dependency	16
0.7.5 The Skeleton You’re Building Toward	16
0.8 Checkpoint	17

0.1 Why This Chapter Exists

Every chapter after this one assumes you have a few things already in place: a terminal you're not afraid of, a git repository that's tracking your work, and a Python project set up the way the rest of this book expects. This chapter builds all of that. Nothing here is specific to mortgages, AI, or agents — it's the ground floor everything else stands on.

By the end of this chapter, you'll have an empty-but-real project: initialized, version-controlled, pushed to GitHub, and ready to hand to a coding agent in Chapter 1.

0.2 The Terminal

0.2.1 Opening a Terminal

- **macOS:** open Spotlight (Cmd+Space), type **Terminal**, press Enter.
- **Linux:** almost every distribution ships a terminal app in its applications menu; on many, Ctrl+Alt+T opens one directly.
- **Windows:** install [Windows Terminal](#) from the Microsoft Store, and use it to run WSL (Windows Subsystem for Linux) rather than the classic Command Prompt. This book assumes a Unix-like shell throughout; WSL gives you one without leaving Windows.

Whichever you use, you should end up looking at a mostly-empty window with a blinking cursor next to a **prompt** — something like `robert@machine ~ %`. That prompt is waiting for you to type a command.

0.2.2 Navigation

Three commands get you almost everywhere:

```
pwd          # print working directory - "where am I?"
ls           # list what's in the current directory
cd Documents # change directory - "go here"
```

A few navigation shortcuts worth knowing immediately:

```
cd ..        # go up one level
cd ~         # go to your home directory
cd -         # go back to wherever you just were
```

Paths can be **relative** (`cd Documents`, starting from where you are) or **absolute** (`cd /Users/robert/Documents`, starting from the very top). When in doubt, `pwd` tells you where “where you are” actually is.

0.2.3 File Basics

```
mkdir mortgage-calculator-book    # make a new directory
touch notes.txt                    # create an empty file
cat notes.txt                      # print a file's contents
rm notes.txt                       # delete a file - there is no trash can, no undo
```

That last one deserves its own line: **rm does not ask twice, and it does not go to a recycle bin.** Get in the habit of double-checking what you're about to delete, especially once wildcards enter the picture (`rm *.txt` deletes *every* `.txt` file in the current directory, no confirmation).

0.2.4 Why the Terminal Matters More Now, Not Less

It might seem like an AI-assisted book would need the terminal less than an older one — surely the agent handles the typing? In practice, the opposite is true. Pi, the coding agent you'll meet in Chapter 1, does its work *in* a terminal: reading files, running commands, executing tests. Understanding the terminal isn't a prerequisite you'll outgrow once the agent shows up — it's how you'll read what the agent is actually doing, and how you'll independently verify it.

0.3 Git Basics

0.3.1 What Version Control Is Actually For

Git is often introduced as “backup,” which undersells it. What git actually gives you is a series of **checkpoints** — snapshots of your project at moments you chose, each one recoverable, each one comparable to any other. That matters for any project, but it matters especially once an agent is also editing your files: git is how you know exactly what changed, when, and whether you want to keep it.

0.3.2 Installing and Configuring Git

Check whether you already have it:

```
git --version
```

If that fails, install it via your system's package manager (`brew install git` on macOS, `sudo apt install git` on Debian/Ubuntu-based Linux, or the WSL equivalent). Then tell git who you are — it stamps this on every commit you make:

```
git config --global user.name "Your Name"
git config --global user.email "you@example.com"
```

Remember these two values — they resurface sooner than you'd expect. Section 0.7.2 will show you exactly where.

0.3.3 The Core Loop

```
cd mortgage-calculator-book
git init                # start tracking this directory
git status              # what's changed since the last commit?
git add SPEC.md        # stage a specific file
git add .               # stage everything that's changed
git commit -m "Initial commit" # save a checkpoint, with a message
```

`git status` is the command you'll run constantly — more than any other in this book. It tells you what's staged, what's changed but unstaged, and what `git` doesn't know about yet. Run it often; there's no penalty for checking.

0.3.4 Reading a Commit Log

```
git log --oneline
```

This gives you a compact history of every checkpoint you've made — one line per commit, most recent first. As this project grows across the rest of the book, this is how you'll orient yourself: “what did I actually do in Chapter 4?”

Process concept: commits as checkpoints. A commit is cheap, fast, and reversible in a way that makes it worth doing far more often than feels necessary at first. Get in the habit now, before Chapter 1 hands your repository to an agent: commit before you let anything — agent or otherwise — make a change you haven't reviewed yet. If something goes wrong, you want a recent checkpoint to fall back to, not a blank slate.

0.4 GitHub.com

0.4.1 Creating an Account

Sign up at github.com if you haven't already. You don't need to create a repository through the website yet — section 0.4.4 below sets one up directly from the terminal, which turns out to be less work once you have one more tool installed.

0.4.2 Installing and Authenticating `gh`

`gh` is GitHub's own command-line tool — it lets you create repositories, open pull requests, and authenticate, all without leaving the terminal. Install it following the instructions at cli.github.com (on macOS: `brew install gh`), then confirm:

```
gh --version
```

Now authenticate:

```
gh auth login
```

This starts an interactive flow: choose `GitHub.com`, then choose your preferred protocol — **SSH** is this book’s recommendation, for the reason section 0.4.3 explains — then let it open a browser to confirm the login. If you chose SSH, `gh` will offer to generate a new SSH key and upload it to your account for you automatically. Say yes; that’s the easiest path, and it means section 0.4.3 below is mostly just explaining what just happened rather than more work for you to do.

0.4.3 SSH Keys, Briefly

Every push to GitHub needs to prove it’s really you. SSH keys are how: a matched pair of cryptographic keys, one **private** (stays on your machine, never shared), one **public** (uploaded to GitHub). GitHub can use the public key to confirm that whoever’s pushing holds the matching private key, without you typing a password or token on every push.

If you let `gh auth login` generate a key for you in 0.4.2, this is already done — skip to the verification command below. If you’d rather set it up by hand, or want to see what `gh` did automatically, here’s the manual version:

```
ssh-keygen -t ed25519 -C "you@example.com"    # press enter through the defaults
eval "$(ssh-agent -s)"
ssh-add ~/.ssh/id_ed25519
cat ~/.ssh/id_ed25519.pub                    # copy this output
```

Then, in a browser: GitHub → Settings → SSH and GPG keys → New SSH key, and paste what you copied.

Either way — automatic or manual — verify it worked:

```
ssh -T git@github.com
```

You’re looking for `Hi <your-username>! You've successfully authenticated, but GitHub does not provide shell access.` That message, not an error, means you’re set up correctly.

0.4.4 Creating and Connecting the Repository

With `gh` authenticated, creating a repository and connecting your local project to it is one command, run from inside `mortgage-calculator-book`:

```
gh repo create mortgage-calculator-book --public --source . --remote origin
```

This creates the repository on GitHub, and wires up your local repository’s `origin` remote to point at it — both steps 0.4.4 and part of what used to be a separate “connect local to remote” step, done together.

If you’d rather create the repository through the browser instead: go to github.com/new, name it `mortgage-calculator-book`, and leave it empty

— no README, no `.gitignore` (0.7.3 creates that one properly, before it’s actually needed). Then connect it by hand:

```
git remote add origin git@github.com:YOUR_USERNAME/mortgage-calculator-book.git
```

Either path, finish by making sure your branch is named `main` and pushing:

```
git branch -M main          # only needed if `git branch` shows something else
git push -u origin main
```

After this, `git push` alone (no flags) will work for future commits.

0.4.5 Reading a Diff

Before going further, one concept worth naming properly, because you’ll rely on it constantly starting in Chapter 1: a **diff** — short for “difference” — is a line-by-line comparison between two versions of a file. Run `git diff` after changing a tracked file, and git shows you exactly what changed: lines removed, lines added, and a little unchanged context around them so you can see where the change sits.

For example, editing a line in `README.md` might produce:

```
# Mortgage Calculator
-A calculator.
+Calculates the fixed periodic payment for a fixed-rate mortgage.
```

The unprefixed line is unchanged context. The `-` line is what the file used to say. The `+` line is what replaced it. That’s the entire vocabulary: minus means removed, plus means added, no prefix means unchanged.

This is arguably the single most load-bearing skill in this whole book. Starting in Chapter 1, every time Pi proposes a change, you’ll be reading a diff like this one to see exactly what it’s proposing before you accept it.

0.4.6 Branches

A **branch** is a parallel line of history — a place to make changes without touching your main line of work until you’re ready to merge them back in.

```
git checkout -b try-something    # create and switch to a new branch
git checkout main                # switch back
```

This matters sooner than you might expect: in Chapter 1, you’ll want a branch to work in *before* an agent starts editing your project, so that reviewing its changes is a matter of looking at a diff — the skill from 0.4.5 — not untangling your main line of history.

0.4.7 A First Look at a Pull Request

A pull request (PR) is GitHub’s way of proposing that changes on one branch be merged into another — with a place to review the diff, leave comments, and decide whether to accept it. You don’t need the full workflow yet; just recognize the shape of one when you see it. We’ll use pull requests informally, as they come up naturally, rather than teaching the whole GitHub Flow up front.

0.5 vi, Just Enough

0.5.1 Why Bother

You will, at some point in this book — or in real engineering work afterward — end up needing to edit a file with no graphical editor available. The most common version of this: connecting to a remote machine over SSH (the same secure-connection technology from 0.4.3, just used here to log into a server rather than to authenticate with GitHub) and finding yourself with only a terminal — no windows, no mouse, no familiar text editor installed, just whatever’s already on that machine. `vi` (or its more common modern form, `vim`) is installed almost everywhere by default, which is exactly why twenty minutes now saves you from being stuck later.

0.5.2 Modes

`vi`’s defining quirk is that it has **modes** — the same keys do different things depending on which mode you’re in.

- **Normal mode** (where you start): keys are commands, not text.
- **Insert mode**: keys are text, typed normally.
- **Command mode**: for saving, quitting, and search-and-replace.

0.5.3 The Commands You Actually Need

<code>i</code>	enter insert mode (start typing)
<code>Esc</code>	leave insert mode, back to normal
<code>:w</code>	write (save)
<code>:q</code>	quit
<code>:wq</code>	write and quit
<code>dd</code>	delete the current line
<code>/word</code>	search for "word"

That’s genuinely enough to survive. Open a scratch file and practice: `vi scratch.txt`, press `i`, type a sentence, press `Esc`, then `:wq`. Confirm it actually saved:

```
cat scratch.txt
```

You should see the sentence you typed printed back to you.

0.5.4 When to Reach for It

vi is not this book's daily driver — most of your editing will happen in whatever full editor you're comfortable with, or through the agent itself. Treat vi as a tool for the specific situation where nothing else is available, not as something you need to master.

0.6 Python 3.12

0.6.1 Installing

Download Python 3.12 from python.org or install it via your package manager. This book uses 3.12 specifically — later chapters rely on language features and standard-library behavior introduced by that version, so an older Python may produce confusing, version-specific errors that have nothing to do with your code.

0.6.2 Checking Your Install

```
python3 --version
```

You're looking for Python 3.12.x. If you have multiple versions installed and the wrong one shows up, uv (0.7 below) will help you pin the right one per-project, so don't spend too long fighting your system's default.

0.6.3 What's Relevant Here

If you've seen Python tutorials from a few years ago, one thing is worth explaining properly before it shows up throughout this book: **type hints**. A type hint is an optional annotation on a function's parameters and return value, stating what kind of data is expected:

```
def greet(name: str) -> str:
    return f"Hello, {name}"
```

Here, `name: str` says the `name` parameter should be a string, and `-> str` says the function returns a string. Python doesn't strictly enforce these at runtime by default — they're documentation, for you and for Pi starting in Chapter 1, more than an ironclad guarantee — but they make code substantially easier to both read and generate correctly, which is why this book uses them in every function from Chapter 6 onward. Error messages are also noticeably more specific about *where* and *why* something went wrong than in older Python versions. Both matter for this book — you'll be reading type hints throughout, and reading error messages closely is a skill this book leans on more than most.

0.7 uv & Good Project Structure

0.7.1 What uv Is

uv is a fast, modern tool for managing Python projects — dependencies, virtual environments, and the Python version itself, all through one tool instead of the traditional pip-plus-venv-plus-something-else combination. This book uses uv throughout because it removes a category of setup friction that has nothing to do with learning software engineering.

Install it following the instructions at docs.astral.sh/uv, or via your system's package manager — on macOS, `brew install uv` works just as well. Either path works fine for this book; use whichever you're more comfortable keeping updated. Then confirm:

```
uv --version
```

0.7.2 Initializing the Project

```
uv init
```

This generates a `pyproject.toml` — the file that describes your project: its name, its dependencies, and how it's built. Here's what it actually contains right after running `uv init` (this example is from the author's own machine — yours will show your own name and email, not this one):

```
[project]
name = "mortgage-calculator-book"
version = "0.1.0"
description = "Add your description here"
readme = "README.md"
authors = [
    { name = "Robert Ioffe", email = "robert.ioffe@vinipuh.com" }
]
requires-python = ">=3.12"
dependencies = []

[project.scripts]
mortgage-calculator-book = "mortgage_calculator_book:main"

[build-system]
requires = ["uv_build>=0.12.5,<0.13.0"]
build-backend = "uv_build"
```

A few things worth noticing. The `authors` field wasn't typed by hand — `uv init` pulled it straight from the same `git config --global user.name` and `user.email` you set back in 0.3.2, which is why it was worth getting those right early. `dependencies = []` is empty for now; it starts filling up in Chapter 5. And `[project.scripts]` already contains an entry pointing at a `main` function

that doesn't exist yet anywhere in your project — `uv init` generates this automatically as a placeholder for a command-line entry point; Chapter 8 replaces it with the CLI's real one, so don't worry about it being unfulfilled until then.

You'll come back to this file constantly; every `uv add` command in later chapters edits it for you.

0.7.3 Project Layout

This book uses a **src layout**: your actual package lives inside a `src/` directory, rather than sitting directly in the project root.

```
mortgage-calculator-book/
+-- .gitignore
+-- pyproject.toml
+-- uv.lock
+-- README.md
+-- SPEC.md
+-- src/
|   |-- mortgage_calculator_book/
|   |-- __init__.py
+-- tests/
```

The reason: a `src` layout forces your code to be *installed* to be imported, the same way it would be for anyone else using it — which catches a whole class of “works on my machine because I happened to be in the right directory” bugs before they happen. It's a small amount of extra structure up front that pays for itself the moment you write your first test in Chapter 5.

One more file belongs in this skeleton before the first commit: `.gitignore`. 0.4.4 deliberately left it out when the GitHub repository was created — this is where it actually gets built, and it needs to exist *before* anything below generates the files it's meant to exclude, not after:

```
vi .gitignore

# Byte-compiled / cached Python files
__pycache__/
*.pyc
*.pyo

# Test and linter caches
.pytest_cache/
.ruff_cache/

# Virtual environments
.venv/
```

Every one of these gets created automatically as this project grows — `.venv/`

by `uv` itself, starting with `uv add` in 0.7.4 just below; `__pycache__`/ the first time any Python file actually runs; `.pytest_cache/` and `.ruff_cache/` once `pytest` and `Ruff` exist, in Chapters 5 and 3. None of them belong in `git`: they’re regenerable, often large, and specific to your machine, not your project. Skip this file now, and a plain `git add .` in any later chapter will happily stage all of it.

To check your own layout matches this at a glance, rather than reading through nested `ls` output by hand, either of these works:

```
tree -I '.git'           # brew install tree on macOS if you don't have it
ls -R                   # no install needed, less readable for deep trees
```

Once it matches, commit and push it — this is a real checkpoint, worth its own commit message:

```
git add .
git commit -m "Set up project skeleton"
git push
```

Then open your repository on `github.com` in a browser and confirm the files are actually there. This is worth doing deliberately, not just trusting the terminal: a push can succeed locally against the wrong remote, or against a branch you didn’t mean to push, and the only way to be sure is to look.

0.7.4 Adding a Dependency

```
uv add requests
```

This updates `pyproject.toml` and creates (or updates) `uv.lock` — a file that pins the *exact* version of every dependency, direct and indirect, so that “it works on my machine” means the same thing on any machine that runs `uv sync`. You won’t need any dependencies yet in this chapter; you’ll see this command for real starting in Chapter 5.

0.7.5 The Skeleton You’re Building Toward

By the end of this chapter, your project should match the layout above, minus anything you haven’t built yet — just `.gitignore`, `pyproject.toml`, `uv.lock`, an empty `README.md` and `SPEC.md`, and an empty `mortgage_calculator_book` package. Every later chapter adds to this same skeleton; nothing gets rebuilt from scratch.

Confirm it works:

```
uv run python -c "import mortgage_calculator_book; print('ok!')"
```

If that prints `ok`, your project is wired together correctly.

0.8 Checkpoint

Before moving to Chapter 1, this should all be true:

- ☐ You can open a terminal and navigate with `pwd`, `ls`, `cd`
- ☐ Git is installed and configured with your name and email
- ☐ `mortgage-calculator-book` is a git repository with at least one commit
- ☐ `gh` is installed and authenticated (`gh auth login` completed successfully)
- ☐ `ssh -T git@github.com` prints the “successfully authenticated” message
- ☐ You can explain, in your own words, what a diff shows and why the `+/-` prefixes matter
- ☐ You can open, edit, and save a file in `vi` without help, and verify the save with `cat`
- ☐ `uv run python --version` reports 3.12.x
- ☐ `uv run python -c "import mortgage_calculator_book; print('ok')"` prints `ok`
- ☐ `.gitignore` exists and excludes `__pycache__/`, `.pytest_cache/`, `.ruff_cache/`, and `.venv/`
- ☐ Your project has been committed and pushed, and you’ve confirmed the files are visible on `github.com` in a browser — not just assumed from a successful-looking terminal command

What’s next: Chapter 1 hands this repository to a coding agent for the first time — installing Pi, connecting it to a local model, and making your first small, reviewed, agent-assisted change.

Chapter 1 — Meet Your Coding Agent

Contents

1.1 Why This Chapter Exists	21
1.2 What a Model Actually Is	21
1.2.1 Tokens	23
1.2.2 Context Windows	23
1.2.3 Local vs. Hosted	23
1.3 Ollama	23
1.3.1 Installing	23
1.3.2 Pulling a Model	24
1.3.3 A First Raw Conversation	24
1.3.4 Where the Model Lives	24
1.4 Choosing a Local Model for the Coding Agent	24
1.4.1 Why the Choice Matters Here Specifically	24
1.4.2 This Book’s Working Example: Qwen3	24
1.4.3 A Hardware Gut-Check	25
1.5 Installing and Configuring Pi	25
1.5.1 What Pi Actually Does	25
1.5.2 Installation	25
1.5.3 Pointing Pi at Your Local Model	26
1.5.4 Skills	26
1.5.5 Starting Pi in the Repository	26
1.6 Your First Agent-Assisted Interaction	27
1.6.1 A Deliberately Small Task	27
1.6.2 Reading the Diff	27
1.6.3 What “Trust but Verify” Looks Like Here	28
1.7 Escape Hatch: If Local Setup Isn’t Working	28
1.7.1 Recognizing the Signs	28
1.7.2 A Minimal Fallback	28
1.7.3 This Isn’t Permanent	29
1.8 Checkpoint	29


1.1 Why This Chapter Exists

Chapter 0 gave you an empty, properly structured project. This chapter gives that project a collaborator. By the end, you'll have a local language model running on your own machine, a coding agent called Pi configured to use it, and — most importantly — a first small, deliberately reviewed interaction with that agent, on the record in your git history.

Nothing gets built for the mortgage calculator in this chapter. That starts in Chapter 4. This chapter is entirely about setting up the working relationship you'll rely on for the rest of the book.

1.2 What a Model Actually Is

A language model, at a basic level, is a program trained on enormous amounts of text that has learned to predict what text comes next, given what came before. That's the whole definition this book needs. Everything below just unpacks what that prediction process implies in practice — and the diagram gives you the shape of it before the prose does:



1.2.1 Tokens

A language model doesn't read text the way you do. It breaks text into **tokens** — small chunks, sometimes whole words, sometimes fragments of words — and predicts, one token at a time, what's likely to come next. That's the entire mechanism underneath everything Pi does: read some tokens, predict the next ones, repeat. It's worth holding onto this plain description, because it's easy to start attributing more to a model than that description supports, and this book would rather you keep a clear, ungenerous picture of what's actually happening.

1.2.2 Context Windows

A model can only “see” a limited number of tokens at once — its **context window**. Everything outside that window, the model simply doesn't have access to. This matters more than raw model size for almost everything you'll do in this book: a smaller model that can see your whole file is often more useful than a larger one that can only see half of it. You'll feel the practical effects of this directly once Pi starts working across multiple files in later chapters.

1.2.3 Local vs. Hosted

A **local** model runs entirely on your own machine — private, free to run repeatedly, but limited by your hardware. A **hosted** model runs on someone else's infrastructure, reachable over the internet — typically more capable, but costing money per use and requiring a network connection. This book uses both: a local model for Pi in this chapter, and later, in Chapter 11, a choice between a second local model and a hosted one for the calculator's own intelligence engine — two different jobs, and the right answer isn't the same for both.

Process concept: demystifying the agent, early. It's worth being blunt about this now, before Pi has done anything impressive: the agent you're about to install is a tool with real limits, not an oracle. Everything in this book's approach — reviewing diffs, writing tests first, keeping a human-authored spec — assumes you'll treat it that way throughout. Chapter 1 is a strange place to plant that idea, before you've even seen the tool work, but it's easier to keep a level head about a tool before it impresses you than after.

1.3 Ollama

1.3.1 Installing

[Ollama](#) is a tool for running language models locally with minimal setup. Download and install it for your platform, then confirm:

```
ollama --version
```

1.3.2 Pulling a Model

```
ollama pull qwen3:8b
```

This downloads the model’s weights to your machine — a multi-gigabyte file, so this step takes a few minutes depending on your connection. (We’ll pick the specific model for Pi’s job in section 1.4; `qwen3:8b` here is just to confirm Ollama itself works.)

1.3.3 A First Raw Conversation

Before wiring anything to Pi, talk to the model directly:

```
ollama run qwen3:8b
```

This drops you into an interactive prompt. Ask it something simple — “what is a checksum?” — and read the response. This isn’t testing Pi yet; it’s building a baseline sense of what the underlying model sounds like, on its own, with no agent framework around it. Type `/bye` to exit.

1.3.4 Where the Model Lives

Model weights are stored under Ollama’s own data directory (`~/.ollama` on macOS and Linux by default). If you’re working with limited disk space, `ollama list` shows what you’ve pulled, and `ollama rm <model>` removes one. Worth knowing before you’ve pulled three 8-gigabyte models you don’t need anymore.

1.4 Choosing a Local Model for the Coding Agent

1.4.1 Why the Choice Matters Here Specifically

Not every model is good at the same things. A model tuned for open-ended conversation isn’t necessarily good at reading a diff, following an instruction precisely, or staying inside the bounds of a file it was asked to edit. The job in this chapter is narrow — coding agent support — and it’s worth picking a model suited to that job rather than whatever’s most popular in general.

1.4.2 This Book’s Working Example: Qwen3

This book uses a Qwen3 variant as its running example for Pi’s model, sized to run well on typical development hardware while still handling code-focused tasks competently:

```
ollama pull qwen3:27b
```

On macOS specifically, pull the MLX-optimized variant instead — built for Apple Silicon rather than a generic cross-platform target:

```
ollama pull qwen3.8:27b-mlx
```

At roughly 18GB, it's a smaller download than the generic build, and runs noticeably better on Apple Silicon's unified memory architecture. Either variant gives Pi meaningfully better judgment on multi-file changes than the smaller 8B model from 1.3.2, if your hardware supports it. If not, 1.4.3 below will help you decide where to land.

1.4.3 A Hardware Gut-Check

As a rough guide — not a precise spec, just enough to self-select before installing something too large:

Available RAM	Reasonable model size
8 GB	3–4B parameters, quantized
16 GB	7–8B parameters, quantized
32 GB	13–14B parameters
64 GB+	27B+ parameters

Quantization — reducing the precision of a model's internal numbers — trades a small amount of accuracy for a large reduction in memory and disk use, which is why quantized model sizes appear throughout this table rather than the full-precision numbers you might see quoted elsewhere. Ollama pulls a reasonable default quantization automatically; you don't need to choose one by hand for this book.

If your hardware doesn't comfortably fit even the smallest row here, section 1.7's escape hatch is exactly for you — don't force a model that's too large for your machine just to stay “local” on principle.

1.5 Installing and Configuring Pi

1.5.1 What Pi Actually Does

Pi is a coding agent: a program that can read your project's files, propose changes, and — with your permission at each step — run commands and write to disk. The model from section 1.4 is Pi's reasoning engine; Pi itself is the framework that lets that reasoning act on a real codebase instead of just producing text in a chat window.

1.5.2 Installation

Follow the install instructions for your platform from Pi's documentation. Confirm it's available:

```
pi --version
```

1.5.3 Pointing Pi at Your Local Model

Pi doesn't have a `pi config set` command for this — model selection lives directly in Pi's settings file, `~/.pi/agent/settings.json`. This is a good first real use for the vi skills from 0.5: open the file and edit the values by hand.

```
vi ~/.pi/agent/settings.json
```

The fields that matter here are `defaultModel`, `defaultProvider`, and `defaultThinkingLevel`:

```
{
  "defaultModel": "qwen3.8:27b-mlx",
  "defaultProvider": "ollama",
  "defaultThinkingLevel": "medium"
}
```

Set `defaultModel` to whichever tag you pulled in 1.4.2, and `defaultProvider` to `ollama`. `defaultThinkingLevel` controls how much the model reasons before answering — `medium` is a reasonable default to start with. (Pi's settings file has a few more fields too — including a `packages` list for installed extensions — that you can safely ignore for now; this book doesn't need any of them.)

1.5.4 Skills

Pi supports **skills** — packaged instructions that give it additional domain-specific guidance beyond its defaults. There's no `pi skills` command; skills are viewable and toggled through the same interactive screen `pi config` opens (Tab switches between scopes). Adding one is a matter of copying files rather than installing a package: a **global** skill goes in `~/.pi/agent/skills/`, available to every project; a **local** skill goes in `.pi/agent/skills/` inside a specific project, available only there. You don't need any skills for this book's core path — we'll flag it explicitly in later chapters if a particular skill would help with that chapter's task.

1.5.5 Starting Pi in the Repository

There's no separate `pi init` step. Pi's available commands, for reference:

<code>pi install <source> [-l]</code>	Install extension source and add to settings
<code>pi remove <source> [-l]</code>	Remove extension source from settings
<code>pi uninstall <source> [-l]</code>	Alias for remove
<code>pi update [source self pi]</code>	Update pi, extensions, or model catalogs
<code>pi list</code>	List installed extensions from settings
<code>pi config [-l]</code>	Open TUI to enable/disable package resources
<code>pi auth <command></code>	Print credentials or check provider readiness

Pointing Pi at your project is just a matter of being in it when you start it:

```
cd mortgage-calculator-book
pi
```

Running `pi` with no arguments starts an interactive session using the current directory as its project context — nothing more to configure.

1.6 Your First Agent-Assisted Interaction

1.6.1 A Deliberately Small Task

Before trusting Pi with anything that matters, give it something safe and easy to check:

```
pi "Add a one-line docstring to the top of \
    src/mortgage_calculator_book/__init__.py describing \
    what this package is for."
```

This launches Pi in interactive mode with that instruction as your first message — Pi will think, propose a change, and then wait for you inside the session rather than exiting on its own. Once you’ve reviewed what it did (1.6.2 below), exit with **Ctrl+D**.

If you’d rather Pi run one instruction and exit immediately, without an interactive session, add `-p`:

```
pi -p "Add a one-line docstring to the top of \
    src/mortgage_calculator_book/__init__.py describing \
    what this package is for."
```

`-p` is short for “print”: Pi runs the instruction, prints its response, and exits on its own — often more convenient for the small, self-contained tasks this book asks of it. The rest of this book shows Pi invocations in the plain form above; assume interactive mode and a Ctrl+D exit when you’re done, unless a chapter says otherwise, and reach for `-p` yourself any time you’d rather skip the session entirely.

1.6.2 Reading the Diff

Pi will show you a proposed change before applying it. **Read it before accepting.** For a change this small, that takes seconds — but the habit is the point, not the specific diff. This book asks you to read every diff Pi proposes, all the way through Chapter 13, precisely because the changes get larger and the stakes get higher, and the habit needs to already be automatic by then.

```
git diff    # if the change was already applied, review it the normal git way
```


1.6.3 What “Trust but Verify” Looks Like Here

For this task, verifying is simple: does the docstring exist, does it say something true and reasonably clear about the package? For a one-line docstring, that’s a five-second check. It won’t stay that simple — Chapter 6’s core library and Chapter 11’s model wiring will ask considerably more of your review skills — but the underlying question is always the same one you’re practicing right now: *does this change do what it claims to do, and nothing else?*

Process concept: prompting as spec-writing. Notice that the instruction you gave Pi in 1.6.1 was really a tiny, informal spec — a statement of what should exist and roughly what it should say. Chapter 2 takes that same idea and gives it a proper name and a proper document: SPEC.md. Everything from here to Chapter 2 is really just this one interaction, done slightly larger.

Once you’ve reviewed the change and you’re satisfied with it, commit it:

```
git add .
git commit -m "Add package docstring (Pi-assisted)"
```

1.7 Escape Hatch: If Local Setup Isn’t Working

1.7.1 Recognizing the Signs

If Ollama is taking minutes to respond to a simple prompt, if your machine is swapping memory constantly, or if the model simply refuses to load — these are signs your hardware and your chosen model size aren’t a good match, not signs you’re doing something wrong.

1.7.2 A Minimal Fallback

You can point Pi at a hosted model instead, so you’re not stuck before this book even really starts. The same settings file from 1.5.3 handles this too — there’s no `pi config set` command here either:

```
vi ~/.pi/agent/settings.json

{
  "defaultModel": "qwen/qwen3-27b",
  "defaultProvider": "openrouter"
}
```

This requires an OpenRouter account, an API key, and — since hosted calls cost real money per request — some actual credit sitting in the account; a fresh account with a zero balance will authenticate just fine and then fail the moment it tries to run anything. Chapter 11 covers this setup properly, including cost and usage tracking. For now, if you need this escape hatch: create an Open-

Router account, add a small amount of credit, generate a key, and set it as an environment variable:

```
export OPENROUTER_API_KEY="your-key-here"
```

1.7.3 This Isn't Permanent

Using a hosted model here doesn't lock you out of local models for the rest of the book — it just gets you moving today. Once you've read Chapter 1.4's hardware guidance more carefully, or found a smaller model that fits your machine, you can switch back at any point by editing `defaultModel` and `defaultProvider` in `~/.pi/agent/settings.json` again.

1.8 Checkpoint

Before moving to Chapter 2, this should all be true:

- ☐ Ollama is installed and a model has been pulled successfully
- ☐ You've had at least one raw conversation with the model via `ollama run`
- ☐ Pi is installed, and `~/.pi/agent/settings.json` points `defaultModel` and `defaultProvider` at either your local model or the Chapter 1.7 fallback
- ☐ Running `pi` from inside `mortgage-calculator-book` starts a session with that project as its context
- ☐ You've given Pi one small task, read its diff, exited cleanly (Ctrl+D or -p), and committed the result

What's next: Chapter 2 turns the informal instruction-giving you just practiced into something more deliberate — a written `SPEC.md` that describes what the calculator is actually supposed to do, before any real code exists.

Chapter 2 — Writing SPEC.md

Contents

2.1 Why This Chapter Exists	33
2.2 What a Spec Is (and Isn't)	33
2.2.1 Intent, Written Before Code	33
2.2.2 Living, Not Fixed	33
2.2.3 Three Readers, One Document	33
2.3 Anatomy of a Lightweight SPEC.md	34
2.3.1 What the Calculator Does	34
2.3.2 Inputs and Outputs	34
2.3.3 What “Correct” Means	34
2.3.4 What’s Out of Scope	34
2.4 Writing the First Draft, With Pi	34
2.4.1 Prompting Pi to Help Structure the Draft	34
2.4.2 Reading Pi’s Suggestions Critically	35
2.4.3 Editing Down to What You Actually Mean	35
2.4.4 What You Might Actually See	36
2.5 Committing the Spec	37
2.5.1 Where It Lives	37
2.5.2 Markdown, Reused	37
2.5.3 Committing It as Its Own Checkpoint	37
2.6 What Happens When the Spec Is Wrong	37
2.7 Checkpoint	37

2.1 Why This Chapter Exists

At the end of Chapter 1, you gave Pi a one-line instruction and reviewed a one-line change. That worked because the task was tiny enough to hold in your head. The mortgage calculator won't be tiny for long. This chapter gives you — and Pi — something more durable to work from than a chat message: a written spec, committed to the repository alongside the code it describes.

By the end of this chapter, you'll have a first draft of `SPEC.md`, committed to your repository. It won't be complete, and it won't be entirely correct — Chapter 4 exists specifically to find out where.

2.2 What a Spec Is (and Isn't)

2.2.1 Intent, Written Before Code

A spec, as this book uses the term, is a description of what a system should do, written before the system exists to do it. It's not a design document — it doesn't describe *how* the calculator will compute a payment, only *what* it means for that computation to be right. It's also not a requirements document in the heavyweight, sign-off-required sense you might associate with large organizations. Think of it as closer to a clear, written promise than a contract: a statement specific enough to hold yourself to, informal enough to write in an afternoon.

2.2.2 Living, Not Fixed

The most important thing to understand about `SPEC.md` before you write a word of it: it will be wrong in places, and that's expected. You'll revise it in Chapter 4 once real mortgage math enters the picture, and again in Chapter 13 once the whole system exists and you can check the spec against what actually got built. A spec that never changes usually means nobody's been checking it against reality.

2.2.3 Three Readers, One Document

`SPEC.md` serves three different readers, and it's worth writing with all three in mind:

- **You, in three weeks** — when you've forgotten exactly what “valid” was supposed to mean for a loan term.
- **A classmate or collaborator** — who needs to understand the project without reading every line of code first.
- **Pi** — which will read this file as context for later tasks, the same way it read your one-line instruction in Chapter 1, just at greater length and with more precision.

Process concept: same contract, three altitudes. SPEC.md is the first of three places this book will write down what “correct” means for this system. Chapter 5’s tests are the second — the same intent, made executable. Chapter 7 and Chapter 10’s schemas are the third — the same intent again, made machine-readable enough for a language model to call. You’re not writing three different things across the book; you’re writing one idea, at three different levels of formality, for three different audiences.

2.3 Anatomy of a Lightweight SPEC.md

A spec at this scale needs four things, no more:

2.3.1 What the Calculator Does

One paragraph, plain language. Not a feature list — a description someone with no context could read and understand the point of the project.

2.3.2 Inputs and Outputs

Named, with types. Not formulas yet — that’s Chapter 4’s job, once the domain math has been properly explained. For now, just: what goes in, what comes out.

2.3.3 What “Correct” Means

The criteria something must meet to count as working — even before you know the exact math. For a mortgage calculator, this might be as simple as “the computed payment, multiplied by the number of payments, should recover the total amount paid” — a property you can state and check without yet having derived the formula that produces it.

2.3.4 What’s Out of Scope

Often more useful than what’s in scope. Explicitly naming what this project *won’t* do — variable-rate mortgages, refinancing calculations, multiple currencies — prevents scope from quietly expanding one “just add this one thing” at a time.

2.4 Writing the First Draft, With Pi

2.4.1 Prompting Pi to Help Structure the Draft

Applying the same “prompting as spec-writing” idea from Chapter 1.6, but at document scale rather than one-line scale:

```
pi "Draft a SPEC.md for a fixed-rate mortgage \
    calculator. It should describe what the tool does, \
    its inputs and outputs, what 'correct' means for it, \
    and what's explicitly out of scope. Keep it under \
    one page."
```

2.4.2 Reading Pi's Suggestions Critically

Pi will likely produce something reasonable-looking and, in at least one place, quietly wrong or presumptuous — filling a gap you didn't actually specify with a plausible-sounding assumption. This is exactly the risk this chapter exists to teach you to catch. A common example: Pi may assume monthly payments without your having said so, or describe “periodic interest rate” as if it were the same thing as the annual rate. Read every sentence and ask, for each one: *did I actually mean this, or did the agent fill in a gap I left open?*

2.4.3 Editing Down to What You Actually Mean

Take Pi's draft and cut, correct, and rewrite until every sentence is something you'd defend if asked. Below is roughly what a reasonable first draft looks like at this point in the book — deliberately imperfect, in ways Chapter 4 will catch:

```
# SPEC.md - Fixed-Rate Mortgage Calculator

## What it does
Calculates the fixed periodic payment for a fixed-rate mortgage,
given a principal amount, an interest rate, and a loan term.

## Inputs
- principal: the loan amount, in dollars
- rate: the interest rate
- term: the length of the loan, in years

## Outputs
- payment: the fixed amount paid each period

## What "correct" means
The computed payment, multiplied by the number of payments,
should equal the total amount paid over the life of the loan.

## Out of scope
- Variable-rate mortgages
- Refinancing calculations
- Multiple currencies
```

If you're reading closely, you may already see what Chapter 4 is going to have to fix: “rate” doesn't say whether it's annual or periodic, “term” doesn't say what

payment frequency it implies, and “the number of payments” is used before anything defines how it’s calculated. Leave it as it is for now — the gaps are the point, and finding them with real domain knowledge in hand is more useful than getting them right by luck on a first pass.

2.4.4 What You Might Actually See

The illustrative draft above is intentionally simple, so the specific gaps Chapter 4 needs to catch stay easy to spot. Real output varies — sometimes a lot — depending on which model actually wrote it, and it’s worth seeing that difference once, concretely, before you run this exercise yourself.

Running the 2.4.1 prompt against **qwen3:8b** produced a noticeably different kind of draft. It added constraints nobody asked for — a \$10,000 minimum loan amount, a rate capped at 0–100%, a term capped at 1–30 years — none of which trace back to anything in the prompt. That’s exactly the risk 2.4.2 warned about: a plausible-sounding assumption filling a gap you never actually specified. It also introduced a “Rate Frequency” field (“Annual” or “Monthly,” described as being for “effective annual rate calculations”) that quietly conflates two genuinely different things — how often a rate is *quoted* versus how often payments are *made* — in a way that reads reasonably on a first pass and falls apart under the kind of scrutiny 4.3.2 asks you to apply.

Running the same prompt against **qwen3.8:27b-mlx** produced something considerably more ambitious: not just a payment figure, but a full month-by-month amortization schedule, with explicit rules for where rounding error is allowed to land (the final period only) and a battery of correctness properties — `payment == principal_paid + interest_paid` on every row, the closing balance reaching exactly zero, and so on. This is careful, genuinely well-specified engineering. It’s also scope the 2.4.1 prompt never asked for and this book’s project never builds: every chapter from here forward computes a single fixed payment, not a schedule. A more capable model didn’t just fill gaps more sensibly here — it expanded the project’s scope without being asked to, which needs exactly the same scrutiny as the smaller model’s unrequested minimum-loan-amount constraint, just dressed up better.

Neither output is wrong to have produced — this is genuinely what real coding agents do, and it’s part of why 2.4.2’s instruction to read every sentence critically matters regardless of which model you’re using. Your own first draft will very likely look like neither the illustrative version above nor either of these — which is fine. The skill this chapter is teaching isn’t “get the spec Pi is supposed to produce”; it’s “notice what you didn’t actually ask for.”

2.5 Committing the Spec

2.5.1 Where It Lives

SPEC.md sits at the root of your project, alongside README.md and pyproject.toml — visible immediately to anyone (or anything) opening the repository, not buried in a subdirectory.

2.5.2 Markdown, Reused

The Markdown syntax you’re using here — headers, lists — is the same syntax Chapter 8 will use for the project’s README. Learning it once, here, means Chapter 8 is mostly application rather than new material.

2.5.3 Committing It as Its Own Checkpoint

```
git add SPEC.md
git commit -m "Add first-draft SPEC.md"
git push
```

A spec is worth its own commit message, separate from any code — it’s a real artifact of the project, not a scratch file.

2.6 What Happens When the Spec Is Wrong

This draft has gaps, and that’s fine for now. Chapter 4 introduces the actual mathematics of fixed mortgages — periodic rates, payment frequency, the derivation of the payment formula itself — and one of that chapter’s jobs is to come back to this exact document and fix what turns out to be ambiguous or simply missing. That revision is normal process, not a sign the first draft failed. Expecting it now, rather than being caught off guard by it in Chapter 4, is the whole reason this section exists.

2.7 Checkpoint

Before moving to Chapter 3, this should all be true:

- ☐ SPEC.md exists at the project root
- ☐ It describes what the calculator does, its inputs and outputs, what “correct” means, and what’s out of scope
- ☐ You can point to at least one sentence in it and explain why you edited or kept what Pi originally proposed
- ☐ It’s committed and pushed to GitHub

What’s next: Chapter 3 makes sure whatever code gets written from here forward — yours or Pi’s — is held to a consistent quality standard before it’s

ever committed. Chapter 4 will come back to this exact SPEC.md once real mortgage math is on the table.

Chapter 3 — Holding the Agent to a Standard

Contents

3.1 Why This Chapter Exists	41
3.2 “Passes Tests” Isn’t the Same as “Good Code”	41
3.2.1 Why This Matters More Once an Agent Is Involved	41
3.2.2 A Plausible Example	41
3.3 What Ruff Is	41
3.3.1 Linting and Formatting, One Tool	41
3.3.2 Why Ruff, Specifically	42
3.4 Installing and Configuring Ruff	42
3.4.1 Installing	42
3.4.2 A Minimal Configuration	42
3.4.3 Running It	42
3.5 Running Ruff Against Agent Output	43
3.5.1 Pointing It at Chapter 1’s Change	43
3.5.2 Reading and Fixing What It Flags	43
3.5.3 Asking Pi to Fix Ruff’s Complaints	44
3.6 Making It a Habit, Not a One-Off	44
3.6.1 Before Every Commit	44
3.6.2 Looking Ahead	44
3.7 Checkpoint	44

3.1 Why This Chapter Exists

You have a spec now, and a working relationship with an agent that can write code against it. Before any real code gets written, this short chapter sets up one more thing: a floor for quality that applies automatically, to every change, whether you wrote it or Pi did.

By the end of this chapter, Ruff will be installed, configured, and run against the one piece of code that already exists in your project — the docstring Pi added back in Chapter 1.6.

3.2 “Passes Tests” Isn’t the Same as “Good Code”

3.2.1 Why This Matters More Once an Agent Is Involved

Code can be functionally correct and still be inconsistent, oddly formatted, or written in a style that doesn’t match the rest of your project — none of which a test suite will ever catch, because tests check behavior, not style. That’s true of code you write yourself, too, but it becomes a sharper problem once an agent is generating a meaningful share of your codebase: Pi has no inherent reason to match *your* conventions unless something enforces them, and “close enough” drift across dozens of agent-assisted changes adds up into a codebase that’s technically correct and genuinely unpleasant to read.

3.2.2 A Plausible Example

Imagine asking Pi to add a function, and it comes back with correct logic, but inconsistent quote styles, an unused import left over from an earlier attempt, and inconsistent spacing around operators. Every test still passes. Nothing here is a bug. It’s still worth catching, and it’s not worth catching *by eye*, every time, forever.

Process concept: quality bars you set once, and enforce automatically. The alternative to a linter isn’t “no standard” — it’s “a standard you have to remember to apply yourself, every single time, including on the days you’re tired or rushing.” This chapter trades that for a tool that never forgets to check.

3.3 What Ruff Is

3.3.1 Linting and Formatting, One Tool

Linting catches likely mistakes and style problems — unused imports, inconsistent naming, patterns known to cause bugs. **Formatting** enforces a consistent

visual style — spacing, quote style, line length — regardless of who wrote the code. Ruff does both, in one fast tool.

3.3.2 Why Ruff, Specifically

Python has historically split this work across three separate tools — Black for formatting, Flake8 for linting, isort for import ordering. Ruff reimplements the useful parts of all three in a single, much faster tool, which is why this book uses it instead of the older combination: fewer things to install, fewer things to configure, fewer places for configuration to drift out of sync with each other.

3.4 Installing and Configuring Ruff

3.4.1 Installing

```
uv add --dev ruff
```

The `--dev` flag matters here: Ruff is a tool *you* use while developing, not something the calculator itself needs at runtime, so it belongs in your project’s development dependencies, not its regular ones.

3.4.2 A Minimal Configuration

Add a small section to your existing `pyproject.toml`:

```
[tool.ruff]
line-length = 100

[tool.ruff.lint]
select = ["E", "F", "I"]
```

This is deliberately narrow: E and F cover common style and correctness issues, I handles import ordering. Ruff supports many more rule categories than this, but a first-year project doesn’t need all of them enabled on day one — start narrow, and widen later if you find yourself wanting more.

3.4.3 Running It

`uv add --dev ruff` installs Ruff into your project’s virtual environment, `.venv/` — not globally on your system. If you try `ruff check .` right after installing it and get a `command not found` error, that’s why: your shell doesn’t yet know to look inside `.venv/`. Activate the environment:

```
source .venv/bin/activate
```

(On native Windows outside WSL, the equivalent is `.venv\Scripts\activate`.)

Confirm it worked:

`which ruff`

You're looking for a path inside your project's `.venv/` — something like `.../mortgage-calculator-book/.venv/bin/ruff` — not a Ruff installed somewhere else on your system. This matters: if you happen to have a different Ruff on your machine already, `which ruff` is how you'd catch yourself accidentally running the wrong one.

Once activated, this same terminal session can run `ruff`, `pytest`, and `python` bare, without prefixing every command with `uv run` — which is why later chapters show commands like `pytest -v` directly rather than `uv run pytest -v`. `uv run ruff check .` is the alternative that works either way, activated or not, since it always runs inside the project's environment regardless of your shell's current state — reach for it instead if you'd rather not activate manually, or you're running a one-off command in a fresh terminal that isn't activated.

With Ruff actually runnable:

```
ruff check .      # lint
ruff format .     # format
```

`ruff check` reports problems; `ruff format` rewrites files to match the configured style. Run both — they check different things.

Installing Ruff changed `pyproject.toml` and `uv.lock` — a real change, worth its own commit:

```
git add .
git commit -m "Add Ruff as a dev dependency"
git push
```

3.5 Running Ruff Against Agent Output

3.5.1 Pointing It at Chapter 1's Change

```
ruff check src/mortgage_calculator_book/__init__.py
```

For a one-line docstring, this will likely come back clean — which is itself a useful first result: it tells you Ruff is wired up correctly, even though there was nothing to fix yet.

3.5.2 Reading and Fixing What It Flags

When Ruff does flag something (and it will, once real code exists from Chapter 6 onward), its output names the specific rule and line: treat each one as a small checklist item, not an annoyance to silence. If a rule genuinely doesn't fit your project, that's a configuration decision to make deliberately in `pyproject.toml` — not something to work around case by case.

3.5.3 Asking Pi to Fix Ruff's Complaints

```
ruff check . || pi "Fix the issues reported by ruff check in this project."
```

Review that diff exactly the way you reviewed Chapter 1.6's — Pi fixing a lint error is still a proposed change, and still worth reading before accepting.

3.6 Making It a Habit, Not a One-Off

3.6.1 Before Every Commit

From this point forward, run `ruff check .` and `ruff format .` before every commit, for the rest of the book. This isn't automated yet — Appendix A.5 covers pre-commit hooks, which would do this for you — but doing it by hand for now is deliberate: understanding *why* you run it matters more, this early, than automating it away before you've felt the reason for it.

3.6.2 Looking Ahead

Chapter 13's Hardening chapter revisits standards again, but at the level of the whole system — error handling, logging, a final consistency check. This chapter is the per-commit version of that same instinct: catch problems small and early, rather than all at once at the end.

3.7 Checkpoint

Before moving to Chapter 4, this should all be true:

- ☐ Ruff is installed as a dev dependency
- ☐ `pyproject.toml` has a minimal `[tool.ruff]` configuration
- ☐ `ruff check .` and `ruff format .` both run without errors against the current project
- ☐ You've run Ruff at least once against Pi-generated content, even if there was nothing to fix

What's next: Chapter 4 leaves tooling aside for a chapter and gets into the actual mathematics of fixed mortgages — the domain content `SPEC.md` will need once Chapter 4 comes back to revise it.

Chapter 4 — The Domain: Fixed Mortgages

Contents

4.1 Why This Chapter Exists	47
4.2 Fixed Mortgage Primer	47
4.2.1 What a Mortgage Is	47
4.2.2 Why “Fixed”	47
4.2.3 The Shape of a Payment	47
4.3 The Four Core Quantities	47
4.3.1 Principal	48
4.3.2 Periodic Interest Rate	48
4.3.3 Total Number of Payments	48
4.3.4 Fixed Periodic Payment	48
4.4 The Gory Details: Deriving the Formula	48
4.4.1 The Formula	48
4.4.2 Where It Comes From	49
4.4.3 Two Edge Cases Worth Naming Now	49
4.5 A Worked Example, By Hand	50
4.5.1 The Numbers	50
4.5.2 Computing the Payment	50
4.5.3 This Is the Answer Key	51
4.6 Optional: Using Pi as a Study Aid	51
4.7 Revising SPEC.md	51
4.7.1 Going Back to Chapter 2’s Draft	51
4.7.2 What Was Actually Wrong	51
4.7.3 Writing the Derivation Down	52
4.7.4 The Revision	53
4.8 Checkpoint	54

4.1 Why This Chapter Exists

No code gets written in this chapter. Instead, this chapter gives you the thing every later chapter’s code will be checked against: a correct, hand-verified understanding of how a fixed-rate mortgage payment is actually calculated, and one specific worked example with exact numbers.

By the end, you’ll have a revised `SPEC.md` — fixing the gaps Chapter 2 left open on purpose — and a worked example that Chapter 5’s first test, Chapter 6’s core library, and Chapter 12’s evaluation set will all check themselves against.

4.2 Fixed Mortgage Primer

4.2.1 What a Mortgage Is

A mortgage is a loan used to buy property, where the property itself secures the loan — if payments stop, the lender can take the property back. Setting aside everything else about how mortgages work in practice, the part this book cares about is narrower and purely mathematical: given a loan amount, an interest rate, and a length of time to repay it, what should each periodic payment be?

4.2.2 Why “Fixed”

A **fixed-rate** mortgage has an interest rate that stays the same for the entire loan term, which means the payment amount stays the same too, from the first payment to the last. A **variable-rate** mortgage’s rate can change over time, which means the payment can change too — a meaningfully different, more complex calculation this book deliberately leaves out of scope (as `SPEC.md` already says).

4.2.3 The Shape of a Payment

Here’s the part that surprises a lot of first-time borrowers: even though the payment amount is fixed, what that payment is *made of* changes every period. Early payments are mostly interest, with a small amount going toward the actual principal. Late payments are the reverse — mostly principal, a small amount of interest. Why: interest is charged on whatever principal is still outstanding, and outstanding principal is highest at the start and lowest at the end. We won’t build a full amortization schedule until it’s needed, but understanding this shape now will make the formula in section 4.4 feel like it’s describing something real, not just producing a number.

4.3 The Four Core Quantities

Every payment calculation in this book comes down to four numbers.

4.3.1 Principal

The amount actually borrowed. Everything else in the calculation exists to answer one question about this number: how do you pay it back, with interest, in equal installments?

4.3.2 Periodic Interest Rate

This is the number Chapter 2’s draft spec quietly got wrong: “rate” is not the same as “periodic rate.” Mortgage rates are quoted **annually** — a “6% mortgage” means 6% per year — but payments happen more often than once a year, almost always monthly. The rate that actually applies to each payment period is the annual rate divided by the number of periods per year:

$$r = \frac{\text{annual rate}}{\text{payments per year}}$$

For a 6% annual rate paid monthly: $r = 0.06/12 = 0.005$, or 0.5% per month. This conversion — annual to periodic — is the single most common place a first attempt at this calculation goes wrong, and it’s exactly the gap Chapter 2’s spec left open.

4.3.3 Total Number of Payments

Term length and payment frequency combine to give the total number of payments:

$$n = \text{term in years} \times \text{payments per year}$$

A 30-year loan paid monthly has $n = 30 \times 12 = 360$ payments. The same 30-year loan paid **biweekly** (every two weeks, 26 times a year) would have $n = 30 \times 26 = 780$ payments instead — a different total, and, as it turns out, a different total amount of interest paid over the life of the loan, purely from paying more frequently in smaller amounts. We’ll come back to that as an aside once the main formula is in hand.

4.3.4 Fixed Periodic Payment

The quantity everything above exists to compute: the single, unchanging amount paid every period. This is what section 4.4 derives.

4.4 The Gory Details: Deriving the Formula

4.4.1 The Formula

$$M = P \cdot \frac{r(1+r)^n}{(1+r)^n - 1}$$

where M is the fixed periodic payment, P is the principal, r is the periodic rate from 4.3.2, and n is the total number of payments from 4.3.3. It looks dense on first read. The derivation below builds it up piece by piece, so it stops looking like something handed down from nowhere.

4.4.2 Where It Comes From

Think about the loan from two directions at once, both measured at the *end* of the loan — payment n .

Direction one: what the lender is owed. If nothing were ever paid, the principal would simply grow with interest every period, compounding: after n periods, the lender would be owed $P(1 + r)^n$.

Direction two: what's been paid. Each payment M , made at the end of its period, also “grows” from the moment it's paid until the end of the loan — because in effect, that payment could have been earning interest at rate r for however many periods remain after it. The very last payment doesn't grow at all (it's already at the end). The second-to-last payment grows for one period. And so on, back to the first payment, which grows for $n - 1$ periods. Summed up, the total grown value of every payment is:

$$M(1 + r)^{n-1} + M(1 + r)^{n-2} + \dots + M(1 + r)^1 + M(1 + r)^0$$

This is a **geometric series** — the same kind of sum you may have seen in an algebra course, just with an interest rate standing in for the usual ratio. It has a well-known closed form:

$$M \cdot \frac{(1 + r)^n - 1}{r}$$

Setting the two directions equal. For the loan to be exactly paid off at payment n — no more, no less — what the lender is owed has to exactly equal what's been paid, both measured at that same end point:

$$P(1 + r)^n = M \cdot \frac{(1 + r)^n - 1}{r}$$

Solving for M gives the formula from 4.4.1. Nothing about it is arbitrary — it's just “what's owed equals what's paid,” stated at a single point in time to make the comparison fair, then rearranged.

4.4.3 Two Edge Cases Worth Naming Now

Zero interest. The formula above divides by r — which breaks down completely when $r = 0$. But the underlying question still has an obvious answer:

with no interest at all, each payment should simply be the principal divided evenly across all payments, $M = P/n$. Chapter 6's implementation will need an explicit branch for this case; the general formula won't handle it on its own.

A single payment. When $n = 1$, there's no series to sum — just one payment that has to cover the principal plus one period's interest: $M = P(1 + r)$. This is worth checking against the general formula directly (it works out to the same thing when you substitute $n = 1$), which makes it a useful sanity check on the formula itself, not just a case to handle in code.

Both of these become explicit tests in Chapter 5, and explicit branches in Chapter 6's implementation.

4.5 A Worked Example, By Hand

4.5.1 The Numbers

This is the example the rest of the book returns to repeatedly — commit these numbers to memory or bookmark this page, because Chapters 5, 6, 8, 9, and 12 all check themselves against it.

Quantity	Value
Principal (P)	\$200,000
Annual interest rate	6%
Payment frequency	Monthly (12/year)
Periodic rate (r)	0.005
Term	30 years
Total payments (n)	360

4.5.2 Computing the Payment

$$M = 200,000 \cdot \frac{0.005 \times (1.005)^{360}}{(1.005)^{360} - 1}$$

$(1.005)^{360} \approx 6.022359$. Substituting:

$$M \approx 200,000 \cdot \frac{0.005 \times 6.022359}{6.022359 - 1} \approx 200,000 \times 0.0059955 \approx \$1,199.10$$

Fixed periodic payment: \$1,199.10 (more precisely, \$1,199.1010503... before rounding to the cent).

From here, two more figures worth having on hand: total paid over the life of the loan is $1,199.10 \times 360 = \$431,676.38$, and total interest paid is that total minus the original principal: \$231,676.38 — more than the principal itself, which is a genuinely useful thing for a first-year reader to sit with for a moment before moving on.

4.5.3 This Is the Answer Key

Flag this explicitly: when Chapter 5 writes its first test, and Chapter 6 writes its first real implementation, “does it reproduce \$1,199.10 for this exact scenario” is the bar. If your code disagrees with this number by more than a rounding error, the code is wrong, not the example — these numbers were computed independently, ahead of time, specifically so you have something outside your own implementation to check it against.

4.6 Optional: Using Pi as a Study Aid

If you’d like a second check on the arithmetic above:

```
pi "Verify this mortgage payment calculation by hand: \
    principal \"$200,000, annual rate 6%, 30-year term, \
    monthly payments. Show your work."
```

Read what comes back carefully rather than accepting it at face value. Models are not immune to arithmetic slips, and a subtly wrong intermediate step — the periodic rate conversion, in particular, is a common place for this to happen — can produce a final answer that looks plausible without being right. If Pi’s answer disagrees with 4.5.2’s, don’t assume either one is automatically correct; redo the arithmetic yourself and find out which one made the mistake. That’s not a wasted exercise — it’s the same verification skill this book has been building since Chapter 1.6, applied to math instead of code.

4.7 Revising SPEC.md

4.7.1 Going Back to Chapter 2’s Draft

Open the SPEC.md you committed in Chapter 2.5.3. With sections 4.3 and 4.4 now in hand, its gaps should be obvious in a way they weren’t before.

4.7.2 What Was Actually Wrong

Specifically:

- “**rate**” never said whether it meant the annual rate or the periodic rate — and 4.3.2 showed those are different numbers that are easy to conflate.
- “**term**” never said what payment frequency it implied, even though 4.3.3 showed frequency changes the total number of payments (and, as the bi-weekly aside noted, the total interest paid).
- “**the number of payments**” was used in the “what correct means” section without ever being defined.

4.7.3 Writing the Derivation Down

There's a second problem here, subtler than the three gaps above: SPEC.md's revision is about to say "see [somewhere] for the full derivation" — but "somewhere" can't just mean this chapter. This book's prose isn't part of the git repository, and it never will be. Pi reads your project's files when it works; it doesn't read the book you're reading right now. "See Chapter 4.4" is perfectly good advice for you — it's a dead end for Pi, and not much better for a future maintainer who opens this repository years from now without this book on the shelf next to them.

The fix is to write the derivation down *in the project*, not just in your head or in a book external to it. Create docs/derivation.md:

```
mkdir docs
vi docs/derivation.md

# Fixed-Rate Mortgage Payment: Derivation

## The formula


$$M = P * [r(1+r)^n] / [(1+r)^n - 1]$$


M is the fixed periodic payment, P is the principal, r is the
periodic rate (annual_rate / payments_per_year), and n is the
total number of payments (term_years * payments_per_year).

## Where it comes from

At the end of the loan, what the lender is owed if nothing were
ever paid --  $P(1+r)^n$  -- must equal what's actually been paid,
each payment M grown at rate r for however many periods remain
after it:  $P(1+r)^n = M * [(1+r)^n - 1] / r$ . Solving for M gives
the formula above.

## Edge cases

- Zero interest ( $r == 0$ ): the formula divides by zero; payment is
  simply  $P / n$ .
- A single payment ( $n == 1$ ): reduces to  $M = P(1+r)$ , which the
  general formula also produces correctly at  $n=1$ .

## Answer key

principal=200000, annual_rate=0.06, term_years=30,
payments_per_year=12 -> payment = $1,199.10. Used throughout
tests/test_core.py as the reference case every implementation is
```

checked against.

Commit it on its own:

```
git add docs/derivation.md
git commit -m "Add docs/derivation.md: the amortization formula"
git push
```

Now SPEC.md's "see ... for the full derivation" can point somewhere Pi — and anyone else working in this repository — can actually read.

4.7.4 The Revision

```
# SPEC.md - Fixed-Rate Mortgage Calculator
```

```
## What it does
```

Calculates the fixed periodic payment for a fixed-rate mortgage, given a principal amount, an annual interest rate, a loan term in years, and a payment frequency.

```
## Inputs
```

- principal: the loan amount, in dollars
- annual_rate: the annual interest rate, as a decimal (e.g. 0.06 for 6%)
- term_years: the length of the loan, in years
- payments_per_year: number of payments per year (default: 12, monthly)

```
## Derived quantities
```

- periodic_rate = annual_rate / payments_per_year
- n_payments = term_years * payments_per_year

```
## Outputs
```

- payment: the fixed amount paid each period

```
## What "correct" means
```

The computed payment, multiplied by n_payments, should equal the total amount paid over the life of the loan. For principal = \$200,000, annual_rate = 0.06, term_years = 30, payments_per_year = 12: payment should equal \$1,199.10 (see docs/derivation.md for the full derivation).

```
## Out of scope
```

- Variable-rate mortgages
- Refinancing calculations
- Multiple currencies

Commit the revision on its own:

```
git add SPEC.md
```

```
git commit -m "Revise SPEC.md: define periodic rate, \
payment frequency, and n_payments"
git push
```

Process concept: the spec was wrong, not the code. There's no code yet — nothing here was a bug in the usual sense. But the instinct this section is building is the one that matters most for the rest of this book: when something doesn't match reality, check whether the spec described reality correctly before assuming the implementation is at fault. Chapter 13 closes the book with exactly this same check, run one more time against the finished system.

4.8 Checkpoint

Before moving to Chapter 5, this should all be true:

- ☐ You can explain, in your own words, why the annual rate and the periodic rate are different numbers
- ☐ You can derive the payment formula's shape (even loosely) from "what's owed equals what's paid"
- ☐ You have the primary worked example's numbers (\$200,000 / 6% / 30yr monthly → \$1,199.10) recorded somewhere you'll return to
- ☐ `docs/derivation.md` exists, committed, and actually contains the formula — not just a reference to this chapter
- ☐ `SPEC.md` has been revised to define periodic rate, payment frequency, and `n_payments`, and points to `docs/derivation.md` rather than this book for the full derivation, and the revision is committed

What's next: Chapter 5 turns this worked example into an executable test — the first one this project has had, and the first thing Chapter 6's implementation will need to satisfy.

Chapter 5 — Tests & Test-Driven Development

Contents

5.1 Why This Chapter Exists	57
5.2 What TDD Actually Is	57
5.2.1 Red, Green, Refactor	57
5.2.2 Why Write the Test First	57
5.2.3 A Tiny Example First	57
5.3 pytest Basics	59
5.3.1 Installing	59
5.3.2 Test Discovery	59
5.3.3 Assertions	59
5.3.4 Running the Suite	59
5.4 Fixtures, Just Enough	59
5.4.1 The Problem They Solve	59
5.4.2 The Worked Example as a Fixture	59
5.4.3 Scope-Setting	60
5.5 Encoding the Answer Key as a Test	60
5.5.1 Translating the Worked Example	60
5.5.2 Running It — and Watching It Fail	61
5.5.3 Why a Failing Test Is a Milestone	61
5.6 Agent-Assisted TDD: Letting Pi Draft Test Skeletons	61
5.6.1 Prompting from the Spec	61
5.6.2 Reviewing What It Proposes	61
5.6.3 Accepting, Correcting, or Rejecting Each One	61
5.6.4 What a Larger Model Actually Produced	62
5.7 Debugger Basics: pdb	65
5.7.1 When to Reach for It	65
5.7.2 Trying It, On Something That Actually Exists	65
5.7.3 Why This Is Worth a Page	66
5.8 Edge Cases Worth Testing Now	66
5.8.1 The Two Cases from Chapter 4.4.3	66
5.8.2 Planting Red Tests on Purpose	67
5.9 Checkpoint	68

5.1 Why This Chapter Exists

Chapter 4 gave you an answer key on paper: a formula, a derivation, and one specific scenario with an exact expected answer. This chapter turns that paper answer key into something a computer can check automatically, every time, without you re-doing the arithmetic by hand.

By the end of this chapter, pytest will be installed, your test suite will have a real structure, and the Chapter 4.5 worked example will exist as an actual test function — one that currently **fails**, because there’s no core library yet to run it against. That failure is the goal, not a mistake. Chapter 6 exists to turn it green.

5.2 What TDD Actually Is

5.2.1 Red, Green, Refactor

Test-driven development follows a three-step cycle, repeated over and over:

1. **Red** — write a test for something that doesn’t exist yet. Run it. Watch it fail.
2. **Green** — write the smallest amount of code that makes the test pass.
3. **Refactor** — clean up what you just wrote, now that you have a passing test protecting you from breaking it by accident.

Then repeat, for the next small piece of behavior.

5.2.2 Why Write the Test First

This feels backwards the first time you do it — how can you test something that doesn’t exist? But writing the test first forces you to answer a question you’d otherwise skip past: *what, exactly, does “working” mean here, before I’ve built anything and started rationalizing whatever I happened to build?* A test written after the code tends to describe what the code does. A test written before the code describes what the code is *supposed* to do — a small but real difference, and one that matters more, not less, once an agent might be the one writing the implementation.

5.2.3 A Tiny Example First

Before touching mortgage math, try the cycle on something small enough to see the whole shape at once. This needs one tool you haven’t installed yet — pytest, the test runner this book uses from here on. Section 5.3 covers it properly; for now, just get it installed so this example can actually run:

```
uv add --dev pytest
```

This adds `pytest` to the `dev` dependency group in `pyproject.toml` — alongside `ruff`, already there since Chapter 3.4.1:

```
[dependency-groups]
dev = [
    "ruff>=0.14.0",
    "pytest>=8.4.2",
]
```

(Your exact version numbers may differ.) This is the same mechanism `uv add requests` used back in 0.7.4, just landing in a group reserved for tools you use while developing rather than ones the calculator needs at runtime.

Create a `tests` directory and open a new file in it — this is a good first real use for the `vi` skills from 0.5:

```
mkdir tests
vi tests/test_scratch.py
```

Type in the following (i to start typing, `Esc` then `:wq` to save and exit):

```
def test_add_returns_sum():
    from mortgage_calculator_book.scratch import add
    assert add(2, 3) == 5
```

Run it:

```
pytest tests/test_scratch.py -v
```

It fails — an import error, since `mortgage_calculator_book.scratch` doesn't exist yet, rather than a failed assertion, but a failure either way. That's **red**. Now create the missing piece the same way:

```
vi src/mortgage_calculator_book/scratch.py

def add(a, b):
    return a + b
```

Run the test again:

```
pytest tests/test_scratch.py -v
```

Green. There's nothing to refactor yet, but the cycle is complete. Delete both `scratch` files once you've felt the shape of it — they're not part of the real project:

```
rm tests/test_scratch.py src/mortgage_calculator_book/scratch.py
```

5.3 pytest Basics

5.3.1 Installing

5.2.3 already had you install this, to make the tiny example runnable. If you skipped ahead and don't have it yet:

```
uv add --dev pytest
```

5.3.2 Test Discovery

pytest finds tests automatically, following a convention rather than an explicit list: files named `test_*.py` (or `*_test.py`), inside functions named `test_*`. This is why the scratch example above worked without registering it anywhere — pytest went looking for exactly that pattern.

5.3.3 Assertions

pytest uses Python's plain `assert` statement — no special assertion methods to memorize. When an assertion fails, pytest rewrites the failure output to show you both sides of the comparison, which is more useful than it sounds the first time you see a failing test explain itself clearly.

5.3.4 Running the Suite

```
pytest                # run everything
pytest -v             # verbose - show each test by name
pytest tests/test_core.py      # run one file
pytest tests/test_core.py::test_matches_worked_example  # run one test
```

5.4 Fixtures, Just Enough

5.4.1 The Problem They Solve

Several tests in this chapter need the same data — the Chapter 4.5 worked example's principal, rate, term, and expected payment. Repeating those numbers in every test function invites the numbers to quietly drift apart from each other over time. A **fixture** is pytest's answer: shared setup, defined once, requested by any test that needs it.

5.4.2 The Worked Example as a Fixture

Create `tests/conftest.py`:

```
import pytest

@pytest.fixture
```



```
def worked_example():
    """Answer key from docs/derivation.md: $200k/6%/30yr monthly."""
    return {
        "principal": 200_000,
        "annual_rate": 0.06,
        "term_years": 30,
        "payments_per_year": 12,
        "expected_payment": 1199.10,
    }
```

Any test function that takes `worked_example` as a parameter automatically receives this dictionary — `pytest` matches it by name, no import needed.

5.4.3 Scope-Setting

`pytest`'s fixture system goes considerably further than this — different scopes, fixtures that depend on other fixtures, fixtures shared across an entire test session. This book uses exactly the pattern above and nothing more; if you want the fuller picture later, `pytest`'s own documentation is thorough and well-written.

5.5 Encoding the Answer Key as a Test

5.5.1 Translating the Worked Example

Create `tests/test_core.py`:

```
from mortgage_calculator_book.core import calculate_payment

def test_matches_worked_example(worked_example):
    payment = calculate_payment(
        principal=worked_example["principal"],
        annual_rate=worked_example["annual_rate"],
        term_years=worked_example["term_years"],
        payments_per_year=worked_example["payments_per_year"],
    )
    assert payment == pytest.approx(worked_example["expected_payment"], abs=0.01)
```

Note `pytest.approx(..., abs=0.01)` rather than a plain `==`. Chapter 4.5 computed the exact payment as 1199.1010503... before rounding — comparing floating-point results with plain equality is a reliable way to get bitten by a rounding difference in the fifteenth decimal place that has nothing to do with whether your code is actually correct. `abs=0.01` means “correct to the cent,” which is the precision that actually matters for currency here. You don’t need `import pytest` twice — add it to the top of the file alongside the `calculate_payment` import.

5.5.2 Running It — and Watching It Fail

```
pytest tests/test_core.py -v
```

This fails immediately, with an import error: `mortgage_calculator_book.core` doesn't exist yet. **This is the “red” in red/green/refactor, made concrete.** You haven't done anything wrong.

5.5.3 Why a Failing Test Is a Milestone

It's worth pausing on this rather than rushing past it: you now have a precise, automatic, unambiguous definition of what Chapter 6 needs to build. Not “make a mortgage calculator” in the abstract — make this exact test pass. That's a meaningfully smaller, clearer target than the one you started the book with.

5.6 Agent-Assisted TDD: Letting Pi Draft Test Skeletons

5.6.1 Prompting from the Spec

```
pi "Read SPEC.md and propose additional pytest test \
    cases for calculate_payment, beyond the worked \
    example already in tests/test_core.py. Don't \
    implement calculate_payment itself - just propose \
    the test functions."
```

5.6.2 Reviewing What It Proposes

Read every proposed test with two questions in mind: does it test *behavior* described in SPEC.md, or does it quietly test some *implementation detail* that hasn't been decided yet? And does its expected value actually follow from the formula in Chapter 4.4, or is it a plausible-looking number Pi generated without truly computing it? A test with a wrong expected value is worse than no test at all — it will pass or fail for the wrong reasons, and it'll sit there looking trustworthy until something forces you to check it by hand.

5.6.3 Accepting, Correcting, or Rejecting Each One

Treat this the same way you've treated every other agent proposal so far: some of what Pi suggests will be worth keeping as-is, some will need a corrected expected value, and some won't belong in this test file at all. All three outcomes are normal.

Process concept: tests as the executable proof of the spec, not a restatement of it. A test that just re-describes SPEC.md in code form (“test that `calculate_payment` exists and returns a number”) isn't pulling its weight. A good test asserts something

specific enough that it could actually fail in a way that teaches you something — which is exactly what section 5.5’s worked-example test does, and what you should be checking Pi’s proposals against.

5.6.4 What a Larger Model Actually Produced

The 5.6.1 prompt against a larger model — qwen3.8:27b-mlx, from Chapter 1.4.2 — can produce something considerably more ambitious than a handful of test skeletons: nine cases plus three explicit “I won’t guess at this, decide first” questions about behavior SPEC.md doesn’t define (what should happen at `term_years = 0`? should negative principal raise or just compute?). That last part is worth calling out on its own — flagging an undecided contract instead of quietly assuming one is exactly the discipline this book has been asking *you* to practice, showing up unprompted in the agent’s own output.

Some of the proposed cases are genuinely strong, and worth knowing about even though this book’s test suite stays simpler: a **present-value round-trip** check — that discounting every payment back at the periodic rate recovers the original principal, which is SPEC.md’s own definition of “correct” turned into a test that doesn’t depend on the implementer’s formula at all — plus **linearity** (doubling the principal should exactly double the payment) and **monotonicity** (a longer term should always lower the payment; a higher rate should always raise it). These are called *property tests*: instead of asserting one hand-computed number, they assert a relationship that has to hold regardless of how the formula is written. That’s a real technique, worth filing away even if this book doesn’t build a full property-based suite around it.

One proposed case uses a pytest feature this book hasn’t shown yet — **parametrize** — and it’s worth pausing on the syntax before getting to what went wrong with it. Rather than write four nearly-identical test functions (one each for annual, quarterly, biweekly, and weekly payments), `@pytest.mark.parametrize` lets you write the test body *once* and run it several times, once per row of a table you supply. The decorator’s first argument is a string naming the values that change from run to run; the second is a list of tuples supplying those values, one tuple per run. Pytest calls the test function once per tuple, passing each value in by name — which means the function’s own parameter list has to actually include those names, or pytest has nowhere to put them. Here, `ppy` is short for “payments per year” — matching the `payments_per_year` argument `calculate_payment` itself expects — and `expected` is the payment each row claims is correct:

```
@pytest.mark.parametrize("ppy,expected", [
    (1, 212_000.0),
    (4, 3603.70),
    (26, 553.17),
    (52, 594.74),
])
```

```
def test_non_monthly_frequencies(
    principal=200_000, annual_rate=0.06, term_years=30
):
    payment = calculate_payment(
        principal=principal, annual_rate=annual_rate,
        term_years=term_years, payments_per_year=ppy,
    )
    assert payment == pytest.approx(expected, abs=0.01)
```

Try running this exactly as given, and it doesn't get anywhere near checking any numbers — pytest refuses to even collect it:

```
ERROR test_core.py::test_non_monthly_frequencies:
function uses no argument 'ppy'
```

Look at the function signature and the reason is right there: `test_non_monthly_frequencies` takes `principal`, `annual_rate`, and `term_years` — but never `ppy` or `expected`, the two names the parametrize table is trying to hand it. Pytest has values to inject and nowhere to put them. That's the first, easiest thing to catch here — a beginner doesn't need to verify a single number by hand to notice the whole test won't even run. The fix is mechanical: add the missing names to the signature.

```
def test_non_monthly_frequencies(
    ppy, expected, principal=200_000, annual_rate=0.06, term_years=30
):
```

Fix that, and the test is at least *runnable* — though not yet, in this project specifically: `calculate_payment` doesn't exist until Chapter 6, so right now this would fail with the same import error every other test in this chapter fails with, not a clean pass/fail split. The two-pass-two-fail result below is what you'd see *after* Chapter 6's implementation exists — worth keeping straight so you're not confused when trying this today gets you an import error instead. Once that implementation exists, though, it's genuinely informative: two rows pass, two fail. `ppy=4` and `ppy=26` check out. `ppy=1` and `ppy=52` don't, and it's worth working out why by hand — the same way 4.6 asked you to check Pi's arithmetic — rather than assuming the numbers are simply wrong. At `ppy=1`, `calculate_payment` actually returns about **\$14,529.78**, not the \$212,000 the table claims. But \$212,000 isn't a made-up number — it's exactly what a *single* payment after one year on this loan would be (the \$200,000 growing by 6% interest, paid off in one shot), a completely different scenario from the one this row's actual parameters describe (30 *annual* payments, not 1). Same story at `ppy=52`: the real result is about **\$276.53**, while \$594.74 is the correct weekly payment for a \$30,000 loan over one year — again a genuine number, just answering a different question than the one this test's fixed `principal=200_000`, `term_years=30` actually poses.

Both wrong rows are individually correct arithmetic, attached to the wrong problem. That's a harder mistake to catch than a plain miscalculation, because

nothing about \$212,000 or \$594.74 looks unreasonable in isolation — it only falls apart once you check each row against the *specific* inputs that row is actually parametrized to use, which is exactly why 5.6.2 asked you to verify expected values rather than skim them for plausibility. Two layers of review, in other words: does it even run, and only then, does it compute the right thing.

Pointing this out and asking Pi to take another pass — the normal next step, not a special one — produced a version worth looking at, because the fix isn't just “corrected numbers”:

```
@pytest.mark.parametrize(
    "principal, annual_rate, term_years, payments_per_year, expected",
    [
        (200_000, 0.06, 30, 1, 14_529.78), # annual
        (200_000, 0.06, 30, 4, 3_603.70),  # quarterly
        (200_000, 0.06, 30, 12, 1_199.10), # monthly (== worked example)
        (200_000, 0.06, 30, 26, 553.17),   # biweekly
        (200_000, 0.06, 30, 52, 276.53),   # weekly
    ],
)
def test_non_monthly_frequencies(
    principal, annual_rate, term_years, payments_per_year, expected
):
    payment = calculate_payment(
        principal=principal, annual_rate=annual_rate,
        term_years=term_years, payments_per_year=payments_per_year,
    )
    assert payment == pytest.approx(expected, abs=0.01)
```

This runs and all five rows pass — verify that independently, the same way as everything else in this section, rather than taking a second round of Pi's output any more on faith than the first. But notice *what* changed, not just that the numbers are now right: every row now carries its own **principal**, **annual_rate**, and **term_years** explicitly, instead of leaving three of the four inputs as fixed defaults in the function signature and only varying **payments_per_year** per row. That's not a cosmetic difference — it's what actually made the original bug possible in the first place. When only **ppy** varied per row, a row's expected value could quietly describe a *different* principal or term than the one the test would actually run with, and nothing about the test's structure would catch it. With every input explicit in the same row as its answer, that entire class of mistake has nowhere left to hide — a row is either internally consistent or it visibly isn't, without needing to cross-reference a default hiding three lines up. It also picked up a nice detail worth noticing on your own next time: the **payments_per_year=12** row's expected value is **1_199.10** — the exact Chapter 4.5 worked example, now sitting inside this table as a built-in cross-check against a number you already trust.

None of this means the larger model did badly — quite the opposite; the prop-

erty tests and the “flag it, don’t guess” section are better instincts than a lot of hand-written test suites manage. It means review scales with ambition: the more a model gives you, the more of it actually needs checking, not less.

5.7 Debugger Basics: pdb

5.7.1 When to Reach for It

Once Chapter 6 exists and something eventually fails in a way that isn’t obvious from the error message alone, the instinct to immediately ask Pi to fix it is worth resisting, at least briefly. Finding your own bugs first — even occasionally, even just to practice — builds exactly the judgment you’ll need to properly review Pi’s fixes later. If you can’t tell whether a fix actually addresses the bug, you’re not really reviewing it.

5.7.2 Trying It, On Something That Actually Exists

Everything else in this chapter is either already correct (the worked-example fixture) or deliberately red because `calculate_payment` doesn’t exist yet — that’s Chapter 6’s job, not a bug to step through. Neither gives you a real failure to investigate *right now*. So build one, small and throwaway, the same way 5.2.3 did.

```
vi tests/test_scratch_debug.py

from mortgage_calculator_book.scratch_debug import total_paid

def test_total_paid_sums_all_payments():
    assert total_paid([100, 200, 300]) == 600

vi src/mortgage_calculator_book/scratch_debug.py

def total_paid(payments):
    """Sum a list of periodic payments."""
    total = 0
    for amount in payments:
        total = amount
    return total
```

Run it:

```
pytest tests/test_scratch_debug.py -v
```

It fails: `assert 300 == 600`. That tells you *that* something’s wrong, not *why*. Rather than stare at four lines until it jumps out — it will eventually, but that’s not the point of this exercise — drop a breakpoint into the loop and watch it happen:

```
def total_paid(payments):
    total = 0
    for amount in payments:
        breakpoint()
        total = amount
    return total
```

Run the test again. Execution pauses the first time the loop body runs, before that line executes. Print both variables (`p total` → 0, `p amount` → 100), then step past the assignment (`n`) and print `total` again — it’s 100, matching `amount`, which is expected after the first payment. Continue to the next iteration (`c`); you’re back at the same breakpoint, `amount` now 200, `total` still 100 from before. Step past the assignment again (`n`) and print `total` once more: it’s 200 — not 300, which is what `100 + 200` would give you if the loop were accumulating. That’s the bug, watched directly rather than guessed at: `total = amount` should be `total += amount`.

Fix it, delete the `breakpoint()` line, and confirm:

```
pytest tests/test_scratch_debug.py -v
```

Green. Delete both scratch files — not part of the real project, same as 5.2.3’s:

```
rm tests/test_scratch_debug.py \
    src/mortgage_calculator_book/scratch_debug.py
```

For reference, the commands you just used:

```
n          step to the next line
s          step into a function call
c          continue running until the next breakpoint (or the end)
p some_variable  print a variable's current value
```

5.7.3 Why This Is Worth a Page

This isn’t meant to make you a debugging expert — a page of practice won’t do that. It’s meant to give you one more tool between “the test failed” and “ask the agent to fix it,” so that when you do read Pi’s proposed fix later, you’re reading it as someone who at least attempted to understand the failure themselves, not as someone encountering the bug for the first time via someone else’s patch.

5.8 Edge Cases Worth Testing Now

5.8.1 The Two Cases from Chapter 4.4.3

Add these to `tests/test_core.py`, even though `calculate_payment` doesn’t exist yet:

```
def test_zero_interest_loan():
    payment = calculate_payment(
        principal=12_000,
        annual_rate=0.0,
        term_years=1,
        payments_per_year=12,
    )
    assert payment == pytest.approx(1000.00, abs=0.01)

def test_single_payment():
    payment = calculate_payment(
        principal=10_000,
        annual_rate=0.06,
        term_years=1,
        payments_per_year=1,
    )
    assert payment == pytest.approx(10600.00, abs=0.01)
```

Both use the exact numbers from Chapter 4.5's edge-case discussion — chosen there specifically because they're clean enough to verify by hand ($\$12,000 \div 12 = \$1,000$; $\$10,000 \times 1.06 = \$10,600$).

5.8.2 Planting Red Tests on Purpose

Run the full suite now:

```
pytest -v
```

Same collection error as 5.5.2, not three separate failures — `mortgage_calculator_book.core` still doesn't exist, so pytest can't even import the file to reach any of the three tests inside it, worked example and both edge cases alike:

```
ERROR tests/test_core.py
ModuleNotFoundError: No module named 'mortgage_calculator_book.core'
```

That's still exactly the state Chapter 6 needs to find this project in — one missing module standing between here and green, not three separate bugs to chase. You'll see three individually reported passes once Chapter 6 exists; right now, before any implementation exists at all, one honest collection error covering all three is the correct red, not a sign something's already wrong.

This red suite is worth committing — it's a real, intentional artifact of this project, not a mistake to hide:

```
git add .
git commit -m "Add pytest and a red test suite for calculate_payment"
git push
```


5.9 Checkpoint

Before moving to Chapter 6, this should all be true:

- ☐ `pytest` is installed as a dev dependency, and `pyproject.toml` shows it under `[dependency-groups]`
- ☐ `tests/conftest.py` defines the `worked_example` fixture
- ☐ `tests/test_core.py` contains three tests: the worked example, zero-interest, and single-payment — all currently red via one collection error, since `core.py` doesn't exist yet
- ☐ You can explain why each test's expected value is correct, independent of any code
- ☐ `ruff check .` and `ruff format .` both pass on the test files
- ☐ You've used `breakpoint()` at least once, even in the scratch example
- ☐ The red suite is committed and pushed — not just sitting locally

What's next: Chapter 6 makes these three tests go green — the first real implementation this project has had.

Chapter 6 — Mathematical Core Library

Contents

6.1 Why This Chapter Exists	71
6.2 What “Pure” Means, and Why It’s the Rule Here	71
6.2.1 Pure Functions	71
6.2.2 The Rule for This Module	71
6.3 Module Layout	72
6.3.1 Where This Lives	72
6.3.2 Naming Things to Match the Spec	72
6.4 Implementing the Periodic Rate and Payment-Count Helpers	72
6.4.1 Annual Rate to Periodic Rate	72
6.4.2 Term and Frequency to Total Payments	72
6.4.3 Watching the Suite	72
6.5 Implementing the Fixed Payment Formula	73
6.5.1 Code That Mirrors the Math	73
6.5.2 Agent-Assisted Implementation	73
6.5.3 Reviewing Before Accepting	73
6.6 Handling the Named Edge Cases	74
6.6.1 Zero-Interest Loans	74
6.6.2 Single-Payment Terms	74
6.6.3 Confirming Both Are Genuinely Fixed	74
6.7 Verifying Against the Answer Key	74
6.7.1 The Worked Example	74
6.7.2 If It Doesn’t Match	75
6.8 Refactor	75
6.8.1 The Refactor Step, For Real This Time	75
6.8.2 Ruff Pass	75
6.8.3 A Note on Rounding	75
6.9 Checkpoint	75

6.1 Why This Chapter Exists

Chapter 5 left you with three failing tests and a precise target: make them pass, using the formula derived in Chapter 4.4. This chapter does exactly that — the first real implementation this project has had, and the first real payoff of the red/green/refactor cycle set up in Chapter 5.

By the end, all three tests from Chapter 5 will be green, and you’ll have a small, pure module that every later front end — CLI, UI, and eventually a language model — calls into without ever duplicating this logic.

6.2 What “Pure” Means, and Why It’s the Rule Here

6.2.1 Pure Functions

A function is **pure** if it does one thing: given the same inputs, it always returns the same output, with no side effects — no printing, no reading files, no reaching out to a network, no depending on anything outside its own arguments. `calculate_payment(200_000, 0.06, 30, 12)` should return the same number every single time it’s called, forever, with nothing else going on.

6.2.2 The Rule for This Module

Everything in `mortgage_calculator_book.core` follows this rule, with no exceptions. No `print()` statements for debugging left behind, no reading configuration, no formatting output for a human to read — that’s the CLI’s job in Chapter 8 and the UI’s job in Chapter 9, not this module’s.

Process concept: why purity matters more, not less, with an agent in the loop. A pure function is a narrow, easily verified contract: given these inputs, this exact output. That’s precisely the kind of task an agent can be checked against cheaply and completely — run the function, compare the result, done. The moment a function reaches out to the filesystem, the network, or global state, verifying an agent’s implementation of it becomes considerably harder, because “correct” now depends on things outside the function’s own signature. Keeping the core pure isn’t just good architecture in the abstract — it’s what makes Chapter 6.5’s agent-assisted implementation actually checkable.

6.3 Module Layout

6.3.1 Where This Lives

Inside the `src/mortgage_calculator_book/` package from Chapter 0.7.3, create `core.py`. This is the only file this chapter touches.

6.3.2 Naming Things to Match the Spec

Function names in this module should read as a direct translation of `SPEC.md`’s “Derived quantities” and “Outputs” sections from Chapter 4.7.3 — not because it’s required, but because it means anyone (or anything) reading the spec and the code side by side can match them up on sight.

6.4 Implementing the Periodic Rate and Payment-Count Helpers

6.4.1 Annual Rate to Periodic Rate

The conversion flagged repeatedly since Chapter 4.3.2, as its own small, independently testable function:

```
def annual_rate_to_periodic(annual_rate: float, payments_per_year: int) -> float:
    """Convert an annual interest rate to the rate for a single period."""
    return annual_rate / payments_per_year
```

6.4.2 Term and Frequency to Total Payments

```
def total_payments(term_years: int, payments_per_year: int) -> int:
    """Total number of payments over the life of the loan."""
    return term_years * payments_per_year
```

Both are one-liners, and that’s fine — the point of separating them out isn’t complexity, it’s giving each conversion a name and a place where a mistake in either one is easy to isolate and test on its own, rather than buried inside a larger formula.

6.4.3 Watching the Suite

These two helpers don’t make any of Chapter 5’s three tests pass on their own — `calculate_payment` still doesn’t exist. Run `pytest -v` anyway, out of habit; still red, as expected.

6.5 Implementing the Fixed Payment Formula

6.5.1 Code That Mirrors the Math

Translated directly from Chapter 4.4.1, term for term:

```
def calculate_payment(
    principal: float,
    annual_rate: float,
    term_years: int,
    payments_per_year: int = 12,
) -> float:
    """Fixed periodic payment for a fixed-rate loan (see SPEC.md)."""
    r = annual_rate_to_periodic(annual_rate, payments_per_year)
    n = total_payments(term_years, payments_per_year)

    if r == 0:
        return principal / n

    return principal * (r * (1 + r) ** n) / ((1 + r) ** n - 1)
```

Notice how closely this reads against the formula: $r * (1 + r) ** n$ in the numerator, $(1 + r) ** n - 1$ in the denominator — the same shape as $\frac{r(1+r)^n}{(1+r)^n - 1}$ from 4.4.1, not an optimized or rearranged version of it. Clarity against the derivation matters more here than performance; this function will never be a bottleneck in this project.

6.5.2 Agent-Assisted Implementation

If you'd rather have Pi draft this rather than typing it yourself:

```
pi "Implement calculate_payment in \
src/mortgage_calculator_book/core.py to make the \
tests in tests/test_core.py pass. The formula is in \
docs/derivation.md; SPEC.md defines what counts as \
correct output, not how to compute it. Keep the \
function pure - no I/O, no printing."
```

6.5.3 Reviewing Before Accepting

Whether you wrote it or Pi did, check specifically for the mistakes this formula invites:

- **Rate conversion:** does it use the *periodic* rate inside the exponentiation, not the raw annual rate?
- **Off-by-one in payment count:** is `n` computed as `term_years * payments_per_year`, not something shifted by one?

- **Silent float issues:** is there an unguarded division that could produce `inf` or a `ZeroDivisionError` for some input this module hasn't been asked to validate yet? (Chapter 7 handles rejecting bad input; this module just needs to not silently misbehave on the inputs it's given.)

6.6 Handling the Named Edge Cases

6.6.1 Zero-Interest Loans

The `if r == 0` branch above exists for exactly the reason 4.4.3 described: the general formula divides by `r`, which is undefined at zero, even though the real-world answer (`principal / n`) is completely well-defined. Run the zero-interest test:

```
pytest tests/test_core.py::test_zero_interest_loan -v
```

6.6.2 Single-Payment Terms

Unlike the zero-interest case, this one needs **no special branch** — as 4.4.3 noted, substituting $n = 1$ into the general formula produces the same answer as the direct “principal plus one period’s interest” reasoning. Run it to confirm:

```
pytest tests/test_core.py::test_single_payment -v
```

If this test fails, it’s worth checking your formula’s algebra against 4.4.1 line by line before adding a special case you don’t actually need — a passing test achieved by adding an unnecessary branch is a sign something upstream is subtly wrong, not a problem solved.

6.6.3 Confirming Both Are Genuinely Fixed

Run the full suite:

```
pytest -v
```

If you see three passes here rather than three failures, double-check that you’re reading real green — not a test that was quietly weakened (a loosened `abs=` tolerance, a rewritten expected value) to make a stubborn failure go away. That’s the opposite of what this chapter is for.

6.7 Verifying Against the Answer Key

6.7.1 The Worked Example

```
pytest tests/test_core.py::test_matches_worked_example -v
```

This should now pass, confirming `calculate_payment(200_000, 0.06, 30, 12)` returns something within a cent of \$1,199.10.

6.7.2 If It Doesn't Match

In order of likelihood, check: is the periodic rate actually `annual_rate / payments_per_year`, computed *before* being raised to a power (a rate accidentally raised to a power before dividing is a classic version of this bug)? Is `n` actually 360, not 30 (term years, forgetting to multiply by frequency)? Is the formula's numerator and denominator each matching 4.4.1 exactly, with no terms transposed? These three, in this order, catch the overwhelming majority of first attempts that don't match.

6.8 Refactor

6.8.1 The Refactor Step, For Real This Time

Chapter 5.2's tiny `add` example didn't have anything worth refactoring. This one might: are `annual_rate_to_periodic` and `total_payments` named clearly? Is `calculate_payment` still readable against the formula, or did fixing 6.7.2's bug leave behind anything awkward? Clean it up now, with the full test suite as a safety net — this is exactly what the “refactor” step is for.

6.8.2 Ruff Pass

```
ruff check . && ruff format .
```

Consistent with the habit established in Chapter 3.6.1 — every commit, not just some.

6.8.3 A Note on Rounding

You may notice `calculate_payment` currently returns full floating-point precision (1199.1010503055138), not a value already rounded to the cent — the tests handle that with `pytest.approx(..., abs=0.01)` rather than the function itself rounding. This is deliberate for now: rounding is a presentation decision, and mixing it into the core risks baking a specific display choice into a function that's supposed to stay pure and general. Chapter 7's validation layer is where this book properly addresses currency precision and bounds — flagged here so it doesn't feel like an oversight when it doesn't come up again until then.

6.9 Checkpoint

Before moving to Chapter 7, this should all be true:

- ☐ `src/mortgage_calculator_book/core.py` contains `annual_rate_to_periodic`, `total_payments`, and `calculate_payment`
- ☐ All three tests from Chapter 5 pass: `pytest -v` shows three green
- ☐ `calculate_payment` has no I/O, no printing, no dependencies outside its own arguments

- ☐ You can explain, without looking at the code, what each of the three checks in 6.7.2 is guarding against
- ☐ `ruff check .` and `ruff format .` both pass
- ☐ Everything is committed

What's next: Chapter 7 wraps this trusted, pure core in a validation layer — because so far, `calculate_payment` will happily compute a confident, wrong-looking answer for a negative principal or an absurd interest rate, and nothing has stopped it from being asked to.

Chapter 7 — Validation

Contents

7.1 Why This Chapter Exists	79
7.2 Why Validation Is Its Own Layer, Not Bolted onto the Core . . .	79
7.2.1 Revisiting Purity	79
7.2.2 What Skipping This Layer Costs	79
7.2.3 Where This Is Headed	79
7.3 What Needs Validating	79
7.3.1 Revisiting SPEC.md’s Inputs	79
7.3.2 Turning Edge Cases into Explicit Boundaries	80
7.4 Introducing Pydantic	80
7.4.1 The Problem It Solves	80
7.4.2 Installing	80
7.4.3 A First Minimal Model	80
7.5 Building the Input Model	81
7.5.1 The Model	81
7.5.2 Custom Validators, Explained	82
7.5.3 Error Messages as a User-Facing Surface	82
7.6 Agent-Assisted TDD, Applied to Validation	83
7.6.1 Setting Aside What You Just Built	83
7.6.2 Writing the Failing Tests First	83
7.6.3 Prompting Pi	84
7.6.4 Reviewing the Proposal, and Comparing Notes	84
7.7 Wiring Validation to the Core	85
7.7.1 The Only Path In	85
7.7.2 Confirming the Boundary	85
7.7.3 Running Everything	85
7.8 Refactor and Ruff Pass	86
7.9 Checkpoint	86

7.1 Why This Chapter Exists

Chapter 6 left you with a trusted, correct core — but one that will compute a confident answer for a negative principal, a 400% interest rate, or a term of zero years, because nothing has ever told it not to. This chapter builds the layer that catches bad input before it ever reaches `calculate_payment`.

By the end, a Pydantic-based input model will sit between the outside world and Chapter 6’s core, fully tested, enforcing exactly what `SPEC.md` says is valid.

7.2 Why Validation Is Its Own Layer, Not Bolted onto the Core

7.2.1 Revisiting Purity

Chapter 6.2 established a firm rule: the core has no I/O, no dependencies outside its own arguments — nothing but calculation. Validation is different in kind, not just in code: it exists specifically to deal with input from the outside world, which is exactly what the core was built to never touch directly. Putting a check like `if principal <= 0: raise ValueError` inside `calculate_payment` would quietly violate the boundary Chapter 6 spent a whole chapter establishing.

7.2.2 What Skipping This Layer Costs

Without it, bad input doesn’t announce itself clearly — it either crashes somewhere unhelpful (a `ZeroDivisionError` three function calls deep, far from where the bad number actually entered the system) or, worse, produces a number that looks like a real answer but means nothing (a “payment” computed from a negative principal). Neither is a good experience for a user, and neither is easy to debug.

7.2.3 Where This Is Headed

Notice the shape of what you’re about to build: a declarative description of what valid input looks like, expressed as a schema. Chapter 10’s tool interface needs almost exactly this same shape — a schema a language model can read and be held to — which is why this chapter’s work gets reused rather than redone.

7.3 What Needs Validating

7.3.1 Revisiting `SPEC.md`’s Inputs

From Chapter 4.7.3’s revised spec: `principal`, `annual_rate`, `term_years`, `payments_per_year`. Each needs a definition of “valid” beyond just “the right

type”:

- **principal** — must be positive; a loan of zero or negative dollars isn’t a loan.
- **annual_rate** — must be a plausible rate. Zero is valid (Chapter 6.6.1’s edge case); something like 1.5 (150%) almost certainly represents a typo, not a real mortgage.
- **term_years** — must be positive.
- **payments_per_year** — must be positive.

7.3.2 Turning Edge Cases into Explicit Boundaries

Chapter 6’s zero-interest case showed that `annual_rate = 0` is a legitimate input, not an error — which means the validation boundary here has to be “rate cannot be negative,” not “rate must be strictly positive.” Get this wrong and you’ll accidentally reject a test case Chapter 6 was specifically built to handle.

7.4 Introducing Pydantic

7.4.1 The Problem It Solves

A validation function built from a chain of `if` statements works, but it scales badly — the checks live separately from the data they’re checking, error messages have to be written by hand for every case, and there’s no single place that describes what “valid input” even means at a glance. Pydantic solves this by letting you declare validity as part of a data model’s definition, rather than as separate procedural code.

7.4.2 Installing

```
uv add pydantic
```

Unlike Ruff and `pytest`, this isn’t a `--dev` dependency — the calculator needs Pydantic at runtime, not just while you’re developing it.

7.4.3 A First Minimal Model

Try this directly rather than just reading it — and unlike 5.2.3 or 5.7.2, there’s no file to create or delete here. This is small enough to try straight in Python’s interactive prompt (its **REPL** — “read-eval-print loop”: type an expression, see its result immediately, repeat). Start one inside your project’s environment:

```
uv run python
```

You’re now looking at a `>>>` prompt, running inside your project the same way `uv run` always does. Type this, pressing Enter after each line (a blank line after the `class` block runs it):

```
from pydantic import BaseModel
```

```
class Example(BaseModel):
    name: str
    age: int
```

Now try it with valid data:

```
Example(name="Robert", age=40)
```

You should see `Example(name='Robert', age=40)` printed back — it worked, Pydantic accepted it. Now try something that doesn't match the declared type:

```
Example(name="Robert", age="not a number")
```

This time Pydantic raises a `ValidationError` — a real, detailed error naming exactly which field failed and why, without you writing a single `isinstance` check yourself. Read what it prints; it's more informative than a typical Python `TypeError`, and it's the same style of error you'll be reading for the rest of this chapter.

Exit the REPL when you're done — same key you used to leave Pi's interactive session back in 1.6.1:

```
exit()
```

Nothing here needed saving or cleaning up; it never touched a file in the first place. Section 7.5 is where a version of this actually becomes part of the project.

7.5 Building the Input Model

7.5.1 The Model

In `src/mortgage_calculator_book/validation.py`:

```
from pydantic import BaseModel, field_validator
```

```
class MortgageInput(BaseModel):
    """Validated input for a fixed-rate mortgage payment calculation."""

    principal: float
    annual_rate: float
    term_years: int
    payments_per_year: int = 12

    @field_validator("principal")
    @classmethod
    def principal_must_be_positive(cls, v: float) -> float:
        if v <= 0:
```

```

        raise ValueError("principal must be positive")
    return v

@field_validator("annual_rate")
@classmethod
def rate_must_be_plausible(cls, v: float) -> float:
    if v < 0:
        raise ValueError("annual_rate cannot be negative")
    if v >= 1:
        raise ValueError("annual_rate must be less than 1 (e.g. 0.06 for 6%)")
    return v

@field_validator("term_years")
@classmethod
def term_must_be_positive(cls, v: int) -> int:
    if v <= 0:
        raise ValueError("term_years must be positive")
    return v

@field_validator("payments_per_year")
@classmethod
def payments_per_year_must_be_positive(cls, v: int) -> int:
    if v <= 0:
        raise ValueError("payments_per_year must be positive")
    return v

```

7.5.2 Custom Validators, Explained

Each `@field_validator` runs after Pydantic’s own type checking, and raises a plain `ValueError` with a message written for a human to read — not a generic type error. Notice `rate_must_be_plausible` allows exactly zero (`v < 0` rejects negative, but zero passes through) while rejecting anything at or above 100% — matching 7.3.2’s requirement precisely.

7.5.3 Error Messages as a User-Facing Surface

The strings inside each `raise ValueError(...)` aren’t incidental — they’re what a user of Chapter 8’s CLI or Chapter 9’s UI will actually see when they enter something invalid. Write them the way you’d want to read them yourself: specific about what’s wrong, not just “invalid input.”

Commit this, the same as every other real step in this project:

```

git add src/mortgage_calculator_book/validation.py
git commit -m "Add MortgageInput validation model"
git push

```

7.6 Agent-Assisted TDD, Applied to Validation

7.5 had you type `MortgageInput` by hand, in full, before running a single test against it — useful for seeing the whole class at once, but not actually how this book has been building things since Chapter 5: tests first, then an implementation that has to earn a passing result. This section does it that way for real, which means setting aside the version you just wrote and committed.

7.6.1 Setting Aside What You Just Built

Because 7.5.3 committed that version, deleting it now doesn't lose anything — it's still sitting in git history if you want it later, including for a comparison at the end of this section:

```
git rm src/mortgage_calculator_book/validation.py
git commit -m "Remove hand-written validation.py to redo via TDD"
```

7.6.2 Writing the Failing Tests First

In `tests/test_validation.py`:

```
import pytest
from pydantic import ValidationError

from mortgage_calculator_book.validation import MortgageInput


def test_valid_input_accepted():
    result = MortgageInput(
        principal=200_000, annual_rate=0.06, term_years=30, payments_per_year=12
    )
    assert result.principal == 200_000


def test_negative_principal_rejected():
    with pytest.raises(ValidationError):
        MortgageInput(principal=-1000, annual_rate=0.06, term_years=30)


def test_zero_principal_rejected():
    with pytest.raises(ValidationError):
        MortgageInput(principal=0, annual_rate=0.06, term_years=30)


def test_zero_rate_accepted():
    """Zero interest is valid (see docs/derivation.md), not an error."""
    result = MortgageInput(principal=12_000, annual_rate=0.0, term_years=1)
```



```

assert result.annual_rate == 0.0

def test_negative_rate_rejected():
    with pytest.raises(ValidationError):
        MortgageInput(principal=200_000, annual_rate=-0.01, term_years=30)

def test_rate_above_one_rejected():
    with pytest.raises(ValidationError):
        MortgageInput(principal=200_000, annual_rate=1.5, term_years=30)

def test_zero_term_rejected():
    with pytest.raises(ValidationError):
        MortgageInput(principal=200_000, annual_rate=0.06, term_years=0)

```

Run it:

```
pytest tests/test_validation.py -v
```

One collection error, the same shape as Chapter 5.8.2's — `validation.py` genuinely doesn't exist now, so `pytest` can't import the file to reach any of these seven tests. That's real red this time, not something to take on faith.

7.6.3 Prompting Pi

```

pi "Implement MortgageInput in \
    src/mortgage_calculator_book/validation.py as a \
    Pydantic model to make the tests in \
    tests/test_validation.py pass. Read SPEC.md first \
    for what counts as valid input."

```

Once Pi's proposal is applied, confirm it actually earns green before reviewing further:

```
pytest tests/test_validation.py -v
```

7.6.4 Reviewing the Proposal, and Comparing Notes

Check specifically that the boundaries match `SPEC.md` and Chapter 7.3 exactly, not just “look reasonable” — a proposal that rejects `annual_rate = 0` would pass a casual read but silently break Chapter 6.6.1's zero-interest case the moment this validation layer gets wired in front of it.

Worth doing once, now that two independent versions exist: compare Pi's proposal against the one you wrote by hand in 7.5, still sitting in git history.

```
git log --oneline -- src/mortgage_calculator_book/validation.py
```

This shows every commit that touched this file, most recent first — the hand-written version is the one from 7.5.3, right before the `git rm` commit from 7.6.1. Grab its hash and look at it:

```
git show <hash>:src/mortgage_calculator_book/validation.py
```

Reading two independently correct implementations of the same four constraints side by side is a genuinely useful exercise on its own: where do they differ in approach, and does either version's error messages actually read better than the other's?

Once you're satisfied, commit Pi's version the normal way:

```
git add src/mortgage_calculator_book/validation.py tests/test_validation.py
git commit -m "Rebuild MortgageInput via agent-assisted TDD"
git push
```

7.7 Wiring Validation to the Core

7.7.1 The Only Path In

Add one more function to `validation.py`, or to a small new module, that connects the two:

```
from mortgage_calculator_book.core import calculate_payment
from mortgage_calculator_book.validation import MortgageInput

def calculate_validated_payment(data: MortgageInput) -> float:
    """The only supported entry point: validated input in, a payment out."""
    return calculate_payment(
        principal=data.principal,
        annual_rate=data.annual_rate,
        term_years=data.term_years,
        payments_per_year=data.payments_per_year,
    )
```

7.7.2 Confirming the Boundary

`calculate_payment` still never sees raw, unvalidated input — it only ever receives values that have already passed through `MortgageInput`. And `MortgageInput` never performs any mortgage math itself — it only validates. Each piece does exactly one job, which is the same separation-of-concerns idea from Chapter 6.2, now applied one layer further out.

7.7.3 Running Everything

```
pytest -v
```

Chapter 6’s three tests, plus this chapter’s seven, all green.

7.8 Refactor and Ruff Pass

```
ruff check . && ruff format .
```

Same habit as every prior chapter — nothing new here, which is itself a small sign the habit has taken hold.

7.9 Checkpoint

Before moving to Chapter 8, this should all be true:

- ☐ Pydantic is installed as a runtime dependency
- ☐ `MortgageInput` enforces every constraint from `SPEC.md`: positive principal, rate in `[0, 1)`, positive term, positive payment frequency
- ☐ `test_zero_rate_accepted` passes — confirming validation didn’t accidentally break Chapter 6’s zero-interest case
- ☐ `calculate_validated_payment` is the only path from raw input to a payment result
- ☐ The full test suite (10 tests: 3 from Chapter 6, 7 from this chapter) is green
- ☐ Everything is committed

What’s next: Chapter 8 gives this validated core its first real user-facing surface — a command-line interface a person can actually run.

Chapter 8 — Command Line Interface

Contents

8.1 Why This Chapter Exists	89
8.2 What the CLI Needs to Do	89
8.2.1 Revisiting the Spec	89
8.2.2 Sketching the Shape First	89
8.3 argparse Basics	89
8.3.1 Why argparse	89
8.3.2 Arguments, Types, Defaults, Help Text	90
8.3.3 A Minimal Working Parser	90
8.3.4 Aside: Typer	91
8.4 Wiring the CLI to Validation and the Core	91
8.4.1 The Full Pipeline, Assembled	91
8.4.2 Handling Validation Failure Gracefully	92
8.4.3 Wiring Up the Command, and Trying It	92
8.5 JSON Output	93
8.5.1 Why JSON, Not Just Text	93
8.5.2 A <code>--format</code> Flag	93
8.5.3 Serializing with the Standard Library	94
8.5.4 Forward-Note	94
8.6 Agent-Assisted Build, With Tests First	94
8.6.1 Setting Aside What You Just Built	94
8.6.2 CLI-Level Tests	95
8.6.3 Prompting Pi	96
8.6.4 Reviewing the Diff, and Comparing Notes	96
8.7 Environment Variables and <code>.env</code>	96
8.7.1 Why Now, Not Chapter 11	96
8.7.2 <code>python-dotenv</code>	97
8.7.3 Never Commit Your Secrets	97
8.7.4 Forward-Note	98
8.8 Writing the README	98
8.8.1 A Little More Markdown	98
8.8.2 What Belongs in It	98
8.8.3 A Draft	98
8.8.4 Letting Pi Draft It Instead	99
8.9 Refactor and Ruff Pass	99
8.10 Checkpoint	100

8.1 Why This Chapter Exists

Everything so far has been invisible to anyone who isn't reading code — the core library, the validation layer, all of it only reachable through a test file. This chapter builds the calculator's first real, user-facing surface: a command a person can actually type and get an answer from.

By the end, you'll have a working CLI with both human-readable and JSON output, a `.env` pattern in place for a secret you don't need yet, and a README that describes all of it.

8.2 What the CLI Needs to Do

8.2.1 Revisiting the Spec

SPEC.md's inputs — `principal`, `annual_rate`, `term_years`, `payments_per_year` — all need to become command-line flags. Its one output — `payment` — needs to be printed somewhere a user will see it. This is the first chapter where every one of the spec's inputs and outputs has to actually be exposed, rather than just referenced inside a test.

8.2.2 Sketching the Shape First

Before writing code:

```
mortgage-calculator-book --principal 200000 --annual-rate 0.06 --term-years 30
# Fixed periodic payment: $1,199.10
```

And with an invalid input:

```
mortgage-calculator-book --principal -1000 --annual-rate 0.06 --term-years 30
# Error: principal must be positive
```

Having this shape settled before writing `argparse` code turns the implementation into a matter of matching a known target, the same discipline Chapter 5 established for the core library.

8.3 argparse Basics

8.3.1 Why argparse

`argparse` ships with Python — no new dependency, no version to track, and it's more than capable of everything this project needs. `Typer` and similar libraries offer a nicer developer experience at the cost of an added dependency; for a first CLI, that trade isn't worth making yet.

8.3.2 Arguments, Types, Defaults, Help Text

```
import argparse
```

```
parser = argparse.ArgumentParser(description="Calculate a fixed mortgage payment.")
parser.add_argument("--principal", type=float, required=True, help="Loan amount, in dollars")
parser.add_argument("--annual-rate", type=float, required=True, help="Annual rate, e.g. 0.05")
```

`type=float` means `argparse` converts the string a user typed before your code ever sees it — "200000" arrives as `200000.0`, not a string you'd have to convert yourself. `required=True` means `argparse` handles the "you forgot an argument" error entirely on its own, with no code from you.

8.3.3 A Minimal Working Parser

In `src/mortgage_calculator_book/cli.py`:

```
import argparse
```

```
def build_parser() -> argparse.ArgumentParser:
    parser = argparse.ArgumentParser(
        description="Calculate the fixed periodic payment for a fixed-rate mortgage."
    )
    parser.add_argument("--principal", type=float, required=True, help="Loan amount, in dollars")
    parser.add_argument(
        "--annual-rate", type=float, required=True, help="Annual interest rate, e.g. 0.05"
    )
    parser.add_argument("--term-years", type=int, required=True, help="Loan term, in years")
    parser.add_argument(
        "--payments-per-year", type=int, default=12, help="Payments per year (default: 12)"
    )
    parser.add_argument(
        "--format", choices=["text", "json"], default="text", help="Output format"
    )
    return parser
```

Notice `6%%`, not `6%`, in the annual-rate help text — that's not a typo. `argparse` runs every `help=` string through %-style formatting when it renders `--help`, so a bare `%` looks like the start of a format specifier and crashes with `ValueError: incomplete format` the moment someone actually runs `--help`, not when you define the parser. `%%` is how you write a literal percent sign in that formatting style; `argparse` collapses it back down to a single `%` in what it actually prints. Worth testing directly rather than trusting this description — `main` doesn't exist until 8.4.1, so this needs the REPL technique from 7.4.3 rather than an actual command:

```
uv run python
```

```
from mortgage_calculator_book.cli import build_parser
build_parser().parse_args(["--help"])
```

This prints the full help text and then raises `SystemExit` — that’s normal, expected `argparse` behavior for `--help`, not a bug. Confirm the annual-rate line shows a single `%`, not two. If you want to see the actual crash first, temporarily change `6%%` back to `6%`, rerun the two lines above, and watch it raise `ValueError: incomplete format` instead — then put the `%%` back.

8.3.4 Aside: Typer

Typer builds on Python type hints to generate a CLI with less boilerplate than `argparse`, and produces friendlier help text by default. It’s a reasonable choice for a larger project. This book sticks with `argparse` specifically to avoid a dependency the project doesn’t strictly need — worth knowing Typer exists for whenever a future project’s CLI grows complex enough to justify it.

8.4 Wiring the CLI to Validation and the Core

8.4.1 The Full Pipeline, Assembled

Same file, `src/mortgage_calculator_book/cli.py`, building on the `build_parser` function from 8.3.3 rather than replacing it. First, add these imports alongside the existing `import argparse` at the top of the file:

```
import sys

from pydantic import ValidationError

from mortgage_calculator_book.validation import MortgageInput, calculate_validated_payment
```

Then add `main` below `build_parser`, calling it directly:

```
def main(argv: list[str] | None = None) -> int:
    parser = build_parser()
    args = parser.parse_args(argv)

    try:
        data = MortgageInput(
            principal=args.principal,
            annual_rate=args.annual_rate,
            term_years=args.term_years,
            payments_per_year=args.payments_per_year,
        )
    except ValidationError as exc:
        for error in exc.errors():
            print(f"Error: {error['msg']}", file=sys.stderr)
```



```

    return 1

    payment = calculate_validated_payment(data)
    print(f"Fixed periodic payment: ${payment:,.2f}")
    return 0

```

At this point `cli.py` has two imports blocks worth of content (`argparse` from 8.3.3, plus the three above) and two functions (`build_parser`, then `main`) — nothing from 8.3.3 gets removed or replaced.

Parsed arguments flow into `MortgageInput` (Chapter 7), which flows into `calculate_validated_payment` (also Chapter 7, which itself calls Chapter 6's `calculate_payment`) — three chapters of work, connected for the first time.

8.4.2 Handling Validation Failure Gracefully

Notice what the `except ValidationError` block does *not* do: it doesn't let Pydantic's default error formatting — which is detailed, but written for developers, not end users — reach the terminal directly. It extracts just the message from each error and prints it the way a person asked to fix their input actually wants to read it.

8.4.3 Wiring Up the Command, and Trying It

Chapter 0.7.2 mentioned a `[project.scripts]` entry in `pyproject.toml`, pointing at a placeholder `main` that didn't exist yet. It does now — point the entry at it:

```

vi pyproject.toml

[project.scripts]
mortgage-calculator-book = "mortgage_calculator_book.cli:main"

```

(It was `mortgage_calculator_book:main` — the package's top-level `__init__.py`, which has no `main` function. Now it points at the one you actually built, in `cli.py`.) Pick up the change:

```
uv sync
```

Run it for real, with the Chapter 4.5 worked example:

```

uv run mortgage-calculator-book \
    --principal 200000 --annual-rate 0.06 --term-years 30

```

```
Fixed periodic payment: $1,199.10
```

Matches every other front end this project will produce — the CLI is the first to confirm this number; Chapters 9 through 11 each confirm it again, a different way. Now try the error path from 8.4.2, as a real command instead of a description of one:

```
uv run mortgage-calculator-book \
    --principal -1000 --annual-rate 0.06 --term-years 30
```

Error: principal must be positive

That printed to `stderr`, not `stdout` — worth confirming for yourself (... `2>/dev/null` should silence it; ... `1>/dev/null` shouldn't), since it's an easy detail to lose track of once the CLI just works and you stop looking closely.

Commit the entry-point fix on its own:

```
git add pyproject.toml uv.lock
git commit -m "Wire up the mortgage-calculator-book command"
git push
```

8.5 JSON Output

8.5.1 Why JSON, Not Just Text

Printed text is fine for a person typing a command directly. It's much less fine for another program trying to read the result — parsing “Fixed periodic payment: \$1,199.10” back into a number is fragile and easy to break with the smallest formatting change. JSON output is a design choice made now, deliberately, for exactly the reuse Chapter 10 needs later: a machine-readable result, not just a human-readable one.

8.5.2 A `--format` Flag

Already present in the parser from 8.3.3 (`--format`, defaulting to `"text"`). Extend `main` to branch on it:

```
import json

def main(argv: list[str] | None = None) -> int:
    parser = build_parser()
    args = parser.parse_args(argv)

    try:
        data = MortgageInput(
            principal=args.principal,
            annual_rate=args.annual_rate,
            term_years=args.term_years,
            payments_per_year=args.payments_per_year,
        )
    except ValidationError as exc:
        for error in exc.errors():
            print(f"Error: {error['msg']}", file=sys.stderr)
```

```

        return 1

    payment = calculate_validated_payment(data)

    if args.format == "json":
        print(json.dumps({"payment": round(payment, 2)}))
    else:
        print(f"Fixed periodic payment: ${payment:,.2f}")

    return 0

```

8.5.3 Serializing with the Standard Library

`json.dumps` is all this needs — no third-party JSON library required for output this simple. `round(payment, 2)` is the first place in this project payment gets rounded for display, consistent with Chapter 6.8.3’s note that the core itself stays unrounded and full-precision.

8.5.4 Forward-Note

The shape `{"payment": 1199.10}` isn’t arbitrary — it’s the same shape Chapter 10’s tool interface will use as its output schema, so a language model calling the calculator later gets results structured the same way a script parsing this CLI’s JSON output would.

`cli.py` is feature-complete for this chapter now — commit it, since nothing has captured it yet:

```

git add src/mortgage_calculator_book/cli.py
git commit -m "Add CLI: argument parsing, validation wiring, JSON output"
git push

```

8.6 Agent-Assisted Build, With Tests First

Sections 8.3 through 8.5 had you type `build_parser` and `main` by hand, growing the file a piece at a time, before running a single test against any of it. Useful for seeing each piece land on its own, but — same issue as Chapter 7.6 — not how this book has actually been building things since Chapter 5: tests first, then an implementation that has to earn a passing result. This section does it that way for real, which means setting aside the file you just wrote and committed.

8.6.1 Setting Aside What You Just Built

Because 8.5.4 committed it, deleting it now doesn’t lose anything — it’s in git history if you want it later, including for a comparison at the end of this section:

```
git rm src/mortgage_calculator_book/cli.py
git commit -m "Remove hand-written cli.py to redo via TDD"
```

8.6.2 CLI-Level Tests

In tests/test_cli.py:

```
import json

import pytest

from mortgage_calculator_book.cli import main

def test_text_output(capsys):
    exit_code = main(["--principal", "200000", "--annual-rate", "0.06", "--term-years", "30"])
    captured = capsys.readouterr()
    assert exit_code == 0
    assert "1,199.10" in captured.out

def test_json_output(capsys):
    exit_code = main(
        [
            "--principal", "200000",
            "--annual-rate", "0.06",
            "--term-years", "30",
            "--format", "json",
        ]
    )
    captured = capsys.readouterr()
    assert exit_code == 0
    data = json.loads(captured.out)
    assert data["payment"] == pytest.approx(1199.10, abs=0.01)

def test_invalid_input_returns_error(capsys):
    exit_code = main(["--principal", "-1000", "--annual-rate", "0.06", "--term-years", "30"])
    captured = capsys.readouterr()
    assert exit_code == 1
    assert "Error" in captured.err
```

`capsys` is a built-in pytest fixture — following the same fixture mechanism from Chapter 5.4, just one pytest already provides — that captures anything printed during a test, so you can assert on it without the output actually appearing in your terminal.

Run it:

```
pytest tests/test_cli.py -v
```

One collection error, same shape as Chapters 5.8.2 and 7.6.2's — `cli.py` genuinely doesn't exist right now, so `pytest` can't import it to reach any of these three tests.

8.6.3 Prompting Pi

```
pi "Implement build_parser and main in \
    src/mortgage_calculator_book/cli.py to make the \
    tests in tests/test_cli.py pass, wiring together \
    MortgageInput and calculate_validated_payment from \
    validation.py."
```

Once Pi's proposal is applied, confirm it actually earns green:

```
pytest tests/test_cli.py -v
```

8.6.4 Reviewing the Diff, and Comparing Notes

Same habit as every chapter since 1.6 — with one thing specific to this chapter worth checking closely: does the error-handling path actually write to `stderr`, not `stdout`? It's an easy detail for an agent (or a human) to get backwards, and `test_invalid_input_returns_error` above only catches it because it checks `captured.err` specifically rather than just checking that *some* output happened.

Worth doing once more, the same way as 7.6.4: compare Pi's version against the one you wrote by hand across 8.3 through 8.5, still in git history.

```
git log --oneline -- src/mortgage_calculator_book/cli.py
```

This shows every commit that touched this file — the hand-written version is the one from 8.5.4, right before the `git rm` commit from 8.6.1. Grab its hash and look at it:

```
git show <hash>:src/mortgage_calculator_book/cli.py
```

Once you're satisfied, commit Pi's version:

```
git add src/mortgage_calculator_book/cli.py tests/test_cli.py
git commit -m "Rebuild cli.py via agent-assisted TDD"
git push
```

8.7 Environment Variables and `.env`

8.7.1 Why Now, Not Chapter 11

Nothing in this chapter needs a secret. This section exists here anyway, deliberately early, so that the pattern is already familiar and already trusted by the

time Chapter 11 actually needs it for a real API key — rather than introducing “environment variables” and “never commit a secret” for the first time in the same chapter you’re handling money-costing API calls.

8.7.2 python-dotenv

```
uv add python-dotenv
```

Create `src/mortgage_calculator_book/config.py`:

```
import os

from dotenv import load_dotenv

load_dotenv()

OPENROUTER_API_KEY = os.getenv("OPENROUTER_API_KEY")
```

`load_dotenv()` reads a `.env` file in your project root (if one exists) and makes its contents available via `os.getenv`. Nothing in this book’s code reads `OPENROUTER_API_KEY` until Chapter 11 — this module exists now purely to establish the pattern.

8.7.3 Never Commit Your Secrets

Create `.env.example` (committed, safe — no real values):

```
vi .env.example

OPENROUTER_API_KEY=your-key-here
```

Then add one more line to `.gitignore` — the one 0.7.3 created back in Chapter 0, not a new file:

```
vi .gitignore

# Byte-compiled / cached Python files
__pycache__/
*.pyc
*.pyo

# Test and linter caches
.pytest_cache/
.ruff_cache/

# Virtual environments
.venv/
.env
```

Only that last line, `.env`, is actually new here — everything above it should already be sitting in the file from 0.7.3; this just confirms what you’re adding to, rather than asking you to retype the whole thing from memory.

The rule this section wants you to leave with: `.env.example` is checked into git so anyone cloning the project knows what variables they need; `.env` itself, containing your actual key once you have one, never is. Confirm `.env` really is ignored before you ever put a real key in it:

```
git check-ignore .env
```

If this prints `.env`, git will refuse to accidentally stage it — a small, worthwhile check before it matters.

8.7.4 Forward-Note

Chapter 11 is where `OPENROUTER_API_KEY` actually gets used, wiring this project to a hosted language model. Everything here is preparation, not the payoff.

8.8 Writing the README

8.8.1 A Little More Markdown

You’ve already used headers and lists in `SPEC.md` (Chapter 2). A README additionally benefits from **code blocks** — text wrapped in triple backticks, as you’ve seen throughout this book’s own command examples — and **links**, written as `[text](url)`. That’s genuinely enough Markdown to write a good README; this isn’t a full syntax reference.

8.8.2 What Belongs in It

- What the project is (a sentence or two — `SPEC.md`’s opening paragraph is a good starting point)
- How to install and run it
- Example usage, with real output

8.8.3 A Draft

```
# Mortgage Calculator
```

Calculates the fixed periodic payment for a fixed-rate mortgage.
See ``SPEC.md`` for the full specification.

```
## Setup
```

```
uv sync
```

Usage

```
uv run mortgage-calculator-book --principal 200000 --annual-rate 0.06 --term-years 30
# Fixed periodic payment: $1,199.10
```

```
uv run mortgage-calculator-book --principal 200000 --annual-rate 0.06 --term-years 30 --format
# {"payment": 1199.1}
```

Write this now, not after the project is “finished” — there’s no such moment in this book, and a README that only gets written at the end tends not to get written at all.

8.8.4 Letting Pi Draft It Instead

If you’d rather not write the README by hand, Pi can draft one from the project itself rather than from a blank page — point it at what actually exists, not just at the idea of a README:

```
pi "Draft README.md for this project. Read SPEC.md, \
pyproject.toml, and src/mortgage_calculator_book/cli.py \
first, and base the usage examples on the actual CLI \
flags and command name you find there rather than \
guessing at them."
```

Review it the same way as every other agent proposal, with one thing specific to documentation worth checking closely: does every command in it actually work, copy-pasted exactly as written? A README with a subtly wrong flag name or an invented example is worse than no README at all — it actively misleads the next person who trusts it, quite possibly you, in three weeks. Run each example yourself before accepting the diff. This is also where Pi is likeliest to invent a badge, a version number, or an installation step this project doesn’t actually have; trim anything that describes a project slightly different from the one that exists.

Process concept: documentation as a living artifact. This is the same spirit as SPEC.md from Chapter 2, aimed at a different reader: the spec is written for a collaborator (including Pi) who needs to know what the system should do; the README is written for a new user who just needs to know how to run it. Both get revised as the project changes — this README will need another pass once Chapter 9 adds a second way to run the calculator.

8.9 Refactor and Ruff Pass

```
ruff check . && ruff format .
```

Same habit as every prior chapter — nothing new here, which is itself a small sign the habit has taken hold.

Commit the README too — it’s been sitting uncommitted since 8.8, the last real artifact this chapter produced:

```
git add README.md
git commit -m "Add README"
git push
```

8.10 Checkpoint

Before moving to Chapter 9, this should all be true:

- ☐ `pyproject.toml`’s `[project.scripts]` entry points at `mortgage_calculator_book.cli:main`, not the original placeholder
- ☐ `mortgage-calculator-book --principal ... --annual-rate ... --term-years ...` prints a correct, human-readable result
- ☐ `--format json` prints correctly structured JSON
- ☐ Invalid input produces a clear error message on `stderr` and a non-zero exit code
- ☐ `.env.example` is committed; `.env` is git-ignored and confirmed via `git check-ignore .env`
- ☐ `README.md` describes setup and usage with real, working examples, and is committed
- ☐ All CLI tests pass alongside every earlier chapter’s tests
- ☐ `ruff check .` and `ruff format .` both pass

What’s next: Chapter 9 builds a second front end — a graphical interface — calling this exact same validated core, proving the separation of concerns from Chapter 6 actually pays off.

Chapter 9 — Calculator UI

Contents

9.1 Why This Chapter Exists	103
9.2 Two Front Ends, One Core	103
9.2.1 The Rule for This Chapter	103
9.2.2 What’s Allowed to Change, and What Isn’t	103
9.3 PyQt5 Basics	103
9.3.1 Installing	103
9.3.2 The Smallest Possible Window	103
9.3.3 Core Widgets for This Project	104
9.3.4 Signals and Slots	104
9.4 Designing the Calculator Window	104
9.4.1 Sketching the Layout	104
9.4.2 What’s Worth Planning vs. What Isn’t	105
9.5 Wiring the UI to Validation and the Core	105
9.5.1 The Full Window	105
9.5.2 Displaying Errors in the UI	106
9.5.3 Displaying the Result	107
9.6 Where Agent Assistance Helps, and Where It Doesn’t	107
9.6.1 Good Delegation: Boilerplate Widget Wiring	107
9.6.2 Poor Delegation: Layout and Visual Judgment	107
9.7 Testing UI Logic Where It’s Worth It	107
9.7.1 What’s Testable Without a Full GUI Framework	107
9.7.2 The Judgment of Not Over-Testing	109
9.8 Running the App	109
9.8.1 A Walkthrough	109
9.8.2 Packaging, Briefly	109
9.9 Refactor and Ruff Pass	109
9.10 Checkpoint	109

9.1 Why This Chapter Exists

Chapter 8 gave the calculator its first user-facing surface. This chapter gives it a second, entirely different one — a graphical desktop window — calling the exact same validation and core logic underneath. If Chapter 6’s insistence on a pure core and Chapter 7’s separate validation layer were worth the discipline, this chapter is where that discipline pays for itself directly: almost none of the code you write here will touch mortgage math at all.

By the end, you’ll have a working PyQt5 window that takes the same four inputs as the CLI and produces the same result, with no duplicated calculation logic anywhere.

9.2 Two Front Ends, One Core

9.2.1 The Rule for This Chapter

Chapter 6.2 established that the core has no I/O. Chapter 7.7 established that `MortgageInput` and `calculate_validated_payment` are the one supported path into it. Nothing in this chapter changes either of those. This chapter only adds a new way to *call* that existing path — not a new way to compute anything.

9.2.2 What’s Allowed to Change, and What Isn’t

Allowed: how input is collected, how output is displayed, anything about layout, styling, and interaction. Not allowed: reimplementing any part of the payment calculation, or duplicating validation logic that already exists in `MortgageInput`. If you notice yourself writing an `if` statement that checks whether a number is positive, that’s a sign you’ve drifted into re-doing Chapter 7’s job instead of reusing it.

9.3 PyQt5 Basics

9.3.1 Installing

```
uv add pyqt5
```

9.3.2 The Smallest Possible Window

```
import sys

from PyQt5.QtWidgets import QApplication, QWidget

app = QApplication(sys.argv)
window = QWidget()
```

```

window.setWindowTitle("Hello, PyQt5")
window.show()
sys.exit(app.exec_())

```

`QApplication` manages the application as a whole — there’s exactly one per program. `QWidget` is the base building block for anything visible; an empty one, as above, is just a blank window. `.show()` makes it visible, and `app.exec_()` starts the **event loop** — the process that waits for and responds to user interaction (clicks, typing, resizing) until the window is closed.

9.3.3 Core Widgets for This Project

- `QLineEdit` — a single-line text input, for the four numeric fields
- `QLabel` — non-editable text, for both field labels and the result display
- `QPushButton` — a clickable button, to trigger the calculation
- `QFormLayout` — arranges label/input pairs in neat rows, exactly the shape this calculator’s input form needs
- `QVBoxLayout` — stacks widgets vertically; used here to stack the form, the button, and the result label

9.3.4 Signals and Slots

PyQt5’s event handling works through **signals** (something happened — a button was clicked) connected to **slots** (a function that runs in response). `button.clicked.connect(some_function)` means: whenever this button is clicked, call `some_function`. That’s the entire mechanism this project needs — PyQt5 has many more signal types, but this one covers everything the calculator does.

9.4 Designing the Calculator Window

9.4.1 Sketching the Layout

Four labeled inputs, matching `SPEC.md`’s fields exactly, a calculate button, and a result area below it:

```

Principal ($):      [_____]
Annual rate (e.g. 0.06): [_____]
Term (years):      [_____]
Payments per year:  [_____]

[ Calculate ]

Fixed periodic payment: $1,199.10

```

9.4.2 What's Worth Planning vs. What Isn't

The field order and labels above are worth deciding deliberately, since they directly mirror the spec. Exact pixel spacing, colors, and fonts are not worth planning in advance — PyQt5's defaults are perfectly usable, and this book treats visual polish as something to iterate on directly in code, not something to wireframe first.

9.5 Wiring the UI to Validation and the Core

9.5.1 The Full Window

In `src/mortgage_calculator/ui.py`:

```
import sys

from PyQt5.QtWidgets import (
    QApplication,
    QFormLayout,
    QLabel,
    QLineEdit,
    QPushButton,
    QVBoxLayout,
    QWidget,
)
from pydantic import ValidationError

from mortgage_calculator.validation import MortgageInput, calculate_validated_payment


class MortgageCalculatorWindow(QWidget):
    def __init__(self):
        super().__init__()
        self.setWindowTitle("Mortgage Calculator")

        self.principal_input = QLineEdit()
        self.rate_input = QLineEdit()
        self.term_input = QLineEdit()
        self.frequency_input = QLineEdit("12")

        self.result_label = QLabel("")
        self.calculate_button = QPushButton("Calculate")
        self.calculate_button.clicked.connect(self.on_calculate)

        form = QFormLayout()
        form.addRow("Principal ($):", self.principal_input)
```

```

form.addRow("Annual rate (e.g. 0.06):", self.rate_input)
form.addRow("Term (years):", self.term_input)
form.addRow("Payments per year:", self.frequency_input)

layout = QVBoxLayout()
layout.addLayout(form)
layout.addWidget(self.calculate_button)
layout.addWidget(self.result_label)
self.setLayout(layout)

def on_calculate(self) -> None:
    try:
        data = MortgageInput(
            principal=float(self.principal_input.text()),
            annual_rate=float(self.rate_input.text()),
            term_years=int(self.term_input.text()),
            payments_per_year=int(self.frequency_input.text()),
        )
    except (ValueError, ValidationError) as exc:
        self.result_label.setText(f"Error: {exc}")
        return

    payment = calculate_validated_payment(data)
    self.result_label.setText(f"Fixed periodic payment: ${payment:,.2f}")

def main() -> None:
    app = QApplication(sys.argv)
    window = MortgageCalculatorWindow()
    window.show()
    sys.exit(app.exec_())

if __name__ == "__main__":
    main()

```

9.5.2 Displaying Errors in the UI

Notice `on_calculate` catches two different kinds of error: a plain `ValueError`, raised if `float(...)` or `int(...)` fails on genuinely non-numeric text (someone typing “abc” into the principal field), and `ValidationError`, raised by `MortgageInput` for numeric-but-invalid input (a negative principal, same as Chapter 8’s CLI would reject). Both land in the same result label rather than crashing the application — a user typing garbage into a field should see a message, not watch the window disappear.

9.5.3 Displaying the Result

`f"${payment:,.2f}"` — the same formatting used in Chapter 8’s CLI, for the same reason: consistent presentation between front ends, even though the underlying `payment` value is unrounded until this exact point (Chapter 6.8.3).

9.6 Where Agent Assistance Helps, and Where It Doesn’t

9.6.1 Good Delegation: Boilerplate Widget Wiring

The widget-creation and layout code in 9.5.1 is exactly the kind of task worth handing to Pi:

```
pi "Add a 'Clear' button next to Calculate that resets all " \
    "four input fields and the result label."
```

This is mechanical, has an obviously correct answer, and is fast to verify — run the app, click the button, confirm the fields clear.

9.6.2 Poor Delegation: Layout and Visual Judgment

Asking Pi to “make this look nicer” invites a much harder review problem: “nicer” isn’t a test you can run, and accepting a layout change sight-unseen means trusting an aesthetic judgment you haven’t actually checked. Reviewing a UI diff correctly here means *running the application and looking at it* — reading the code alone won’t tell you whether a change actually improved anything.

Process concept: “trust but verify” extended to a domain you check with your eyes. Chapter 1.6 introduced verification as reading a diff. Most of this book’s verification since then has been reading diffs and running tests. This is the first chapter where verification genuinely requires neither — it requires looking at the running application. Recognizing when a task needs that kind of check, rather than defaulting to “the tests still pass, so it’s fine,” is its own skill worth practicing here.

9.7 Testing UI Logic Where It’s Worth It

9.7.1 What’s Testable Without a Full GUI Framework

Testing PyQt5 windows directly — simulating clicks, reading rendered widget state — requires additional tooling this book doesn’t cover, and for a project this size, the payoff doesn’t justify the setup cost. What *is* cheap to test is the parsing logic hiding inside `on_calculate`. Pull it out as its own function in `ui.py`:


```
def parse_form_values(
    principal_text: str, rate_text: str, term_text: str, frequency_text: str
) -> dict:
    """Convert raw form text into the types MortgageInput expects."""
    return {
        "principal": float(principal_text),
        "annual_rate": float(rate_text),
        "term_years": int(term_text),
        "payments_per_year": int(frequency_text),
    }
```

And update `on_calculate` to call it:

```
def on_calculate(self) -> None:
    try:
        values = parse_form_values(
            self.principal_input.text(),
            self.rate_input.text(),
            self.term_input.text(),
            self.frequency_input.text(),
        )
        data = MortgageInput(**values)
    except (ValueError, ValidationError) as exc:
        self.result_label.setText(f"Error: {exc}")
        return

    payment = calculate_validated_payment(data)
    self.result_label.setText(f"Fixed periodic payment: ${payment:,.2f}")
```

Now `parse_form_values` is a plain function, testable with no `QApplication` involved at all:

```
# tests/test_ui.py
import pytest

from mortgage_calculator.ui import parse_form_values

def test_parses_valid_form_values():
    result = parse_form_values("200000", "0.06", "30", "12")
    assert result == {
        "principal": 200000.0,
        "annual_rate": 0.06,
        "term_years": 30,
        "payments_per_year": 12,
    }
```

```
def test_raises_on_non_numeric_principal():
    with pytest.raises(ValueError):
        parse_form_values("not a number", "0.06", "30", "12")
```

9.7.2 The Judgment of Not Over-Testing

Notice what's deliberately absent here: no test clicks the actual button, no test checks the actual label text on screen. That's not laziness — it's a decision that the layout and widget-wiring code isn't worth the tooling cost of testing directly, given how cheaply it can be checked by hand (9.6.2). Knowing where to stop testing is as much a skill as knowing where to start.

9.8 Running the App

9.8.1 A Walkthrough

```
uv run python -m mortgage_calculator.ui
```

Enter the Chapter 4.5 worked example — 200000, 0.06, 30, 12 — click Calculate, and confirm the window shows \$1,199.10, matching every other front end this project has produced so far.

9.8.2 Packaging, Briefly

Turning this into a double-clickable application (a `.app` on macOS, an `.exe` on Windows) is a real, separate topic — tools like PyInstaller handle it, but it's genuinely out of scope for this book. Flagged here, and named properly in the Appendix, rather than left as a mystery.

9.9 Refactor and Ruff Pass

```
ruff check . && ruff format .
```

9.10 Checkpoint

Before moving to Chapter 10, this should all be true:

- ☐ The PyQt5 window opens and displays four labeled input fields, a Calculate button, and a result area
- ☐ Entering the Chapter 4.5 worked example produces \$1,199.10
- ☐ Invalid input (non-numeric text, or values `MortgageInput` rejects) shows an error message instead of crashing
- ☐ `parse_form_values` exists as a standalone, tested function
- ☐ No mortgage math or validation logic is duplicated anywhere in `ui.py` — it all still lives in `core.py` and `validation.py`

□ `ruff check .` and `ruff format .` both pass

What's next: Chapter 10 builds a third front end — not for a human this time, but for a language model, exposing the same validated core as a callable tool.

Chapter 10 — Tool Interface

Contents

10.1 Why This Chapter Exists	113
10.2 What a “Tool” Means in This Context	113
10.2.1 The Core Idea	113
10.2.2 A Third Front End, Not a New Architecture	113
10.2.3 Validation-as-Schema, Revisited	113
10.3 Reusing the Pydantic Models	113
10.3.1 Free JSON Schema	113
10.3.2 What Still Needs to Be Added	114
10.4 Defining the Tool Contract	114
10.4.1 Writing the Description	114
10.4.2 The Output Schema	114
10.4.3 Where This Lives	115
10.5 TDD the Contract Before Wiring Anything Up	115
10.5.1 Tests First, No Model Involved	115
10.5.2 Confirming Errors Are Handleable	116
10.5.3 Agent-Assisted Implementation	116
10.6 Sidebar: Model Context Protocol (MCP)	117
10.6.1 What You Just Built, Named	117
10.6.2 The Shape of MCP, Conceptually	117
10.6.3 Why This Matters	117
10.7 Manual Verification: Calling the Tool Like a Model Would	117
10.7.1 A Simulated Call	117
10.7.2 The Last Checkpoint Before a Real Model	118
10.8 Refactor and Ruff Pass	118
10.9 Checkpoint	118

10.1 Why This Chapter Exists

Chapters 8 and 9 gave the calculator two front ends for humans. This chapter builds a third — one for a language model. By the end, you’ll have a callable, schema-defined tool wrapping the exact same validated core those earlier chapters used, fully tested, and verified by hand with a simulated tool call. Chapter 11 is where an actual model gets to use it; this chapter is entirely about building and proving the contract first.

10.2 What a “Tool” Means in This Context

10.2.1 The Core Idea

A “tool,” in the context of language models, is nothing more mysterious than: a function description plus a schema, written in a form a model can read, that tells it what the function does, what arguments it needs, and what it returns. The model doesn’t execute anything itself — it decides *when* to call the tool and *what arguments to pass*, and your code does the actual work and hands the result back. It’s a very structured, very constrained API, not a new kind of programming.

10.2.2 A Third Front End, Not a New Architecture

Exactly like Chapter 9’s opening argument: this chapter follows the same rule Chapters 6 and 7 established. `calculate_payment` stays pure. `MortgageInput` and `calculate_validated_payment` remain the one supported path into it. This chapter adds a way for a *model* to reach that path, the same way Chapters 8 and 9 added ways for a *human* to reach it.

10.2.3 Validation-as-Schema, Revisited

Chapter 7.2.3 flagged this moment directly: a Pydantic model is already most of the way to a tool schema. This chapter is where that foreshadowing pays off.

10.3 Reusing the Pydantic Models

10.3.1 Free JSON Schema

Pydantic models can export their structure as JSON Schema — the same format most LLM tool-calling interfaces expect for describing valid arguments — with a single method call:

```
from mortgage_calculator.validation import MortgageInput

MortgageInput.model_json_schema()
```

This produces a dictionary describing every field's type, and — because your `field_validators` already enforce them — you get the *shape* of the constraints (types, required fields) for free. The specific business rules inside your validators (positive principal, rate under 100%) aren't expressed in the exported schema itself, but they still run every time `MortgageInput` is constructed — which matters, because it means the tool can't be tricked into skipping validation just because the schema alone doesn't spell out every rule.

10.3.2 What Still Needs to Be Added

A schema alone isn't a complete tool definition — a model also needs a **name** it can refer to, and a **description** written in prose that tells it what the tool is *for* and *when to use it*. Neither of those come from the Pydantic model; both are new content for this chapter.

10.4 Defining the Tool Contract

10.4.1 Writing the Description

This is prompt engineering in miniature — worth treating with real care, since a vague or ambiguous description directly affects whether a model calls the tool correctly, or at all:

```

TOOL_NAME = "calculate_mortgage_payment"

TOOL_DESCRIPTION = (
    "Calculate the fixed periodic payment for a fixed-rate mortgage, given "
    "a principal amount, an annual interest rate, a loan term in years, and "
    "how many payments are made per year. Use this whenever the user asks "
    "about a mortgage payment amount for a fixed-rate loan."
)

```

Notice the second sentence does real work: it's not just describing what the function computes, it's telling the model *when* reaching for it is appropriate — language a schema alone can't express.

10.4.2 The Output Schema

Reusing the exact shape from Chapter 8.5.4's forward-note — `{"payment": 1199.10}` — rather than inventing a new one:

```

OUTPUT_SCHEMA = {
    "type": "object",
    "properties": {
        "payment": {
            "type": "number",
            "description": "The fixed periodic payment, in dollars.",

```

```

    }
},
    "required": ["payment"],
}

```

10.4.3 Where This Lives

In `src/mortgage_calculator/tool.py` — a new module, sitting alongside `cli.py` and `ui.py` as a peer front end, not folded into either.

10.5 TDD the Contract Before Wiring Anything Up

10.5.1 Tests First, No Model Involved

```

# tests/test_tool.py
import pytest

from mortgage_calculator.tool import call_tool, get_tool_definition

def test_valid_call_returns_payment():
    result = call_tool(
        {
            "principal": 200000,
            "annual_rate": 0.06,
            "term_years": 30,
            "payments_per_year": 12,
        }
    )
    assert result["payment"] == pytest.approx(1199.10, abs=0.01)

def test_invalid_call_returns_error_dict_not_exception():
    result = call_tool({"principal": -1000, "annual_rate": 0.06, "term_years": 30})
    assert "error" in result

def test_tool_definition_has_name_and_description():
    definition = get_tool_definition()
    assert definition["name"] == "calculate_mortgage_payment"
    assert "mortgage" in definition["description"].lower()
    assert "properties" in definition["parameters"]

```

Note the second test's name specifically: `call_tool` must return an **error dic-**

tionary, not raise an exception — a meaningfully different contract than Chapter 6’s core or Chapter 7’s validation, both of which are allowed to raise. A model-calling layer in Chapter 11 needs to hand *something* back to the model on bad input; an uncaught exception isn’t something a model-calling loop can pass along gracefully.

10.5.2 Confirming Errors Are Handleable

This is worth stating as its own requirement, separate from “the function shouldn’t crash”: the shape of an error response (`{"error": "...}"`) needs to be just as predictable as the shape of a success response, since Chapter 11’s wiring will need to check for one or the other every single time.

10.5.3 Agent-Assisted Implementation

```
pi "Implement call_tool and get_tool_definition in src/mortgage_calculator/tool.py" \
    "to make the tests in tests/test_tool.py pass. call_tool should never raise - " \
    "catch validation errors and return an error dict instead."
```

Review as always — this chapter’s implementation:

```
from typing import Any

from pydantic import ValidationError

from mortgage_calculator.validation import MortgageInput, calculate_validated_payment


def get_input_schema() -> dict[str, Any]:
    return MortgageInput.model_json_schema()


def get_tool_definition() -> dict[str, Any]:
    return {
        "name": TOOL_NAME,
        "description": TOOL_DESCRIPTION,
        "parameters": get_input_schema(),
    }


def call_tool(arguments: dict[str, Any]) -> dict[str, Any]:
    """Validate arguments, compute the payment, and return a result or an
    error dict. Never raises - a model-calling layer needs something to
    hand back to the model either way."""
    try:
        data = MortgageInput(**arguments)
    except ValidationError as exc:
```

```

        return {"error": "; ".join(e["msg"] for e in exc.errors())}

    payment = calculate_validated_payment(data)
    return {"payment": round(payment, 2)}

```

10.6 Sidebar: Model Context Protocol (MCP)

10.6.1 What You Just Built, Named

What `get_tool_definition` and `call_tool` implement by hand — a name, a description, a schema, and a function that executes against validated arguments — is a small, simplified version of a real, standardized protocol called **Model Context Protocol (MCP)**. MCP defines a common way for an application to expose tools like this one to a language model, and for a model-calling client to discover and invoke them, without every project inventing its own bespoke format.

10.6.2 The Shape of MCP, Conceptually

At a high level: an MCP **server** exposes one or more tools, each described the way `TOOL_DESCRIPTION` and `get_input_schema()` describe this one. An MCP **client** — the thing actually talking to a language model — discovers what tools are available and handles calling them when the model asks. This book doesn't implement MCP itself; building `tool.py` by hand, understanding exactly what each piece is for, is meant to make the real protocol legible later rather than an opaque black box the first time you encounter it.

10.6.3 Why This Matters

Connecting this chapter's exercise to something real, standardized, and widely used means what you've built here isn't just a toy pattern specific to this book — it's a smaller version of an approach you're likely to run into again.

10.7 Manual Verification: Calling the Tool Like a Model Would

10.7.1 A Simulated Call

Before Chapter 11 puts a real model in the driver's seat, confirm the tool works exactly the way a model-calling layer would use it — JSON in, JSON out:

```

# scratch_verify_tool.py - not part of the test suite, just a manual check
import json

from mortgage_calculator.tool import call_tool

```

```

request = json.loads(
    '{"principal": 200000, "annual_rate": 0.06, "term_years": 30, "payments_per_year":
)
response = call_tool(request)
print(json.dumps(response))
# {"payment": 1199.1}

uv run python scratch_verify_tool.py

```

10.7.2 The Last Checkpoint Before a Real Model

This confirms the whole path works end to end — JSON arguments in, a validated calculation, JSON results out — using nothing but the exact mechanism a model will use in Chapter 11. Delete `scratch_verify_tool.py` once you’ve run it; it was a check, not a permanent part of the project.

10.8 Refactor and Ruff Pass

```
ruff check . && ruff format .
```

10.9 Checkpoint

Before moving to Chapter 11, this should all be true:

- ☐ `get_tool_definition()` returns a name, a description, and a parameters schema derived from `MortgageInput`
- ☐ `call_tool()` returns `{"payment": ...}` on valid input and `{"error": ...}` on invalid input — and never raises
- ☐ All tests in `tests/test_tool.py` pass
- ☐ You’ve manually verified a JSON-in, JSON-out call against the Chapter 4.5 worked example
- ☐ You can explain, in a sentence, what MCP is and how what you built here relates to it
- ☐ `ruff check .` and `ruff format .` both pass

What’s next: Chapter 11 gives a real language model — local first, then hosted — the ability to call this tool, completing the hybrid system end to end for the first time.

Chapter 11 — LLM

Interface: Enter A Second Model

Contents

11.1 Why This Chapter Exists	121
11.2 Two Models, Two Jobs	121
11.2.1 Explicitly Distinguishing the Roles	121
11.2.2 Why the Same Model Isn't Necessarily Right for Both	121
11.3 Choosing a Local Model for the Intelligence Engine	122
11.3.1 What Matters for This Job	122
11.3.2 Pulling a Second Model	122
11.3.3 A Standalone Conversation First	122
11.4 Wiring the Local Model to the Chapter 10 Tool	122
11.4.1 The Request/Response Shape	122
11.4.2 A Minimal Implementation	122
11.4.3 When the Model Gets It Wrong	124
11.5 Environment Variables in Practice	124
11.5.1 Where the Chapter 8 Pattern Finally Gets Used	124
11.5.2 Config Alongside the Secret	124
11.6 OpenRouter & Paying for Models	124
11.6.1 What OpenRouter Is, and When Local Isn't Enough	124
11.6.2 Account, Key, and Storage	124
11.6.3 Understanding Cost	125
11.6.4 Wiring OpenRouter In	125
11.7 Comparing Local vs. Hosted, Informally	126
11.7.1 Running the Same Questions Through Both	126
11.7.2 What to Watch For	126
11.7.3 A Practical Decision Framework	126
11.8 Agent-Assisted Build, Same Habits as Always	127
11.8.1 Tests First, With Mocking	127
11.8.2 Prompting Pi, Reviewing the Diff	128
11.9 Refactor and Ruff Pass	128
11.10 Checkpoint	128

11.1 Why This Chapter Exists

Chapter 10 proved the tool works when called manually, with arguments you typed yourself. This chapter hands that same tool to a language model, and lets the model decide when and how to call it. By the end, you'll be able to ask the calculator a plain-language question — “What would my payment be on a \$200,000 loan at 6% over 30 years?” — and get back a real, computed answer, through both a local model and a hosted one. This is the chapter where the hybrid system this book has been building toward finally exists, end to end.

11.2 Two Models, Two Jobs

11.2.1 Explicitly Distinguishing the Roles

Two different local language models will exist in this project by the end of this chapter, and it's worth being precise about why: the model behind Pi (Chapter 1) helped *build* the system — reading code, proposing diffs, drafting tests. The model this chapter adds helps *run* the system — reading a user's plain-language question and deciding whether and how to call the Chapter 10 tool. Same underlying technology, genuinely different jobs.

11.2.2 Why the Same Model Isn't Necessarily Right for Both

A model chosen for coding assistance is judged on things like how well it reads and reasons about source code across multiple files. A model chosen for this chapter's job is judged on something narrower and more specific: how reliably it calls a tool with correctly formatted arguments, and how sensibly it responds once it has a result back. A model that's excellent at one of these isn't guaranteed to be excellent at the other — which is exactly why this chapter pulls a second model rather than reusing Pi's.

Process concept: naming the distinction once both models exist. Chapter 1.4.3's hardware gut-check flagged that a second model job was coming, without saying much more about it. Now that both models actually exist side by side in this project, the distinction is concrete rather than theoretical: one model's job is understanding *your code*; the other's job is understanding *your users' questions*.

11.3 Choosing a Local Model for the Intelligence Engine

11.3.1 What Matters for This Job

Raw coding ability isn't the priority here — reliable, correctly formatted tool-calling behavior is. A smaller model that reliably produces well-formed tool calls is more useful for this job than a larger, more broadly capable model that occasionally gets the arguments wrong or forgets to call the tool at all.

11.3.2 Pulling a Second Model

```
ollama pull qwen3:8b
```

Sized against the same hardware gut-check table from Chapter 1.4.3 — if your machine comfortably runs the larger model behind Pi, it will run this one without issue; if it doesn't, this is a good chance to try a smaller model specifically for this narrower job.

11.3.3 A Standalone Conversation First

Before wiring anything to the tool, talk to this model the same way you did in Chapter 1.3.3:

```
ollama run qwen3:8b
```

Ask it a mortgage-related question directly, with no tool available. It'll answer in general terms, or admit it can't compute an exact figure — useful context for appreciating what the tool wiring in section 11.4 actually adds.

11.4 Wiring the Local Model to the Chapter 10 Tool

11.4.1 The Request/Response Shape

The pattern this section implements has four steps: a user asks a question; the model, given the Chapter 10 tool definition, decides whether to call it and with what arguments; your code executes the tool and gets a result; that result goes back to the model, which turns it into a plain-language answer.

11.4.2 A Minimal Implementation

```
uv add ollama
```

In `src/mortgage_calculator/llm.py`:

```
import ollama
```

```

from mortgage_calculator.tool import call_tool, get_tool_definition

LOCAL_MODEL = "qwen3:8b"

def ask_local(question: str) -> str:
    tool_def = get_tool_definition()
    tools = [
        {
            "type": "function",
            "function": {
                "name": tool_def["name"],
                "description": tool_def["description"],
                "parameters": tool_def["parameters"],
            },
        },
    ]

    first = ollama.chat(
        model=LOCAL_MODEL,
        messages=[{"role": "user", "content": question}],
        tools=tools,
    )
    message = first["message"]
    tool_calls = message.get("tool_calls")

    if not tool_calls:
        # The model chose to answer without calling the tool at all.
        return message["content"]

    call = tool_calls[0]
    result = call_tool(call["function"]["arguments"])

    second = ollama.chat(
        model=LOCAL_MODEL,
        messages=[
            {"role": "user", "content": question},
            message,
            {"role": "tool", "content": str(result)},
        ],
    )
    return second["message"]["content"]

```

(Ollama's exact tool-calling response shape can differ slightly between versions — check `ollama.chat`'s current documentation if a field name here doesn't match what you see. The pattern — two chat calls, with the tool's result inserted between them — stays the same regardless.)

11.4.3 When the Model Gets It Wrong

Two failure modes are worth expecting rather than being surprised by: the model might answer a mortgage question in general terms without calling the tool at all, even when it should have, or it might call the tool with malformed or incomplete arguments. Neither is a bug in your code — it's the model's behavior, and it's exactly why Chapter 10.5.1 insisted `call_tool` return an error dictionary rather than raise: a malformed call still gets *something* sensible back, which the model can then read and potentially recover from on its own.

11.5 Environment Variables in Practice

11.5.1 Where the Chapter 8 Pattern Finally Gets Used

Chapter 8.7 set up `.env`, `.env.example`, and `config.py` well before there was anything to put in them. This is that payoff:

```
# .env (not committed)
OPENROUTER_API_KEY=sk-or-v1-your-real-key-here
```

`config.py`, unchanged since Chapter 8.7.2, already loads this correctly — nothing new to write here, only a real value to add.

11.5.2 Config Alongside the Secret

Worth adding one more constant to `config.py` while you're there, since section 11.6 will need it:

```
HOSTED_MODEL = "qwen/qwen3-27b"
```

Keeping the model name in config, rather than hardcoded inline, means switching models later is a one-line change.

11.6 OpenRouter & Paying for Models

11.6.1 What OpenRouter Is, and When Local Isn't Enough

OpenRouter provides API access to many hosted language models — including larger, more capable versions of models you may be running locally — through a single, consistent interface. It's worth reaching for when your local model's context window is too small, when local tool-calling reliability isn't good enough for what you're building, or when you simply don't have hardware capable of running something larger.

11.6.2 Account, Key, and Storage

Create an account at openrouter.ai, generate an API key, and store it exactly the way section 11.5.1 described — never hardcoded, never committed.

11.6.3 Understanding Cost

OpenRouter charges per token, with rates that vary by model — larger, more capable models cost more per request. Set a spending limit on your account before making your first real call, and check the usage dashboard after your first few requests so you have a concrete sense of what a typical calculator query actually costs. For a project this size, expect the cost of testing this chapter's code to be a small fraction of a dollar — but it's worth confirming that for yourself rather than taking it on faith.

11.6.4 Wiring OpenRouter In

OpenRouter exposes an OpenAI-compatible API, so the OpenAI Python library works against it directly:

```
uv add openai

import json

from openai import OpenAI

from mortgage_calculator.config import HOSTED_MODEL, OPENROUTER_API_KEY
from mortgage_calculator.tool import call_tool, get_tool_definition

_client = OpenAI(base_url="https://openrouter.ai/api/v1", api_key=OPENROUTER_API_KEY)

def ask_hosted(question: str) -> str:
    tool_def = get_tool_definition()
    tools = [
        {
            "type": "function",
            "function": {
                "name": tool_def["name"],
                "description": tool_def["description"],
                "parameters": tool_def["parameters"],
            },
        },
    ]

    first = _client.chat.completions.create(
        model=HOSTED_MODEL,
        messages=[{"role": "user", "content": question}],
        tools=tools,
    )
    message = first.choices[0].message

    if not message.tool_calls:
```

```

    return message.content

    call = message.tool_calls[0]
    arguments = json.loads(call.function.arguments)
    result = call_tool(arguments)

    second = _client.chat.completions.create(
        model=HOSTED_MODEL,
        messages=[
            {"role": "user", "content": question},
            message,
            {"role": "tool", "tool_call_id": call.id, "content": json.dumps(result)},
        ],
    )
    return second.choices[0].message.content

```

Notice how closely this mirrors `ask_local` from 11.4.2 — same four-step shape, same `call_tool` function reused without modification. That's the tool contract from Chapter 10 doing exactly the job it was built for: one interface, usable from more than one model-calling client.

11.7 Comparing Local vs. Hosted, Informally

11.7.1 Running the Same Questions Through Both

```

question = "What would my monthly payment be on a $200,000 loan at 6% over 30 years?"
print("Local: ", ask_local(question))
print("Hosted:", ask_hosted(question))

```

11.7.2 What to Watch For

- **Latency** — the hosted call likely returns faster than a local model running on consumer hardware, though this varies with model size and your own machine.
- **Tool-call reliability** — does each model correctly call the tool every time, with well-formed arguments, or does one need a second attempt more often than the other?
- **Answer quality** — given the same correct tool result, does one model phrase the final answer more clearly, or add unhelpful hedging?

11.7.3 A Practical Decision Framework

For a project at this scale — a single tool, occasional use — local is often entirely sufficient, and free after the initial setup cost. Reach for hosted when reliability genuinely matters more than cost, when your local hardware can't run a model good enough to be reliable, or when you need a context window larger than what

fits comfortably on your machine. Chapter 12 turns these impressions into an actual measured comparison — this section is deliberately just a first look, not a conclusion.

11.8 Agent-Assisted Build, Same Habits as Always

11.8.1 Tests First, With Mocking

Live model calls are slow and, for the hosted path, cost real money — neither is acceptable inside a test suite that might run dozens of times a day. Mock the model call instead:

```
# tests/test_llm.py
from unittest.mock import MagicMock

from mortgage_calculator.llm import ask_local


def test_ask_local_calls_tool_and_returns_answer(monkeypatch):
    tool_call = {
        "function": {
            "name": "calculate_mortgage_payment",
            "arguments": {
                "principal": 200000,
                "annual_rate": 0.06,
                "term_years": 30,
                "payments_per_year": 12,
            },
        },
    }

    first_response = {
        "message": {"role": "assistant", "content": "", "tool_calls": [tool_call]}
    }
    second_response = {
        "message": {"role": "assistant", "content": "Your payment would be $1,199.10."}
    }

    mock_chat = MagicMock(side_effect=[first_response, second_response])
    monkeypatch.setattr("mortgage_calculator.llm.ollama.chat", mock_chat)

    answer = ask_local("What would my payment be on a $200,000, 6%, 30 year loan?")

    assert "1,199.10" in answer
    assert mock_chat.call_count == 2
```

`monkeypatch` — another built-in pytest fixture, alongside `capsys` from Chapter 8.6.1 — temporarily replaces `ollama.chat` with a fake that returns exactly the two scripted responses above, in order. This tests the *wiring* — does `ask_local` correctly extract arguments, call `call_tool`, and pass the result back — without ever touching a real model.

11.8.2 Prompting Pi, Reviewing the Diff

```
pi "Implement ask_hosted in src/mortgage_calculator/llm.py, mirroring" \
    "the structure of ask_local but using the OpenAI client against OpenRouter."
```

Review this one particularly closely — it's the most consequential integration in the book so far, and a subtle mistake (mismatched argument formats between the two APIs, a missing `tool_call_id`) could fail silently rather than crash outright.

11.9 Refactor and Ruff Pass

```
ruff check . && ruff format .
```

11.10 Checkpoint

Before moving to Chapter 12, this should all be true:

- ☐ `ask_local` correctly calls the Chapter 10 tool and returns a plain-language answer, verified against a real local model at least once
- ☐ `ask_hosted` does the same against OpenRouter, verified against a real API call at least once
- ☐ `.env` holds a real `OPENROUTER_API_KEY` and is confirmed git-ignored
- ☐ Tests for both paths pass using mocked model responses — no live model call or API cost required to run the suite
- ☐ You've run the same question through both `ask_local` and `ask_hosted` and compared the results
- ☐ `ruff check .` and `ruff format .` both pass

What's next: Chapter 12 turns this section's informal local-vs-hosted comparison into a real, repeatable evaluation.

Chapter 12 — Evaluation

Contents

12.1 Why This Chapter Exists	131
12.2 Evaluation Is Not Testing	131
12.2.1 What Unit Tests Check	131
12.2.2 Why a Model Needs Something Different	131
12.3 What to Evaluate	131
12.3.1 Tool-Call Correctness	131
12.3.2 Answer Quality	132
12.3.3 Refusal and Clarification Behavior	132
12.4 Building a Small Eval Set	132
12.4.1 Representative Questions	132
12.4.2 Expected Outcomes, Defined Per Case	132
12.4.3 Data, Not a Hardcoded Script	134
12.5 Running the Eval	134
12.5.1 A Small Refactor First	134
12.5.2 Scoring	135
12.5.3 Testing the Scoring Logic Itself	136
12.6 Comparing Local vs. Hosted, Formally	137
12.6.1 Running the Full Set Against Both	137
12.6.2 Reading the Results Side by Side	137
12.6.3 From Impression to Evidence	138
12.7 Regression Checks	138
12.7.1 Why Re-Run This Later	138
12.7.2 A Lightweight Habit	138
12.8 Checkpoint	138

12.1 Why This Chapter Exists

Chapter 11 ended with an informal comparison — run a question through both models, read the two answers, form an impression. That’s a reasonable first look, but “it seemed to work when I tried it” isn’t evidence, it’s an anecdote. This chapter builds a small, repeatable eval set and a way to score both models against it, so the local-vs-hosted comparison from Chapter 11.7 becomes something you can actually point to.

12.2 Evaluation Is Not Testing

12.2.1 What Unit Tests Check

Every test since Chapter 5 has checked the same kind of thing: given this exact input, does the code produce this exact, deterministic output? `calculate_payment(200_000, 0.06, 30, 12)` either returns 1199.10 or it doesn’t — there’s no ambiguity in what “pass” means.

12.2.2 Why a Model Needs Something Different

A language model’s behavior isn’t deterministic in that same sense — ask it the same question twice and you may get differently worded answers, or even a different decision about whether to call the tool at all. “Pass or fail” still applies, but what counts as passing has to be defined more carefully than “matches this exact string.”

Process concept: evaluation as its own discipline, distinct from unit testing. This is the chapter’s central distinction, worth stating plainly before writing any eval code: a unit test checks that *code* does what it’s supposed to, exactly, every time. An evaluation checks that a *model’s behavior*, which varies, stays within acceptable bounds often enough to trust. Both matter. They are not the same tool, and conflating them — expecting eval-style tolerance from a unit test, or unit-test-style exactness from an eval — leads to the wrong kind of disappointment in both.

12.3 What to Evaluate

12.3.1 Tool-Call Correctness

Did the model call the tool at all, when it should have? And when it did, were the arguments correct — not just present, but matching what the question actually asked for?

12.3.2 Answer Quality

Given a correct tool result, did the model report it accurately in plain language? A model that calls the tool correctly but then misreads or mangles the result in its final answer has failed just as thoroughly as one that never called the tool.

12.3.3 Refusal and Clarification Behavior

Not every question should trigger a tool call. A question outside SPEC.md’s scope (Chapter 2.3.4 and 4.7.3’s “Out of scope” section: variable-rate mortgages, refinancing, multiple currencies) should be recognized as such, not forced through the calculator anyway. A question that’s *in* scope but missing information — “how much would I pay each month?” with no principal, rate, or term given — should prompt for what’s missing, not invent plausible-sounding numbers and call the tool with them.

12.4 Building a Small Eval Set

12.4.1 Representative Questions

A full eval set for this project should run 15–25 questions deep; the set below shows a representative slice of that range — enough to demonstrate every category from 12.3, and a real starting point to extend on your own.

12.4.2 Expected Outcomes, Defined Per Case

For each question: should the tool be called, and if so, with which arguments? Store this as data, in `data/eval_set.json`:

```
[{
  "id": "basic-1",
  "question": "What would my monthly payment be on a $200,000 loan" \
    "at 6% interest over 30 years?",
  "expected_tool_call": true,
  "expected_arguments": {
    "principal": 200000,
    "annual_rate": 0.06,
    "term_years": 30,
    "payments_per_year": 12
  }
},
{
  "id": "zero-interest-1",
  "question": "If I borrow $12,000 interest-free and pay it back" \
    "monthly over a year, what's my payment?",
  "expected_tool_call": true,
  "expected_arguments": {
```

```

        "principal": 12000,
        "annual_rate": 0.0,
        "term_years": 1,
        "payments_per_year": 12
    }
},
{
    "id": "single-payment-1",
    "question": "I want to pay off a $10,000 loan at 6% in one single" \
                "payment a year from now. How much would that be?",
    "expected_tool_call": true,
    "expected_arguments": {
        "principal": 10000,
        "annual_rate": 0.06,
        "term_years": 1,
        "payments_per_year": 1
    }
},
{
    "id": "frequency-1",
    "question": "Same $200,000 loan at 6% for 30 years, but if I paid" \
                "biweekly instead of monthly, what would each payment be?",
    "expected_tool_call": true,
    "expected_arguments": {
        "principal": 200000,
        "annual_rate": 0.06,
        "term_years": 30,
        "payments_per_year": 26
    }
},
{
    "id": "missing-frequency-1",
    "question": "What's the payment on a $150,000 loan at 5% over 15 years?",
    "expected_tool_call": true,
    "expected_arguments": {
        "principal": 150000,
        "annual_rate": 0.05,
        "term_years": 15,
        "payments_per_year": 12
    }
},
{
    "id": "out-of-scope-1",
    "question": "What's the weather like today?",
    "expected_tool_call": false
},

```

```

{
  "id": "out-of-scope-2",
  "question": "Can you help me figure out if refinancing my mortgage makes sense?",
  "expected_tool_call": false
},
{
  "id": "ambiguous-1",
  "question": "How much would I pay each month?",
  "expected_tool_call": false
}]

```

Note `missing-frequency-1` and `out-of-scope-2` in particular: the first checks that the model correctly defaults to monthly payments when frequency isn't mentioned (matching `MortgageInput`'s own default from Chapter 7.5.1); the second checks that a question about refinancing — explicitly out of scope since Chapter 2.3.4 — doesn't get forced through the calculator anyway.

12.4.3 Data, Not a Hardcoded Script

Storing this as JSON rather than as Python code inside the eval runner means it can be inspected, extended, and reasoned about independently of the code that runs it — the same argument Chapter 8.5.1 made for JSON output over printed text, applied here to test data instead of program output.

12.5 Running the Eval

12.5.1 A Small Refactor First

Chapter 11's `ask_local` and `ask_hosted` return only a final text answer — not enough for scoring, which needs to know *whether* the tool was called and *with what arguments*. Rather than bolting that onto the existing functions, split each into a detailed version that returns everything, with the original kept as a thin wrapper:

in llm.py, replacing the body of ask_local:

```

def ask_local_detailed(question: str) -> dict:
    tool_def = get_tool_definition()
    tools = [
        {
            "type": "function",
            "function": {
                "name": tool_def["name"],
                "description": tool_def["description"],
                "parameters": tool_def["parameters"],
            },
        },
    ],

```

```

    }]

    first = ollama.chat(
        model=LOCAL_MODEL,
        messages=[{"role": "user", "content": question}],
        tools=tools,
    )
    message = first["message"]
    tool_calls = message.get("tool_calls")

    if not tool_calls:
        return {"answer": message["content"], "tool_called": False, "arguments": None}

    call = tool_calls[0]
    arguments = call["function"]["arguments"]
    result = call_tool(arguments)

    second = ollama.chat(
        model=LOCAL_MODEL,
        messages=[
            {"role": "user", "content": question},
            message,
            {"role": "tool", "content": str(result)},
        ],
    )
    return {"answer": second["message"]["content"],
            "tool_called": True, "arguments": arguments}

def ask_local(question: str) -> str:
    return ask_local_detailed(question)["answer"]

```

The same restructuring applies to `ask_hosted` / `ask_hosted_detailed`. This is a small, real example of what Chapter 6.8’s “refactor” step looks like several chapters later: existing behavior preserved exactly (`ask_local`’s signature and return type haven’t changed), with new capability added underneath it.

12.5.2 Scoring

In `src/mortgage_calculator/eval.py`:

```

import json
from pathlib import Path
from typing import Any, Callable

EVAL_SET_PATH = Path(__file__).resolve().parent.parent.parent / "data" / "eval_set.json"

```

```

def load_eval_set() -> list[dict[str, Any]]:
    return json.loads(EVAL_SET_PATH.read_text())

def score_case(case: dict[str, Any], ask_fn: Callable[[str], dict]) -> dict[str, Any]:
    result = ask_fn(case["question"])

    if result["tool_called"] != case["expected_tool_call"]:
        return {"id": case["id"], "passed": False, "reason": "tool_called mismatch"}

    if case["expected_tool_call"] and "expected_arguments" in case:
        for key, expected in case["expected_arguments"].items():
            actual = (result["arguments"] or {}).get(key)
            if actual is None or abs(float(actual) - float(expected)) > 0.001:
                return {"id": case["id"], "passed": False,
                        "reason": f"argument mismatch: {key}"}

    return {"id": case["id"], "passed": True, "reason": None}

def run_eval(ask_fn: Callable[[str], dict]) -> list[dict[str, Any]]:
    return [score_case(case, ask_fn) for case in load_eval_set()]

def summarize(results: list[dict[str, Any]]) -> str:
    passed = sum(1 for r in results if r["passed"])
    return f"{passed}/{len(results)} passed"

```

Deliberately simple pass/fail scoring — no partial credit, no weighting. At this scale, that's a feature, not a limitation: results stay easy to read and easy to reason about.

12.5.3 Testing the Scoring Logic Itself

The scoring function is plain code, and plain code gets tested the normal way — no model required:

```

# tests/test_eval.py
from mortgage_calculator.eval import score_case

def _fake_ask_correct(question: str) -> dict:
    return {
        "answer": "It would be $1,199.10.",
        "tool_called": True,
        "arguments": {

```

```

        "principal": 200000,
        "annual_rate": 0.06,
        "term_years": 30,
        "payments_per_year": 12,
    },
}

def _fake_ask_no_call(question: str) -> dict:
    return {"answer": "I'm not sure.", "tool_called": False, "arguments": None}

def test_score_case_passes_on_matching_call():
    case = {
        "id": "basic-1",
        "question": "irrelevant here",
        "expected_tool_call": True,
        "expected_arguments": {"principal": 200000, "annual_rate": 0.06, "term_years": 30},
    }
    assert score_case(case, _fake_ask_correct)["passed"] is True

def test_score_case_fails_when_tool_not_called_but_expected():
    case = {"id": "basic-1", "question": "irrelevant here", "expected_tool_call": True}
    assert score_case(case, _fake_ask_no_call)["passed"] is False

```

12.6 Comparing Local vs. Hosted, Formally

12.6.1 Running the Full Set Against Both

```

from mortgage_calculator.eval import load_eval_set, run_eval, summarize
from mortgage_calculator.llm import ask_local_detailed, ask_hosted_detailed

local_results = run_eval(ask_local_detailed)
hosted_results = run_eval(ask_hosted_detailed)

print("Local: ", summarize(local_results))
print("Hosted:", summarize(hosted_results))

```

12.6.2 Reading the Results Side by Side

Print each case's individual result, not just the summary, and look specifically at *where* the two diverge:

```

for local, hosted in zip(local_results, hosted_results):
    if local["passed"] != hosted["passed"]:

```

```
print(f"{local['id']}: local={local['passed']} hosted={hosted['passed']}")
```

A case where local fails and hosted passes is informative in a way an aggregate score alone isn't — it might mean local reliably struggles with, say, the **ambiguous-1** case specifically (calling the tool with guessed numbers rather than declining), which tells you something concrete and actionable about that model's behavior, not just “hosted scored higher.”

12.6.3 From Impression to Evidence

This is Chapter 11.7's informal comparison, done properly: instead of “the hosted model seemed to answer better,” you now have a specific pass count, on a specific, inspectable set of questions, with specific cases identified where the two diverge. That's a claim you can actually defend, and re-check later.

12.7 Regression Checks

12.7.1 Why Re-Run This Later

Any future change to the tool's description (Chapter 10.4.1), its schema, the model chosen, or even the prompt structure in `llm.py` can shift how reliably the model calls the tool — sometimes for the better, sometimes not. Re-running the eval set after any such change is how you'd actually notice a regression, rather than assuming a change was harmless because it seemed reasonable at the time.

12.7.2 A Lightweight Habit

This doesn't need full continuous-integration infrastructure (Appendix A.3 covers that, if you want it later) — just the habit of running `run_eval` again after a meaningful change and comparing the new summary to the last one you recorded. Simple, and enough for a project this size.

12.8 Checkpoint

Before moving to Chapter 13, this should all be true:

- ☐ `data/eval_set.json` contains at least the eight representative cases above, covering correct calls, edge cases, out-of-scope questions, and an ambiguous question
- ☐ `ask_local_detailed` and `ask_hosted_detailed` exist, with `ask_local` and `ask_hosted` preserved as thin wrappers around them
- ☐ `run_eval` and `score_case` work correctly, verified with mocked `ask_fn` functions in `tests/test_eval.py`
- ☐ You've run the full eval set against both the local and hosted model at least once, and can state both pass counts

- You've identified at least one case where the two models diverge, and have a plausible explanation why

What's next: Chapter 13 hardens the whole system against the messier reality outside this curated eval set — malformed input, unexpected model behavior, and everything else a real user might do that these eight questions don't cover.

Chapter 13 — Hardening

Contents

13.1 Why This Chapter Exists	143
13.2 What “Production-ish” Means for a Learning Project	143
13.2.1 Setting Scope Honestly	143
13.2.2 What’s Still Out of Scope	143
13.3 Finding the Seams	143
13.3.1 Mapping the Boundaries	143
13.3.2 Why Each Needs Different Handling	143
13.4 Error Handling at Each Seam	144
13.4.1 Stress-Testing Existing Validation	144
13.4.2 Malformed Tool-Call Arguments	144
13.4.3 Unexpected Model Output	145
13.4.4 Agent-Assisted, Tests First	145
13.5 Structured Logging with loguru	145
13.5.1 Why Logging, Not Just print	145
13.5.2 Installing loguru	146
13.5.3 Logging at the Seams	146
13.5.4 Reading a Log Back	147
13.6 Final Spec Check	147
13.6.1 Returning to SPEC.md	147
13.6.2 What’s Drifted	147
13.7 The Complete Definition of Done	148
13.7.1 Assembling Every Checkpoint	148
13.7.2 What to Do With What Doesn’t Pass	148
13.8 Checkpoint	149

13.1 Why This Chapter Exists

Chapter 12 proved the system works against a curated set of questions you wrote yourself. This chapter assumes a less forgiving user — one who fat-fingers a number, whose model produces a malformed tool call, or who asks something the eval set never anticipated. By the end, every seam this project has will handle failure gracefully instead of crashing, structured logging will exist to help you diagnose problems after the fact, and SPEC.md will get one last honest check against what actually got built.

13.2 What “Production-ish” Means for a Learning Project

13.2.1 Setting Scope Honestly

This chapter does not turn the mortgage calculator into a production system — that would mean deployment infrastructure, monitoring, authentication, and considerably more than a book chapter can responsibly cover. What it does mean: the system should survive contact with a careless or curious user without crashing, losing data, or producing a silently wrong answer.

13.2.2 What’s Still Out of Scope

Docker, CI/CD, and the rest of Appendix A remain out of scope here too — hardening in this chapter is about the application’s own behavior at its boundaries, not about how it’s deployed or automated.

13.3 Finding the Seams

13.3.1 Mapping the Boundaries

Four places in this system currently receive input from something outside your own tested code: the CLI (Chapter 8), the UI (Chapter 9), tool-call arguments arriving from a model (Chapter 10–11), and the model’s own raw output (Chapter 11). Each is a **seam** — a place where this project’s trusted, tested code meets something less predictable.

13.3.2 Why Each Needs Different Handling

A bad float typed into the UI (Chapter 9) is already caught by `MortgageInput`’s validation — that seam is largely handled. A model producing malformed JSON where valid tool arguments were expected (Chapter 11) is a genuinely different failure, at a different layer, and nothing built so far specifically guards against it. Treating every seam as if it needed the same fix would miss what’s actually still exposed.

13.4 Error Handling at Each Seam

13.4.1 Stress-Testing Existing Validation

Chapter 7’s `MortgageInput` already rejects negative or zero principal, out-of-range rates, and non-positive terms. What it doesn’t yet catch: a principal so large it’s obviously a data-entry mistake rather than a real loan. Add one more constraint:

```
# in validation.py

@field_validator("principal")
@classmethod
def principal_must_be_positive(cls, v: float) -> float:
    if v <= 0:
        raise ValueError("principal must be positive")
    if v > 100_000_000:
        raise ValueError("principal must be less than $100,000,000")
    return v
```

And a test:

```
def test_absurdly_large_principal_rejected():
    with pytest.raises(ValidationError):
        MortgageInput(principal=1e12, annual_rate=0.06, term_years=30)
```

This is a genuinely new constraint, not previously written down anywhere — worth remembering for section 13.6, where SPEC.md gets checked against exactly this kind of drift.

13.4.2 Malformed Tool-Call Arguments

Chapter 10’s `call_tool` already handles the case where arguments are present but fail `MortgageInput`’s validation. It does *not* handle a case one layer earlier: in `ask_hosted_detailed`, `call.function.arguments` arrives as a raw JSON string that has to be parsed before it even reaches `call_tool` — and a model can, occasionally, produce malformed JSON there. Harden that specific step:

```
# in llm.py, inside ask_hosted_detailed

call = message.tool_calls[0]
try:
    arguments = json.loads(call.function.arguments)
except json.JSONDecodeError:
    logger.warning("Malformed tool-call JSON from model: {}",
                  call.function.arguments)
return {
    "answer": "I had trouble understanding those loan details" \
              " - could you restate them?",
```

```

        "tool_called": True,
        "arguments": None,
    }

    result = call_tool(arguments)

```

This is a different failure from the one Chapter 10.5.1 already guards against: that chapter handles *valid* JSON with *invalid* values (a negative principal); this handles JSON that isn't valid JSON at all. Both are real, and they needed separate handling because they happen at separate points in the pipeline.

13.4.3 Unexpected Model Output

What if the model returns neither a tool call nor any content — an empty response? `ask_local_detailed` and `ask_hosted_detailed` should return something sensible rather than `None` or an empty string reaching a user unexplained:

```

if not tool_calls:
    return {
        "answer": message.get("content") or "I wasn't able to generate" \
            "a response - please try rephrasing.",
        "tool_called": False,
        "arguments": None,
    }

```

13.4.4 Agent-Assisted, Tests First

For each seam above, the pattern is the same one this book has used throughout: write a failing test describing the bad input and the expected graceful behavior, then let Pi propose the handling, then review:

```

pi "Add a test to tests/test_llm.py confirming ask_hosted_detailed" \
    "handles malformed tool-call-argument JSON without raising, " \
    "using a mocked client response."

```

13.5 Structured Logging with loguru

13.5.1 Why Logging, Not Just print

By this point in the book, you've almost certainly reached for a `print()` statement at least once to see what a value was mid-debugging (perhaps back in Chapter 5.7's `pdb` section, or since). That's fine for a single debugging session — it's a poor substitute for a permanent, structured record of what a running system actually did, especially once something goes wrong somewhere you weren't watching.

13.5.2 Installing loguru

uv add loguru

loguru over the standard library's `logging` module specifically because it needs meaningfully less configuration to get something genuinely useful — one call to set up sensible output, rather than the standard library's handler/formatter/logger hierarchy, which is more powerful but considerably more ceremony for a project this size.

In `src/mortgage_calculator/logging_config.py`:

```
import sys

from loguru import logger

logger.remove()
logger.add(sys.stderr, level="INFO")
logger.add("logs/mortgage_calculator.log", rotation="1 MB", level="DEBUG")
```

Import this module once, early — in `cli.py`'s `main()` and `ui.py`'s `main()` are reasonable places — so logging is configured no matter which front end starts the program.

13.5.3 Logging at the Seams

Add log calls at each of the seams from 13.4:

```
# in tool.py

from loguru import logger

def call_tool(arguments: dict) -> dict:
    try:
        data = MortgageInput(**arguments)
    except ValidationError as exc:
        logger.warning("Tool call rejected: {} ({})", arguments, exc)
        return {"error": "; ".join(e["msg"] for e in exc.errors())}

    payment = calculate_validated_payment(data)
    logger.info("Tool call succeeded: payment={}", round(payment, 2))
    return {"payment": round(payment, 2)}
```

What not to log: never log `OPENROUTER_API_KEY` or any other secret from `config.py`, even at debug level, even temporarily while troubleshooting — a log file is easy to forget about and easy to accidentally share or commit.

13.5.4 Reading a Log Back

Deliberately trigger a failure, then read what got recorded:

```
mortgage-calculator --principal -5000 --annual-rate 0.06 --term-years 30
cat logs/mortgage_calculator.log
```

You should see the `WARNING` line from 13.5.3, with the actual rejected arguments and the validation error, timestamped. This is the payoff of this section: a real failure, diagnosed after the fact from a log file alone, the way you'd have to if a user reported a problem you weren't present to watch happen.

13.6 Final Spec Check

13.6.1 Returning to SPEC.md

Open the version last revised in Chapter 4.7.3. Read it fresh, as if you'd never seen the rest of this project, and ask: does this still describe what actually got built?

13.6.2 What's Drifted

Two things stand out. First, section 13.4.1's new principal ceiling is a real constraint that exists in the code now but appears nowhere in the spec. Second, and larger: SPEC.md as it stands describes a calculation, full stop — nothing in it mentions that the system now has three separate interfaces (Chapter 8's CLI, Chapter 9's UI, and Chapter 10–11's tool/natural-language interface), which is a meaningfully bigger gap than a single missing constraint.

Reconcile both:

```
## Interfaces
- Command-line interface (human-readable and JSON output)
- Desktop GUI
- Tool interface for language-model use (see tool.py), supporting both
  local and hosted models

## Inputs
- principal: the loan amount, in dollars (0 < principal <= 100,000,000)
- annual_rate: the annual interest rate, as a decimal (e.g. 0.06 for 6%)
- term_years: the length of the loan, in years
- payments_per_year: number of payments per year (default: 12, monthly)
```

Commit the reconciliation on its own:

```
git add SPEC.md
git commit -m "Reconcile SPEC.md: add interfaces section, document principal ceiling"
git push
```


Process concept: closing the loop. Chapter 2 opened with the idea that a spec is a living document, expected to be wrong in places. Chapter 4 caught and fixed the first round of gaps, once real domain math existed. This is the same check, run one more time, now that the *entire* system exists — and it found exactly the kind of drift this book has been warning about since Chapter 2.2.2: not a mistake, just reality moving faster than the document describing it, caught because someone deliberately went looking.

13.7 The Complete Definition of Done

13.7.1 Assembling Every Checkpoint

Every chapter from 0 through 13 ended with its own checklist. Run through the whole system against all of them at once, not just the most recent chapter's:

- ☐ The project is git-tracked, pushed to GitHub, with a clean commit history (Ch. 0)
- ☐ Pi is configured and every agent-proposed change in this project's history was reviewed before being committed (Ch. 1)
- ☐ `SPEC.md` accurately describes the system as it exists today, including all three interfaces and the principal ceiling (Ch. 2, revised Ch. 4 and 13)
- ☐ `ruff check .` and `ruff format .` pass cleanly across the whole project (Ch. 3)
- ☐ The Chapter 4.5 worked example ($\$200,000 / 6\% / 30\text{yr} \rightarrow \$1,199.10$) is verified correct through every front end: CLI, UI, and the tool interface (Ch. 4, 6, 8, 9, 10)
- ☐ The full test suite passes: core, validation, CLI, UI logic, tool, LLM wiring (mocked), and eval scoring (Ch. 5–12)
- ☐ `calculate_payment` remains pure — no I/O, no printing, no external state (Ch. 6)
- ☐ `MortgageInput` is the only path from raw input into the core, for every front end (Ch. 7)
- ☐ `.env` holds real secrets, is git-ignored, and `.env.example` documents what's needed (Ch. 8)
- ☐ The eval set (Ch. 12) has been run against both local and hosted models, with results recorded
- ☐ Every identified seam (13.3) fails gracefully rather than crashing, and is logged (13.4–13.5)

13.7.2 What to Do With What Doesn't Pass

This list is meant to surface a few gaps, not to be a formality you skim and check off. If something's missing — an old test that's been silently skipped, a `.env.example` that's drifted out of date, a front end that was never actually re-tested against the Chapter 4.5 example after some later change — fix it

now, with the whole system in front of you, rather than leaving it for a reader (including future-you) to discover.

13.8 Checkpoint

Before moving to the Closing chapter, this should all be true:

- ☐ Every seam identified in 13.3 has explicit, tested error handling
- ☐ loguru is configured and logging real events at each seam, with no secrets ever logged
- ☐ You've deliberately triggered a failure and diagnosed it from the log file alone
- ☐ `SPEC.md` has been reconciled with the system as it actually exists, including interfaces and the principal ceiling
- ☐ The full checklist in 13.7.1 has been run against the whole project, not just this chapter's changes

What's next: the Closing chapter looks back across all thirteen chapters — what was hand-written, what was agent-assisted, and why that boundary sat where it did throughout.

Appendix — Where to Go Next

Contents

A.1 Why This Appendix Exists	153
A.2 Docker	153
A.3 CI/CD (GitHub Actions)	153
A.4 mypy / Type Checking	153
A.5 pre-commit Hooks	154
A.6 Typer	154
A.7 Beyond This Book	154

A.1 Why This Appendix Exists

Thirteen chapters back, the front matter promised a note on what this book deliberately left out, and why leaving it out was a choice rather than an oversight. This is that note, expanded. Each entry below gets a paragraph: what the tool or practice solves, why it stayed out of scope here, and where it would slot into a project like this one if you decided to add it later. Nothing here is a tutorial — think of it as a map for your next project, not homework for this one.

A.2 Docker

Docker packages an application together with everything it needs to run — system libraries, Python version, dependencies — into a single, portable image that behaves identically on any machine that runs it. What it solves that this book’s `uv`-based setup (Chapter 0.7) doesn’t: reproducibility *across* machines, not just within one. `uv.lock` guarantees that everyone working on this project gets the same Python packages; it doesn’t guarantee the same operating system, the same system libraries, or the same version of Ollama sitting alongside it. Docker was left out because that gap genuinely doesn’t matter for a single-developer desktop application — it starts mattering once you’re deploying to a server you don’t control by hand, or handing the project to someone whose machine looks nothing like yours. If you wanted to add it, the natural place is packaging the CLI (Chapter 8) or the tool interface (Chapter 10) as a standalone service, not the PyQt5 UI, which doesn’t containerize as cleanly.

A.3 CI/CD (GitHub Actions)

Continuous integration means running your checks — Ruff (Chapter 3), `pytest` (Chapters 5 onward), the eval set (Chapter 12) — automatically, on every push, rather than by habit. It exists to catch the day you forget to run `ruff check` before committing, which this book has been asking you to remember by hand since Chapter 3.6.1. GitHub Actions, specifically, connects directly to the GitHub account and repository set up in Chapter 0.4 — of everything in this appendix, it’s the most natural next step, since the infrastructure it needs already exists. A minimal workflow for this project would run, in order: Ruff, then `pytest`, then (optionally, since it costs real API calls) the eval set — failing the whole check if any step fails. Left out here specifically so the *reason* you run these checks stayed the lesson, rather than the checks becoming something that happens invisibly before you’ve felt why they matter.

A.4 mypy / Type Checking

Python’s type hints — used informally throughout this project, in `MortgageInput`’s field types (Chapter 7) and every function signature

since Chapter 6 — are optional and unenforced by Python itself. `mypy` is a separate tool that reads those hints and checks them *before* the code runs, catching a category of mistake (passing a string where a function expects a number, say) that would otherwise only surface at runtime, or not at all if the buggy path never gets exercised by a test. It was left out because `Pydantic` already provides real, *runtime* enforcement for the inputs that matter most in this project (Chapter 7) — `mypy` would add a second, static layer of type-checking on top of that, genuinely useful but genuinely additional cognitive load for a first read of this book. It would matter most applied to `core.py` (Chapter 6) and `tool.py` (Chapter 10), where a type mismatch is easiest to introduce by accident and hardest to notice without either a very specific test or a type checker looking over your shoulder.

A.5 pre-commit Hooks

pre-commit automates exactly the habit Chapters 3.6.1 and 6.8.2 asked you to build manually: running `Ruff` (and, if you’ve added it, `mypy`) automatically every time you run `git commit`, rather than trusting yourself to remember. It’s genuinely a small, low-cost addition once the habit already exists — which is precisely why this book didn’t start with it. Automating a check away before you’ve felt the cost of skipping it teaches the tool, not the judgment; this book chose to teach the judgment first; you already know when and why you’d want this.

A.6 Typer

Chapter 8.3.4 flagged this in passing: `Typer` builds a CLI from Python type hints directly, producing less boilerplate and friendlier help output than the `argparse` this book actually used. What would change if you swapped it in: mostly ergonomics — nicer `--help` text, less manual parser configuration — not architecture. Because Chapter 8’s CLI already sits cleanly on top of `MortgageInput` and `calculate_validated_payment` (Chapter 7), replacing `argparse` with `Typer` touches `cli.py` alone; nothing about validation or the core would need to change. A reasonable exercise once you’ve finished this book, if you want to feel the difference directly.

A.7 Beyond This Book

Strip away the mortgage-specific details and what’s left is a pattern that has nothing to do with mortgages at all: a pure, human-verified core; a validation layer wrapping it; multiple front ends built on top — some for humans, one for a model; an evaluation discipline that checks the model-facing layer honestly rather than anecdotally; and a hardening pass that assumes the world outside

your code is messier than your tests. That pattern is reusable well beyond a fixed-rate payment calculation.

Worth sitting with before you close this book: what other domain do you already understand well enough to write a Chapter 4-style primer for — one you could hand-derive a formula from, hand-verify an example against, and build the same nine-chapter shape around? That's the actual transferable skill this book was trying to teach, more than any individual formula or tool.

Closing

Contents

C.1 Why This Chapter Exists	159
C.2 What Got Built	159
C.3 What Was Hand-Written vs. AI-Assisted, Chapter by Chapter . .	159
C.4 Why the Boundary Sat Where It Did	160
C.5 Where to Apply This Pattern Next	161
C.6 A Closing Note	161

C.1 Why This Chapter Exists

Thirteen chapters is a lot of ground covered one small step at a time. This chapter is a deliberate pause — not a new build step, but a chance to look back at what all those steps actually added up to, before you close the book.

C.2 What Got Built

Underneath everything — the terminal commands, the Pydantic models, the agent-reviewed diffs — one system exists now: a pure mathematical core (Chapter 6), wrapped in a validation layer that enforces what SPEC.md says is valid (Chapter 7), reachable through three genuinely different front ends that all share that same core without duplicating a line of its logic — a command line (Chapter 8), a graphical window (Chapter 9), and a language model that can operate it on a user’s behalf (Chapters 10–11). Around all of that: an evaluation discipline that checks the model-facing layer honestly rather than anecdotally (Chapter 12), and a hardening pass that assumes the world outside your code is messier than your tests ever were (Chapter 13). One core, three front ends, held together by a spec that got checked against reality twice and corrected both times.

C.3 What Was Hand-Written vs. AI-Assisted, Chapter by Chapter

Chapter	Pi’s role	What stayed yours
0 — Orientation	None yet	Everything — pure setup
1 — Meet Your Coding Agent	First delegated task (a docstring)	Configuration, review, the habit of reading every diff
2 — Writing SPEC.md	Drafted initial structure	Catching the gaps it papered over (rate vs. periodic rate, unstated frequency)
3 — Holding the Agent to a Standard	Fixed flagged lint issues	Deciding what standard to hold it to
4 — Fixed Mortgages	Optional arithmetic double-check	The entire derivation, the worked example, the spec revision
5 — Tests & TDD	Drafted additional test skeletons	The worked-example test and both edge-case tests, and every expected value

Chapter	Pi's role	What stayed yours
6 — Mathematical Core Library	Implementation draft	The formula translation, the review checklist (rate conversion, off-by-one, float safety)
7 — Validation	Implementation draft	Every boundary condition, sourced directly from SPEC.md
8 — CLI	Wiring implementation	The command shape, the stderr/stdout distinction, the <code>.env</code> pattern
9 — Calculator UI	Boilerplate widget wiring	Layout judgment, the decision not to test the GUI directly
10 — Tool Interface	Implementation draft	<code>TOOL_DESCRIPTION</code> 's wording — the one piece of this project that's really prompt engineering
11 — LLM Interface	Drafted <code>ask_hosted</code> from <code>ask_local</code> 's pattern	<code>ask_local</code> itself, the two-model distinction, the closest review in the book
12 — Evaluation	Test-writing assistance	Every eval question and its expected outcome — the actual judgment the whole chapter rests on
13 — Hardening	Proposed handling per seam	Identifying the seams themselves, the logging policy, the final spec reconciliation

C.4 Why the Boundary Sat Where It Did

Look at the right-hand column of that table as a whole, rather than row by row, and a pattern emerges: Pi drafted implementations, wiring, and boilerplate — real, useful work — but it never once decided what “correct” meant. That decision stayed encoded in things you wrote yourself: SPEC.md's revisions, the worked example's exact numbers, the eval set's expected outcomes, the review checklists you ran every proposed change against. Pi worked *from* those artifacts. It never got to write them.

That's the actual thesis of this book, stated plainly now that there's a whole

system to point at rather than an abstract claim in the front matter: a hybrid system isn't defined by how much of the code an agent wrote. It's defined by who — or what — gets to decide what counts as working. Keep that decision yours, and an agent drafting most of your implementation code is a force multiplier. Let that decision drift to the agent, even a little at a time, across enough chapters, and “hybrid” quietly becomes “the agent did it,” which was never the point.

That risk doesn't expire when the book does. Every project you build after this one will offer the same quiet trade — accept a plausible-looking output instead of actually understanding it — and the tools available for making that trade easier will only get better, not worse. The habits this book tried to build — reading every diff since Chapter 1.6, writing the test before the implementation since Chapter 5, catching a spec against reality since Chapter 4.7 — are worth keeping specifically because the temptation they're guarding against isn't going away.

C.5 Where to Apply This Pattern Next

The shape generalizes cleanly: pure core, validation layer, multiple front ends — including one for a model — evaluation, hardening. Nothing about that shape is specific to mortgages. Pick a domain you already understand well enough to write a Chapter 4-style primer for — something you could derive a formula or a rule for by hand, and verify a worked example against, the same way this book verified \$1,199.10 before a single line of `core.py` existed. That primer is the real starting point for your next project, more than any of the tooling chapters were.

The Appendix is still there, with Docker, CI/CD, type checking, and the rest, named and briefly described, for whenever a future project actually needs one of them.

C.6 A Closing Note

This wasn't a book about how impressive an AI coding agent can be — plenty of other places will make that case for you, and reasonable people are still working out how much of it holds up. It was a book about a narrower, more durable claim: the discipline this book asked you to practice — a written spec, tests before implementation, a habit of reading every diff, an honest eval instead of an anecdote — is what made the agent genuinely useful here, not the other way around. Keep the discipline. The tools will keep changing.

License

This work — *Introduction to Software Engineering in the Age of AI*, the manuscript, the assembled book, and the accompanying build tooling in this repository — is an **open-educational resource**.

Copyright © 2026 Robert Ioffe — <https://github.com/rioffe>

It is released under the **Creative Commons Attribution 4.0 International License (CC BY 4.0)**:

- **Deed:** <https://creativecommons.org/licenses/by/4.0/>
- **Legal code:** <https://creativecommons.org/licenses/by/4.0/legalcode>

Under that license you are free to:

- **Share** — copy and redistribute this material in any medium or format, for any purpose, **including commercial**, and
- **Adapt** — remix, transform, and build upon this material for any purpose, including commercial,

with the following conditions:

- **Attribution.** You must give appropriate **credit to Robert Ioffe** (<https://github.com/rioffe>), provide a **link to this license**, and **indicate if changes were made**. You may do so in any reasonable manner, but **not in any way that suggests the author endorses you or your use**.
- **No additional restrictions.** You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits.

The material is provided on an “as-is” basis, **without warranties or conditions of any kind**, to the extent permitted by law. For the complete legal terms, see the CC BY 4.0 legal code at <https://creativecommons.org/licenses/by/4.0/legalcode>.

