Contents

ARCHITECTURE — speccheck 1.24.0 **1**

1. The one idea . . . 2
2. Package layout and dependency direction . . . 3
3. The executable flow (spec §3.2) . . . 5
3.1 The pipeline, stage by stage . . . 6
4. Data model . . . 8
5. Extraction: the spec side (extract.py) . . . 9
6. Extraction: the code side (extract.scan_roots) . . . 11
7. Attribution (attribute.py, swift.py, jsts.py) . . . 12
8. Results mapping (results.py) . . . 12
9. The status algorithm (graph.py) . . . 13
10. The judge (judge.py, judge_mock.py, judge_llm.py) and the triage pass (jev.py) . . . 15
    10.1 Contract and validation . . . 15
    10.1a The progress indicator (R-30, C-11, K-13) . . . 16
    10.2 The mock provider . . . 16
    10.3 The LLM provider: Ollama, OpenRouter, or any OpenAI-compatible endpoint . . . 16
    10.4 The triage pass (jev.py, v1.15) . . . 18
11. Reporting and the write protocol (report.py, impact.py, explain.py) . . . 18
12. The CLI (cli.py) . . . 20
13. Determinism, checked four ways . . . 21
14. The fixture and the self-check, as one artifact . . . 22
15. Test architecture . . . 22
    15.1 Tools (tools/) . . . 24
16. Things deliberately not built . . . 25

ARCHITECTURE — speccheck 1.24.0

This document describes the system as built, module by module and data flow by data flow. It is a companion to README.md (how to use it), SPEC.md (what it must do), and SPEC_BUILD_REPORT.md (the evidence that it does). Spec IDs are cited inline so that every design element can be traced back to the clause that demanded it.

It describes the build of SPEC.md **v1.24**, and the increments that got there:

Version	What it added	Modules it touched
v1.6	the Swift adapter (R-31, D-17/D-18)	swift.py (new), attribute.py, results.py, judge_mock.py
v1.7/v1.8	a heading-declared ID's statement is its title plus its section body (R-33)	extract.py, report.py, judge_llm.py
v1.9	clause-grounded verdicts (R-34, K-15, E-48)	judge.py, judge_llm.py, judge_prompt.md
v1.10/v1.11	recorded tests (R-35, E-50/E-51) and the fixture's long-body contract	extract.py, graph.py, report.py
v1.13	spec-internal edges (C-12) and the impact subcommand (C-13, R-36/R-37)	extract.py, impact.py (new), report.py, cli.py
v1.14	DECLARED vs INCIDENTAL citations (R-39, C-14–C-16)	attribute.py, graph.py, report.py, judge.py


Version	What it added	Modules it touched
v1.15	the Jev pre-triage pass (K-16, C-17, I-015)	`jev.py` (new), `judge.py`, `cli.py`
v1.16	the judge request's `related` neighbourhood (R-38, D-28/D-28b)	`judge_llm.py`, `judge.py`, `jev.py`
v1.17	the `explain` subcommand and the C-18 trace (R-40, I-016)	`explain.py` (new), `cli.py`
v1.18	the CLI documents its own parameters and environment (R-41, C-19, I-017)	`cli.py`
v1.19/v1.19.1	Lean proof evidence: `--proof`/`--proof-results`, a per-id `proof` field that is never a status input (R-100, C-20, C-21, K-17, E-63)	`lean.py` (new), `proof.py` (new), `graph.py`, `report.py`, `cli.py`
v1.20	determinacy: `judge_available` total over the never-issued case, `explain --spec` required, usage-before-contract exit precedence (K-18, E-64)	`cli.py`, `judge.py`, `report.py`
v1.21	range edges and row-cell edges (C-12), the cut-row Note (E-66), the symlink hint (E-09)	`extract.py`, `cli.py`
v1.22	the JavaScript/TypeScript adapter and the vitest/jest-junit join (R-104, D-56)	`jsts.py` (new), `attribute.py`, `results.py`
v1.23/v1.23.1	foreign references and `--namespace` (R-101, R-102, C-22); the citation map (R-103, C-23); the first full review's fixes (F-701..F-717)	`extract.py`, `cli.py`, `attribute.py`, `graph.py`, `report.py`, `explain.py`, `jsts.py`, `judge_mock.py`, `results.py`
v1.24	`UNPROVEN` on a non-strict run `--strict` would reject (R-105); CommonMark backtick spans in the row splitter; the cut-row and isolated-id Notes (E-66, E-77); the JS/TS adapter's text moved to C-24	`report.py`, `extract.py`, `cli.py`

1. The one idea

`speccheck` answers a single question: *for every ID a specification declares, what evidence exists that the implementation realizes it?* Everything in the design follows from one boundary drawn in §0 of the spec:

> **The model may only ever make the news worse.** Every status is computed deterministically from evidence the operator can `grep`; the judge may downgrade a status with cited evidence, never upgrade one.

That boundary splits the program into halves that never share state — and since v1.15 there is a third, weaker model-backed part, on the same side of the line as the judge:




The kernel produces every status, count, and metric. The judge, when enabled, sees one `(test case, ID)` edge at a time, and its only effect on the world is C-05 step 5: `PASSING → WEAKLY_PASSING` (I-004; property-tested by T-28). The triage pass sees every eligible edge *before* the judge does and its answers are used for exactly one thing — the order in which the judge is asked (K-16) — and are then discarded (I-015). And since v1.17 the kernel's own facts are rendered a third way: `explain` composes the `IdRecord`/edge/verdict facts and `impact`'s walk into one id's trace, adding no fact of its own (R-40, I-016). Since v1.19 a fourth input can ride alongside: Lean proof citations and a build manifest (`--proof`, `--proof-results`) give each id a proof state, reported beside its status and never folded into it (E-63).

2. Package layout and dependency direction

```
src/speccheck/
  __init__.py          __version__ = "1.24.0"      (K-10: pyproject reads it back)          3 lines
  __main__.py          python -m speccheck                                                    7
  cli.py               §5 surface: parsing, help (C-19), K-18 validation order, wiring, exit
                       codes, logging, --progress, E-41, --self-check, the three subcommands,
                       --namespace, the --citation-map read/validate/resolve stage (C-23)  1527
  extract.py           C-01 grammar, declarations, retirement, the recorded marker, K-14 cap,
```

	C-01 (c) decisions and TABLEs, CommonMark code spans, C-12 edges (ranges, row cells), isolated ids, the C-22 foreign pass, the tree walk, citations	842
attribute.py	C-03 test-case delimitation (ast) and attribution, C-14 declared, dispatch to the Swift and JS/TS adapters	231
swift.py	R-31 the Swift adapter: @Test / XCTest spans, brace fallback, MODULE	230
jsts.py	R-104 the JS/TS adapter: tokenizer, it/test calls, describe chains, `each` patterns, the regex-vs-division rule	309
results.py	C-04 JUnit parsing and the join: join_name, path classnames, templated titles, jest-junit's leading " > "	184
graph.py	C-05 status algorithm, edge selection, C-07 metrics	280
judge.py	C-06 types, validation (K-15 clause grounding), the run runner, C-11 ProgressLine, K-12 budget	450
judge_mock.py	R-22 deterministic provider (Python, Swift, JS/TS tokens)	63
judge_llm.py	C-06/C-09 provider and the R-38 `related` neighbourhood builder	270
jev.py	C-17 triage provider and the K-16 ordering pass	290
lean.py	C-20 the lean adapter: declaration heads, doc-comment id tags	139
proof.py	C-21 the proof manifest and the K-17 join to proof citations	152
impact.py	C-13 changed set, walk, reverify	238
explain.py	C-18 the one-id trace renderer, pure	119
report.py	C-07 JSON, C-08 Markdown, C-13 impact reports, §5.1 line, §5.4 rule, §3.1 writer, the CONFORMING/UNPROVEN word	722
judge_prompt.md	C-10 instruction text (package data, hashed into reports)	
_selfcheck/	byte-identical copy of fixtures/target/ (package data)	

Imports flow strictly downward; no module imports `cli`, and nothing in the kernel imports a provider or an HTTP client:




Three consequences of that graph are load-bearing:

- **I-006 (network boundary)** is a property of the import layout, not of a runtime check: `httpx` is imported inside `judge_llm._httpx_post` and `jev._httpx_post`, which only run when `--judge llm` issues a request. `--judge none|mock` never loads an HTTP client; `--self-check` additionally installs a guard that makes `socket.socket.__init__` raise, and T-43 asserts the guard never fires.
- **`graph → judge`** is an import of *types only* (`JudgedVerdict`). The kernel knows the shape of a verdict so it can apply step 5; it has no idea how one is produced. **`explain → judge`** is the same kind of import, for rendering a verdict (C-18).
- **The proof modules feed the graph a parallel field and nothing else.** `graph` imports `ProofEdge` to carry it on `IdRecord.proof`, but neither `deterministic_status` nor `apply_verdicts` reads it (E-63); `jsts` imports nothing from the package.
- **`explain` and `impact` are consumers, not stages.** Neither writes a report the other can read (`explain` writes nothing at all, D-33), and neither can change a status: they are pure functions of what the kernel already computed (I-016, I-013).

3. The executable flow (spec §3.2)

The spec draws the system once, in §3.2, as inputs feeding actors that hand artifacts to one another. This is that drawing, redrawn with the module that plays each actor, and with the triage pass (v1.15) and the two composition surfaces (v1.13, v1.17) in place:



Reading it left to right:


1. **Four core inputs, three of them optional, and three more opt-in ones.** Only `SPEC.md` is required. Without `--src`/`--tests` every ID is `UNCITED`; without `junit.xml` no ID can be better than `UNVERIFIED`. The citation map (v1.23) and the Lean proof and manifest (v1.19) are read only when their flags are given. Each input is read once, by exactly one actor, never written (I-001), and never scanned for citations (C-03, F-702).
2. **Two extractions that never meet.** The spec is parsed for *declarations* (what IDs exist, with statement text, retired and recorded flags) and for the *edges* its own statements name (C-12); the code trees are scanned for *citations* (where each ID token occurs). The same regex recognizes the token in both, but the spec is never scanned for citations and the code is never parsed for declarations — a `~~R-07~~` in a comment is a plain citation of `R-07` (E-20). One exception applies to both sides alike (v1.23, C-22): a token written `<ns>:ID` is someone else's id, so it is neither a citation nor an edge unless `<ns>` is the `--namespace` value.
3. **Attribution gives test citations an owner and a classification.** A source citation is a `(file, line)`; a test citation additionally names the enclosing test case (or the file-level case) and carries `declared` — whether its line is inside the case's own docstring or is a whole-line comment (C-14, E-56). That owner is what the JUnit join and the judge both key on, which is why `TestCase` is a hashable value object (§4). A citation map adds citations here too, after the scan and before the graph: each resolving entry becomes an ordinary `Citation` on an existing case, flagged `mapped` (C-23), so nothing downstream treats it differently except the labels and `declared_ratio`.

4. **The Grapher is where everything converges** — and the last point at which anything is *decided* without a model. It joins declarations to citations to outcomes, computes every status with C-05 steps 1–4, classifies undeclared and retired citations as dangling and stale, and computes the metrics. Everything on the `DET` artifact is reproducible from the report's own evidence table plus `grep` and the results file (R-24).
5. **The triage pass is a rehearsal, not a verdict.** With `--jev-pre-triage` under `--judge llm`, every judge-eligible edge is first sent to the C-17 endpoint, whose per-edge top-choice probability orders the judge's queue (ascending; a failed edge first, E-59). Its answer is read for that order and nothing else: it is never validated as a verdict, never recorded, never a metric (I-015). Under `--judge none/mock` the flag is inert and no C-17 variable is read (K-16).
6. **The judge is a side branch, not a stage.** With `--judge none` the deterministic result goes straight to the Reporter. Otherwise the Grapher hands over only the `(test case, ID)` edges of `PASSING`, non-recorded IDs whose test passed; the judge answers one question per edge, the kernel validates every answer (including the clause grounding of K-15), and step 5 may turn `PASSING` into `WEAKLY_PASSING`. Nothing flows back into the earlier artifacts: citations, outcomes, and counts are already fixed.
7. **Three renderers, one truth.** `check` renders the JSON and derives the Markdown from it; `impact` renders its own pair from the walk; `explain` renders one id's trace to stdout and writes nothing. The `check` exit code and summary line are computed from the JSON alone (I-009), so an operator holding only `speccheck.json` and the `--strict` flag can recompute what the process exited with.

The next diagram is the same flow seen as an ordered sequence of stages, with the exit paths the spec assigns to each.

3.1 The pipeline, stage by stage


`cli._run_stages()` runs the §3.1 stages in order; `check` and `explain` share it (v1.17: the trace cannot disagree with the report about a status, I-016), and `impact` runs its own shorter path over the same `SpecIndex`. Each stage is a pure function of the previous stage's output; there is no cache, no persistent state, and no partial output mode.


argv + env
parse_config → Action
Config | ImpactConfig | ExplainConfig
(paths resolved once, all inside --root; E-09;
every named file readable; --namespace grammar;
all before any file is parsed, K-18)
exit 2 on any usage error
exit 2
impact
parse SPEC.md → SpecIndex
changed set (--changed | --against) → walk → reports
extract-spec
parse_spec(SPEC.md) → SpecIndex
(ids, decisions, C-12 edges, notes)
E-01 / E-02 / E-03
exit 3
exclusion set: spec, results, citation map, proof manifest,
out/*.json, out/*.md, out/.*.tmp (C-03)
scan-tests + attribute
scan_roots(--tests) → attribute_file() → TestCase[], citations kind=test
scan-src
scan_roots(--src) → citations kind=src
apply-map (if --citation-map)
load_citation_map → apply_citation_map (C-23)
E-70
exit 3
map-results (if --results)
parse_junit → join_results → outcome per TestCase
E-05
exit 3
graph + status
build_graph → IdRecord[] with C-05 steps 1-4,
dangling, stale
explain
proof (if --proof / --proof-results)
scan_lean_paths → parse_proof_results → join_proof (K-17)
C-18 trace → stdout (no file, D-33)
E-65
exit 3
--judge?
exit 0; 2 for E-60 / E-64; 3 for E-05 / E-70
mock / llm
--jev-pre-triage?
yes
triage (K-16)
one C-17 request / eligible edge → order the queue
none
no
judge
eligible_edges → build_request (declared, related) → run_judge → apply_verdicts (step 5)
llm on a TTY: ProgressLine on stderr for the duration (R-30, C-11)
Ctrl-C at any stage (E-41)
exit 3, interrupted
report
build_report → dumps / render_markdown → write_reports
E-18
exit 3
summary line → stdout (R-21, R-29)
exit 0 / 1 from the JSON

Stage timings and counts are logged at `INFO` (`stage=<name> … ms=<n>`), never file contents, statements, or prompts (I-007). Exit codes are total: usage → `2`, input contract → `3`, any uncaught exception → `3` with a one-line message (traceback only at `DEBUG`), a `KeyboardInterrupt` → `3` with the message `interrupted` after the same cleanup (E-41), and everything else is the report's own `exit_code` — except `impact` and `explain`, which never exit `1`: nothing they render is pass/fail (§5.4).

4. Data model

The data model is the spec's §4 contracts, as frozen dataclasses. Nothing is mutable except the `IdRecord`/`TestEdge` pair that the status algorithm and step 5 fill in.



Seven representational choices matter downstream:

- **IDs are normalized once, at the token boundary** (`extract.normalize_id`): `R-7`, `R-07`, `R-007` become `R-07`; `I-5` becomes `I-005`. Every later structure keys on the normalized string, so I-011 (injective within a family, never across families) holds by construction.

- **Test cases are hashable value objects.** `TestCase` is frozen, so it serves as the dictionary key that joins three independent producers — the attributor (which cases exist), the results mapper (which case a JUnit `<testcase>` landed on), and the judge runner (which edge a verdict belongs to) — without any ID-assignment step. The judge runner returns `dict[(TestCase, id) → JudgedVerdict]`, which is why output order never depends on completion order (K-06).
- **File-level cases are real cases with `name == ""`.** A citation outside any delimited span (module docstring, helper, fixture, an unparseable `.py`, any non-Python file) belongs to that case. They are excluded from the results join, so they can never carry an outcome and can only ever contribute `UNVERIFIED` (E-13) — the JSON writes `""`, the Markdown renders `(file)`, and a file-level citation is always `declared: false` (E-56).
- **Edges are declaration facts, not citations.** An `Edge` records only that one statement names another id (C-12). It is never a status input, never a citation, never a metric — it feeds `impact`'s walk (C-13) and the judge's `related` neighbourhood (R-38) and nothing else. D ids are never citation targets and never appear in `ids` (D-25).
- **`related` is built once and carried on the request.** `judge_llm.related_titles` computes the C-12 `depends_on` neighbourhood of the judged edge — both directions, in-scope R/C/I/K/E ids only, the statement's own references first, capped at eight 160-character titles, a retired neighbour tagged `(retired)` (E-57) — and `JudgeRequest.related` carries it to both consumers (the LLM user message and the C-17 triage `state`, D-28b). It is request-side only: it appears in no report, no metric and no `schema_version` (T-83).
- **A foreign reference is masked, not filtered** (C-22, v1.23). `extract.mask_foreign` blanks the id of every `<ns>:ID` whose `ns` is not the `--namespace` value, and both `citations_in_file` and C-12's `targets_of` run the ordinary token and range regexes over the masked text. One matcher serves citations, edges and ranges, so a token cannot be foreign for one and local for another. `foreign_in_file` lists what was masked, as `ForeignRef`s for the JSON and one Note (E-67).
- **A mapped citation is an ordinary `Citation`** (C-23). `apply_citation_map` turns each resolving `MapEntry` into `Citation(kind="test", line=case.start, declared=True, mapped=True)` before `build_graph`, unless that (id, case) is already cited (E-73). C-05 therefore cannot tell it apart; only the renderers (`mapped`, `(map)`, the summary suffix) and `declared_ratio`, which leaves it out, read the flag.

5. Extraction: the spec side (`extract.py`)

`parse_spec` is a single pass over `SPEC.md` lines with a fence tracker (C-01, Q-008): a fence opens on a line whose first non-space characters are ``` ``` ``` or `~~~` and closes only on a line that is the *same* three-character marker followed by nothing but whitespace — so an info string never closes, tildes never close backticks, and an unclosed fence runs to end of file (E-04, T-05). Outside fences, two declaration forms are recognized:

Form	Rule	Example
table row	first non-space char `|`; cells split on unescaped `|` outside backtick spans; the **entire** trimmed first cell is `**ID**`, `~~**ID**~~`, or `**~~ID~~**`, optionally followed by whitespace-separated decoration (R-32, E-44); statement = second cell	`| **R-07** | statement |`

Form	Rule	Example
heading	`#`-run, then the ID token (optionally `~~`-wrapped) as the **first** token; statement = the title plus the whole section body to the next heading of the same or a higher level (R-33), fenced blocks included, capped per K-14	`### C-03 statement`


A bold ID anywhere else is not a declaration (E-31); separator rows never are. A second declaration of the same `(family, number)` raises `SpecError` — E-02 if both have the same retired flag, E-03 otherwise — naming both lines; there is no "first wins" (Q-006). Zero in-scope IDs is E-01. All three surface as exit `3` with no report written.

Three further things are read from the same pass:

- **The `*(recorded)*` marker** (R-35, C-01): a T id whose row carries the literal marker is RECORDED — it still needs a citing test with a passed outcome, but none of its edges is ever sent to the judge, so C-05 step 5 never applies to it. On a non-T id the marker is ignored with a Note (E-50).
- **The decision table** (C-01 (c), v1.13): the §12 table's rows are `D-nn` declarations, with the *Affects* column found by header name, not by position; each id token in that cell becomes an `affects` edge (C-12). A decision row outside the table, or a bold `**D-nn**` row inside it, declares nothing (T-79).
- **The typed edges** (C-12, R-36): every id token in every declared statement becomes an edge — `depends_on` between two R/C/I/K/E ids, `verifies` between a T id and an R/C/I/K/E id (recorded in the direction of the T id), `depends_on` between two T ids. An edge to an undeclared id is a Note, not an error; an edge to a retired id is recorded with `retired: true` (E-55). The whole array is sorted in C-12 order, which is what makes `impact` deterministic (I-002) and `related` stable. Since v1.21 a range (`R-07..R-10`, `to`, `through`, an en or em dash) also names every declared id strictly between its endpoints, and a table row's other cells feed edges (so an edge case's outcome column reaches `impact`) without changing `text` or `title` (D-50). Since v1.23 a foreign reference is masked before both passes, so `platform:R-01..R-05` names only `R-05` (E-69, F-716). A row whose statement cell holds an odd number of unescaped `$`, or (v1.24) that has more cells than its TABLE's header, gets the E-66 Note: an unescaped `|` split it. Since v1.24 the splitter reads backtick spans as CommonMark code spans (`code_spans`: a run of N backticks closes at the next run of exactly N), so `` ` ``` ` `` no longer flips it "outside" for the rest of the row, the failure that cut a real spec's statement in half and left a stray closing `|` on 32 others. And after the edges are built, the declared, non-retired ids no edge touches are kept on `SpecIndex.isolated`, *not* in `notes`. `check` and `explain` add one Note naming them (E-77); `impact`, which copies `notes`, does not.

`SPEC.md` itself is decoded with `errors="replace"` and a Note when any byte was replaced (E-11), and its K-14 truncation marker rides into the statement text as ordinary content (E-46).

6. Extraction: the code side (`extract.scan_roots`)



Citation is literal and total: comments, strings, and code count alike (D-03), and fences are *not* excluded in source files. Exclusion by resolved path happens before size/binary filtering and is silent, which is what lets `--src .` with `--out` inside the tree stay byte-deterministic across runs (E-23, E-34, T-36). The walker sorts directory entries and the final file list, and the PATHS list is deduplicated by resolved path, so citation order — and therefore every downstream list — is independent of filesystem order and of how the paths were named (I-002, I-012, T-78).

7. Attribution (`attribute.py`, `swift.py`, `jsts.py`)

For `.py` files under a `--tests` root, `ast.parse` yields the test cases of C-03:

- every module-level `def test_*` / `async def test_*`;
- every `test*` method (underscore optional, F-102) that is a *direct* member of a top-level class recognized by name (`Test*`) or by base (`*TestCase` as a `Name` or `Attribute`).

A span runs from the first decorator line to `end_lineno` (B-03 in the build report). Methods of unrecognized or nested classes are not cases; their lines fall to the file-level case and the file gets one `undelimited tests in …` Note (E-28). A `SyntaxError` (or the other exceptions `ast.parse` can raise on hostile input) makes the whole file file-level with a `parse fallback:` Note (E-12).

Swift files (R-31, v1.6) are delimited by `swift.py` without a toolchain (D-17): a Swift Testing `@Test` function or an XCTest `test*` method opens a span at its attribute/doc-comment block and closes by counting braces, with comments and string literals excluded from the count, and a brace fallback when the shape is unusual (E-42, E-43). The classname's `MODULE` component is the first path component of the file under its `--tests` root — or, for a file named directly as a PATHS element, its parent directory's last component (D-18, D-23). A `///` or `/** … */` doc-comment line is DECLARED exactly as a Python docstring is.

JavaScript/TypeScript files (R-104, v1.22; `.ts .tsx .mts .cts .js .jsx .mjs .cjs`) are delimited by `jsts.py`, again without a toolchain (D-56). It tokenizes rather than parses: comments, strings, template literals and regex literals are opaque tokens, and every rule reads tokens, never raw text. Whether a `/` opens a regex or divides is decided by the previous significant token (absent, punctuation other than `)`, `]`, `}`, or a listed keyword means regex; C-03, F-708). A case is an `it`/`test` call (with `skip`, `only`, `each`, … modifiers) whose first argument is a literal title. It is named by the titles of the `describe`/`suite` calls enclosing it, joined with `" > "`, and spans from the comment block above the call to its closing parenthesis. The classname is the file path with `/`→`.` and the extension kept. A dynamic title makes the call undelimited (E-75), and a file whose parentheses do not balance overall, or that has an unterminated comment, string, template or regex, falls back to file level (E-74). A comment-only line is DECLARED, a comment trailing code is not (C-14).

Every citation gets a `declared` flag (C-14, v1.14): true when the citation's own line lies inside the citing case's docstring or is a whole-line comment (`#` in Python; the Swift adapter's existing doc-comment recognition; a comment-only line for JS/TS), false otherwise — including a trailing comment on a code line, a string literal, every `"src"`-kind citation and every file-level one (E-56). The fact is computed under every judge mode, needs no results file and no network (I-014), and has three consumers: `tests[].declared` and `declared_ratio` in the JSON (C-16), the judge's request (C-15), and the `explain` trace.


Any other file type is one file-level case whose `classname` is derived exactly as for Python — path with `/`→`.` and the final extension dropped (F-108) — so that a JUnit result for a Go or Ruby file can still join it by suffix.

The attributor never sees the spec: it does not know which IDs are declared. Dangling and stale classification happens in the graph, from the `SpecIndex`.

8. Results mapping (`results.py`)

`parse_junit` accepts a `<testsuites>` or `<testsuite>` root (namespaces tolerated), treats every `<testcase>` below it as one result, and derives the outcome from its children in the fixed priority `failure > error > skipped > passed`. A missing `name` is E-05.

The join (C-04, F-006, F-101, F-105) is two-keyed:




Everything from the first `[` is stripped for the join, so parametrized variants and duplicates land on one case whose single `outcome` is the worst of them (E-06, E-24). Unattributed results are reported, sorted, and change no status.

Three rules arrived with the JS/TS adapter (v1.22, R-104) and one with v1.23.1. A path classname (`src/calc.test.ts`, as vitest and jest-junit write it) is read as dotted before the suffix rule, so it joins even when the runner's root is a sub-directory of `--root`. Case names go through the same `join_name` as result names, so a title holding `[` or `(` reduces identically on both sides. An `it.each` title's placeholders (`%s`, `%i`, `$name`) make a pattern that every filled result joins as a variant (E-76). And a result name beginning with `" > "` — jest-junit's `"{classname} > {title}"` for a test outside every `describe`, measured by T-117 — has that prefix dropped first (C-04).

9. The status algorithm (`graph.py`)

`deterministic_status` is C-05 steps 1–4 verbatim; `apply_verdicts` is step 5 and is the only function in the program that reads a verdict.



`eligible_edges` selects exactly the edges the judge may see: `PASSING` after step 4, **not** a recorded id, and the test outcome is `passed` (I-010, R-35; T-31 counts calls with a stub). The graph also classifies every citation whose ID is undeclared as *dangling* and every citation of a retired ID as *stale*; retired IDs keep empty `src/tests` so the same evidence is not listed twice (B-05).

Metrics (`compute_metrics`) use `decimal` throughout: each ratio is `Decimal(n) / Decimal(d)` under a 28-digit context, quantized to four places with `ROUND_HALF_EVEN`, or `None` when `d == 0` (I-008, Q-009). The seven in-scope statuses and the six families are always present as keys, zero or not (F-016). `conformance` is `passing / in_scope`; `judge_strength` is the share of judged edges the judge did not downgrade; `unknown_rate` is the share of judged edges that came back `UNKNOWN`; `declared_ratio` is the share of


in-scope R/C/I/K/E citations inside attributed non-file-level cases that are DECLARED (C-16), mapped citations excluded (F-703) — each recomputable from the report's own evidence (T-37). A mapped edge carries `lines: []`, since its evidence is in the map, not in the test.

`IdRecord.proof` (v1.19) is filled after the graph, by `proof.join_proof`, and is read by no step of C-05. A `checked` proof never promotes an `UNVERIFIED` id, and a `failed` one never demotes a `PASSING` id. The one place a proof state reaches the exit code is `--strict` with a readable `--proof-results` (D-45).

10. The judge (`judge.py`, `judge_mock.py`, `judge_llm.py`) and the triage pass (`jev.py`)

10.1 Contract and validation

A provider implements one method, `judge(JudgeRequest) → Verdict`, and may raise. The kernel never trusts what comes back:



`available` (C-07 `judge_available`) is total under `mock/llm` (v1.20): `false` when at least one edge was judge-eligible and no call succeeded — every call failed at the transport level (E-14), or none was issued because the budget allowed none (E-35) — and `true` otherwise. A malformed 200 counts as a call that succeeded (B-07); no eligible edge at all is vacuously available (E-36). The budget deadline is set by the first worker to issue a request and checked by every worker *before* it issues, so in-flight requests always complete and their verdicts count (Q-010; T-61). K-12's `N%` form is the same bookkeeping with a count instead of a

clock: exactly $\lceil N/100 \times E \rceil$ of the E eligible edges are issued, in K-16's order, and the rest take the same disposition as a deadline miss (`UNKNOWN`, `judge: budget`, `coerced`).

The request object carries everything the judge may consider: `id`, `statement` (C-10: the full text, body included, R-33), `declared` (C-15), `related` (R-38), and the line-numbered `source`. The reply object is unchanged since v1.9: `{verdict, clause, evidence[], rationale}`.

10.1a The progress indicator (R-30, C-11, K-13)


With `--judge llm` the judge stage is the only slow part of a run, so `run_judge` accepts a `ProgressLine` (created in `cli.py` when `--progress` resolves to on: `auto` means stderr is a TTY and verbosity is not `DEBUG`). It is a context manager around the whole stage: the first draw (`0/n`, `0:00 elapsed`, `?:??`) happens on entry, before the first request; every worker calls `advance()` once its verdict is determined; a daemon thread coalesces those into at most one draw per 100 ms and adds a 1 s tick so `elapsed` and the ETA keep moving; `__exit__` draws the final state (unless an exception is propagating) and then erases. Each draw is one write of `\r` + line + padding to the widest line so far — no terminal escapes, so a shrinking ETA leaves no residue on any console that honours a carriage return — and the erase is `\r` + spaces + `\r`. The line is written to the raw stderr stream, never through the logger, and `cli.py` defers the judge stage's INFO lines (mode, URL, model, stage summary) until after `run_judge` returns, so the logger is silent while the line is displayed. Under K-12's `N%` form the unissued edges are advanced before the stage starts, so the bar's total is the eligible set (K-13).

10.2 The mock provider

`MockJudge` reads the line-numbered `source` in the request, flags every line matching `^\s*assert\b`, containing `.assert`, or containing `pytest.raises(` — plus, since v1.6, Swift's `#expect(`, `#require(`, `XCTAssert`, `XCTFail(` and `Issue.record(` (R-31), and since v1.23.1 vitest/jest's `expect(` and `expect.` (F-706) — and returns `ASSERTS` with those lines as evidence or `EXECUTES_ONLY` with none (R-22). It has no configuration and no I/O, which is what makes `--judge mock` byte-deterministic and usable in `--self-check`. It reads no statement semantics, so it ignores `declared` and `related` entirely.

10.3 The LLM provider: Ollama, OpenRouter, or any OpenAI-compatible endpoint

`LlmJudge` implements C-06's wire format against any OpenAI-compatible `chat/completions` endpoint. The reference deployment is a local **Ollama** server, which serves that shape at `http://localhost:11434/v1/chat/completions`:



Design points:


- **Exactly one request per edge, no retries** (K-06). Concurrency comes from the runner's thread pool (`--judge-concurrency`), not from the provider.
- **K-05 is a single wall-clock deadline**, not httpx's per-phase timeouts alone: the request runs on a daemon thread and the caller waits at most `SPECCHECK_JUDGE_TIMEOUT` seconds for the full body. The per-phase timeouts are set as well so the abandoned thread also ends.
- **The transport is injectable** (`LlmJudge(config, post=…)`), which is how T-33 records the exact bytes and counts concurrency, and how the CLI-level tests (T-59, T-61) stub failures, UNKNOWN shares, and slow calls by monkeypatching `judge_llm._httpx_post`.
- **Configuration is environment-only** (C-09): URL, model, key, optional timeout — all three of the first required, with no default endpoint. A missing variable is a usage error naming the variable; the key's text is replaced by `***` in the one place a raw response is logged (DEBUG), and never appears anywhere else (R-23, I-007). The `--help` epilog states all of this (R-41, C-19).
- **The instruction text is data, not code.** `judge_prompt.md` is package data, read through `importlib.resources`, sent verbatim as the system message, and its SHA-256 lands in the report as `judge_prompt_sha256` (R-26). T-54 asserts the file equals the C-10 block in `SPEC.md`; the current text (v1.23.1) carries the any-clause rule (v1.7), the clause-first question (v1.9), the `declared` skepticism rule (v1.14), the `related` rule (v1.16), and a `declared` definition that covers a citation-map entry (F-703).
- **The endpoint is a URL, nothing more.** The provider has no vendor branches: the same code talked to local Ollama for the recorded T-49 runs, to OpenRouter for every Phase B gate in this repository's history (`openai/gpt-4o-mini` through v1.15, `google/gemini-3.8-flash` from v1.16, `openai/gpt-6-luna-pro` from v1.20), and would talk to Anthropic's OpenAI-compatible endpoint the same way. Only the three `SPECCHECK_JUDGE_*` variables change.
- **Thinking models** (Ollama returns their reasoning in `message.reasoning`) exhausted the v1.1 pin of `max_tokens: 400` before emitting the verdict; v1.2 pins 4000 (D-07). The provider does not special-

case this: an empty or truncated `content` is a malformed response, full stop.

- **The `related` neighbourhood is built here, not in the judge** (R-38, D-28): `related_titles` walks the `SpecIndex`'s edges, so the same list feeds the LLM user message and the C-17 triage `state` and the two cannot drift (T-83).

10.4 The triage pass (`jev.py`, v1.15)

`--jev-pre-triage` (K-16) spends a much cheaper model on the question *which edges need the real judge?* before any real-judge request is issued:



Its four variables are read only when the pass runs (`--jev-pre-triage` under `--judge llm`), so the flag needs no credential under `--judge none/mock` (K-16, I-006). The answer is discarded once the order exists: it never becomes a `Verdict`, never reaches `speccheck.json` or the Markdown report, never touches `judge_available` or `unknown_rate` (I-015, E-59). With `--judge-budget N%` the same order decides which edges are issued at all, which is the whole point of the pass: a truncated run spends itself on the edges the triage is least sure about rather than on declaration order. When the budget is unlimited and the pass therefore buys nothing, one Note says so (D-30).

11. Reporting and the write protocol (`report.py`, `impact.py`, `explain.py`)

`build_report` assembles the C-07 object in key order (`schema_version "1.5"` since v1.14; `judge_prompt_sha256` is inserted only for `llm`), computes `strict_judge_failure` (R-28, `unavailable` taking precedence over `unknown_rate`, Q-004) and then `exit_code` from the document itself. The Markdown is rendered *from the JSON object*, so the two can never disagree, and the §1 verdict line in the Markdown is the same `summary_line()` the CLI prints. The JSON carries `ids` (with `title`, `recorded`, `statement`, `status`, `src`, `tests`, `unrun`), `decisions` and `edges` (v1.13, C-12), `dangling`, `stale`, `unattributed_results`, `notes`, `metrics` and `exit_code`. The summary line's first word is `NOT CONFORMING` on exit `1`, and on exit `0` `CONFORMING` only when R-15's conditions hold (every in-scope id `PASSING`, nothing dangling or stale), else `UNPROVEN` (v1.24, R-105). It is read from the JSON like the rest of the line, so a non-strict run keeps its exit `0` while no longer calling an unproven tree conforming. The per-edge `declared` flag and the `declared_ratio` metric arrived in v1.14 (C-16); `title` in v1.7, `clause` in v1.9 and `recorded` in v1.10. `schema_version` is `"1.5"` and has not moved since v1.14: everything later is either request-side or a *conditional* key, present only when its input is — `proof` (top level and per id, with `--proof`/`--proof-results`, v1.19), `foreign` (when a foreign reference was found, v1.23), and `citation_map` with `mapped` on every `tests[]`, `dangling` and `stale` entry (with `--citation-map`, v1.23). A run that needs none of them is byte identical to the previous version's (I-018, I-019; T-100, T-109). The Markdown gains a `Proof (state)` column under


`--proof`, and renders a mapped citation as `<file> (map)`; the summary line gains `; citations: <M> mapped` when $M > 0$.

Ratios are Decimals but `json.dumps` cannot emit them with a fixed number of places, so a tiny sentinel type (`_Num`) is serialized through `default=` as `"\x00NUM:0.9000\x00"` and rewritten to the bare number after dumping. The result is a JSON text that is byte-determined without reference to binary floating point (Q-009): `0.9000`, never `0.9`.

`impact.py` builds the C-13 pair from the same `SpecIndex`: `resolve_changed_ids` (or `diff_changed_set` against `--against`), `walk` — breadth-first over reverse `depends_on` from an obligation and forward `affects` from a decision, each id at its shortest depth with the edge that first reached it (I-013) — `reverify_set`, and the optional citation/test-case lists from `--src/ --tests`. `render_impact_markdown` and the C-13 summary line come from the same report object.

`explain.py` renders the C-18 trace for one id: six sections in a fixed order, the C-05 step that set the status (numbered as C-05 numbers it since v1.23.1, F-711), the statement, the source citations, one line per citing case with its outcome and verdict (and the verdict's `clause/rationale` when a judge recorded one; `(mapped)` for a citation-map edge), and the `impact (<depth>):` section built from the same `walk/reverify_set`. It is a pure function of those facts — no clock, no filesystem, no environment — and the run writes nothing at all (D-33, I-016).

The writer is the only code in the program that creates or deletes files (I-001):



`write_impact_reports` follows the identical protocol for `impact.json/IMPACT_REPORT.md`, and the two subcommands never touch each other's files (I-001). `explain` has no writer to follow it: it prints to stdout (C-18, D-33). `_replace` and `_make_nonce` are module-level so T-45 can inject a failure between the two renames and observe the nonce.

12. The CLI (`cli.py`)

`cli.py` owns everything the spec calls a *surface*: three subcommands (`check` v0.1, `impact` v1.13, `explain` v1.17) plus `--self-check`.

- **Parsing** — an `argparse` parser whose `error()` raises `UsageError` instead of exiting, so every usage problem funnels through one `except` that logs at `ERROR` and returns `2`. Manual validation covers what argparse cannot express with the spec's exact messages: `--judge` values, `--verbose` levels, `--progress` modes, `--max-unknown` as a Decimal in `[0, 1]`, integer ranges, the `path outside --root:` rule (E-09) after a single `resolve()` per path, `--changed`/`--against` exclusivity (E-54), the `N%`-requires-`--jev-pre-triage` rule (E-58), the PATHS element that is neither file nor directory (E-52), and the `--namespace` grammar with its at-most-once rule (a custom `_Once` action, since argparse keeps the last value; R-102, E-68).
- **Validation order is a contract** (v1.20, K-18): every usage check — values, `--root` containment, and that every file a flag names (`--spec`, `--results`, `--proof-results`, `--against`, `--citation-map`) can be read — completes in the config builders before any file is *parsed*. So an invocation with both a usage fault and an input-contract fault exits `2`. The citation map's split follows: unreadable is `2` there, a malformed map is `3` in the apply-map stage (E-70).
- **Help is a contract** (v1.18, R-41, C-19): every argument definition of the four parsers carries an entry naming purpose, accepted values as literal tokens, the default and the preconditions, with metavars from §5.1's vocabulary (`NS` since v1.23); each screen ends with the `environment:` block (the eight `SPECCHECK_*` names, their read conditions and requiredness, plus `COLUMNS`) and the exit-code epilog. The enumerated clauses are built from the same constants the validators check (`JUDGE_MODES`, `VERBOSE_LEVELS`, `PROGRESS_MODES`), so help and usage error cannot disagree (T-95); the block is bound to the code's own `SPECCHECK_*` literals by T-98; the rendered bytes are pinned at `COLUMNS=80` by T-97. `--help` reads no file, no variable and no socket (I-017).
- **Configs** — a frozen `Config` for `check` (resolved paths, validated options, the judge/Jev env configs), and `ImpactConfig` / `ExplainConfig` beside it; `Action` says which one argv asked for. `explain`'s subparser defines neither `--out` nor `--strict`, so both are rejected by omission (E-54's pattern) and its config reuses `_build_check_config` with the two absent.
- **Wiring** — `_run_stages()` is the §3 pipeline above, shared by `execute()` (`check`) and `execute_explain()` (`explain`), which is what keeps the trace's status equal to the report's (I-016). `execute_impact()` runs the shorter path. Providers are constructed by `_make_provider` and `_make_triage_provider`, which are the seams T-31/T-89 use to count calls. `_progress_enabled()` decides whether the judge stage gets a `ProgressLine` (R-30, E-39): LLM judge only, never at `DEBUG`, `auto` means `sys.stderr.isatty()`, `always` overrides only the TTY test. Because the indicator owns stderr while displayed, the judge stage's own INFO lines — mode, URL and model, the stage summary — are logged only after `run_judge` returns (K-13, F-201).
- **Diagnostics** — one `logging.StreamHandler` on stderr, logger `speccheck`, format `%(levelname)s %(message)s`, level `ERROR` unless `--verbose`; handlers are reset on every `main()` call so the in-process test runner never accumulates them. Notes are logged at `INFO`; nothing is logged at `WARNING` (F-014). The progress indicator bypasses the logger entirely: it is written to the raw `sys.stderr` stream and erased before anything else is logged.
- **Interrupts** — `main()` catches `KeyboardInterrupt` explicitly (it is a `BaseException`, so the generic `except Exception` would let it escape with Python's exit 130): it logs `ERROR interrupted`, a traceback only at `DEBUG`, and returns `3` — keeping K-01's closed set of exit codes (E-41, D-16). Cleanup happens where the state lives: `write_reports` removes its temporaries and any already-renamed report on any `BaseException`, and `ProgressLine.__exit__` erases the line, so an interrupt leaves neither a half-written report nor a half-drawn bar. Two details make the interrupt *prompt* (v1.5, E-41): `run_judge` never blocks on an untimed future wait — it polls `concurrent.futures.wait(..., timeout=0.25)`, because an untimed lock wait is not SIGINT-interruptible on macOS CPython, so a bare `pool.map()` only noticed Ctrl-C once a request happened to finish — and `LlmJudge` runs the transport in a daemon thread and waits on it in 0.25 s polls that also watch an `abort` event. On interrupt `run_judge` sets the event, cancels queued futures, and joins the pool, which returns within one poll; the abandoned HTTP requests die with the daemon threads. Measured: one SIGINT against a stub server holding

requests for 15 s ends the run in 0.2 s (it was 15 s).

- **The summary line** — written as UTF-8 bytes to `stdout.buffer` when one exists, so the ASCII line is identical under a C locale or a `cp1252` stdout (R-29; T-44 runs both). `explain` writes its trace through the same byte path, for the same reason.
- **Exit codes** — `check` and `impact` as §5.4 says; `explain` returns `0` once the trace is written (nothing it renders is pass/fail), `2` for E-60's undeclared id or E-64's missing `--spec`, `3` for an input-contract violation (E-01..E-03, E-05, E-70).
- **`--self-check`** — copies `_selfcheck/` to a fresh temp dir, installs the socket guard, `chdir`s there, runs `run_check([...pinned argv...])` **in the same process** with stdout captured, compares the two outputs with the packaged goldens byte-for-byte, removes the directory, prints `self-check: ok` (or the first mismatch), and exits `0/1`. The inner run is expected to exit `1` — the fixture has planted defects — and that code is deliberately not the self-check's result (F-107, Q-003).

13. Determinism, checked four ways

I-002 says identical inputs give byte-identical reports on any OS. The design achieves it by never letting anything volatile into the data:

Source of variation	Where it is removed
filesystem order	`_walk` sorts entries; `scan_roots` sorts files; every list in the report is sorted by a stated key (C-07)
absolute paths	`to_posix_relative` against `--root`, `/` separators (R-20) — including in the `explain` trace
dictionary / set iteration	citations are grouped in dicts but emitted sorted; verdicts are keyed by `(TestCase, id)`; the walk's queue is sorted by (depth, id)
floating point	`decimal` with fixed quantization; JSON numbers via the `_Num` sentinel
judge completion order	the runner preserves request order; results are keyed, not appended
triage completion order	`run_triage` sorts the whole set after the pass, by (p(e), id) (K-16)
citation-map entry order	entries resolve to a set of (id, case) pairs; duplicates collapse (E-73), and unresolved-entry Notes sort with every other Note
foreign references	`foreign` is sorted by (file, line, namespace, id) before the Note names the first three (E-67)
the temp-file nonce	never written into either report
the progress indicator	stderr only, drawn on a TTY (or `--progress always`) and erased; nothing about it reaches stdout or either report (T-62 compares against a `--progress never` run)
terminal width	affects `--help` wrapping only (I-017), which is why T-97's goldens pin `COLUMNS=80`
time, host, version	not emitted at all — only `schema_version`

It is then verified four ways: T-36 (same fixture, different absolute paths, `--src .`, planted temporaries → identical bytes), T-92 (the `explain` trace, twice, and against the golden JSON's status), the checked-in goldens under `fixtures/target/golden/` (T-46, T-80, T-97 for the help screens), and `--self-check` from the installed package.

14. The fixture and the self-check, as one artifact

`fixtures/target/` is a small calculator project — 20 in-scope ids and 2 retired — engineered so that every status and every defect class has exactly one live example: one `UNCITED` R, one `UNTESTED` C, one `UNVERIFIED` E, one `FAILING` T, one `SKIPPED` K, one assertion-free test (→ `WEAKLY_PASSING` under the mock judge), one dangling citation, one stale citation, one unattributed result, one file-level citation, plus a parametrized test so `results[]/param` are exercised. Since v1.13 it also carries a §12 decision table (three rows: two declared targets, one undeclared, one retired — T-79/T-80), and since v1.16 the eight adjacent/generic pairs of T-76/T-84: each adjacent case cites an id, runs its code and asserts only a neighbour's fact, so a judge without `related` cannot tell it apart from a test that proves the id.

Its five goldens were produced by the tool and hand-verified: `golden/speccheck.json` and `golden/SPEC_CONFORMANCE_REPOR` (T-46 byte-compares both), `golden/impact.json` and `golden/IMPACT_REPORT.md` (T-80), and `golden/judge_labels.json` — 40 hand labels for the judged edges, the T-49/T-84 oracle (T-24 recomputes the metrics; T-37 recomputes every status from the evidence table and the JUnit file).

`src/speccheck/_selfcheck/` is a byte-identical copy, kept in sync by `tools/sync_selfcheck.py` and guarded by T-60, and shipped in the wheel via hatch `artifacts` (so that root-level `.gitignore` patterns for `junit.xml`/`speccheck.json` cannot silently exclude it — a defect the installed-wheel check caught during the build).

15. Test architecture

The suite (`tests/`, 175 test functions, 189 collected cases — `T-47`'s repair table and a few other parametrized tests expand) mirrors the spec's §9 groups one file per group:

File	§9 group	Functions
`test_01_extraction.py`	9.1 spec-side extraction (T-01..T-07, T-55, T-70, T-72, T-119, T-120)	13
`test_02_attribution.py`	9.2 attribution, Swift, declared (T-08..T-14, T-56, T-57, T-65..T-67, T-85)	14
`test_03_results.py`	9.3 the JUnit join (T-15..T-19, T-52, T-58, T-68)	8
`test_04_status.py`	9.4 the status algorithm and metrics (T-20..T-25, T-53, T-77)	8
`test_05_judge.py`	9.5 the judge contract (T-26..T-33, T-54, T-69, T-74, T-75, T-83, T-89)	19
`test_06_reports.py`	9.6 the reports and the writer (T-34..T-38)	7
`test_07_cli.py`	9.7 CLI, exit codes, diagnostics, boundary (T-39..T-45, T-50, T-59..T-64, T-78, T-90, T-101, T-103, T-118)	25
`test_08_golden.py`	9.8 the golden fixture end to end (T-46, T-47, T-71, T-73, T-76, T-86, T-88)	7
`test_09_self_application.py`	9.9/9.10/9.11 the recorded rows and the prose guards (T-48, T-49, T-51, T-84, T-87, T-91, T-94, T-112)	11

File	§9 group	Functions
`test_10_edges.py`	9.12 the decision-table grammar and C-12 edges, ranges, row cells, E-66, isolated ids (T-79, T-104..T-106, T-121)	13
`test_11_impact.py`	9.12 the `impact` CLI, changed set, walk, reverify (T-80, T-81, and T-82's presence check)	9
`test_12_explain.py`	9.13 the `explain` trace (T-92, T-93, T-102, E-61)	5
`test_13_help.py`	9.14 the help contract (T-95..T-98)	4
`test_14_proof.py`	9.15 Lean proof evidence (T-99, T-100)	13
`test_15_jsts.py`	9.16 the JS/TS adapter, the vitest and jest-junit joins (T-113..T-117)	7
`test_16_namespaces.py`	9.17 foreign references and `--namespace` (T-107..T-109)	7
`test_17_citation_map.py`	9.17 the citation map (T-109..T-111)	5

Each test function's docstring starts with the `T-nn` it realizes and ends with the R/C/I/K/E ids it proves — that is what makes self-application (T-48) report every one of the 307 ids as `PASSING`, and it is why the literal ignore-marker strings are confined to `tests/data/markers/` (F-109: a marker in a test module would make the checker ignore the test's own citation, which happened once during the build and was caught by self-application). The same rule covers `<ns>:ID` forms since v1.23 (F-713): they live in `tests/data/namespaces/` behind a line-1 `speccheck:ignore-file` marker that the tests drop when they copy a file into a project, and the test modules build every such token, and every undeclared id they need, at runtime, so self-application finds no foreign reference and no dangling citation in the suite itself.

Two helpers in `conftest.py` carry most of the weight: `run_cli(argv, cwd, env, tty=False)` runs `cli.main` in-process with `stdout`/`stderr` replaced by byte buffers, so exit codes, the summary line's bytes, and stderr silence are all observable without a subprocess (`tty=True` swaps in a `TtyWrapper` whose `isatty()` is true, which is how T-63 exercises `--progress auto`; the `\r`-separated capture is what T-62 parses for the C-11 draws and erase); and `project({...})` materializes a throwaway project from a file mapping in an isolated directory per call. The judge tests use stub providers and a recording HTTP stub with a concurrency counter; nothing in the gating suite touches the network.

Three tests cite no ID and are **uncited by design** — they guard artifacts the spec does not describe, so no row owns them: `test_prose_artifacts_claim_the_shipped_version` (the README's introduction, this report's title and `SPEC.md`'s status line must agree with `__version__`, F-3), `test_article_quotes_and_numbers_match_the_tree` (the article's quoted spec rows must be verbatim in `SPEC.md`, and its quoted numbers must match the tree, F-4), and `test_obligation_census_script_and_labels_are_well_f` (the census tooling and its ten seed labels, whose own proposal is `docs/proposals/PROPOSAL_obligation_census.md`). Being uncited, they add no conformance edge — which is also why the article guard builds the row ids from parts rather than writing them: citation is literal (F-013), and naming `R-11`/`E-16` there would have put two meaningless edges into the judge's eligible set.

The LLM judge itself has touched the suite in two ways, both intended: the v1.4 Phase B gate (`gpt-4o-mini` via OpenRouter) judged five tests as proving their IDs only by implication (R-20, K-02, K-03, K-08, E-29), and each was strengthened to assert the behavior outright; and the v1.16 build's first Phase B run flagged one id `WEAKLY_PASSING` whose only judged edge was a presence check (F-2), which was fixed in the test rather than by relaxing the gate. Under v1.20 four Phase B passes (`openai/gpt-6-luna-pro`) found two

more tests weaker than they claimed (E-34's leftover-file test, R-16's determinism test), both strengthened; v1.23.1's Phase B on the same model passed first time, 0 weak over 993 judged edges.

15.1 Tools (`tools/`)

The scripts beside the suite are not collected by pytest; all import `speccheck` directly and drive it in-process through `cli.run_check(argv, env, stdout)` — the same entry the self-check uses — so they exercise the real pipeline without a subprocess or a shell.

Script	Serves	What it does
`bench.py`	K-08 / T-51 (recorded)	Copies the golden fixture to a temp dir and times `check --judge mock --strict` five times; then generates a 10,000-file tree (5,000 source modules in 50 packages, 5,000 test modules in 50 groups, 100 declared IDs across all six families, a matching `junit.xml`) and times it five times. Prints the medians, the machine description, and PASS/FAIL against the 2 s / 60 s bounds.
`eval_judge.py`	T-49 (opt-in, needs a judge endpoint)	Runs `check --judge llm` three independent times on a fresh copy of the fixture, then scores every judged edge against `golden/judge_labels.json`: accuracy over non-`UNKNOWN` verdicts and `unknown_rate` over all judged edges, per run, no pooling. Prints model, date, `judge_prompt_sha256`, and PASS only if *every* run reaches $\geq$ 0.90 / $\leq$ 0.10.
`adjacent_eval.py`	T-84 (recorded)	Runs the fixture's eight adjacent edges under two C-10 texts — the shipped one and the pre-v1.16 text recovered from git by digest — three times each, and prints per-run downgrade counts, so "the model downgrades these anyway" can be told apart from "`related` moved it".
`sync_selfcheck.py`	F-107 / T-60	Copies `fixtures/target/` into `src/speccheck/_selfcheck/` (ignoring caches and dot-files); `--check` reports any drift and exits 1. Run it after editing the fixture or regenerating the goldens.

Script	Serves	What it does
`impact_backtest.py`	T-82 (recorded, needs `git`)	Scores `impact --against` on two ranges of this repository's own history against the ids whose citations the build ranges touched; prints recall and precision per depth cutoff.
`census.py`, `census_jev_tasks.py`, `census_prompt.md`, `census_labels.json`	the obligation census (`docs/proposals/PROPOSAL_obligation_census.md`)	Classify every live R/C/I/K/E id by the shape of its obligation (`expr`, `struct`, `behavior`, `prose`) and the checker that could verify it; `--ratify` folds a hand-edited census back in; the labels file is the ten-subject seed set the classifier is scored against.
`judge_crosscheck_tasks.py`, `jev_client.py`, `judge_crosscheck_report.py`	`JUDGE_CROSSCHECK_REPORT.md`	Build one C-17 `state` per judged edge from a `speccheck.json`, send them to Jev, and join the answers back to the recorded verdicts — the tooling behind the cross-model conflict numbers the v1.14–v1.16 proposals cite.
`format_task.py`, `test_format_task.py`	the census/cross-check workflow	Render one census task record as Markdown.
`jev_report.py`	the obligation census	Folds a Jev batch into the census's recommendation and accuracy bar, as a fourth model.
`proof_evidence.py`	C-21 / T-99	A standalone sidecar for a project laid out the way `spec-proof` scaffolds one: reads its `proof/` lake project and test results and writes the C-21 manifest `--proof-results` reads. Not part of the kernel; `check` never runs a prover.
`lean_doc.py`	the `proof/` documentation	Extracts the Markdown module header a Lean file opens with.

One thing is still deliberately absent: nothing regenerates the report goldens automatically. They are produced by running the checker on the fixture and copying the reports into `golden/` by hand, so that a change to them is always a deliberate, reviewable diff (the v1.16 increment regenerated them four times that way, and the diffs were read each time).

16. Things deliberately not built

Per the spec's non-goals and O-2/O-3: no semantic analysis of code, no test execution, no spec-quality review, no remediation, no multi-spec runs, no daemon/watch/IDE/web surface. Language adapters exist for Python (`ast`), Swift (v1.6, R-31) and JavaScript/TypeScript (v1.22, R-104); Go remains O-2, and other files get file-level attribution, which the join still supports by suffix. `--namespace` does not make speccheck multi-spec: another project's ids are recognized only to be *ignored* (C-22), and a run still checks exactly one spec.

The decisions the spec's §12 records (D-01..D-57) are the design's own forks; the ones later increments confirmed are cited throughout this document, and the ones still marked `confirm` are listed in `SPEC.md` §12 with the branch the build took. Three absences are worth naming because they were considered and rejected rather than forgotten:

- **No machine-readable interface schema.** `--help` is prose (v1.18), checked against the validators by T-95/T-98; there is no `--help-json`, because the tokens a caller needs are exactly the ones the usage errors already name, and a second rendering is a second thing to keep equal (D-40).
- **No environment preflight.** No `--check-env`/`--doctor`: the help *describes* the environment, it does not inspect it, so a missing or malformed variable is still discovered at parse time, naming the variable (E-21).
- **No report-as-input.** `explain` recomputes from the same inputs `check` uses rather than reading a previous `speccheck.json` (D-35); the checker never reads its own outputs, and the spec, the results file, the citation map, the proof manifest and its own reports are excluded from every scan (C-03, F-002, F-702).
- **No inferred citations.** A citation map states citations outside the code, but it is written by a person and labelled `mapped` everywhere it is read (D-54); nothing in the tool guesses which test proves which id.
- **No `--exclude` for scan roots** — self-application therefore cites the packaged fixture copy under `src/speccheck/_selfcheck/` as source evidence, which inflates R-01's evidence list but never a status.