



BioHackathon series:
[EuroBioC26 Hackathon](#)
Turku, Finland, 2026
[Project 2](#)

Submitted: 02 Jun 2026

License:
Authors retain copyright and
release the work under a Creative
Commons Attribution 4.0
International License ([CC-BY](#)).

Published by [BioHackrXiv.org](#)

BiocExecute: Make package functions or workflows executable in the command line

Guillaume Deflandre ¹, Leopold Guyot ², Rasmus Hindstrom ³, and Claire Rioualen ⁴

¹ First Affiliation ² Second affiliation ³ Third affiliation ⁴ IFB-core, French Institute of Bioinformatics (IFB), CNRS, INSERM, INRAE, CEA, 94800 Villejuif, France

Introduction

Commandline executables for bioconductor functions and scripts

This project was originally envisioned as a package or function for converting package maintainer or user supplied scripts into commandline executables. The R and Bioconductor paradigms of interactivity through a responsive and informative REPL have been a formula for success for academic users for a long time. But as computational biology becomes increasingly interdisciplinary and increasingly relies on high performance compute, high throughput compute and experimentation, and cloud compute, formalizing portable and flexible implementations of R and Bioconductor tooling is an imperative to ensure that that work, and Bioconductor itself maintain relevancy.

There already exist at least two tools that do 'app' style script conversion; R2G2 - Galaxy specific integration and Rapp - commandline executables. So developing a package for this project may not be necessary. Long term, the goal of this project is to lay the groundwork for programmatic generation of tooling within Bioconductor packages that can be slotted into modern workflow management systems, or other interactive platforms like Galaxy.

Key Considerations:

Where is the right place for 'app-ification' of a script to take place? Should it happen upon package installation? Overhead checking of things like package versions or argument types are mostly cheap, how much of those checks should we enforce? What do graceful failures for these scripts look like?

Meeting information

If you want to submit a preprint to BioHackrXiv, first check if your meeting is registered. You can find a list of meetings [here](#). If your meeting is missing, please contact your meeting organizers. The above list also provides information on the YAML fields with information about the meeting.

The following fields need to be given:

```
biohackathon_name: "BioHackathon Europe 2023"
biohackathon_url:  "https://biohackathon-europe.org/"
biohackathon_location: "Barcelona, Spain, 2023"
group: Project 26
git_url: https://github.com/yourOrganization/your_report_repo
```

The [BioHackrXiv meeting pages](#) provide content to use for the first three fields. The `git_url` field must have the link to the GitHub repository with your preprint (draft).

Author information

Information about the authors is given in the [YAML](#) format at the top of this template. For authors you provide their names, their affiliations. That is the minimum, but as BioHackrXiv is moving to a situation where more metadata is shared, and used by, for example, EuropePMC, adding additional information is encouraged.

BioHackathons is about hacking together, and the minimal number of authors for reports is two. This makes a minimal example look like this:

```
authors:
  - name: First Author
    affiliation: 1
  - name: Last Author
    affiliation: 2
affiliations:
  - name: First Affiliation
    index: 1
  - name: ELIXIR Europe
    index: 2
```

Author identifiers

Ideally, authors provide their [ORCID](#) identifier. For affiliations, it is added with the `orcid:` field. So, an author record would look like this:

```
authors:
  - name: First Author
    affiliation: 1
    orcid: 0000-0000-0000-0000
```

Research Organization Registry identifiers

Matching the author identifier, the affiliations can be further specified with the [Research Organization Registry](#) (ROR) identifier. For example, this is the affiliation identifier can be added with the `ror:` field:

```
affiliations:
  - name: ELIXIR Europe
    ror: 044rwnt51
    index: 2
```

Contributor Role Taxonomy

A last feature since is minimal support for the Contributor Role Taxonomy (CRediT). You can specify the role of authors in writing the report with the `role:` field. However, the authors are responsible for selecting the right terms from [CRediT](#). An example looks like this:

```
authors:
  - name: First Author
    affiliation: 1
    orcid: 0000-0000-0000-0000
    role: Conceptualization, Writing - review & editing
```

A full examples

A full example then has this structure:



```
authors:
- name: First Author
  affiliation: 1
  role: Writing - original draft
- name: Last Author
  orcid: 0000-0000-0000-0000
  affiliation: 2
  role: Conceptualization, Writing - review & editing
affiliations:
- name: First Affiliation
  index: 1
- name: ELIXIR Europe
  ror: 044rwnt51
  index: 2
```

Formatting

This document use Markdown and you can look at [this tutorial](#).

Subsection level 2

Please keep sections to a maximum of only two levels.

Tables

Tables can be added in the following way, though alternatives are possible:

Table: Note that table caption is automatically numbered and should be given before the table itself.

```
| Header 1 | Header 2 |
| ----- | ----- |
| item 1 | item 2 |
| item 3 | item 4 |
```

This gives:

Table 1: Note that table caption is automatically numbered and should be given before the table itself.

Header 1	Header 2
item 1	item 2
item 3	item 4

Figures

A figure is added with:

```
![Caption for BioHackrXiv logo figure](./biohackrxiv.png)
```

This gives:



Figure 1: Caption for BioHackrXiv logo figure

Figures can be scaled by adding the width or height to the Markdown like this:

```
![Caption for BioHackrXiv logo figure](./biohackrxiv.png){ width=50px }
```

Other main section on your manuscript level 1

Lists can be added with:

1. Item 1
2. Item 2

Citation Typing Ontology annotation

You can use [CiTO](#) annotations, as explained in [this BioHackathon Europe 2021 write up](#) and [this CiTO Pilot](#). Using this template, you can cite an article and indicate *why* you cite that article, for instance DisGeNET-RDF (Queralt-Rosinach et al., 2016).

The syntax in Markdown is as follows: a single intention annotation looks like `[@usesMethod In:Krewinkel2017]`; two or more intentions are separated with colons, like `[@extends:discusses:Nielsen2017Scholia]`. When you cite two different articles, you use this syntax: `[@citesAsDataSource:Ammar2022ETL; @citesAsDataSource:Arend2022BioHackEU22]`.

Possible CiTO typing annotation include:

- `citesAsDataSource`: when you point the reader to a source of data which may explain a claim
- `usesDataFrom`: when you reuse somehow (and elaborate on) the data in the cited entity
- `usesMethodIn`
- `citesAsAuthority`
- `citesAsEvidence`
- `citesAsPotentialSolution`
- `citesAsRecommendedReading`
- `citesAsRelated`
- `citesAsSourceDocument`
- `citesForInformation`
- `confirms`
- `documents`
- `providesDataFor`
- `obtainsSupportFrom`
- `discusses`
- `extends`



- agreesWith
- disagreesWith
- updates
- citation: generic citation

Results

Discussion

...

Acknowledgements

...

References

Queralt-Rosinach, N., Pinero, J., Bravo, À., Sanz, F., & Furlong, L. I. (2016). DisGeNET-RDF: harnessing the innovative power of the Semantic Web to explore the genetic basis of diseases. *Bioinformatics*, 32(14), 2236–2238. <https://doi.org/10.1093/bioinformatics/btw214> [cito:citesAsAuthority]

Author contributions

Guillaume Deflandre: Author, creator Leopold Guyot: Author Rasmus Hindstrom: Author Claire Rioualen: Author