Index

'*Note*: Page numbers followed by "f" indicate figures, "t" indicate tables and "b" indicate boxes.'

A
Active elements, 535, 545–546
Active sources, 545–546
"Adaptive filters", 21
ADC. *See* Analog-to-digital converter (ADC)
Adder, 711
Additive Gaussian noise, 22–29
Admittance, 598. *See also* Nodal analysis
  matrix, 598–599
Aliasing, 171–172, 175, 475
Alpha waves, 15, 91b–92b, 112–113
American Wire Gauge (AWG), 538b
Ammeters, 663, 664b
Amplification, 682. *See also* Gain
Amplifier, 262, 682–684. *See also* Operational amplifier (op amp)
  buffer, 711–712, 711f
  differential, 683, 684f, 709–710
  with "differential input" configuration, 683f
  ideal, 682–683, 683f
  instrumentation, 716–719, 718f
  inverting, 684, 688–691, 688b–690b
  noninverting, 686–688, 687b–688b
  operational. *See* Operational amplifier
  transconductance, 712–714, 712f, 713b–714b
Amplitude
  peak-to-peak, 55b–56b, 79b–80b, 82b–83b, 334b–335b
  resolution, 177
  RMS, 53. *See also* Root mean square (RMS)
  slicing. *See* Quantization
Analog
  circuit elements, 681
  circuitry, 681
  encoding, 11–12
  filters, 714–716, 716b
  models, 41–44
  signals, 11–12
  system, 529–530, 534–535
Analog circuits and models analysis. *See also* Discrete linear systems analysis
  conservation laws
    KCL, 596–601, 598b–601b
    KVL, 578–596, 579f, 580b–582b
    Newton's law, 601–607, 604b–607b
  resonance, 607–622, 608f
Analog electronics
  amplifier, 682–684
  inverting amplifier, 688–691, 688b–690b
  noninverting amplifier, 686–688, 687b–688b
  operational amplifier, 684–686
    practical, 691–707
Analog-to-digital converter (ADC), 14, 14b, 177, 681
Analogy, 42–43
Analysis
  chaos, 31
  cluster, 460
  continuous Fourier series, 170
  finite element, 560
  Fourier, 75, 137
  linear systems, 209–211
  mesh, 578–596
  nodal, 580, 596–601
  phasor analysis, 75, 249–253, 253b, 548–554, 569–570, 570b
  signal, 5
  texture, 516–521
  time-frequency, 200–201
Anti-aliasing filter, 356–357
Aperiodic signals, 32–38
Applied convolution–basic filters, 228–234, 229b–234b
Arctangent function, 123b–125b
Arithmetic operators, 250
Arrays, 17b–18b
ASCII code, 681
Associativity, 248
Attenuates, 198–200
Attenuation, 58b
  filter. *See* Filter—attenuation slope
Attenuator, 58b
Attractor, 463b–464b

Autocorrelation, 99–103. *See also* Shifted correlations
  functions, 186–187, 468b–471b
Autocovariance, 103–105, 104b–105b
Average/averaging, 190–191, 191b–193b
  ensemble, 65–66, 65f, 66b–67b
  for noise reduction, 63–65
  periodogram, 190
AWG. *See* American Wire Gauge (AWG)
Axis image command, 493–494
Axis off command, 493–494
Axons, 10–11

B
Band-pass filters, 358, 373b–374b
Band-stop filter, 358, 382
Bandwidth (BW), 28, 28b–29b, 112, 195–196,
    198–200, 691–695, 693b–695b
Bel, 56–57
Beta waves, 15, 112–113
Bias currents, 702
Bilateral *z*-transform, 348
Bioelectric energy, 7–8
Bioelectric signals. *See* Biosignals
Bioengineering, 3–4
  signals and systems
    biological systems, 4, 29–47
    biosignal, 6–20
    mass communication, 3
    noise, 21–29
    physiological system, 4f
    signal analysis, 5
Biological noise sources, 21–22
Biological signals, 200
Biological systems, 4, 29–47
  causal *vs*. noncausal signals and systems, 38
  deterministic signal properties, 32–38
    time-invariant *vs*. nonstationary signals and
      systems, 37–38
  deterministic *vs*. stochastic signals and systems,
      29–32
    chaotic signals and systems, 30–31
    fractal signals and images, 31–32
  linear *vs*. nonlinear signals and systems, 39–41
    biosystems modeling, 41–47
Biomedical instrument elements, 682f
Biomedical signals, 345–346
Biosignals, 4, 6–20, 681
  biological signal sources, 6, 6t
  biotransducers and common physiological
      measurements, 7–9
  signal representation, 9–15
  two-dimensional signals, 16–20
Biosystems modeling, 41–47
  analog models, 42–44
  systems models, 44–47
Biotransducers, 681
  and physiological measurements, 7–9
Black and white images (BW images), 493
Black boxes, 246
Blackman windows, 368–369, 369b–370b
Bode plot, 246, 261–275
  combining multiple elements, 275–285, 278b–283b
    constructing transfer function from system
      spectrum, 284–285
  constant gain element, 262
  derivative element, 262–264
  first-order element, 264–269
  integrator element, 264
  primitives, 261–262, 275, 276t
  second-order element, 269–275
  techniques, 301
Boltzman's constant (k), 27
Bridge circuit, 716–717, 717f
Broad-spectrum noise, 26–27
Buffer amplifier, 711–712, 711f
Butterworth filters, 359–360, 387–388, 389b–390b
BW. *See* Bandwidth (BW)
BW images. *See* Black and white images
    (BW images)
Bytes, 681

C
Calculus operations in Laplace domain, 299–300
Capacitance, 540–541
Capacitive elements, 538
Capacitors, 538–545, 544f
  decoupling, 700, 708–709, 708f, 720
  impedance, 550
  parallel, 635
  series, 634f
Caps. *See* Capacitors
Cardiac internal pressures, 7–8
Cardiac microphone, 7, 7f
Cardiovascular system, 3, 31
Cauer filters. *See* Elliptic filters
Causal filters, 363–364
Causal signals and systems, 38
Causality, 38
caxis command, 493–494
Centimeters, grams, dynes (cgs), 560, 565b,
    671b–672b
Central Limit Theorem, 23
cgs. *See* Centimeters, grams, dynes (cgs)
Chaos analysis, 31
Chaotic signals and systems, 30–31
Characteristic equation, 311–312, 318–319

Chebyshev filter, 359–360
  type I filters, 387–388, 389b–390b
  type II filters, 387–388, 389b–390b
Chemical energy, 6
Cheyne–Stokes respiration, 3–4
Chirp signal, 176–177
Chloride membrane channel, 596–597
Chronic myeloid leukemia, 437b–440b
Circuit(s), 577
  elements
    analog system *vs*. general systems, 534–535
    electrical elements, 535–548, 559
    Laplace domain–electrical elements, 554–559
    mechanical elements, 560–573
    phasor analysis, 548–554
  reduction. *See* Network reduction
  variables
    electrical variables, 530–532
    mechanical variables, 530–532
    system variables, 530–534
    voltage and current definitions, 532–534
Classic feedback system, 248b–249b
Climate control system, 45
Closed-loop gain, 692–694
Cluster analysis, 460
CMRR. *See* Common mode rejection ratio (CMRR)
Coarse graining, 474–475
  data scaling through, 475–478
Colormap, 492
Common mode rejection ratio (CMRR), 719
Common mode voltage, 719
Complex
  frequency, 297–298, 303
  notation, 247
  numbers, 73
  QRS, 455–456, 457f
  representation, 127–133
    of sinusoids, 73–75
  second-order processes with complex roots, 320–321, 320b–321b
  sinusoidal signals, 68
  system simulations, 418–421, 418b–421b
Compliance, 43, 552b–554b, 562–563, 601–602
Computed tomography scanner (CT scanner), 9
Computer-based methods, 211, 301
Conductance, 537
Conservation
  of energy, 577–578
  laws
    KCL, 596–601, 598b–601b
    KVL, 578–596, 579f, 580b–582b
    Newton's law, 601–607, 604b–607b
  of mass or charge, 577–578
Constant gain element, 262–263, 262f–263f, 306
Continuity-based methods, 515–521
  texture analysis and nonlinear filtering, 516–521
Continuous Fourier series analysis, 170
Continuous Fourier transform, 133–137, 180
Continuous signals, 9–15
  time–frequency transformation, 113–137
Continuous simulation, 412b–415b
Continuous systems, digital simulation of, 400–403
Continuum mechanics, 560
Contractile element, 42, 601–602, 602f
Contraction
  isometric, 566
  isotonic, 566
Control system performance improving, 422–429
Controller, 45
Conversion
  digital format, 14
  energy, 7
  signal, 47
  Thévenin—Norton circuit, 654–656, 656b
  time–frequency, 47
Convolution, 209–210, 245
  applied convolution–basic filters, 228–234
  convolution in frequency domain, 234–237
  impulse response to systems output to input–convolution, 216–228
  integral equation, 217–218
  linear systems analysis, 209–211
  slice in time, 211–216
  sum, 220–221
  in two dimensions, 501–502
Correlation, 5, 78
  coefficient, 78
    signal representation, 111–112
  dimension, 461, 467–472, 468b–471b
  equation, 501
  kernel, 501–502
  between signals, 81–84
Correlation integral. *See* Correlation sum
Correlation sum, 467–468
"Cosine transforms", 186–189
Covariance, 78, 81–82
Critical frequency (f_c), 196
Cross-correlation, 79b–80b, 84–99, 91b–94b
  equation, 218
  signals in different lengths, 96–99
Cross-covariance, 103–105
CT scanner. *See* Computed tomography scanner (CT scanner)
Current, 531–534, 533f–534f
  noise source, 704
  source, 546, 546f

Cutoff frequency, 196, 266
determination, 378–380
of filter, 475
Cyclical neutropenia, 437b–440b

D
DAC. *See* Digital-to-analog converter (DAC)
Damping factor, 269–270, 313, 320
Dark current, 28, 713b–714b
Dashpot, 560–561
Data
acquisition and storage, 170–186
amplitude slicing, 177–179
length and spectral resolution, 180–183
sampling, 170–177, 235–237
scaling through coarse graining, 475–478
truncation, 179–186
DC. *See* Direct current (DC)
Decibels (dB), 56–58, 193b–195b
Decoupling capacitor, 700, 708–709, 708f, 720
Delay embedding, 464–466
Delta function, 211–212
Delta wave, 112–113
Denominator polynomials, 316
Derivative element, 262–264, 306, 306f
Derivative filters, 375–378
Deterministic signal properties, 32–38
Deterministic signals and systems, 29–32
Detrended fluctuation analysis (DFA), 461, 478–483, 482b–483b
detrending signal, 481f
influence of short-and long-term processes, 480f
Detrending, 38, 479, 481f
DFA. *See* Detrended fluctuation analysis (DFA)
DFT. *See* Discrete Fourier transform (DFT)
Dielectric constant, 541–542
Dielectric material, 541–542
Difference equations, 353–356, 355b–356b
Differential amplifier, 683, 684f, 709–710
circuit, 709f, 718f
superposition, 710f
Differential equations, 5
Differential signal, 683–684
Differentiators, 250
Digital circuits, 681
Digital differentiation, 375
Digital filters, 345–346, 357
Digital signals, 12–15, 112. *See also* Analog signals
processing, 226
quantization, 13–15
time sampling, 12–13
Digital simulation, 399–400
of continuous systems, 400–403
Digital transfer function, 349–351
Digital-to-analog converter (DAC), 14–15
Digitized signal. *See* Digital signals
Direct current (DC), 539, 642
Dirichlet conditions, 120
Discrete domain, time–frequency transformation in, 137–160
Discrete equation, 55–56
Discrete Fourier transform (DFT), 137–143, 142b–143b, 148–158, 171, 180, 183f, 345–346, 496
MATLAB implementation, 143–148
phase wrapping, 150–151
redundancy, 149–150
respiratory example, 155–158
time shifts effect on Fourier Transform, 151–155
Discrete linear systems analysis. *See also* Analog circuits and models analysis
design of finite impulse response filters, 364–380, 367b–368b
difference equations, 353–356, 355b–356b
FIR filter design using Signal Processing Toolbox, 380–390
IIR filter design using Signal Processing Toolbox, 380–390
linear filters, 356–364
system and signal analysis techniques, 346t
z-transform, 347–352
Discrete signals, 9–15, 65–66
Discrete systems for filtering, 357
Displacement, 566
generator, 568
Distributed model, 43–44
Dot product, 81
Double band-pass filter, 386b, 387f, 387b
double command, 493
Downsampling factor, 474–475, 476f
Drift, 21

E
ECG. *See* Electrocardiography (ECG)
Ectopic beats, 456b–460b
Edge detection methods, 511–515
binary image, 515f
edges of blood cells, 514f
histogram of image, 517f
image of blood cells, 513b–515b
Sobel derivative filter, 512, 512f, 514f
EEG. *See* Electroencephalography (EEG)
Effector mechanism, 45
EGG. *See* Electrogastrogram (EGG)
Elasticity, 563–565, 565b
Electric and electronic circuits, 530

Electrical analog computer, 399
Electrical circuits, 529, 577
Electrical elements, 535–548, 544t, 559, 577–578
  fluid analogy, 546–548
  passive electrical elements, 536–545
  with zero initial conditions, 555, 556t
Electrical energy, 8–9
Electrical systems, 532
  resonance, 608
  signals of, 530–534
Electrical variables, 530–532, 532t
Electrocardiogram. *See* Electrocardiography (ECG)
Electrocardiography (ECG), 7–9, 9f, 14, 229b, 230f, 357
  recordings, 21–22
  signal, 455–456, 456b–460b
Electrode, 7–8
Electroencephalogram. *See* Electroencephalography (EEG)
Electroencephalography (EEG), 8–9, 15, 111, 286b, 373–374
  rhythm, 454–455
  signals, 37–38, 53, 133–134, 179–180, 374f, 452–453
Electrogastrogram (EGG), 8–9
Electromyogram (EMG), 8–9
Electronic circuits, 681
Electronic noise, 22, 26–29
  Johnson noise, 27–28
  shot noise, 28–29
Electrons, 533–534
Electrooculogram (EOG), 8–9
Electroretinogram (ERG), 8–9
Elliptic filters, 387–388, 389b–390b
Embedding dimension, 464–465
"Embedding", 464
EMG. *See* Electromyogram (EMG)
Energy, 7–8
  bioelectric, 7–8
  chemical, 6
  conservation, 577–578
  conversion, 7
  electrical, 8–9
  forms, 6, 6t
  spectral density, 187
  storage devises, 538–543, 542b, 551b
  users, 536–538
Ensemble average, 65–66, 65f, 66b–67b
  signal, 65–66
Ensemble averaging, 65–68, 66b–67b
Entropy, 472
Environmental noise, 21
EOG. *See* Electrooculogram (EOG)
Equivalent impedance, 633–637, 638b–639b, 641–642, 642b–646b, 648, 657b–660b, 667–668
ERG. *See* Electroretinogram (ERG)
Ergodicity, 450–460
Estimation process, 181–182
Euclidian distance, 467–468
Euler, Leonhard, 73–74
Euler's equation, 252
Euler's identity, 127
"Even functions", 122–125
Exception, 4–5
"Expectation" of mean, 450
External energy, 8–9
External transducers, 8

F

Fast Fourier transform (FFT), 127, 345–346
FDATool. *See* Filter Design and Analysis Tool (FDATool)
"Feature detection", 456–460
Feedback
  control system, 45, 422, 422f
    controller in, 424
  gain, 248b–249b, 695
    inverse of, 699f
    magnitude frequency plot, 699f
  network, 697f, 698–700
  pathway, 45, 248b–249b
Feedforward
  gain, 248b–249b, 256b–257b
  pathway, 248b–249b
Fetal ECG signal, 361, 362f
FFT. *See* Fast Fourier transform (FFT)
Filter Design and Analysis Tool (FDATool), 381
Filter gain, 385–387
Filter/filtering, 5, 356–357
  attenuation slope, 359
  bandwidth, 358
  coefficients, 229b–232b
  design, 356, 499–500
  image, 499
  initial sharpness, 359–360
  order, 359, 378
  "rolloff", 359
  synthesis, 356
  type, 358
  weights, 229b–232b
Finite element analysis, 560
Finite impulse response filters (FIR filters), 347, 357, 358f, 359, 364–380, 499, 500f. *See also* Infinite impulse response filters (IIR filters)
  band-pass filter, 373b–374b

Finite impulse response filters (FIR filters) (*Continued*)
Blackman window, 369b–370b
cutoff frequency determination, 378–380
derivative filters, 375–378
design using Signal Processing Toolbox, 380–390
filter characteristics, 361–362, 362t
impulse response of rectangular window filter, 366f
low-pass rectangular window filter, 371b
magnitude spectrum of rectangular window filter, 365f, 367b–368b
skip factor determination, 378–380
FIR filters. *See* Finite impulse response filters (FIR filters)
First-order
characteristic equation, 311–312, 328
element, 264–269, 265f–267f, 269b, 303, 308–312, 308b–312b
polynomial of frequency variable, 265
systems, 255
"Fixed point" attractor, 463b–464b
Fluid analogy, 546–548, 547f
FM. *See* Frequency modulation (FM)
Force–velocity
curve, 566–567, 567f
equation, 562
relationship, 560
of mass, 570
Fourier analysis, 75, 137, 200
Fourier coefficients, 118–122
Fourier series, 114–115, 548–549
analysis, 115–118, 120–121, 127, 129, 235–236
equation, 115
of pulse waveform, 130b–132b
theorem, 112
of triangle waveform, 123b–125b
of waveform, 132b–133b
Fourier transform, 112, 115–118, 120–121, 129, 229b–232b, 285–286, 285f, 286b, 295, 297, 548–549
of pulse, 136b
time shifts effect on, 151–155
Fractal behavior, 460–461
or fractal scaling methods, 460–461
Fractal dimension, 461–472, 461f
correlation dimension, 467–472
delay embedding, 464–466
state variables and state space, 462–464
time course and phase plane of second-order system, 463b–464b
Fractal scaling methods, 460–461
Fractal signals and images, 31–32
Frequency, 28b–29b
complex, 297–298, 303
critical, 196
cutoff, 196, 266, 378–380, 475
frequency-domain
analyses, 210
convolution, 236
fundamental, 116
image sampling, 495–496
Nyquist, 171
resonant, 608, 615b–618b, 619t
sampling, 173–174
spatial, 19, 491
spectrum, 5
undamped natural, 269–270, 313
vector, 259b–260b
Frequency domain, 15, 111–112, 245, 328–330, 329b–330b
converting Laplace transform to, 301, 302t
convolution in, 234–237
data sampling revisited, 235–237
impulse signal in, 214–216, 214b–215b
representation, 112
signal analysis, 195–196
data acquisition and storage, 170–186
EEG, 111
power spectrum, 186–190
signal bandwidth, 195–200
spectral averaging, 190–195
time-frequency analysis, 200–201
signals, 15
time–frequency domains, 112–113
transformations, 112
time–frequency transformation
of continuous signals, 113–137
in discrete domain, 137–160
transformation from *z*-domain to, 351–352, 351b–352b
Frequency modulation (FM), 10–11
Friction, 560
element, 560–561, 561f
Fundamental frequency, 116

G

Gain, 58b
closed-loop, 692–694
element, 220
feedback, 248b–249b, 695
feedforward, 248b–249b, 256b–257b
filter, 385–387
loop, 695–696
noise, 693–694
open-loop, 692, 693f
passband, 358
Gain bandwidth product (GBP), 695
Galvanic skin response (GSR), 8–9

Gases, 3
Gaussian distribution, 23–24, 23f, 24b–26b, 63b
Gaussian image filter, 503–504, 503b–504b
Gaussian noise, 26
Gaussian random signal, 101
GBP. *See* Gain bandwidth product (GBP)
General systems, 529, 534–535
Generic two-element system, 534–535, 535f
Gibbs artifacts, 121–122, 122f, 368–369
Glucose–insulin concentrations, Stolwijk–Hardy model of, 430–432, 430b, 431t
Graham Bell, Alexander, 56–57
Graphical User Interface (GUI), 403
Grassberger–Procaccia algorithm, 467–468
Gravitational mass, 567–568
Gravity, force due to, 568
Gross nonlinearities, 449
"Ground", voltage of earth, 533
GSR. *See* Galvanic skin response (GSR)
GUI. *See* Graphical User Interface (GUI)
Guyton–Coleman body fluid balance system, 254b, 308b–310b

H

Half-power point. *See* "−3 dB point"
Hamming window, 183–184, 184f, 200, 368–369
"Haralick" operator, 516–520
Harmonic decomposition, 116f
Harmonic series, 114–115
"Harmonically related" waves, 82b–83b
Heart rate variability (HRV), 188b–189b, 190, 193b–195b
High-frequency asymptote, 265
High-pass filter, 358, 382, 505–506
Higher frequency sine waves, 174
Higher-order transfer functions, 321–323, 322b–323b
Hippus, 3–4
Histogram, 24f, 24b–26b
Hodgkin–Huxley model, 596–597, 597f
Holter monitor, 22
Holter recording, 21–22
Home thermostat, 45
HRV. *See* Heart rate variability (HRV)
Hurst coefficient, 478–479
"Hurst" operator, 516–520

I

Ideal amplifier, 682–683, 683f
  properties, 682–683
Ideal measurement devices, 662–665, 664b
Ideal sources, 646–656
  electrical characteristics, 663t, 668t
  voltage–current plot, 646–649, 647f–649f
IDFT. *See* Inverse discrete Fourier transform (IDFT)
IFFT. *See* Inverse fast Fourier transform (IFFT)
IIR filter design using Signal Processing Toolbox, 380–390
IIR filters. *See* Infinite impulse response filters (IIR filters)
Image
  filter/filtering, 498–500, 502
  format and display, 492–494
  imaging system, 9
  Processing Toolbox, 491–492
  routine, 493
  sampling frequency, 495–496
  segmentation, 509–521
    continuity-based methods, 515–521
    edge detection methods, 511–515
    pixel-based methods, 509–511
imfill routine, 513b–515b
Impedance, 549–550
  capacitor, 550
  equivalent, 633–637, 638b–639b, 641–642, 642b–646b, 648, 657b–660b, 667–668
  input, 631, 654, 665, 706
  Laplace, 555, 557
  load, 663, 665–666
  matching, 666
  mechanical, 569–570, 671–672
  phasor, 580b–582b, 603b, 605b–607b, 638b–639b
Impulse and frequency response methods, 338
Impulse function, 137, 211, 211f, 300–301, 301f
  continuous, 212f
Impulse response, 211
  finding impulse response, 226
  of hypothetical system, 219f
  input signal first enters target system, 218f
  MATLAB implementation, 226–228
  output response produced by four time slices, 219f
  summation of 150 impulse responses, 220f
  systems output to input–convolution, 216–228, 217f, 221b–228b
Impulse signal, 211–216, 215f
  impulse signal in frequency domain, 214–216
  real-world impulse signals, 212–214
Inductance, 538
Inductor–resistor–inductor, 637–638
Inductors, 538–543, 562, 562f
Inertial elements, 538, 548
Inertial mass, 567–568
Infinite impulse response filter characteristics, 361–362, 362t
Infinite impulse response filters (IIR filters), 347, 357, 358f. *See also* Finite impulse response filters (FIR filters)

Information-based methods, 472–478
DFA, 478–483
multiscale entropy, 475–478
sample entropy, 472–475
Initial and Final Value Theorems, 326–328, 327b–328b
Input current sources, 702–705, 705b
Input elements, 700f
Input impedance, 631, 654, 665, 706
Input offset voltage, 701
Input transducers, 7
Input voltage sources, 701–702, 701b–702b
Input–convolution, impulse response to systems output to, 216–228, 217f
Instrumentation amplifier, 716–719, 718f
Integration, 479–480
Integrators, 250
element, 264, 307–308
Intensity histogram, 509–510, 510b–511b
Intuitive feel for convolution, 218
Inverse 2-D Fourier transform, 496
Inverse discrete Fourier series, 137
Inverse discrete Fourier transform (IDFT), 137
Inverse fast Fourier transform (IFFT), 127
Inverse Fourier transform, 120–121
Inverse Laplace transform, 302
Inverse *z*-transform method, 351
Inverting amplifier, 684, 688–691, 688b–690b
Inverting input, 683
Isolated pole, 264
"Isolated zero", 262–263, 278b–280b
Isometric
condition, 667–668
contraction, 566
Isotonic contraction, 566

J

Johnson noise, 26–28
equation for, 704

K

KCL. *See* Kirchhoff's current law (KCL)
Kinetic energy variable, 532, 577
Kirchhoff's current law (KCL), 577–579, 579f, 596–601, 598b–601b, 654
Kirchhoff's voltage law (KVL), 577–596, 579f, 580b–582b, 632–633, 654
mesh analysis
MATLAB implementation, 592–596, 592b–594b
multiple loops, 586–591, 586b–590b
single loops, 580–586, 584b–586b
"Kurtosis", 450
KVL. *See* Kirchhoff's voltage law (KVL)

L

"Lags", 88–89
Laplace analysis, 529–530
Laplace domain, 260b–261b, 296, 328–330, 329b–330b, 529
calculus operations in, 299–300
frequency domain, and time domain, 328–330
Laplace domain–electrical elements, 554–559
electrical elements with zero initial conditions, 555
nonzero initial conditions, 555–559
representations of mechanical elements, 570–573, 571f, 572b
sources–common signals in, 300–301
transfer function, 302–323, 307b–308b
constant gain element, 306
derivative element, 306
first-order element, 308–312
integrator element, 307–308
second-order element, 312–321
time delay element, 304–306
Laplace impedance for inductor, 555
Laplace transfer function, 347, 399–401, 715–716
Laplace transform, 296–302, 299b, 347
converting Laplace transform to frequency domain, 301
inverse, 302
nonzero initial conditions–initial and final value theorems, 324–328
system identification, 331–338
time plot of step function, 295f
"Laplace variable". *See also* Complex frequency
"Laplacian of Gaussian" filter, 505–506, 505b
"Laplacian" operator, 516–520
Least significant bit (LSB), 14b
"Limit cycle" attractor, 463b–464b
Linear, time-invariant, discrete-time systems (LTID), 345–346
Linear and time invariant systems (LTI systems), 449
Linear correlation, 76–78
Linear filters/filtering, 356–364, 499–509
application, 507–509
causal and noncausal filters, 363–364
convolution in two dimensions, 501–502
finite impulse response *vs.* infinite impulse response filter characteristics, 361–362, 362t
impulse response, 358f
linear image filters, 502–506
magnitude spectra of Gaussian low-pass filter, 504f
properties, 358–360
filter attenuation slope, 359
filter bandwidth, 358
filter initial sharpness, 359–360
filter type, 358

Linear image filters, 502–506
Linear model for skeletal muscle, 601–602, 602f
Linear phase property of FIR filters, 362
Linear signals and systems, 39–41
Linear system(s), 117–118, 449
  analysis, 5, 209–211
    superposition and linearity, 210–211
  in frequency domain
    bode plot, 261–275
    bode plots combining multiple elements, 275–285
    phasor analysis, 249–253
    systems analysis models, 246–249
    transfer function, 253–261
    transfer function and Fourier transform, 285–286
Linear time invariant (LTI), 39, 250, 295, 345
Linearity, 39, 210–211
Living systems, signals producing by, 6–20
Load, 649–650, 651b, 653–654, 662
  electrical characteristics, 663t, 668t
  ideal, 662–663
  impedance, 663, 665–666
Load resistor. *See* Load
Logistic
  difference equation, 30
  equation, 30
  map, 30
Long-terminteractions, 460
Loop gain, 695–696
Lorenz attractor, 468b–471b
Low-frequency asymptotes, 265–266
Low-pass filter/filtering, 358, 382, 515–516, 515b–516b, 517f
LSB. *See* Least significant bit (LSB)
LTI. *See* Linear time invariant (LTI)
LTI systems. *See* Linear and time invariant systems (LTI systems)
LTID. *See* Linear, time-invariant, discrete-time systems (LTID)
Lumped-parameter
  analysis, 560
  mechanical analysis, 560
  mechanical systems analysis, 601
Lyapunov exponent, 461

M

Magnetic resonance imaging (MRI), 8–9, 19–20, 507f, 507b–508b
Magnitude
  and phase spectra of transfer function, 268–269, 268f
  spectrum, 216, 216f, 262, 263f
Makay and Glass model of neutrophil density, 436–440, 437b–440b
Manual convolution, 223–226, 225f–226f
Mass
  communication, 3
  element, 561, 562f
MATLAB®, 5, 13, 16–20, 61, 69b–70b, 74–75, 81–82, 93–94, 380, 632, 641b–646b
  abs, 109, 130b–132b, 259b–260b
  angle, 74–75, 144–146, 150, 259b–260b
  atan, 71–72, 144b–146b
  atan2, 71–72, 109
  butter, 388, 397
  cheby1, 388
  cheby2, 388
  colormap, 17b–18b, 49–50, 493
  conv, 227–228, 227t, 227b–228b, 232b–234b, 237, 363–364, 371b, 381, 382b–385b, 392
  corrcoef, 81–82, 82b–83b
  cov, 81–82, 82b–83b
  ellip, 388, 389b–390b
  fir1, 382–385, 382b–385b, 388
  fir2, 382–387, 382b–385b
  image Processing Toolbox, 491, 492f
  implementation, 226–228, 227t, 496–498, 592–596, 592b–594b
    of DFT, 143–148
  interp1 routine, 188b–189b
  for Norton equivalent, 660b–662b
  pcolor, 17b–20b, 493
  power spectrum routines, 191b–193b
  rand function, 23–24
  routine filter2, 501–502
  signal, 385
  Signal Processing Toolbox, 185–186, 357
  sig_noise, 148, 149b–150b, 204, 394
  simulation program, 403
  Simulink, 399–400
  unwrap, 150–151, 152b–155b
  var, 518b–520b
  welch, 191b–195b, 198b–200b
  xcorr routine, 97b–99b
  yulewalk, 385
Matrix equation, 591
Maximum power
  theorem, 667
  transfer, 666–667
Mean, 450
  signal measurements, 53–59
Measurement
  artifact, 21–22. *See also* Gibbs artifacts
  loading, 662–667
    ideal and real measurement devices, 662–665, 664b
    maximum power transfer, 666–667

Mechanical elements, 560–573, 569t, 577–578
elasticity, 563–565
Laplace domain representations of mechanical elements, 570–573
mechanical sources, 566–568
passive mechanical elements, 560–563
phasor analysis of mechanical systems, 569–570
Mechanical impedance, 569–570, 671–672
Mechanical sources, 566–568, 566f–568f
Mechanical systems, 529, 577, 601–607, 603b, 615b, 667–672
phasor analysis, 569–570
resonance, 608
signals of electrical system and, 530–534
Mechanical variables, 530–532, 532t
"Memoryless" element, 262
Mesh analysis, 580
MATLAB implementation, 592–596, 592b–594b
multiple loops, 586–591, 586b–590b
single loops, 580–586, 584b–586b
Meters, kilograms, seconds (mks), 560
Microprocessors, 681
Mirror
image frequencies, 171
symmetry functions, 122–125
mks. *See* Meters, kilograms, seconds (mks)
Modern information theory, 11–12
Modern medical technology, 5
Motion artifact, 21–22
Motor, 568, 569f
MRI. *See* Magnetic resonance imaging (MRI)
MSE. *See* Multiscale entropy (MSE)
Multilead EEG signal, 16
Multimesh circuits, shortcut method for, 591
Multiple loops, 586–591, 586b–590b
shortcut method for multimesh circuits, 591
Multiple sources, 673–675, 673b–675b
Multiplication process, 171
Multiscale entropy (MSE), 461, 475–478, 477b
Multiscale entropy, 472

N

Negative feedback control system, 46
Neighborhood operations, 492, 499, 516–520
Nervous system, 3–4
Networks, 577
ideal sources, 646–656
electrical characteristics, 663t
voltage–current plot, 646–649, 647f–649f
measurement loading, 662–667
mechanical systems, 667–672, 669b–672b
multiple sources, 673–675, 673b–675b
Norton theorem, 657–662, 660b–662b
passive networks
successive series–parallel combination, 637–641, 638b–639b
voltage–current method, 641–646, 642b–646b
real current sources, 651–654, 654b
real voltage sources, 649–651, 651b
reduction, 631–632
Thévenin Theorem, 657–662, 657b–660b
Thévenin—Norton circuit conversion, 654–656, 656b
Neuromuscular motor reflex model, 432–436, 433b–436b
Neutrophil density, Makay and Glass model of, 436–440, 437b–440b
Newton's law, 601–607, 604b–607b. *See also* Kirchhoff's voltage law (KVL)
"No other connection" rule, 632–633
Nodal analysis, 580, 596–601
"Node", 579
Noise, 21–29
averaging for noise reduction, 63–65
biological noise sources, 21–22
"cancellation" techniques, 21
gain, 693–694
noise-free sine wave, 29
properties, 22–29
electronic noise, 26–29
sources of variability, 22t
voltage source, 701–702
Noncausal
filters, 363–364
signals and systems, 38
Noninverting
amplifier, 686–688, 687b–688b
input, 683
Nonlinear
chaotic systems, 467
filtering, 516–521
signals and systems, 39–41, 449, 460
Nonlinearity, 41, 449. *See also* Signal nonlinearity
Nonstationarities, 453–454
Nonstationarity, 37, 449
Nonstationary signals and systems, 37–38
Nonzero initial conditions, 324–326, 555–559, 557f–558f, 558b–559b, 570–573, 571f
nonzero initial conditions–initial and final value theorems, 324–328, 325b–326b
Normalized
force, 563
stretching, 564
Norton
circuits, 653–654
"equivalent" circuit, 652–653, 652f
theorem, 657–662, 660b–662b

Numerator polynomials, 316
Nyquist frequency, 171

O
Octave, 115
"Odd functions", 122–125
Off-diagonals, 84
Offset current, 702–703
Ohm's law, 27, 536, 559
One-dimensional signals (1-D signals), 9–10, 491
op amp. *See* Operational amplifier (op amp)
"Open circuits", 648
Open-loop gain, 692, 693f
  curve, 694–695, 694f
Operational amplifier (op amp), 684–686
  adder, 711
  analog filters, 714–716, 716b
  buffer amplifier, 711–712, 711f
  circuit used to constructing inverting amplifier, 689f
  differential, 683, 684f, 709–710, 718f
  feedback control system, 684f
  instrumentation amplifier, 716–719, 718f
  inverting, 688–691, 688b, 689f, 689b–690b, 703f
  LF356, 694f, 695, 708f
  noninverting, 686–688, 687f, 687b, 688f, 688b
  phase shift, 695, 697–698, 700
  power supply, 707–709
  practical, 691–707
    input characteristics, 700–706
    limitations in transfer characteristics, 691–700
    output characteristics, 706–707, 706f
  transconductance amplifier, 712–714, 712f, 713b–714b
  voltage divider network, 685f
Orthogonal/orthogonality, 81
  sets, 81
  signals, 81
Overlapping segments, 191

P
Padding techniques, 181
Parallel elements, 634–637, 634f, 635b–636b
  combining two parallel impedances, 636–637
"Parasitic" elements, 543–545
Partial fraction
  expansion–manual methods, 314–316, 315b–316b
  expansion–MATLAB, 316–319, 318b–319b
Passband, 358
  gain, 358
Passive elements, 535
  electrical elements, 536–545, 561
    electrical elements, 543–545
    energy storage devises, 538–543
    energy users, 536–538
  mechanical elements, 560–563, 563t
Passive networks
  successive series–parallel combination, 637–641, 638b–639b
  voltage–current method, 641–646, 642b–646b
Pattern recognition, 456–460
Pearson correlation coefficient, 76–78, 82
Period doubling, 30
Periodic
  impulse function, 171
  signals, 32–38, 33f, 114
Periodograms, 190–191
PET. *See* Positron emission tomography (PET)
Phase
  plane, 462–464
  space, 461
    trajectory, 465b–466b
  spectrum, 264
  trajectory, 464–465, 465b–466b, 467f
    in "state space" or "phase space", 461
Phasor analysis, 75, 246, 249–253, 253b, 529–530, 548–554
  of mechanical systems, 569–570, 570b
  phasor representation–electrical elements, 549–554, 551b–554b
Photodetectors, 28
Physiological process, 7–8
PhysioNet database, 104–105, 188b–189b
PID controller, 422–429
Pixel(s), 16
  coordinate system, 492, 492f
  pixel-based methods, 509–511
    image with two regions different average gray levels, 512f
    threshold level adjustment, 509–511
Polynomial equation, 321
Positive feedback oscillation, 695
Positron emission tomography (PET), 8–9, 8f
Potassium membrane channel, 596–597
"Potential difference", 532–533
Potential energy, 531
  variable, 530–531
Potentiometer, 537
Power, 57
  in mechanical systems, 532
  ratio, 58b
  spectral density, 187
  supply, 707–709
Power spectrum (PS), 169, 186–190
Practical op amps, 691–707
  input characteristics, 700–706
    input current sources, 702–705, 705b

Practical op amps (*Continued*)
input elements, 700f
input impedance, 706
input voltage sources, 701–702, 701b–702b
limitations in transfer characteristics of real op amps, 691–700
bandwidth, 691–695, 693b–695b
feedback network, 697f, 698–700
open-loop magnitude gain characteristics, 692f
stability, 695–700
output characteristics, 706–707, 706f
Premature
atrial contractions, 456b–460b
ventricular contractions, 456b–460b
"Prewitt" edge detector filter, 502
Proportional controller, 424
PS. *See* Power spectrum (PS)
"Pseudocolor" images, 493
Pulse, 137, 226
train, 235

Q

QRS complex, 455–456, 457f
Quantization, 12–15, 177–179
error, 177–179
Quotes, 4

R

Radiation detectors, 8–9
Radio frequency radiation (rf radiation), 8–9
Ramp function, 300, 301f
Random noise, 4–5
Random processes, 21
Random signal, 4–5
Randomness, 52–53
"Range" operator, 516–520
Ratio of stress to strain, 564
Reaction time, 304
Real current sources, 651–654, 654b
Real measurement devices, 662–665, 664b
Real op amps
input characteristics, 700–706
limitations in transfer characteristics, 691–700
Real roots, second-order elements with, 313–314, 314f
Real voltage sources, 649–651, 651b
Real-valued signals, sinusoids as, 68–73
Real-world impulse signals, 212–214, 212b–214b
Reality check, 543–545
"Rectangular window" filters, 364–365, 365f–366f
Reference signals, 76, 84–87
Regions of interest (ROIs), 492
"Resampling", 188b–189b
Rescaling operations, 509
Resistive elements, 648
Resistivity, 536, 536t
Resistors, 536–538, 537f, 538b
Resonance, 578, 607–622, 608f
resonant bandwidth, 608–622
resonant frequency, 608, 615b–618b, 619t
Resonant
circuits, 578
systems, 578
Response
delay, 304
latency, 304
of system elements to sinusoidal inputs, 249–253, 253b
Responsivity, 713b–714b
Revised cross-correlation routine, 97b–99b
rf radiation. *See* Radio frequency radiation (rf radiation)
Ringing, 618
"RLC" circuit, 580b–582b
RMS. *See* Root mean square (RMS)
ROIs. *See* Regions of interest (ROIs)
"Rolls off" signal, 198–200
Root mean square (RMS), 53, 177–179
signal measurements, 53–59
dB, 56–58
signal-to-noise ratio, 58–59
RR intervals, 478–479
Rubric ExG, 8–9

S

"Salt and pepper" noise, 508f, 508b
Sample entropy, 472–475, 473b–474b, 478
Sampling
frequency, 173–174
interval, 12
process, 12, 235, 235f
theorem, 170–177
Scale operation, 250
Scaling region, 468–471
Scatter plot, 456b–460b
Scattergram, 456b–460b
Second time-domain approach, 211
Second-order
characteristic equations, 311–312
element, 269–275, 270b, 272f, 272b, 273f, 303, 312–321
higher-order transfer functions, 321–323
partial fraction expansion–manual methods, 314–316
partial fraction expansion–MATLAB, 316–319
with real roots, 313–314

second-order processes with complex roots, 320–321
frequency characteristics, 328
function, 256b–257b
processes with complex roots, 320–321, 320b–321b
transfer function variables, 313
underdamped system, 320–321
Selectivity, 611–612
Self cross-correlation, 99
Semaphore telegraph, 6
Sensitivity functions, 713b–714b
Sequence samples, 472
Series electrical elements, 632–634, 632f, 633b–634b
Shannon's sampling theorem, 174
Shifted correlations, 84–99, 86b–87b
cross-correlating signals in different lengths, 96–99
zero padding, 89–96
Short circuit, 539
Short-term Fourier transform (STFT), 200, 210, 454–455
"Shot" noise, 26, 28–29
Signal conversion, 47
Signal Processing Tool (SPTool), 90, 381
FIR and IIR filter design using, 380–390
Signal-to-noise ratio (SNR), 58–59, 149, 177, 357
Signal(s), 51
amplitude, 10–11
analysis in frequency domain, 195–196
data acquisition and storage, 170–186
EEG, 5, 51, 111, 169, 209
power spectrum, 186–190
signal bandwidth, 195–200
spectral averaging, 190–195
time-frequency analysis, 200–201
time–frequency domain transformations, 112
time–frequency domains, 112–113
time–frequency transformation in discrete domain, 137–160
time–frequency transformation of continuous signals, 113–137
analysis in time domain, 5, 51, 169, 209
basic waveform, 68–75
measurements, 52–68
signal properties, 52, 52t
time domain analysis, 76–105
bandwidth, 195–200
digitization, 183
of electrical and mechanical systems, 530–534
entropy, 472
magnitude spectrum, 197–198
nonlinearity, 460–483
detrended fluctuation analysis, 478–483, 482b–483b
fractal dimension, 461–472, 461f
information-based methods, 472–478
processing, 5
processors, 29
producing by living systems, 6–20
profile, 479–480
properties, 10, 59–61
representation, 9–15, 10t, 51
analog signals, 11–12
digital signals, 12–15
time and frequency domains, 15
saturation, 449
scaling, 474–475
spectrum, 245, 257–258
transformations, 111–112
"Simply digital signal", 12–13
Simulation
method, 211
system
digital simulation of continuous systems, 400–403
simulation of first-order system, 403f
Simulink, 5, 47, 403–421, 406b–418b
biological examples, 429–440
Makay and Glass model of neutrophil density, 436–440, 437b–440b
model of neuromuscular motor reflex, 432–436, 433b–436b
Stolwijk–Hardy model of glucose–insulin concentrations, 430–432, 430b, 431t
complex system simulations, 418–421, 418b–421b
improving control system performance, 422–429
initial Simulink window, 405f
libraries, 405t
model specification and simulation, 404–418
"sinc" function, 365
Sine wave, 17b–18b, 32, 76–78
Single complex variable, 251
Single loops, 580–586, 584b–586b
circuit, 586–590
Single-pole low-pass filter, 714
Sinks, 404–406
Sinusoidal
decomposition, 114–115
function, 297
grating, 16–18, 17b, 18f, 18b
properties in time and frequency domains, 113–114
representation, 5
response of system elements to sinusoidal inputs, 249–253, 253b
signal, 55b–56b, 58b, 548–549
waveform, 5
Sinusoids, 68–75, 84, 113
complex representation of, 73–75
as real-valued signals, 68–73

Skeletal muscle, 604b–605b
  linear model for, 601–602, 602f
Skewness, 450–452
Skip factor, 375–376
  determination, 378–380
Slice in time, 211–216
Slicing, 509
Small movements approach, 45–46
SNR. *See* Signal-to-noise ratio (SNR)
"Sobel" filter, 502
  Sobel derivative filter, 512, 512f
Sodium membrane channel, 596–597
Sources, 404, 408f
  sources–common signals in Laplace domain, 300–301
Space filling, 461–462
Spatial derivatives, 512
Spatial frequency, 19, 491
Spectra, 15
Spectral
  analysis, 190
  averaging, 190–195
  domain, 112
  techniques, 191b–193b
Spectrum, 26–27, 112, 215
  of system elements, 261–275
    constant gain element, 262
    derivative element, 262–264
    first-order element, 264–269
    integrator element, 264
    second-order element, 269–275
  of transfer function, 257–261, 258f, 259b–261b
Speed, 6
SPTool. *See* Signal Processing Tool (SPTool)
Square wave, 115
Stability, 695–700
Standard deviation, 59–62
State space, 461–464, 463b–464b
State variables, 462–464, 463b–464b
Stationarity, 450–460
Stationary systems, 449
Step function, 295
STFT. *See* Short-term Fourier transform (STFT)
Stimuli, 4–5
Stochastic behavior, 21, 29
Stochastic processes, 21, 450–460
  alpha wave activity, 455f
  band-limited Gaussian signal, 450b–452b
  examples from two clusters, 460f
  nonstationary EEG signal, 453f
  scatter plot of features, 459f
  time-dependent activity, 454b–455b
  value of five EEG signals, 452t
  value of moments of five band-limited Gaussian signals, 452t
Stochastic signals and systems, 29–32
Stolwijk–Hardy model, 449
  for extracellular glucose–insulin concentrations, 449
  of glucose–insulin concentrations, 430–432, 430b, 431t
Stopband, 358
Strain, 563
Strange attractors, 463b–464b
Stress, 563
Successive series–parallel combination, 637–641, 638b–639b
  resonance revisited, 639–641, 641b
Summation, 76–78, 401–403
Superposition, 210–211, 221
Symmetry, 122–127
System, 3–5
  analysis models, 5, 246–249, 248b–249b
    two systems or elements connected together with transfer functions, 247f
    typical graphical representation of systems elements, 246f
  constructing transfer function from system spectrum, 284–285, 284b–285b
  elements response to sinusoidal inputs, 249–253, 253b
  identification, 245–246, 331–338, 332b–338b
  models, 41–42, 44–47, 45f, 246, 404
  simplifications, 632–637
    parallel elements, 634–637, 634f, 635b–636b
    series electrical elements, 632–634, 632f, 633b–634b
  systems-based approach, 3–4
  variables, 530–534
    electrical and mechanical variables, 530–532
    voltage and current, 532–534

T

Tapering window, 183–184, 201–202
Template
  samples, 472
  sequences, 472
Texture analysis, 516–521, 517f, 518b–520b
  histogram of original texture pattern, 520f
  isolated regions of texture pattern, 520f
  texture pattern, 519f, 521f
"Thermal" noise, 26
Theta waves, 15
Thévenin circuit, 666f
Thévenin sources. *See* Real voltage sources
Thévenin Theorem, 657–662, 657b–660b
Thévenin—Norton circuit conversion, 654–656, 656b

"3 dB down point". *See* "−3 dB point"
"−3 dB point", 197−198, 266, 269b, 693−694
Three-dimensional space (3-D space), 491
Three-point moving average. *See* Three-point running average
Three-point running average, 229f, 229b−230b, 231f
Threshold level adjustment, 509−511
Thresholding, 509
tiff files, 493
Time
  constant, 308, 313
  delay
    element, 303−306, 304b−306b
    theorem, 304−306, 304b−306b
  derivative of current, 538
  domain, 15, 209, 328−330, 329b−330b
    analysis, 76−105, 210
    autocorrelation, 99−103
    autocovariance and cross-covariance, 103−105
    averaging for noise reduction, 63−65
    comparison through correlation, 76−80
    correlations between signals, 81−84
    ensemble averaging, 65−68
    mean and rms signal measurements, 53−59
    measurements, 52−68
    multiplication, 234
    orthogonal signals and orthogonality, 81
    representation, 112
    shifted correlations, 84−99
    variance and standard deviation, 59−62
  sampling, 12−13
  shifting, 92−93
  shifts effect on Fourier Transform, 151−155, 152b−155b
Time-frequency
  analysis, 200−201, 200b−201b, 202f
  of continuous signals, 113−137
    complex representation, 127−133
    continuous Fourier transform, 133−137
    finding Fourier coefficients, 118−122
    Fourier series analysis and Fourier transform, 115−118
    sinusoidal decomposition, 114−115
    sinusoidal properties in time and frequency domains, 113−114
    symmetry, 122−127
  in discrete domain
    DFT, 137−143
    DFT spectrum, 148−158
    MATLAB implementation of DFT, 143−148
  domains, 112−113
    sinusoidal properties in, 113−114
    transformations, 112
Time-invariant signals and systems, 37−38
Tonic cells, 46
Toplitz matrix, 592b−594b
Transconductance amplifier, 712−714, 712f, 713b−714b
  output of photodetector, 713f
Transducer, 7
Transfer Fcn element parameter window, 412b−415b
Transfer function, 216, 246−247, 253−261, 254b−257b, 285−286, 297, 345, 347, 463b−464b, 529, 579−580, 584−586
  elements, 275t
  spectrum, 257−261
Transfer function construction from system spectrum, 284−285, 284b−285b
Transient signals, 32−38, 296
"Trend", 479
Truncation, 183
  data, 179−186
  signal, 234
Two-dimensional convolution, 501
2-D filter, 499−500
  coefficients, 499−500
  implementation, 500f
Two-dimensional Fourier transform (2-D Fourier transform), 495−498
  in continuous form, 496
  magnitude spectrum of horizontal chirp signal image, 499f
  MATLAB implementation, 496−498
Two-dimensional signals (2-D signals), 9−10, 491
  2-D Fourier transform, 495−498
  image format and display, 492−494
  image of blood cells, 494f
  image segmentation, 509−521
  influence of aliasing, 495f
  linear filtering, 499−509
Two-element
  electric circuit, 534−535
  Windkessel model, 43, 43f
Two-point central difference algorithm, 375−378, 376b, 377f
Two-sample template, 472, 473f
"Two-terminal" problem, 641

U

Ultrasound
  imaging, 9
  transducer, 671b−672b
Unbiased sample variance, 61
Undamped natural frequency, 269−270, 313
Undersampling, 495−496
Unilateral *z*-transform, 348

Unit
  delay, 348–349, 349f
  ramp function, 300–301
  step function, 297
  unit16 format, 493–494
  unit8 format, 493–494
Unsharp
  filter, 506
  masking, 506

V
Variability
  heart rate, 103
  sources, 22t
Variables
  electrical, 529
  flow, 531, 562
  kinetic energy, 531
  potential energy, 530–531, 560, 577
Variance, 59–62, 450
Vector, 13
  projection, 78
Velocity, 531
  generator, 568
VER. *See* Visual evoked response (VER)
"Vergence" eye movements, 45–46, 46f
v–i. *See* Voltage–current (*v–i*)
Virtual ground, 688–689
Visual evoked response (VER), 66
Voltage, 42–43, 530–534, 533f–534f, 577–578
  floating, 545–546
  grounded, 545–546
  polarity, 533, 537, 545–546
  sources, 545, 545f, 551f
Voltage–current (*v–i*), 646–649, 647f–649f
  equation, 545, 549
  method, 641–646, 642b–646b
  plot, 647f–649f
  ratio, 549
  real current source, 652f
  real voltage source, 649f
  relationship, 537, 540–541
  Thévenin and Norton circuit, 654f

W
Wavelet, 152b–155b
Weakly stationary, 450
Welch method, 190f, 198b–200b
Welch routine, 191b–193b
White noise. *See* Broad-spectrum noise
"Wide bandwidth" simulations, 403–404
Windkessel model, 43–44
Window
  filter, 364–365
  functions, 183–186, 200
"Windowing" process, 183
Wraparound technique, 89

X
X-ray imaging, 9

Y
Young's modulus, 564–565, 564t
Yule-Walker recursive filter, 385

Z
z-domain to frequency domain, transformation from, 351–352, 351b–352b
z-transform, 345–352
  development, 346–347
  digital transfer function, 349–351
  transformation from *z*-domain to frequency domain, 351–352, 351b–352b
  unit delay, 348–349
Zero initial conditions, electrical elements with, 555, 556t
Zero padding, 89–96, 101–103, 181–182