

Matrix Multiplication

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python

Week 9

Multiplying matrices

- Multiply matrices A , B

- $AB[i, j] = \sum_{k=0}^{n-1} A[i, k]B[k, j]$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Let $A : 1 \times 100$, $B : 100 \times 1$, $C : 1 \times 100$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Let $A : 1 \times 100$, $B : 100 \times 1$, $C : 1 \times 100$

- Computing $A(BC)$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Let $A : 1 \times 100$, $B : 100 \times 1$, $C : 1 \times 100$

- Computing $A(BC)$

- $BC : 100 \times 100$, takes

- $100 \cdot 1 \cdot 100 = 10000$ steps to compute

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Let $A : 1 \times 100$, $B : 100 \times 1$, $C : 1 \times 100$

- Computing $A(BC)$

- $BC : 100 \times 100$, takes

- $100 \cdot 1 \cdot 100 = 10000$ steps to compute

- $A(BC) : 1 \times 100$, takes

- $1 \cdot 100 \cdot 100 = 10000$ steps to compute

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Let $A : 1 \times 100$, $B : 100 \times 1$, $C : 1 \times 100$

- Computing $A(BC)$

- $BC : 100 \times 100$, takes

- $100 \cdot 1 \cdot 100 = 10000$ steps to compute

- $A(BC) : 1 \times 100$, takes

- $1 \cdot 100 \cdot 100 = 10000$ steps to compute

- Computing $(AB)C$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Let $A : 1 \times 100$, $B : 100 \times 1$, $C : 1 \times 100$

- Computing $A(BC)$

- $BC : 100 \times 100$, takes

- $100 \cdot 1 \cdot 100 = 10000$ steps to compute

- $A(BC) : 1 \times 100$, takes

- $1 \cdot 100 \cdot 100 = 10000$ steps to compute

- Computing $(AB)C$

- $AB : 1 \times 1$, takes

- $1 \cdot 100 \cdot 1 = 100$ steps to compute

Multiplying matrices

- Multiply matrices A , B

- $$AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Let $A : 1 \times 100$, $B : 100 \times 1$, $C : 1 \times 100$

- Computing $A(BC)$

- $BC : 100 \times 100$, takes

- $100 \cdot 1 \cdot 100 = 10000$ steps to compute

- $A(BC) : 1 \times 100$, takes

- $1 \cdot 100 \cdot 100 = 10000$ steps to compute

- Computing $(AB)C$

- $AB : 1 \times 1$, takes

- $1 \cdot 100 \cdot 1 = 100$ steps to compute

- $(AB)C : 1 \times 100$, takes

- $1 \cdot 1 \cdot 100 = 100$ steps to compute

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Let $A : 1 \times 100$, $B : 100 \times 1$, $C : 1 \times 100$

- Computing $A(BC)$

- $BC : 100 \times 100$, takes

- $100 \cdot 1 \cdot 100 = 10000$ steps to compute

- $A(BC) : 1 \times 100$, takes

- $1 \cdot 100 \cdot 100 = 10000$ steps to compute

- Computing $(AB)C$

- $AB : 1 \times 1$, takes

- $1 \cdot 100 \cdot 1 = 100$ steps to compute

- $(AB)C : 1 \times 100$, takes

- $1 \cdot 1 \cdot 100 = 100$ steps to compute

- 20000 steps vs 200 steps!

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Given n matrices $M_0 : r_0 \times c_0$,
 $M_1 : r_1 \times c_1, \dots, M_{n-1} : r_{n-1} \times c_{n-1}$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Given n matrices $M_0 : r_0 \times c_0$,

- $M_1 : r_1 \times c_1, \dots, M_{n-1} : r_{n-1} \times c_{n-1}$

- Dimensions match: $r_j = c_{j-1}$, $0 < j < n$

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Given n matrices $M_0 : r_0 \times c_0$,

- $M_1 : r_1 \times c_1, \dots, M_{n-1} : r_{n-1} \times c_{n-1}$

- Dimensions match: $r_j = c_{j-1}$, $0 < j < n$

- Product $M_0 \cdot M_1 \cdots M_{n-1}$ can be computed

Multiplying matrices

- Multiply matrices A , B

- $AB[i,j] = \sum_{k=0}^{n-1} A[i,k]B[k,j]$

- Dimensions must be compatible

- $A : m \times n$, $B : n \times p$

- $AB : m \times p$

- Computing each entry in AB is $O(n)$

- Overall, computing AB is $O(mnp)$

- Matrix multiplication is associative

- $ABC = (AB)C = A(BC)$

- Bracketing does not change answer

- ... but can affect the complexity!

- Given n matrices $M_0 : r_0 \times c_0$,

- $M_1 : r_1 \times c_1, \dots, M_{n-1} : r_{n-1} \times c_{n-1}$

- Dimensions match: $r_j = c_{j-1}$, $0 < j < n$

- Product $M_0 \cdot M_1 \cdots M_{n-1}$ can be computed

- Find an optimal order to compute the product

- Multiply two matrices at a time

- Bracket the expression optimally

Inductive structure

- Final step combines two subproducts

$$(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$$

for some $0 < k < n$

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost
- Final multiplication is $O(r_0 r_k c_{n-1})$

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost
- Final multiplication is $O(r_0 r_k c_{n-1})$
- Inductively, costs of factors are $C(0, k-1)$
and $C(k, n-1)$

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost
- Final multiplication is $O(r_0 r_k c_{n-1})$
- Inductively, costs of factors are $C(0, k-1)$
and $C(k, n-1)$
- $C(0, n-1) =$
 $C(0, k-1) + C(k, n-1) + r_0 r_k c_{n-1}$

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- Which k should we choose?
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost
- Final multiplication is $O(r_0 r_k c_{n-1})$
- Inductively, costs of factors are $C(0, k-1)$
and $C(k, n-1)$
- $C(0, n-1) =$
 $C(0, k-1) + C(k, n-1) + r_0 r_k c_{n-1}$

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost
- Final multiplication is $O(r_0 r_k c_{n-1})$
- Inductively, costs of factors are $C(0, k-1)$
and $C(k, n-1)$
- $C(0, n-1) =$
 $C(0, k-1) + C(k, n-1) + r_0 r_k c_{n-1}$
- Which k should we choose?
 - Try all and choose the minimum!

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost
- Final multiplication is $O(r_0 r_k c_{n-1})$
- Inductively, costs of factors are $C(0, k-1)$
and $C(k, n-1)$
- $C(0, n-1) =$
 $C(0, k-1) + C(k, n-1) + r_0 r_k c_{n-1}$
- Which k should we choose?
 - Try all and choose the minimum!
- Subproblems?

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost
- Final multiplication is $O(r_0 r_k c_{n-1})$
- Inductively, costs of factors are $C(0, k-1)$
and $C(k, n-1)$
- $C(0, n-1) =$
 $C(0, k-1) + C(k, n-1) + r_0 r_k c_{n-1}$
- Which k should we choose?
 - Try all and choose the minimum!
- Subproblems?
 - $M_0 \cdot M_1 \cdots M_{k-1}$ would decompose
as $(M_0 \cdots M_{j-1}) \cdot (M_j \cdots M_{k-1})$
 - Generic subproblem is
 $M_j \cdot M_{j+1} \cdots M_k$

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost
- Final multiplication is $O(r_0 r_k c_{n-1})$
- Inductively, costs of factors are $C(0, k-1)$
and $C(k, n-1)$
- $C(0, n-1) =$
 $C(0, k-1) + C(k, n-1) + r_0 r_k c_{n-1}$
- Which k should we choose?
 - Try all and choose the minimum!
- Subproblems?
 - $M_0 \cdot M_1 \cdots M_{k-1}$ would decompose
as $(M_0 \cdots M_{j-1}) \cdot (M_j \cdots M_{k-1})$
 - Generic subproblem is
 $M_j \cdot M_{j+1} \cdots M_k$
- $C(j, k) =$
 $\min_{j < \ell \leq k} [C(j, \ell-1) + C(\ell, k) + r_j r_\ell c_k]$

Inductive structure

- Final step combines two subproducts
 $(M_0 \cdot M_1 \cdots M_{k-1}) \cdot (M_k \cdot M_{k+1} \cdots M_{n-1})$
for some $0 < k < n$
- First factor is $r_0 \times c_{k-1}$, second is
 $r_k \times c_{n-1}$, where $r_k = c_{k-1}$
- Let $C(0, n-1)$ denote the overall cost
- Final multiplication is $O(r_0 r_k c_{n-1})$
- Inductively, costs of factors are $C(0, k-1)$
and $C(k, n-1)$
- $C(0, n-1) =$
 $C(0, k-1) + C(k, n-1) + r_0 r_k c_{n-1}$
- Which k should we choose?
 - Try all and choose the minimum!
- Subproblems?
 - $M_0 \cdot M_1 \cdots M_{k-1}$ would decompose
as $(M_0 \cdots M_{j-1}) \cdot (M_j \cdots M_{k-1})$
 - Generic subproblem is
 $M_j \cdot M_{j+1} \cdots M_k$
- $C(j, k) =$
 $\min_{j < \ell \leq k} [C(j, \ell-1) + C(\ell, k) + r_j r_\ell c_k]$
- Base case: $C(j, j) = 0$ for $0 \leq j < n$

Subproblem dependency

- Compute $C(i,j)$, $0 \leq i,j < n$

	0	...	i	j	...	$n-1$
0								
...								
i								
...								
...								
j								
...								
$n-1$								


Subproblem dependency

- Compute $C(i,j)$, $0 \leq i,j < n$
 - Only for $i \leq j$
 - Entries above main diagonal

	0	...	i	j	...	$n-1$
0								
...								
i								
...								
...								
j								
...								
$n-1$								

Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$



Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$

	0	...	i	j	...	$n-1$
0								
...								
i								
...								
...								
j								
...								
$n-1$								

Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$

	0	...	i	j	...	$n-1$
0								
...								
i								
...								
...								
j								
...								
$n-1$								


Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$

	0	...	i	j	...	$n-1$
0								
...								
i								
...								
...								
j								
...								
$n-1$								

Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$
 - $O(n)$ dependencies per entry, unlike LCW, LCS and ED



Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$
 - $O(n)$ dependencies per entry, unlike LCW, LCS and ED
- Diagonal entries are base case

	0	...	i	j	...	$n-1$
0	Orange							
...		Orange						
i			Orange					
...				Orange				
...					Orange			
j						Orange		
...							Orange	
$n-1$								Orange

Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$
 - $O(n)$ dependencies per entry, unlike LCW, LCS and ED
- Diagonal entries are base case
- Fill matrix by diagonal, from main diagonal

	0	...	i	j	...	$n-1$
0	■	■						
...		■	■					
i			■	■				
...				■	■			
...					■	■		
j						■	■	
...							■	■
$n-1$								■

Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$
 - $O(n)$ dependencies per entry, unlike LCW, LCS and ED
- Diagonal entries are base case
- Fill matrix by diagonal, from main diagonal

	0	...	i	j	...	$n-1$
0	■	■	■					
...		■	■	■				
i			■	■	■			
...				■	■	■		
...					■	■	■	
j						■	■	■
...							■	■
$n-1$								■

Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$
 - $O(n)$ dependencies per entry, unlike LCW, LCS and ED
- Diagonal entries are base case
- Fill matrix by diagonal, from main diagonal

	0	...	i	j	...	$n-1$
0	■	■	■	■				
...		■	■	■	■			
i			■	■	■	■		
...				■	■	■	■	
...					■	■	■	■
j						■	■	■
...							■	■
$n-1$								■

Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$
 - $O(n)$ dependencies per entry, unlike LCW, LCS and ED
- Diagonal entries are base case
- Fill matrix by diagonal, from main diagonal

	0	...	i	j	...	$n-1$
0								
...								
i								
...								
...								
j								
...								
$n-1$								

Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$
 - $O(n)$ dependencies per entry, unlike LCW, LCS and ED
- Diagonal entries are base case
- Fill matrix by diagonal, from main diagonal

	0	...	i	j	...	$n-1$
0								
...								
i								
...								
...								
j								
...								
$n-1$								

Subproblem dependency

- Compute $C(i,j)$, $0 \leq i,j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i,j)$ depends on $C(i, k-1)$, $C(k,j)$ for every $i < k \leq j$
 - $O(n)$ dependencies per entry, unlike LCW, LCS and ED
- Diagonal entries are base case
- Fill matrix by diagonal, from main diagonal

	0	...	i	j	...	$n-1$
0								
...								
i								
...								
...								
j								
...								
$n-1$								

Subproblem dependency

- Compute $C(i, j)$, $0 \leq i, j < n$
 - Only for $i \leq j$
 - Entries above main diagonal
- $C(i, j)$ depends on $C(i, k-1)$, $C(k, j)$ for every $i < k \leq j$
 - $O(n)$ dependencies per entry, unlike LCW, LCS and ED
- Diagonal entries are base case
- Fill matrix by diagonal, from main diagonal

	0	...	i	j	...	$n-1$
0								
...								
i								
...								
...								
j								
...								
$n-1$								

Implementation

```
def C(dim):
    # dim: dimension matrix,
    #     entries are pairs (r_i,c_i)
    import numpy as np
    n = dim.shape[0]
    C = np.zeros((n,n))
    for i in range(n):
        C[i,i] = 0
    for diff in range(1,n):
        for i in range(0,n-diff):
            j = i + diff
            C[i,j] = C[i,i] +
                    C[i+1,j] +
                    dim[i][0]*dim[i+1][0]*dim[j][1]
            for k in range(i+1,j+1):
                C[i,j] = min(C[i,j],
                            C[i,k-1] + C[k,j] +
                            dim[i][0]*dim[k][0]*dim[j][1])
    return(C[0,n-1])
```

Implementation

```
def C(dim):
    # dim: dimension matrix,
    #     entries are pairs (r_i,c_i)
    import numpy as np
    n = dim.shape[0]
    C = np.zeros((n,n))
    for i in range(n):
        C[i,i] = 0
    for diff in range(1,n):
        for i in range(0,n-diff):
            j = i + diff
            C[i,j] = C[i,i] +
                    C[i+1,j] +
                    dim[i][0]*dim[i+1][0]*dim[j][1]
            for k in range(i+1,j+1):
                C[i,j] = min(C[i,j],
                            C[i,k-1] + C[k,j] +
                            dim[i][0]*dim[k][0]*dim[j][1])
    return(C[0,n-1])
```

Complexity

Implementation

```
def C(dim):
    # dim: dimension matrix,
    #     entries are pairs (r_i,c_i)
    import numpy as np
    n = dim.shape[0]
    C = np.zeros((n,n))
    for i in range(n):
        C[i,i] = 0
    for diff in range(1,n):
        for i in range(0,n-diff):
            j = i + diff
            C[i,j] = C[i,i] +
                    C[i+1,j] +
                    dim[i][0]*dim[i+1][0]*dim[j][1]
            for k in range(i+1,j+1):
                C[i,j] = min(C[i,j],
                            C[i,k-1] + C[k,j] +
                            dim[i][0]*dim[k][0]*dim[j][1])
    return(C[0,n-1])
```

Complexity

- We have to fill a table of size $O(n^2)$

Implementation

```
def C(dim):
    # dim: dimension matrix,
    #     entries are pairs (r_i,c_i)
    import numpy as np
    n = dim.shape[0]
    C = np.zeros((n,n))
    for i in range(n):
        C[i,i] = 0
    for diff in range(1,n):
        for i in range(0,n-diff):
            j = i + diff
            C[i,j] = C[i,i] +
                    C[i+1,j] +
                    dim[i][0]*dim[i+1][0]*dim[j][1]
            for k in range(i+1,j+1):
                C[i,j] = min(C[i,j],
                            C[i,k-1] + C[k,j] +
                            dim[i][0]*dim[k][0]*dim[j][1])
    return(C[0,n-1])
```

Complexity

- We have to fill a table of size $O(n^2)$
- Filling each entry takes $O(n)$

Implementation

```
def C(dim):
    # dim: dimension matrix,
    #     entries are pairs (r_i,c_i)
    import numpy as np
    n = dim.shape[0]
    C = np.zeros((n,n))
    for i in range(n):
        C[i,i] = 0
    for diff in range(1,n):
        for i in range(0,n-diff):
            j = i + diff
            C[i,j] = C[i,i] +
                    C[i+1,j] +
                    dim[i][0]*dim[i+1][0]*dim[j][1]
            for k in range(i+1,j+1):
                C[i,j] = min(C[i,j],
                            C[i,k-1] + C[k,j] +
                            dim[i][0]*dim[k][0]*dim[j][1])
    return(C[0,n-1])
```

Complexity

- We have to fill a table of size $O(n^2)$
- Filling each entry takes $O(n)$
- Overall, $O(n^3)$