

# String Matching: Boyer-Moore algorithm

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python


Week 10

# Speeding up the brute force algorithm

- Text  $t$ , pattern  $p$  of lengths  $n$ ,  $m$
- For each starting position  $i$  in  $t$ ,  
compare  $t[i:i+m]$  with  $p$ 
  - Scan  $t[i:i+m]$  right to left

# Speeding up the brute force algorithm

- Text  $t$ , pattern  $p$  of lengths  $n$ ,  $m$
- For each starting position  $i$  in  $t$ , compare  $t[i:i+m]$  with  $p$ 
  - Scan  $t[i:i+m]$  right to left
- While matching, we find a letter in  $t$  that does not appear in  $p$ 
  - $t = \text{bananmania}$ ,  $p = \text{bulk}$



# Speeding up the brute force algorithm


- Text  $t$ , pattern  $p$  of lengths  $n$ ,  $m$
- For each starting position  $i$  in  $t$ , compare  $t[i:i+m]$  with  $p$ 
  - Scan  $t[i:i+m]$  right to left
- While matching, we find a letter in  $t$  that does not appear in  $p$ 
  - $t = \text{bananmania}$ ,  $p = \text{bulk}$
- Shift the next scan to position after mismatched letter
- What if the mismatched letter does appear in  $p$ ?

|   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|
| b | a | n | a | n | a | m | a | n | i | a |
|---|---|---|---|---|---|---|---|---|---|---|

|   |   |   |   |
|---|---|---|---|
| b | u | l | k |
|---|---|---|---|


# Sliding the search

- Suppose  $c = t[i+j] \neq p[j]$ , but  $c$  does occur somewhere in  $p[j]$




# Sliding the search

- Suppose  $c = t[i+j] \neq p[j]$ , but  $c$  does occur somewhere in  $p[j]$
- Align rightmost occurrence of  $c$  in  $p$  with  $t[i+j]$




# Sliding the search

- Suppose  $c = t[i+j] \neq p[j]$ , but  $c$  does occur somewhere in  $p[j]$
- Align rightmost occurrence of  $c$  in  $p$  with  $t[i+j]$
- Scan this substring of  $t$  next



# Sliding the search


- Suppose  $c = t[i+j] \neq p[j]$ , but  $c$  does occur somewhere in  $p[j]$
- Align rightmost occurrence of  $c$  in  $p$  with  $t[i+j]$
- Scan this substring of  $t$  next
- Use a dictionary `last`
  - For each  $c$  in  $p$ , `last[c]` records rightmost position of  $c$  in  $p$
  - Shift pattern by  $j - \text{last}[c]$





# Sliding the search

- Suppose  $c = t[i+j] \neq p[j]$ , but  $c$  does occur somewhere in  $p[j]$
- Align rightmost occurrence of  $c$  in  $p$  with  $t[i+j]$
- Scan this substring of  $t$  next
- Use a dictionary `last`
  - For each  $c$  in  $p$ , `last[c]` records rightmost position of  $c$  in  $p$
  - Shift pattern by  $j - \text{last}[c]$
- If  $c$  not in  $p$ , shift pattern by  $j+1$




## Example [Boyer, Moore 1977]

```
■ t = "which finally halts.  at that point"  
  p = "at that"
```


# Example [Boyer, Moore 1977]

```
■ t = "which finally halts.  at that point"  
  p = "at that"
```



# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7

# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f", "f" not in pattern, shift by 7, index 7`

# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11

# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f", "f" not in pattern, shift by 7, index 7`
- `t[7:14] == "inally ", " " in pattern, shift by 4 to align " ", index 11`

# Example [Boyer, Moore 1977]

- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17



# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f", "f" not in pattern, shift by 7, index 7`
- `t[7:14] == "inally ", " " in pattern, shift by 4 to align " ", index 11`
- `t[11:18] == "ly halt", "l" not in pattern, shift by 6, index 17`

# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17
- `t[17:24] == "ts. at"`, " " in pattern, shift by 2, index 19

# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17
- `t[17:24] == "ts. at"`, " " in pattern, shift by 2, index 19

# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17
- `t[17:24] == "ts. at"`, " " in pattern, shift by 2, index 19
- `t[19:26] == ". at t"`, " " in pattern, shift by 3, index 22

# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17
- `t[17:24] == "ts. at"`, " " in pattern, shift by 2, index 19
- `t[19:26] == ". at t"`, " " in pattern, shift by 3, index 22

# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17
- `t[17:24] == "ts. at"`, " " in pattern, shift by 2, index 19
- `t[19:26] == ". at t"`, " " in pattern, shift by 3, index 22
- `t[22:29] == "at that"`, report match at index 22, shift by 1, index 23

# Example [Boyer, Moore 1977]


```
■ t = "which finally halts.  at that point"  
  p = "at that"
```



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17
- `t[17:24] == "ts. at"`, " " in pattern, shift by 2, index 19
- `t[19:26] == ". at t"`, " " in pattern, shift by 3, index 22
- `t[22:29] == "at that"`, report match at index 22, shift by 1, index 23

# Example [Boyer, Moore 1977]

```
■ t = "which finally halts.  at that point"  
  p = "at that"
```




- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17
- `t[17:24] == "ts. at"`, " " in pattern, shift by 2, index 19
- `t[19:26] == ". at t"`, " " in pattern, shift by 3, index 22
- `t[22:29] == "at that"`, report match at index 22, shift by 1, index 23
- `t[23:30] == "t that "`, " " in pattern, shift by 4, index 27



# Example [Boyer, Moore 1977]


- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17
- `t[17:24] == "ts. at"`, " " in pattern, shift by 2, index 19
- `t[19:26] == ". at t"`, " " in pattern, shift by 3, index 22
- `t[22:29] == "at that"`, report match at index 22, shift by 1, index 23
- `t[23:30] == "t that "`, " " in pattern, shift by 4, index 27

# Example [Boyer, Moore 1977]

- `t = "which finally halts. at that point"`  
`p = "at that"`



- `t[0:7] == "which f"`, "f" not in pattern, shift by 7, index 7
- `t[7:14] == "inally "`, " " in pattern, shift by 4 to align " ", index 11
- `t[11:18] == "ly halt"`, "l" not in pattern, shift by 6, index 17
- `t[17:24] == "ts. at"`, " " in pattern, shift by 2, index 19
- `t[19:26] == ". at t"`, " " in pattern, shift by 3, index 22
- `t[22:29] == "at that"`, report match at index 22, shift by 1, index 23
- `t[23:30] == "t that "`, " " in pattern, shift by 4, index 27
- `t[27:34] == "at poin"`, "n" not in pattern, shift by 7, index 34, stop

# Implementation

- Initialize `last[c]` for each `c` in `p`
  - Single scan, rightmost value is recorded

```
def boyermoore(t,p):  
    last = {}                                # Preprocess  
    for i in range(len(p)):                    
        last[p[i]] = i  
  
    poslist,i = [],0                          # Loop  
    while i <= (len(t)-len(p)):                 
        matched,j = True,len(p)-1             
        while j >= 0 and matched:              
            if t[i+j] != p[j]:                 
                matched = False                
            j = j - 1  
        if matched:                            
            poslist.append(i)                   
            i = i + 1  
        else:                                  
            j = j + 1  
            if t[i+j] in last.keys():           
                i = i + max(j-last[t[i+j]]),1  
            else:                               
                i = i + j + 1  
    return(poslist)
```

# Implementation

- Initialize `last[c]` for each `c` in `p`
  - Single scan, rightmost value is recorded
- Nested loop, compare each segment `t[i:i+len(p)]` with `p`

```
def boyermoore(t,p):  
    last = {}                                # Preprocess  
    for i in range(len(p)):                    
        last[p[i]] = i  
  
    poslist,i = [],0                          # Loop  
    while i <= (len(t)-len(p)):                
        matched,j = True,len(p)-1  
        while j >= 0 and matched:              
            if t[i+j] != p[j]:                 
                matched = False  
            j = j - 1  
        if matched:                            
            poslist.append(i)  
            i = i + 1  
        else:                                  
            j = j + 1  
            if t[i+j] in last.keys():           
                i = i + max(j-last[t[i+j]],1)  
            else:                                
                i = i + j + 1  
    return(poslist)
```

# Implementation

- Initialize `last[c]` for each `c` in `p`
  - Single scan, rightmost value is recorded
- Nested loop, compare each segment `t[i:i+len(p)]` with `p`
- If `p` matches, record and shift by 1

```
def boyermoore(t,p):  
    last = {}                                # Preprocess  
    for i in range(len(p)):                    
        last[p[i]] = i  
  
    poslist,i = [],0                          # Loop  
    while i <= (len(t)-len(p)):                 
        matched,j = True,len(p)-1  
        while j >= 0 and matched:              
            if t[i+j] != p[j]:  
                matched = False  
            j = j - 1  
        if matched:                             
            poslist.append(i)  
            i = i + 1  
        else:                                   
            j = j + 1  
            if t[i+j] in last.keys():  
                i = i + max(j-last[t[i+j]],1)  
            else:  
                i = i + j + 1  
    return(poslist)
```

# Implementation

- Initialize `last[c]` for each `c` in `p`
  - Single scan, rightmost value is recorded
- Nested loop, compare each segment `t[i:i+len(p)]` with `p`
- If `p` matches, record and shift by 1
- We find a mismatch at `t[i+j]`
  - If `j > last[t[i+j]]`, shift by `j - last[t[i+j]]`
  - If `last[t[i+j]] > j`, shift by 1
    - Should not shift `p` to left!
  - If `t[i+j]` not in `p`, shift by `j+1`

```
def boyermoore(t,p):  
    last = {}                                # Preprocess  
    for i in range(len(p)):                    
        last[p[i]] = i  
  
    poslist,i = [],0                          # Loop  
    while i <= (len(t)-len(p)):                 
        matched,j = True,len(p)-1  
        while j >= 0 and matched:              
            if t[i+j] != p[j]:                 
                matched = False  
                j = j - 1  
            if matched:                         
                poslist.append(i)  
                i = i + 1  
        else:                                  
            j = j + 1  
            if t[i+j] in last.keys():           
                i = i + max(j-last[t[i+j]],1)  
            else:                               
                i = i + j + 1  
    return(poslist)
```

# Summary

- Worst case remains  $O(nm)$ 
  - $t = \text{aaa}\dots\text{a}$ ,  $p = \text{baaa}$

# Summary

- Worst case remains  $O(nm)$ 
  - $t = \text{aaa}\dots\text{a}, p = \text{baaa}$
- Without dictionary, computing `last` is a bottleneck, complexity is  $O(|\Sigma|)$



# Summary

- Worst case remains  $O(nm)$ 
  - $t = \text{aaa...a}$ ,  $p = \text{baaa}$
- Without dictionary, computing `last` is a bottleneck, complexity is  $O(|\Sigma|)$
- Boyer-Moore works well, in practice
  - “Sublinear”
  - Experimentally — English text, 5 character pattern, average number of comparisons is 0.24 per character
  - Performance improves as pattern length grows — more characters skipped

# Summary

- Worst case remains  $O(nm)$ 
  - $t = \text{aaa}\dots\text{a}$ ,  $p = \text{baaa}$
- Without dictionary, computing `last` is a bottleneck, complexity is  $O(|\Sigma|)$
- Boyer-Moore works well, in practice
  - “Sublinear”
  - Experimentally — English text, 5 character pattern, average number of comparisons is 0.24 per character
  - Performance improves as pattern length grows — more characters skipped
- Often used in practice — `grep` in Unix