

Memory Management

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming Concepts using Java

Week 1

Keeping track of variables

- Variables store intermediate values during computation
 - Typically these are local to a function
 - Can also refer to global variables outside the function
 - Dynamically created data, like nodes in a list

Keeping track of variables

- Variables store intermediate values during computation
 - Typically these are local to a function
 - Can also refer to global variables outside the function
 - Dynamically created data, like nodes in a list
- **Scope** of a variable
 - When the variable is available for use

Keeping track of variables

- Variables store intermediate values during computation
 - Typically these are local to a function
 - Can also refer to global variables outside the function
 - Dynamically created data, like nodes in a list

- **Scope** of a variable

- When the variable is available for use
- In the following code, the `x` in `f()` is **not** in scope within call to `g()`

```
def f(l):  
    ...  
    for x in l:  
        y = y + g(x)  
    ...
```

```
def g(m):  
    ...  
    for x in range(m):  
        ...
```

Keeping track of variables

- Variables store intermediate values during computation
 - Typically these are local to a function
 - Can also refer to global variables outside the function
 - Dynamically created data, like nodes in a list

- **Scope** of a variable

- When the variable is available for use
- In the following code, the `x` in `f()` is **not** in scope within call to `g()`

```
def f(l):                                def g(m):
    ...                                  ...
    for x in l:                          for x in range(m):
        y = y + g(x)                      ...
    ...
```


- **Lifetime** of a variable

- How long the storage remains allocated
- Above, lifetime of `x` in `f()` is till `f()` exits
- “Hole in scope” — variable is alive but not in scope

Memory stack


- Each function needs storage for local variables

Memory



Memory stack


- Each function needs storage for local variables
- Create **activation** record when function is called
- Activation records are stacked
 - Popped when function exits



- Call `factorial(3)`
- `factorial(3)` calls `factorial(2)`

Memory stack


- Each function needs storage for local variables
- Create **activation** record when function is called
- Activation records are stacked
 - Popped when function exits
 - Control link points to start of previous record



- Call `factorial(3)`
- `factorial(3)` calls `factorial(2)`

Memory stack


- Each function needs storage for local variables
- Create **activation** record when function is called
- Activation records are stacked
 - Popped when function exits
 - Control link points to start of previous record
 - Return value link tells where to store result



- Call `factorial(3)`
- `factorial(3)` calls `factorial(2)`

Memory stack


- Each function needs storage for local variables
- Create **activation** record when function is called
- Activation records are stacked
 - Popped when function exits
 - Control link points to start of previous record
 - Return value link tells where to store result
- **Scope** of a variable
 - Variable in activation record at top of stack
 - Access global variables by following control links



- Call `factorial(3)`
- `factorial(3)` calls `factorial(2)`

Memory stack

- Each function needs storage for local variables
- Create **activation** record when function is called
- Activation records are stacked
 - Popped when function exits
 - Control link points to start of previous record
 - Return value link tells where to store result
- **Scope** of a variable
 - Variable in activation record at top of stack
 - Access global variables by following control links
- **Lifetime** of a variable
 - Storage allocated is still on the stack



- Call `factorial(3)`
- `factorial(3)` calls `factorial(2)`

Passing arguments to functions

- When a function is called, arguments are substituted for formal parameters

```
def f(a,l):          x = 7
    ...             myl = [8,9,10]
    ...             f(x,myl)
```

Passing arguments to functions

- When a function is called, arguments are substituted for formal parameters

```
def f(a,l):      x = 7
...             myl = [8,9,10]
...             f(x,myl)
```

- Parameters are part of the activation record of the function
 - Values are populated on function call

Passing arguments to functions

- When a function is called, arguments are substituted for formal parameters

```
def f(a,l):          x = 7          a = x
...                myl = [8,9,10]   l = myl
...                f(x,myl)         ... code for f() ...
```

- Parameters are part of the activation record of the function
 - Values are populated on function call
 - Like having implicit assignment statements at the start of the function

Passing arguments to functions

- When a function is called, arguments are substituted for formal parameters

```
def f(a,l):           x = 7           a = x
...                 myl = [8,9,10]    l = myl
...                 f(x,myl)         ... code for f() ...
```

- Parameters are part of the activation record of the function
 - Values are populated on function call
 - Like having implicit assignment statements at the start of the function
- Two ways to initialize the parameters

Passing arguments to functions

- When a function is called, arguments are substituted for formal parameters

```
def f(a,l):           x = 7           a = x
...                   myl = [8,9,10]  l = myl
...                   f(x,myl)        ... code for f() ...
```

- Parameters are part of the activation record of the function
 - Values are populated on function call
 - Like having implicit assignment statements at the start of the function
- Two ways to initialize the parameters
 - Call by **value** — copy the value
 - Updating the value inside the function has no **side-effect**

Passing arguments to functions

- When a function is called, arguments are substituted for formal parameters

```
def f(a,l):          x = 7          a = x
...                 myl = [8,9,10]  l = myl
...                 f(x,myl)        ... code for f() ...
```

- Parameters are part of the activation record of the function
 - Values are populated on function call
 - Like having implicit assignment statements at the start of the function
- Two ways to initialize the parameters
 - Call by **value** — copy the value
 - Updating the value inside the function has no **side-effect**
 - Call by **reference** — parameter points to same location as argument
 - Can have side-effects
 - Be careful: can update the contents, but cannot change the reference itself


- Function that inserts a value in a linked list
 - Storage for new node allocated inside function
 - Node should persist after function exits
 - Cannot be allocated within activation record

Heap

- Function that inserts a value in a linked list
 - Storage for new node allocated inside function
 - Node should persist after function exits
 - Cannot be allocated within activation record
- Separate storage for persistent data
 - **Dynamically** allocated vs **statically** declared
 - Usually called the heap
 - Not the same as the heap data structure!


Heap

- Function that inserts a value in a linked list
 - Storage for new node allocated inside function
 - Node should persist after function exits
 - Cannot be allocated within activation record
- Separate storage for persistent data
 - **Dynamically** allocated vs **statically** declared
 - Usually called the heap
 - Not the same as the heap data structure!
 - Conceptually, allocate heap storage from “opposite” end with respect to stack



Heap

- Function that inserts a value in a linked list
 - Storage for new node allocated inside function
 - Node should persist after function exits
 - Cannot be allocated within activation record
- Separate storage for persistent data
 - **Dynamically** allocated vs **statically** declared
 - Usually called the heap
 - Not the same as the heap data structure!
 - Conceptually, allocate heap storage from “opposite” end with respect to stack
- Heap storage outlives activation record
 - Access through some variable that is in scope



Managing heap storage

- On the stack, variables are deallocated when a function exits

Managing heap storage

- On the stack, variables are deallocated when a function exits
- How do we “return” unused storage on the heap?
 - After deleting a node in a linked list, deleted node is now **dead** storage, unreachable

Managing heap storage

- On the stack, variables are deallocated when a function exits
- How do we “return” unused storage on the heap?
 - After deleting a node in a linked list, deleted node is now **dead** storage, unreachable
- Manual memory management
 - Programmer explicitly requests and returns heap storage
 - `p = malloc(...)` and `free(p)` in C
 - Error-prone — memory leaks, invalid assignments

Managing heap storage

- On the stack, variables are deallocated when a function exits
- How do we “return” unused storage on the heap?
 - After deleting a node in a linked list, deleted node is now **dead** storage, unreachable
- Manual memory management
 - Programmer explicitly requests and returns heap storage
 - `p = malloc(...)` and `free(p)` in C
 - Error-prone — memory leaks, invalid assignments
- Automatic garbage collection (Java, Python, ...)
 - Run-time environment checks and cleans up dead storage — e.g., **mark-and-sweep**
 - Mark all storage that is reachable from program variables
 - Return all unmarked memory cells to free space
 - Convenience for programmer vs performance penalty

Summary

- Variables have **scope** and **lifetime**
 - Scope — whether the variable is available in the program
 - Lifetime — whether the storage is still allocated
- Activation records for functions are maintained as a stack
 - Control link points to previous activation record
 - Return value link tells where to store result
- Heap is used to store dynamically allocated data
 - Outlives activation record of function that created the storage
 - Need to be careful about deallocating heap storage
 - Explicit deallocation vs automatic garbage collection