

Edit Distance

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python

Week 9

Document similarity

- “The students were able to appreciate the concept optimal substructure property and its use in designing algorithms”
- “The lecture taught the students to appreciate how the concept of optimal substructures can be used in designing algorithms”

Document similarity

- “The students were able to appreciate the concept optimal substructure property and its use in designing algorithms”
- “The lecture taught the students to appreciate how the concept of optimal substructures can be used in designing algorithms”
- Edit operations to transform documents
 - Insert a character
 - Delete a character
 - Substitute one character by another

Document similarity

- “The students were able to appreciate the concept optimal substructure property and its use in designing algorithms”
 - “The lecture taught the students to appreciate how the concept of optimal substructures can be used in designing algorithms”
 - Edit operations to transform documents
 - Insert a character
 - Delete a character
 - Substitute one character by another
- “The lecture taught the students ~~were able~~ to appreciate how the concept of optimal substructures ~~property~~ and ~~it~~ be used in designing algorithms”
 - insert, ~~delete~~, substitute

Document similarity

- “The students were able to appreciate the concept optimal substructure property and its use in designing algorithms”
- “The lecture taught the students to appreciate how the concept of optimal substructures can be used in designing algorithms”
- Edit operations to transform documents
 - Insert a character
 - Delete a character
 - Substitute one character by another

- “The lecture taught the students ~~were able~~ to appreciate how the concept of optimal substructures ~~property~~ and ~~it~~ be used in designing algorithms”
- insert, ~~delete~~, substitute

Edit distance

Document similarity

- “The students were able to appreciate the concept optimal substructure property and its use in designing algorithms”
- “The lecture taught the students to appreciate how the concept of optimal substructures can be used in designing algorithms”
- Edit operations to transform documents
 - Insert a character
 - Delete a character
 - Substitute one character by another

- “The lecture taught the students ~~were able~~ to appreciate how the concept of optimal substructures ~~property~~ and ~~it~~ be used in designing algorithms”
- insert, ~~delete~~, substitute

Edit distance

- Minimum number of edit operations needed

Document similarity

- “The students were able to appreciate the concept optimal substructure property and its use in designing algorithms”
- “The lecture taught the students to appreciate how the concept of optimal substructures can be used in designing algorithms”
- Edit operations to transform documents
 - Insert a character
 - Delete a character
 - Substitute one character by another

- “The lecture taught the students ~~were able~~ to appreciate how the concept of optimal substructures ~~property~~ ~~and it~~ ~~be~~ used in designing algorithms”
- insert, ~~delete~~, ~~substitute~~

Edit distance

- Minimum number of edit operations needed
- In our example, 24 characters inserted, 18 ~~deleted~~, 2 ~~substituted~~

Document similarity

- “The students were able to appreciate the concept optimal substructure property and its use in designing algorithms”
- “The lecture taught the students to appreciate how the concept of optimal substructures can be used in designing algorithms”
- Edit operations to transform documents
 - Insert a character
 - Delete a character
 - Substitute one character by another

- “The lecture taught the students ~~were able~~ to appreciate how the concept of optimal substructures ~~property~~ ~~and it~~ ~~be~~ used in designing algorithms”
- insert, ~~delete~~, ~~substitute~~

Edit distance

- Minimum number of edit operations needed
- In our example, 24 characters inserted, 18 ~~deleted~~, 2 ~~substituted~~
- Edit distance is at most 44

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another
- Also called Levenshtein distance
 - Vladimir Levenshtein, 1965

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another
- Also called Levenshtein distance
 - Vladimir Levenshtein, 1965
- Applications
 - Suggestions for spelling correction
 - Genetic similarity of species

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another
- Also called Levenshtein distance
 - Vladimir Levenshtein, 1965
- Applications
 - Suggestions for spelling correction
 - Genetic similarity of species

Edit distance and LCS

- Longest common subsequence of u , v

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another
- Also called Levenshtein distance
 - Vladimir Levenshtein, 1965
- Applications
 - Suggestions for spelling correction
 - Genetic similarity of species

Edit distance and LCS

- Longest common subsequence of u , v
 - Minimum number of deletes needed to make them equal

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another
- Also called Levenshtein distance
 - Vladimir Levenshtein, 1965
- Applications
 - Suggestions for spelling correction
 - Genetic similarity of species

Edit distance and LCS

- Longest common subsequence of u , v
 - Minimum number of deletes needed to make them equal
- Deleting a letter from u is equivalent to inserting it in v

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another
- Also called Levenshtein distance
 - Vladimir Levenshtein, 1965
- Applications
 - Suggestions for spelling correction
 - Genetic similarity of species

Edit distance and LCS

- Longest common subsequence of u , v
 - Minimum number of deletes needed to make them equal
- Deleting a letter from u is equivalent to inserting it in v
 - `bisect`, `secret` — LCS is `sect`

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another
- Also called Levenshtein distance
 - Vladimir Levenshtein, 1965
- Applications
 - Suggestions for spelling correction
 - Genetic similarity of species

Edit distance and LCS

- Longest common subsequence of u , v
 - Minimum number of deletes needed to make them equal
- Deleting a letter from u is equivalent to inserting it in v
 - `bisect`, `secret` — LCS is `sect`
 - Delete `b`, `i` in `bisect` and `r`, `e` in `secret`

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another
- Also called Levenshtein distance
 - Vladimir Levenshtein, 1965
- Applications
 - Suggestions for spelling correction
 - Genetic similarity of species

Edit distance and LCS

- Longest common subsequence of u , v
 - Minimum number of deletes needed to make them equal
- Deleting a letter from u is equivalent to inserting it in v
 - `bisect`, `secret` — LCS is `sect`
 - Delete `b`, `i` in `bisect` and `r`, `e` in `secret`
 - Delete `b`, `i` and then insert `r`, `e` in `bisect`

Edit distance

- Minimum number of editing operations needed to transform one document to the other
 - Insert a character
 - Delete a character
 - Substitute one character by another
- Also called Levenshtein distance
 - Vladimir Levenshtein, 1965
- Applications
 - Suggestions for spelling correction
 - Genetic similarity of species

Edit distance and LCS

- Longest common subsequence of u , v
 - Minimum number of deletes needed to make them equal
- Deleting a letter from u is equivalent to inserting it in v
 - `bisect`, `secret` — LCS is `sect`
 - Delete `b`, `i` in `bisect` and `r`, `e` in `secret`
 - Delete `b`, `i` and then insert `r`, `e` in `bisect`
- LCS equivalent to edit distance without substitution

Inductive structure for edit distance

- $u = a_0 a_1 \dots a_{m-1}$

- $v = b_0 b_1 \dots b_{n-1}$

Inductive structure for edit distance

- $u = a_0 a_1 \dots a_{m-1}$

- $v = b_0 b_1 \dots b_{n-1}$

- Recall LCS

Inductive structure for edit distance

- $u = a_0 a_1 \dots a_{m-1}$

- $v = b_0 b_1 \dots b_{n-1}$

- Recall LCS

- If $a_i = b_j$,

$$LCS(i, j) = 1 + LCS(i+1, j+1)$$

- If $a_i \neq b_j$,

$$LCS(i, j) = \max[LCS(i, j+1), \\ LCS(i+1, j)]$$

Inductive structure for edit distance

- $u = a_0 a_1 \dots a_{m-1}$

- $v = b_0 b_1 \dots b_{n-1}$

- Recall LCS

- If $a_i = b_j$,

$$LCS(i, j) = 1 + LCS(i+1, j+1)$$

- If $a_i \neq b_j$,

$$LCS(i, j) = \max[LCS(i, j+1), \\ LCS(i+1, j)]$$

- Edit distance — aim is to transform u to v

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$

- $v = b_0b_1 \dots b_{n-1}$

- Recall LCS

- If $a_i = b_j$,

$$LCS(i,j) = 1 + LCS(i+1,j+1)$$

- If $a_i \neq b_j$,

$$LCS(i,j) = \max[LCS(i,j+1), \\ LCS(i+1,j)]$$

- Edit distance — aim is to transform u to v

- If $a_i = b_j$, nothing to be done

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$

- $v = b_0b_1 \dots b_{n-1}$

- Recall LCS

- If $a_i = b_j$,

$$LCS(i,j) = 1 + LCS(i+1,j+1)$$

- If $a_i \neq b_j$,

$$LCS(i,j) = \max[LCS(i,j+1), \\ LCS(i+1,j)]$$

- Edit distance — aim is to transform u to v

- If $a_i = b_j$, nothing to be done

- If $a_i \neq b_j$, best among

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$

- $v = b_0b_1 \dots b_{n-1}$

- Recall LCS

- If $a_i = b_j$,

$$LCS(i, j) = 1 + LCS(i+1, j+1)$$

- If $a_i \neq b_j$,

$$LCS(i, j) = \max[LCS(i, j+1), \\ LCS(i+1, j)]$$

- Edit distance — aim is to transform u to v

- If $a_i = b_j$, nothing to be done

- If $a_i \neq b_j$, best among

- Substitute a_i by b_j

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$

- $v = b_0b_1 \dots b_{n-1}$

- Recall LCS

- If $a_i = b_j$,

$$LCS(i, j) = 1 + LCS(i+1, j+1)$$

- If $a_i \neq b_j$,

$$LCS(i, j) = \max[LCS(i, j+1), \\ LCS(i+1, j)]$$

- Edit distance — aim is to transform u to v

- If $a_i = b_j$, nothing to be done

- If $a_i \neq b_j$, best among

- Substitute a_i by b_j

- Delete a_i

Inductive structure for edit distance

- $u = a_0 a_1 \dots a_{m-1}$

- $v = b_0 b_1 \dots b_{n-1}$

- Recall LCS

- If $a_i = b_j$,

$$LCS(i, j) = 1 + LCS(i+1, j+1)$$

- If $a_i \neq b_j$,

$$LCS(i, j) = \max[LCS(i, j+1), \\ LCS(i+1, j)]$$

- Edit distance — aim is to transform u to v

- If $a_i = b_j$, nothing to be done

- If $a_i \neq b_j$, best among

- Substitute a_i by b_j

- Delete a_i

- Insert b_j before a_i

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$
- $v = b_0b_1 \dots b_{n-1}$
- Edit distance — transform u to v
- If $a_i = b_j$, nothing to be done
- If $a_i \neq b_j$, best among
 - Substitute a_i by b_j
 - Delete a_i
 - Insert b_j before a_i

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$
- $v = b_0b_1 \dots b_{n-1}$
- Edit distance — transform u to v
- If $a_i = b_j$, nothing to be done
- If $a_i \neq b_j$, best among
 - Substitute a_i by b_j
 - Delete a_i
 - Insert b_j before a_i
- $ED(i, j)$ — edit distance for $a_ia_{i+1} \dots a_{m-1}$, $b_jb_{j+1} \dots b_{n-1}$

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$
- $v = b_0b_1 \dots b_{n-1}$
- Edit distance — transform u to v
- If $a_i = b_j$, nothing to be done
- If $a_i \neq b_j$, best among
 - Substitute a_i by b_j
 - Delete a_i
 - Insert b_j before a_i
- $ED(i, j)$ — edit distance for $a_ia_{i+1} \dots a_{m-1}$, $b_jb_{j+1} \dots b_{n-1}$
- If $a_i = b_j$,
 $ED(i, j) = ED(i+1, j+1)$

Inductive structure for edit distance

- $u = a_0 a_1 \dots a_{m-1}$
- $v = b_0 b_1 \dots b_{n-1}$
- Edit distance — transform u to v
- If $a_i = b_j$, nothing to be done
- If $a_i \neq b_j$, best among
 - Substitute a_i by b_j
 - Delete a_i
 - Insert b_j before a_i
- $ED(i, j)$ — edit distance for $a_i a_{i+1} \dots a_{m-1}, b_j b_{j+1} \dots b_{n-1}$
- If $a_i = b_j$,
$$ED(i, j) = ED(i+1, j+1)$$
- If $a_i \neq b_j$,
$$ED(i, j) = 1 + \min[ED(i+1, j+1), ED(i+1, j), ED(i, j+1)]$$

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$
- $v = b_0b_1 \dots b_{n-1}$
- Edit distance — transform u to v
- If $a_i = b_j$, nothing to be done
- If $a_i \neq b_j$, best among
 - Substitute a_i by b_j
 - Delete a_i
 - Insert b_j before a_i
- $ED(i, j)$ — edit distance for $a_ia_{i+1} \dots a_{m-1}, b_jb_{j+1} \dots b_{n-1}$
- If $a_i = b_j$,
 $ED(i, j) = ED(i+1, j+1)$
- If $a_i \neq b_j$,
 $ED(i, j) = 1 + \min[ED(i+1, j+1), ED(i+1, j), ED(i, j+1)]$
- Base cases
 - $ED(m, n) = 0$

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$
- $v = b_0b_1 \dots b_{n-1}$
- Edit distance — transform u to v
- If $a_i = b_j$, nothing to be done
- If $a_i \neq b_j$, best among
 - Substitute a_i by b_j
 - Delete a_i
 - Insert b_j before a_i
- $ED(i, j)$ — edit distance for $a_ia_{i+1} \dots a_{m-1}$, $b_jb_{j+1} \dots b_{n-1}$
- If $a_i = b_j$,
$$ED(i, j) = ED(i+1, j+1)$$
- If $a_i \neq b_j$,
$$ED(i, j) = 1 + \min[ED(i+1, j+1), ED(i+1, j), ED(i, j+1)]$$
- Base cases
 - $ED(m, n) = 0$
 - $ED(i, n) = m - i$ for all $0 \leq i \leq m$
Delete $a_ia_{i+1} \dots a_{m-1}$ from u

Inductive structure for edit distance

- $u = a_0a_1 \dots a_{m-1}$
- $v = b_0b_1 \dots b_{n-1}$
- Edit distance — transform u to v
- If $a_i = b_j$, nothing to be done
- If $a_i \neq b_j$, best among
 - Substitute a_i by b_j
 - Delete a_i
 - Insert b_j before a_i
- $ED(i, j)$ — edit distance for $a_ia_{i+1} \dots a_{m-1}$, $b_jb_{j+1} \dots b_{n-1}$
- If $a_i = b_j$,
$$ED(i, j) = ED(i+1, j+1)$$
- If $a_i \neq b_j$,
$$ED(i, j) = 1 + \min[ED(i+1, j+1), ED(i+1, j), ED(i, j+1)]$$
- Base cases
 - $ED(m, n) = 0$
 - $ED(i, n) = m - i$ for all $0 \leq i \leq m$
Delete $a_ia_{i+1} \dots a_{m-1}$ from u
 - $ED(m, j) = n - j$ for all $0 \leq j \leq n$
Insert $b_jb_{j+1} \dots b_{n-1}$ into u

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b							
1	i							
2	s							
3	e							
4	c							
5	t							
6	•							

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b							
1	i							
2	s							
3	e							
4	c							
5	t							
6	•							

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b							6
1	i							5
2	s							4
3	e							3
4	c							2
5	t							1
6	•							0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b						5	6
1	i						4	5
2	s						3	4
3	e						2	3
4	c						1	2
5	t						0	1
6	•						1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b					4	5	6
1	i					3	4	5
2	s					2	3	4
3	e					1	2	3
4	c					1	1	2
5	t					1	0	1
6	•					2	1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b				4	4	5	6
1	i				3	3	4	5
2	s				2	2	3	4
3	e				2	1	2	3
4	c				2	1	1	2
5	t				2	1	0	1
6	•				3	2	1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b			4	4	4	5	6
1	i			3	3	3	4	5
2	s			3	2	2	3	4
3	e			3	2	1	2	3
4	c			2	2	1	1	2
5	t			3	2	1	0	1
6	•			4	3	2	1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b		4	4	4	4	5	6
1	i		4	3	3	3	4	5
2	s		3	3	2	2	3	4
3	e		2	3	2	1	2	3
4	c		3	2	2	1	1	2
5	t		4	3	2	1	0	1
6	•		5	4	3	2	1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b	4	4	4	4	4	5	6
1	i	3	4	3	3	3	4	5
2	s	2	3	3	2	2	3	4
3	e	3	2	3	2	1	2	3
4	c	4	3	2	2	1	1	2
5	t	5	4	3	2	1	0	1
6	•	6	5	4	3	2	1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

Reading off the solution

- Transform **bisect** to **secret**

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b	4	4	4	4	4	5	6
1	i	3	4	3	3	3	4	5
2	s	2	3	3	2	2	3	4
3	e	3	2	3	2	1	2	3
4	c	4	3	2	2	1	1	2
5	t	5	4	3	2	1	0	1
6	•	6	5	4	3	2	1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

Reading off the solution

- Transform `bisect` to `secret`
- Delete `b`

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b	4	4	4	4	4	5	6
1	i	3	4	3	3	3	4	5
2	s	2	3	3	2	2	3	4
3	e	3	2	3	2	1	2	3
4	c	4	3	2	2	1	1	2
5	t	5	4	3	2	1	0	1
6	•	6	5	4	3	2	1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

Reading off the solution

- Transform **bisect** to **secret**
- Delete **b**, Delete **i**

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b	4	4	4	4	4	5	6
1	i	3	4	3	3	3	4	5
2	s	2	3	3	2	2	3	4
3	e	3	2	3	2	1	2	3
4	c	4	3	2	2	1	1	2
5	t	5	4	3	2	1	0	1
6	•	6	5	4	3	2	1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

Reading off the solution

- Transform **bisect** to **secret**
- Delete **b**, Delete **i**, Insert **r**

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b	4	4	4	4	4	5	6
1	i	3	4	3	3	3	4	5
2	s	2	3	3	2	2	3	4
3	e	3	2	3	2	1	2	3
4	c	4	3	2	2	1	1	2
5	t	5	4	3	2	1	0	1
6	•	6	5	4	3	2	1	0

Subproblem dependency

- Subproblems are $ED(i, j)$, for $0 \leq i \leq m, 0 \leq j \leq n$
- Table of $(m + 1) \cdot (n + 1)$ values
- Like LCS, $ED(i, j)$ depends on $ED(i+1, j+1)$, $ED(i, j+1)$, $ED(i+1, j)$
- No dependency for $ED(m, n)$ — start at bottom right and fill by row, column or diagonal

Reading off the solution

- Transform **bisect** to **secret**
- Delete **b** , Delete **i** , Insert **r** , Insert **e**

		0	1	2	3	4	5	6
		s	e	c	r	e	t	•
0	b	4	4	4	4	4	5	6
1	i	3	4	3	3	3	4	5
2	s	2	3	3	2	2	3	4
3	e	3	2	3	2	1	2	3
4	c	4	3	2	2	1	1	2
5	t	5	4	3	2	1	0	1
6	•	6	5	4	3	2	1	0

Implementation

```
def ED(u,v):
    import numpy as np
    (m,n) = (len(u),len(v))
    ed = np.zeros((m+1,n+1))

    for i in range(m-1,-1,-1):
        ed[i,n] = m-i
    for j in range(n-1,-1,-1):
        ed[m,j] = n-j

    for j in range(n-1,-1,-1):
        for i in range(m-1,-1,-1):
            if u[i] == v[j]:
                ed[i,j] = ed[i+1,j+1]
            else:
                ed[i,j] = 1 + min(ed[i+1,j+1],
                                   ed[i,j+1],
                                   ed[i+1,j])

    return(ed[0,0])
```

Implementation

```
def ED(u,v):
    import numpy as np
    (m,n) = (len(u),len(v))
    ed = np.zeros((m+1,n+1))

    for i in range(m-1,-1,-1):
        ed[i,n] = m-i
    for j in range(n-1,-1,-1):
        ed[m,j] = n-j

    for j in range(n-1,-1,-1):
        for i in range(m-1,-1,-1):
            if u[i] == v[j]:
                ed[i,j] = ed[i+1,j+1]
            else:
                ed[i,j] = 1 + min(ed[i+1,j+1],
                                   ed[i,j+1],
                                   ed[i+1,j])

    return(ed[0,0])
```

Complexity

Implementation

```
def ED(u,v):
    import numpy as np
    (m,n) = (len(u),len(v))
    ed = np.zeros((m+1,n+1))

    for i in range(m-1,-1,-1):
        ed[i,n] = m-i
    for j in range(n-1,-1,-1):
        ed[m,j] = n-j

    for j in range(n-1,-1,-1):
        for i in range(m-1,-1,-1):
            if u[i] == v[j]:
                ed[i,j] = ed[i+1,j+1]
            else:
                ed[i,j] = 1 + min(ed[i+1,j+1],
                                   ed[i,j+1],
                                   ed[i+1,j])

    return(ed[0,0])
```

Complexity

- Again $O(mn)$, using dynamic programming or memoization

Implementation

```
def ED(u,v):
    import numpy as np
    (m,n) = (len(u),len(v))
    ed = np.zeros((m+1,n+1))

    for i in range(m-1,-1,-1):
        ed[i,n] = m-i
    for j in range(n-1,-1,-1):
        ed[m,j] = n-j

    for j in range(n-1,-1,-1):
        for i in range(m-1,-1,-1):
            if u[i] == v[j]:
                ed[i,j] = ed[i+1,j+1]
            else:
                ed[i,j] = 1 + min(ed[i+1,j+1],
                                   ed[i,j+1],
                                   ed[i+1,j])

    return(ed[0,0])
```

Complexity

- Again $O(mn)$, using dynamic programming or memoization
 - Fill a table of size $O(mn)$
 - Each table entry takes constant time to compute