# Lists and Arrays in Python

Madhavan Mukund

https://www.cmi.ac.in/~madhavan

Programming, Data Structures and Algorithms using Python
Week 3

# Lists and arrays in Python

- Sequences can be stored as lists or arrays
- Lists are flexible but accessing an element is O(n)
- Arrays support random access but are difficult to expand, contract
- Algorithm analysis needs to take into account the underlying implementation
- How does it work in Python?
  - Is the built-in list type in Python really a "linked" list?
  - Numpy library provides arrays are these faster than lists?

■ Python lists are not implemented as flexible linked lists

- Python lists are not implemented as flexible linked lists
- Underlying interpretation maps the list to an array
  - Assign a fixed block when you create a list
  - Double the size if the list overflows the array

- Python lists are not implemented as flexible linked lists
- Underlying interpretation maps the list to an array
  - Assign a fixed block when you create a list
  - Double the size if the list overflows the array
- Keep track of the last position of the list in the array
  - l.append() and l.pop() are constant time, amortised O(1)
  - Insertion/deletion require time O(n)

PDSA using Python Week 3

- Python lists are not implemented as flexible linked lists
- Underlying interpretation maps the list to an array
  - Assign a fixed block when you create a list
  - Double the size if the list overflows the array
- Keep track of the last position of the list in the array
  - l.append() and l.pop() are constant time, amortised O(1)
  - Insertion/deletion require time O(n)
- Effectively, Python lists behave more like arrays than lists

- Arrays are useful for representing matrices

■ In list notation, these are nested lists 
$$\begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$$
 [[0,1], [1,0]]

- Arrays are useful for representing matrices
- In list notation, these are nested lists  $\begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$  [[0,1], [1,0]]
- Need to be careful when initializing a multidimensional list

```
zerolist = [0,0,0]
zeromatrix = [zerolist,zerolist,zerolist]
```

- Arrays are useful for representing matrices
- In list notation, these are nested lists  $\begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$  [[0,1], [1,0]]
- Need to be careful when initializing a multidimensional list

```
zerolist = [0.0.0]
zeromatrix = [zerolist.zerolist.zerolist]
zeromatrix[1][1] = 1
print(zeromatrix)
```

PDSA using Python Week 3

- Arrays are useful for representing matrices
- In list notation, these are nested lists  $\begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$  [[0,1], [1,0]]
- Need to be careful when initializing a multidimensional list

```
zerolist = [0,0,0]
zeromatrix = [zerolist,zerolist,zerolist]
zeromatrix[1][1] = 1
print(zeromatrix)
[[0, 1, 0], [0, 1, 0], [0, 1, 0]]
```

Mutability aliases different values

4/6

- Arrays are useful for representing matrices
- In list notation, these are nested lists  $\begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$  [[0,1], [1,0]]
- Need to be careful when initializing a multidimensional list

```
zerolist = [0,0,0]
zeromatrix = [zerolist,zerolist,zerolist]
zeromatrix[1][1] = 1
print(zeromatrix)
[[0, 1, 0], [0, 1, 0], [0, 1, 0]]
```

- Mutability aliases different values
- Instead, use list comprehension

■ The Numpy library provides arrays as a basic type

```
import numpy as np
zeromatrix = np.zeros(shape=(3,3))
```

■ The Numpy library provides arrays as a basic type

```
import numpy as np
zeromatrix = np.zeros(shape=(3,3))
```

Can create an array from any sequence type

```
identitymatrix = np.array([[1,0],[0,1]])
```

■ The Numpy library provides arrays as a basic type

```
import numpy as np
zeromatrix = np.zeros(shape=(3,3))
```

Can create an array from any sequence type

```
identitymatrix = np.array([[1,0],[0,1]])
```

arange is the equivalent of range for lists

```
row2 = np.arange(5)
```

■ The Numpy library provides arrays as a basic type

```
import numpy as np
zeromatrix = np.zeros(shape=(3,3))
```

Can create an array from any sequence type

```
identitymatrix = np.array([[1,0],[0,1]])
```

arange is the equivalent of range for lists

```
row2 = np.arange(5)
```

- Can operate on a matrix as a whole
  - C = 3\*A + B
  - $\blacksquare$  C = np.matmul(A,B)
  - Very useful for data science

## Summary

- Python lists are not implemented as flexible linked structures
- Instead, allocate an array, and double space as needed
- Append is cheap, insert is expensive
- Arrays can be represented as multidimensional lists, but need to be careful about mutability, aliasing
- Numpy arrays are easier to use