

# Python Recap – I

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 1

# Computing gcd

- $\text{gcd}(m, n)$  — greatest common divisor
  - Largest  $k$  that divides both  $m$  and  $n$
  - $\text{gcd}(8, 12) = 4$
  - $\text{gcd}(18, 25) = 1$
  - Also **hcf** — highest common factor

# Computing gcd

- $\text{gcd}(m, n)$  — greatest common divisor
  - Largest  $k$  that divides both  $m$  and  $n$
  - $\text{gcd}(8, 12) = 4$
  - $\text{gcd}(18, 25) = 1$
  - Also  $\text{hcf}$  — highest common factor
- $\text{gcd}(m, n)$  always exists
  - 1 divides both  $m$  and  $n$

# Computing gcd

- $\text{gcd}(m, n)$  — greatest common divisor
  - Largest  $k$  that divides both  $m$  and  $n$
  - $\text{gcd}(8, 12) = 4$
  - $\text{gcd}(18, 25) = 1$
  - Also **hcf** — highest common factor
- $\text{gcd}(m, n)$  always exists
  - 1 divides both  $m$  and  $n$
- Computing  $\text{gcd}(m, n)$ 
  - $\text{gcd}(m, n) \leq \min(m, n)$
  - Compute list of common factors from 1 to  $\min(m, n)$
  - Return the last such common factor

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```

# Computing gcd

## Points to note

- Need to initialize `cf` for `cf.append()` to work
  - Variables (names) derive their type from the value they hold

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```

# Computing gcd

## Points to note

- Need to initialize `cf` for `cf.append()` to work
  - Variables (names) derive their type from the value they hold
- Control flow
  - Conditionals (`if`)
  - Loops (`for`)

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```

# Computing gcd

## Points to note

- Need to initialize `cf` for `cf.append()` to work
  - Variables (names) derive their type from the value they hold
- Control flow
  - Conditionals (`if`)
  - Loops (`for`)
- `range(i,j)` runs from `i` to `j-1`

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```

# Computing gcd

## Points to note

- Need to initialize `cf` for `cf.append()` to work
  - Variables (names) derive their type from the value they hold
- Control flow
  - Conditionals (`if`)
  - Loops (`for`)
- `range(i,j)` runs from `i` to `j-1`
- List indices run from `0` to `len(l) - 1` and backwards from `-1` to `-len(l)`

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```



# Computing gcd

## Eliminate the list

- Only the last value of `cf` is important

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```

# Computing gcd

## Eliminate the list

- Only the last value of `cf` is important
- Keep track of most recent common factor (`mrcf`)

```
def gcd(m,n):  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            mrcf = i  
    return(mrcf)
```

# Computing gcd

## Eliminate the list

- Only the last value of `cf` is important
- Keep track of most recent common factor (`mrcf`)
- Recall that `1` is always a common factor
  - No need to initialize `mrcf`

```
def gcd(m,n):  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            mrcf = i  
    return(mrcf)
```

# Computing gcd

## Eliminate the list

- Only the last value of `cf` is important
- Keep track of most recent common factor (`mrcf`)
- Recall that 1 is always a common factor
  - No need to initialize `mrcf`

## Efficiency

- Both versions of `gcd` take time proportional to  $\min(m, n)$

```
def gcd(m,n):  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            mrcf = i  
    return(mrcf)
```

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```

# Computing gcd

## Eliminate the list

- Only the last value of `cf` is important
- Keep track of most recent common factor (`mrcf`)
- Recall that 1 is always a common factor
  - No need to initialize `mrcf`

## Efficiency

- Both versions of `gcd` take time proportional to  $\min(m, n)$
- Can we do better?

```
def gcd(m,n):  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            mrcf = i  
    return(mrcf)
```

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```