

Analysis of Quicksort

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python
Week 3

Quicksort

- Choose a pivot element
- Partition L into lower and upper segments with respect to the pivot
- Move the pivot between the lower and upper segments
- Recursively sort the two partitions

```
def quicksort(L,l,r):  # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot:  # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Analysis

- Partitioning with respect to the pivot takes time $O(n)$

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Analysis

- Partitioning with respect to the pivot takes time $O(n)$
- If the pivot is the median
 - $T(n) = 2T(n/2) + n$
 - $T(n)$ is $O(n \log n)$

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Analysis

- Partitioning with respect to the pivot takes time $O(n)$
- If the pivot is the median
 - $T(n) = 2T(n/2) + n$
 - $T(n)$ is $O(n \log n)$
- Worst case? Pivot is maximum or minimum
 - Partitions are of size 0, $n - 1$
 - $T(n) = T(n - 1) + n$
 - $T(n) = n + (n - 1) + \dots + 1$
 - $T(n)$ is $O(n^2)$

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Analysis

- Partitioning with respect to the pivot takes time $O(n)$
- If the pivot is the median
 - $T(n) = 2T(n/2) + n$
 - $T(n)$ is $O(n \log n)$
- Worst case? Pivot is maximum or minimum
 - Partitions are of size 0, $n - 1$
 - $T(n) = T(n - 1) + n$
 - $T(n) = n + (n - 1) + \dots + 1$
 - $T(n)$ is $O(n^2)$
- Already sorted array: worst case!

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Analysis ...

- However, average case is $O(n \log n)$

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Analysis ...

- However, average case is $O(n \log n)$
- Sorting is a rare situation where we can compute this
 - Values don't matter, only relative order is important
 - Analyze behaviour over permutations of $\{1, 2, \dots, n\}$
 - Each input permutation equally likely

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```


Analysis ...

- However, average case is $O(n \log n)$
- Sorting is a rare situation where we can compute this
 - Values don't matter, only relative order is important
 - Analyze behaviour over permutations of $\{1, 2, \dots, n\}$
 - Each input permutation equally likely
- Expected running time is $O(n \log n)$

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Randomization

- Any fixed choice of pivot allows us to construct worst case input

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Randomization

- Any fixed choice of pivot allows us to construct worst case input
- Instead, choose pivot position **randomly** at each step

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Randomization

- Any fixed choice of pivot allows us to construct worst case input
- Instead, choose pivot position **randomly** at each step
- Expected running time is again $O(n \log n)$

```
def quicksort(L,l,r):  # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot:  # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Iterative quicksort

- Recursive calls work on disjoint segments
 - No recombination of results is required

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Iterative quicksort

- Recursive calls work on disjoint segments
 - No recombination of results is required
- Can explicitly keep track of left and right endpoints of each segment to be sorted

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Quicksort in practice

- In practice, quicksort is very fast

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```

Quicksort in practice

- In practice, quicksort is very fast
- Very often the default algorithm used for in-built sort functions
 - Sorting a column in a spreadsheet
 - Library sort function in a programming language

```
def quicksort(L,l,r): # Sort L[l:r]
    if (r - l <= 1):
        return(L)
    (pivot,lower,upper) = (L[l],l+1,l+1)
    for i in range(l+1,r):
        if L[i] > pivot: # Extend upper segment
            upper = upper+1
        else: # Exchange L[i] with start of upper segment
            (L[i], L[lower]) = (L[lower], L[i])
            # Shift both segments
            (lower,upper) = (lower+1,upper+1)
    # Move pivot between lower and upper
    (L[l],L[lower-1]) = (L[lower-1],L[l])
    lower = lower-1
    # Recursive calls
    quicksort(L,l,lower)
    quicksort(L,lower+1,upper)
    return(L)
```


Summary

- The worst case complexity of quicksort is $O(n^2)$

Summary

- The worst case complexity of quicksort is $O(n^2)$
- However, the average case is $O(n \log n)$

Summary

- The worst case complexity of quicksort is $O(n^2)$
- However, the average case is $O(n \log n)$
- Randomly choosing the pivot is a good strategy to beat worst case inputs

Summary

- The worst case complexity of quicksort is $O(n^2)$
- However, the average case is $O(n \log n)$
- Randomly choosing the pivot is a good strategy to beat worst case inputs
- Quicksort works in-place and can be implemented iteratively

Summary

- The worst case complexity of quicksort is $O(n^2)$
- However, the average case is $O(n \log n)$
- Randomly choosing the pivot is a good strategy to beat worst case inputs
- Quicksort works in-place and can be implemented iteratively
- Very fast in practice, and often used for built-in sorting functions
 - Good example of a situation when the worst case upper bound is pessimistic