

Dealing with errors

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming Concepts using Java

Week 7

When things go wrong

- Our code could encounter many types of errors
 - *User input* — enter invalid filenames or URLs
 - *Device errors* — printer jam, network connection drops
 - *Resource limitations* — disk full
 - *Code errors* — invalid array index, key not present in hash table, refer to a variable that is `null`, divide by zero, ...

When things go wrong

- Our code could encounter many types of errors
 - *User input* — enter invalid filenames or URLs
 - *Device errors* — printer jam, network connection drops
 - *Resource limitations* — disk full
 - *Code errors* — invalid array index, key not present in hash table, refer to a variable that is `null`, divide by zero, ...
- Signalling errors
 - Return an invalid value: `-1` at end of file, `null`
 - What if there is no obvious invalid value?

Exception handling

- Code that generates error **raises** or **throws** an **exception**

Exception handling

- Code that generates error **raises** or **throws** an **exception**
- Notify the type of error
 - Information about the nature of the exception
 - Natural to structure an exception as an object

Exception handling

- Code that generates error **raises** or **throws** an **exception**
- Notify the type of error
 - Information about the nature of the exception
 - Natural to structure an exception as an object
- Caller **catches** the exception and takes corrective action
 - Extract information about the error from the exception object
 - Graceful interruption rather than program crash

Exception handling

- Code that generates error **raises** or **throws** an **exception**
- Notify the type of error
 - Information about the nature of the exception
 - Natural to structure an exception as an object
- Caller **catches** the exception and takes corrective action
 - Extract information about the error from the exception object
 - Graceful interruption rather than program crash
- ...or passes the exception back up the calling chain

Exception handling

- Code that generates error **raises** or **throws** an **exception**
- Notify the type of error
 - Information about the nature of the exception
 - Natural to structure an exception as an object
- Caller **catches** the exception and takes corrective action
 - Extract information about the error from the exception object
 - Graceful interruption rather than program crash
- ...or passes the exception back up the calling chain
- Declare if a method can throw an exception
 - Compiler can check whether calling code has made a provision to handle the exception

Java's classification of errors

- All exceptions descend from class `Throwable`
 - Two branches, `Error` and `Exception`

Java's classification of errors

- All exceptions descend from class `Throwable`
 - Two branches, `Error` and `Exception`
- `Error` — relatively rare, “not the programmer’s fault”
 - Internal errors, resource limitations within Java runtime
 - No realistic corrective action possible, notify caller and terminate gracefully

Java's classification of errors

- All exceptions descend from class `Throwable`
 - Two branches, `Error` and `Exception`
- `Error` — relatively rare, “not the programmer’s fault”
 - Internal errors, resource limitations within Java runtime
 - No realistic corrective action possible, notify caller and terminate gracefully
- `Exception` — two sub branches
 - `RuntimeException`, checked exceptions

Java's classification of errors

- All exceptions descend from class `Throwable`
 - Two branches, `Error` and `Exception`
- `Error` — relatively rare, “not the programmer’s fault”
 - Internal errors, resource limitations within Java runtime
 - No realistic corrective action possible, notify caller and terminate gracefully
- `Exception` — two sub branches
 - `RuntimeException`, checked exceptions
- `RuntimeException` — programming errors that should have been caught by code
 - Array index out of bounds, invalid hash key, ...

Java's classification of errors

- All exceptions descend from class `Throwable`
 - Two branches, `Error` and `Exception`
- `Error` — relatively rare, “not the programmer’s fault”
 - Internal errors, resource limitations within Java runtime
 - No realistic corrective action possible, notify caller and terminate gracefully
- `Exception` — two sub branches
 - `RuntimeException`, checked exceptions
- `RuntimeException` — programming errors that should have been caught by code
 - Array index out of bounds, invalid hash key, ...
- Checked exceptions
 - Typically user-defined, code assumptions violated
 - In a list of orders, quantities should be positive integers

Summary

- Exception handling — gracefully recover from errors that occur when running code
- Throw an exception — generate an object encapsulating information about the error
- Catch an exception — decode the nature of the error and take corrective action
- Java organizes exceptions in a hierarchy, by type
 - `Error` — internal errors within JVM, “not the programmer’s fault”
 - `RuntimeException` — coding errors, could have been avoided by runtime checks in code
 - Checked exceptions — user-defined, violations of assumptions made by code
 - To contrast, `Error` and `RuntimeException` are called unchecked exceptions