

# String Matching: Knuth-Morris-Pratt algorithm

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>


Programming, Data Structures and Algorithms using Python

Week 10

# Pattern matching using automata

- Finite state automaton for pattern  $p$

- States  $\{0, 1, \dots, m\}$
- State  $i$  denotes match upto  $p[:i]$
- Transition  $i \xrightarrow{a} j$  describes how to update the match on reading  $a$



- Start scanning text in **initial state 0**

- In state  $i$ , read  $t[j]$ , take the transition labelled  $t[j]$

- If we reach the **final state  $m$** , we have found a full match for  $p$

- Single scan of  $t$  suffices

Processing *abababac*

$0 \xrightarrow{a} 1 \xrightarrow{b} 2 \xrightarrow{a} 3 \xrightarrow{b} 4 \xrightarrow{a} 5 \xrightarrow{b} 4 \xrightarrow{a} 5 \xrightarrow{c} 6$

# Knuth-Morris-Pratt algorithm


- Compute the automaton for  $p$  efficiently

# Knuth-Morris-Pratt algorithm

- Compute the automaton for  $p$  efficiently
- Match  $p$  against itself
  - $match[j] = k$  if suffix of  $p[:j+1]$  matches prefix  $p[:k]$


# Knuth-Morris-Pratt algorithm

- Compute the automaton for  $p$  efficiently
- Match  $p$  against itself
  - $match[j] = k$  if suffix of  $p[:j+1]$  matches prefix  $p[:k]$
- Suppose suffix of  $p[:j+1]$  matches prefix  $p[:k]$



# Knuth-Morris-Pratt algorithm

- Compute the automaton for  $p$  efficiently
- Match  $p$  against itself
  - $match[j] = k$  if suffix of  $p[:j+1]$  matches prefix  $p[:k]$
- Suppose suffix of  $p[:j+1]$  matches prefix  $p[:k]$ 
  - If  $p[j+1] == p[k]$ , extend the match



# Knuth-Morris-Pratt algorithm

- Compute the automaton for  $p$  efficiently
- Match  $p$  against itself
  - $match[j] = k$  if suffix of  $p[:j+1]$  matches prefix  $p[:k]$
- Suppose suffix of  $p[:j+1]$  matches prefix  $p[:k]$ 
  - If  $p[j+1] == p[k]$ , extend the match
  - Otherwise try to find a shorter prefix that can be extended by  $p[j+1]$



# Knuth-Morris-Pratt algorithm


- Compute the automaton for  $p$  efficiently
- Match  $p$  against itself
  - $match[j] = k$  if suffix of  $p[:j+1]$  matches prefix  $p[:k]$
- Suppose suffix of  $p[:j+1]$  matches prefix  $p[:k]$ 
  - If  $p[j+1] == p[k]$ , extend the match
  - Otherwise try to find a shorter prefix that can be extended by  $p[j+1]$





# Knuth-Morris-Pratt algorithm

- Compute the automaton for  $p$  efficiently
- Match  $p$  against itself
  - $match[j] = k$  if suffix of  $p[:j+1]$  matches prefix  $p[:k]$
- Suppose suffix of  $p[:j+1]$  matches prefix  $p[:k]$ 
  - If  $p[j+1] == p[k]$ , extend the match
  - Otherwise try to find a shorter prefix that can be extended by  $p[j+1]$
- Usually refer to  $match$  as failure function  $fail$ 
  - Where to fall back if match fails



# Computing the fail function

- Initialize `fail[j] = 0` for all `j`

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:            #no match found at j  
            j = j+1  
    return(fail)
```

# Computing the fail function

- Initialize `fail[j] = 0` for all `j`
- `k` keeps track of length of current match
- `j` is next position to update `fail`

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:            #no match found at j  
            j = j+1  
    return(fail)
```

# Computing the fail function

- Initialize `fail[j] = 0` for all `j`
- `k` keeps track of length of current match
- `j` is next position to update `fail`
- If `p[j] == p[k]` extend the match, set `fail[j] = k+1`

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:            #no match found at j  
            j = j+1  
    return(fail)
```

# Computing the fail function

- Initialize `fail[j] = 0` for all `j`
- `k` keeps track of length of current match
- `j` is next position to update `fail`
- If `p[j] == p[k]` extend the match, set `fail[j] = k+1`
- If `p[j] != p[k]` find a shorter prefix that matches suffix of `p[:j]`
  - Step back to `fail[k-1]`

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:            #no match found at j  
            j = j+1  
    return(fail)
```

# Computing the fail function

- Initialize `fail[j] = 0` for all `j`
- `k` keeps track of length of current match
- `j` is next position to update `fail`
- If `p[j] == p[k]` extend the match, set `fail[j] = k+1`
- If `p[j] != p[k]` find a shorter prefix that matches suffix of `p[:j]`
  - Step back to `fail[k-1]`
- If we don't find a nontrivial prefix to extend, retain `fail[j] = 0`, move to next position

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:            #no match found at j  
            j = j+1  
    return(fail)
```

# Analysis of fail computation

- Want to show this takes time  $O(m)$

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:           #no match found at j  
            j = j+1  
    return(fail)
```

# Analysis of fail computation

- Want to show this takes time  $O(m)$
- $j$  incremented  $m-1$  times in `while`

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:            #no match found at j  
            j = j+1  
    return(fail)
```



# Analysis of fail computation

- Want to show this takes time  $O(m)$
- $j$  incremented  $m-1$  times in `while`
- But we also have iterations where  $k$  decreases and  $j$  is unchanged

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:            #no match found at j  
            j = j+1  
    return(fail)
```

# Analysis of fail computation

- Want to show this takes time  $O(m)$
- $j$  incremented  $m-1$  times in `while`
- But we also have iterations where  $k$  decreases and  $j$  is unchanged
- Total number of decreases to  $k$  cannot exceed total number of increments to  $k$

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:           #no match found at j  
            j = j+1  
    return(fail)
```

# Analysis of fail computation

- Want to show this takes time  $O(m)$
- $j$  incremented  $m-1$  times in `while`
- But we also have iterations where  $k$  decreases and  $j$  is unchanged
- Total number of decreases to  $k$  cannot exceed total number of increments to  $k$
- Overall  $k$  is incremented at most  $m-1$  times

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:            #no match found at j  
            j = j+1  
    return(fail)
```

# Analysis of fail computation

- Want to show this takes time  $O(m)$
- $j$  incremented  $m-1$  times in `while`
- But we also have iterations where  $k$  decreases and  $j$  is unchanged
- Total number of decreases to  $k$  cannot exceed total number of increments to  $k$
- Overall  $k$  is incremented at most  $m-1$  times
- Hence overall complexity is  $O(m)$

```
def kmp_fail(p):  
  
    # Initialize  
    m = len(p)  
    fail = [0 for i in range(m)]  
  
    # Update  
    j, k = 1, 0  
    while j < m:  
        if p[j] == p[k]: #k+1 chars match  
            fail[j] = k+1  
            j, k = j+1, k+1  
        elif k > 0:      #find shorter prefix  
            k = fail[k-1]  
        else:            #no match found at j  
            j = j+1  
    return(fail)
```

# Implementing string search using fail function

- Scan `t` from beginning

```
def find_kmp(t, p):  
    n,m = len(t),len(p)  
    if m == 0:  
        return 0 # pattern is empty  
    fail = kmp_fail(p) # preprocessing  
    j = 0 # index into text  
    k = 0 # index into pattern  
    while j < n:  
        if t[j] == p[k]: # matched p[0:k+1]  
            if k == m - 1: # match is complete  
                return(j - m + 1)  
            j,k = j+1,k+1 # extend match  
        elif k > 0:  
            k = fail[k-1] # use smaller prefix  
        else:  
            j = j+1  
    return(-1) # reached end without match
```

# Implementing string search using fail function

- Scan  $t$  from beginning
- $j$  is next position in  $t$
- $k$  is currently matched position in  $p$

```
def find_kmp(t, p):  
    n,m = len(t),len(p)  
    if m == 0:  
        return 0 # pattern is empty  
    fail = kmp_fail(p) # preprocessing  
    j = 0 # index into text  
    k = 0 # index into pattern  
    while j < n:  
        if t[j] == p[k]: # matched p[0:k+1]  
            if k == m - 1: # match is complete  
                return(j - m + 1)  
            j,k = j+1,k+1 # extend match  
        elif k > 0:  
            k = fail[k-1] # use smaller prefix  
        else:  
            j = j+1  
    return(-1) # reached end without match
```

# Implementing string search using fail function

- Scan  $t$  from beginning
- $j$  is next position in  $t$
- $k$  is currently matched position in  $p$
- If  $t[j] == p[k]$  extend the match

```
def find_kmp(t, p):  
    n,m = len(t),len(p)  
    if m == 0:  
        return 0 # pattern is empty  
    fail = kmp_fail(p) # preprocessing  
    j = 0 # index into text  
    k = 0 # index into pattern  
    while j < n:  
        if t[j] == p[k]: # matched p[0:k+1]  
            if k == m - 1: # match is complete  
                return(j - m + 1)  
            j,k = j+1,k+1 # extend match  
        elif k > 0:  
            k = fail[k-1] # use smaller prefix  
        else:  
            j = j+1  
    return(-1) # reached end without match
```

# Implementing string search using fail function

- Scan  $t$  from beginning
- $j$  is next position in  $t$
- $k$  is currently matched position in  $p$
- If  $t[j] == p[k]$  extend the match
- If  $t[j] != p[k]$ , update match prefix

```
def find_kmp(t, p):  
    n,m = len(t),len(p)  
    if m == 0:  
        return 0 # pattern is empty  
    fail = kmp_fail(p) # preprocessing  
    j = 0 # index into text  
    k = 0 # index into pattern  
    while j < n:  
        if t[j] == p[k]: # matched p[0:k+1]  
            if k == m - 1: # match is complete  
                return(j - m + 1)  
            j,k = j+1,k+1 # extend match  
        elif k > 0:  
            k = fail[k-1] # use smaller prefix  
        else:  
            j = j+1  
    return(-1) # reached end without match
```



# Implementing string search using fail function

- Scan  $t$  from beginning
- $j$  is next position in  $t$
- $k$  is currently matched position in  $p$
- If  $t[j] == p[k]$  extend the match
- If  $t[j] != p[k]$ , update match prefix
- If we reach the end of the `while` loop, no match

```
def find_kmp(t, p):  
    n,m = len(t),len(p)  
    if m == 0:  
        return 0 # pattern is empty  
    fail = kmp_fail(p) # preprocessing  
    j = 0 # index into text  
    k = 0 # index into pattern  
    while j < n:  
        if t[j] == p[k]: # matched p[0:k+1]  
            if k == m - 1: # match is complete  
                return(j - m + 1)  
            j,k = j+1,k+1 # extend match  
        elif k > 0:  
            k = fail[k-1] # use smaller prefix  
        else:  
            j = j+1  
    return(-1) # reached end without match
```

# Implementing string search using fail function

- Scan  $t$  from beginning
- $j$  is next position in  $t$
- $k$  is currently matched position in  $p$
- If  $t[j] == p[k]$  extend the match
- If  $t[j] != p[k]$ , update match prefix
- If we reach the end of the `while` loop, no match
- Complexity is  $O(n)$

```
def find_kmp(t, p):  
    n,m = len(t),len(p)  
    if m == 0:  
        return 0 # pattern is empty  
    fail = kmp_fail(p) # preprocessing  
    j = 0 # index into text  
    k = 0 # index into pattern  
    while j < n:  
        if t[j] == p[k]: # matched p[0:k+1]  
            if k == m - 1: # match is complete  
                return(j - m + 1)  
            j,k = j+1,k+1 # extend match  
        elif k > 0:  
            k = fail[k-1] # use smaller prefix  
        else:  
            j = j+1  
    return(-1) # reached end without match
```

# Implementing string search using fail function

- Scan  $t$  from beginning
- $j$  is next position in  $t$
- $k$  is currently matched position in  $p$
- If  $t[j] == p[k]$  extend the match
- If  $t[j] != p[k]$ , update match prefix
- If we reach the end of the `while` loop, no match
- Complexity is  $O(n)$
- This finds first match, modify to find all matches

```
def find_kmp(t, p):  
    n,m = len(t),len(p)  
    if m == 0:  
        return 0 # pattern is empty  
    fail = kmp_fail(p) # preprocessing  
    j = 0 # index into text  
    k = 0 # index into pattern  
    while j < n:  
        if t[j] == p[k]: # matched p[0:k+1]  
            if k == m - 1: # match is complete  
                return(j - m + 1)  
            j,k = j+1,k+1 # extend match  
        elif k > 0:  
            k = fail[k-1] # use smaller prefix  
        else:  
            j = j+1  
    return(-1) # reached end without match
```

# Summary

- The Knuth, Morris, Pratt algorithm efficiently computes the automaton describing prefix matches in the pattern  $p$
- Complexity of preprocessing the `fail` function is  $O(m)$
- After preprocessing, can check matches in the text  $t$  in  $O(n)$
- Overall, KMP algorithm works in time  $O(m + n)$
- However, the Boyer-Moore algorithm can be faster in practice, skipping many positions