

Assertions

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming Concepts using Java

Week 7

Documenting and checking assumptions

- Functions may have constraints on the parameters

```
public static double myfn(double x){  
    // Assume x >= 0  
    ...  
}
```

Documenting and checking assumptions

- Functions may have constraints on the parameters
- We could check the condition and throw an exception

```
public static double myfn(double x)
    throws IllegalArgumentException {
    // Assume x >= 0
    if (x < 0){
        throw new
            IllegalArgumentException("x < 0");
    }
}
```

Documenting and checking assumptions

- Functions may have constraints on the parameters
- We could check the condition and throw an exception
- What if `myfn` is only used internally by our own code
 - Flag errors during development, debugging
 - But diagnostic code should not trigger at run time
 - Performance, and other considerations

```
public static double myfn(double x)
    throws IllegalArgumentException {
    // Assume x >= 0
    if (x < 0){
        throw new
            IllegalArgumentException("x < 0");
    }
}
```

Documenting and checking assumptions

- Functions may have constraints on the parameters
- We could check the condition and throw an exception
- What if `myfn` is only used internally by our own code
 - Flag errors during development, debugging
 - But diagnostic code should not trigger at run time
 - Performance, and other considerations
- Instead, “assert” the property you assume to hold

```
public static double myfn(double x){  
    assert x >= 0;  
}
```

Assertions

- If assertion fails, code throws `AssertionError`

```
public static double myfn(double x){  
    assert x >= 0;  
}
```

Assertions

- If assertion fails, code throws `AssertionError`
- This should **not** be caught
 - Abort and print diagnostic information (stack trace)

```
public static double myfn(double x){  
    assert x >= 0;  
}
```

Assertions

- If assertion fails, code throws `AssertionError`
- This should **not** be caught
 - Abort and print diagnostic information (stack trace)
- Can provide additional information to be printed with diagnostic message

```
public static double myfn(double x){  
    assert x >= 0 : x;  
}
```


Enabling and disabling assertions

- Assertions are enabled or disabled at runtime
 - Does **not** require recompilation

Enabling and disabling assertions

- Assertions are enabled or disabled at runtime
 - Does **not** require recompilation
- Use the following flag to run with assertions enabled

```
java -enableassertions MyCode
```

Enabling and disabling assertions

- Assertions are enabled or disabled at runtime
 - Does **not** require recompilation
- Use the following flag to run with assertions enabled

```
java -enableassertions MyCode
```

- Can use `-ea` as abbreviation for `-enableassertions`

Enabling and disabling assertions

- Assertions are enabled or disabled at runtime
 - Does **not** require recompilation
- Use the following flag to run with assertions enabled
- Can use `-ea` as abbreviation for `-enableassertions`
- Can selectively turn on assertions for a class

```
java -enableassertions MyCode
```

```
java -ea:Myclass MyCode
```

Enabling and disabling assertions

- Assertions are enabled or disabled at runtime
 - Does **not** require recompilation
- Use the following flag to run with assertions enabled

```
java -enableassertions MyCode
```

- Can use `-ea` as abbreviation for `-enableassertions`
- Can selectively turn on assertions for a class

```
java -ea:Myclass MyCode
```

- ...or a package

```
java -ea:in.ac.iitm.onlinedegree MyCode
```

Enabling and disabling assertions

- Assertions are enabled or disabled at runtime

- Does **not** require recompilation

- Use the following flag to run with assertions enabled

```
java -enableassertions MyCode
```

- Can use `-ea` as abbreviation for `-enableassertions`

- Can selectively turn on assertions for a class

```
java -ea:Myclass MyCode
```

- ...or a package

```
java -ea:in.ac.iitm.onlinedegree MyCode
```

- Similarly, disable assertions globally or selectively

```
java -disableassertions MyCode  
java -da:MyClass MyCode
```

Enabling and disabling assertions

- Assertions are enabled or disabled at runtime

- Does **not** require recompilation

- Use the following flag to run with assertions enabled

```
java -enableassertions MyCode
```

- Can use `-ea` as abbreviation for `-enableassertions`

- Can selectively turn on assertions for a class

```
java -ea:Myclass MyCode
```

- ...or a package

```
java -ea:in.ac.iitm.onlinedegree MyCode
```

- Similarly, disable assertions globally or selectively

```
java -disableassertions MyCode  
java -da:MyClass MyCode
```

- Can combine the two

```
java -ea in.ac.iitm.onlinedegree  
-da:MyClass MyCode
```

Enabling and disabling assertions

- Assertions are enabled or disabled at runtime

- Does **not** require recompilation

- Use the following flag to run with assertions enabled

```
java -enableassertions MyCode
```

- Can use `-ea` as abbreviation for `-enableassertions`

- Can selectively turn on assertions for a class

```
java -ea:Myclass MyCode
```

- ...or a package

```
java -ea:in.ac.iitm.onlinedegree MyCode
```

- Similarly, disable assertions globally or selectively

```
java -disableassertions MyCode  
java -da:MyClass MyCode
```

- Can combine the two

```
java -ea in.ac.iitm.onlinedegree  
-da:MyClass MyCode
```

- Separate switch to enable assertions for system classes

```
java -enablesystemassertions MyCode  
java -esa MyCode
```


Summary

- Assertion checks are supposed to flag fatal, unrecoverable errors
 - Do not `catch` them!
- If you need to flag the error and take corrective action, use exceptions instead
- Turned on `only` during development and testing
 - Not checked at run time after deployment