

# Concrete Collections

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming Concepts using Java

Week 6

# Built-in data types

- The `Collection` interface abstracts properties of grouped data
  - Arrays, lists, sets, ...
  - But **not** key-value structures like dictionaries

# Built-in data types

- The `Collection` interface abstracts properties of grouped data
  - Arrays, lists, sets, ...
  - But `not` key-value structures like dictionaries
- Collections can be further organized based on additional properties
  - Are the elements ordered?
  - Are duplicates allowed?
  - Are there constraints on how elements are added, removed?

# Built-in data types

- The `Collection` interface abstracts properties of grouped data
  - Arrays, lists, sets, ...
  - But **not** key-value structures like dictionaries
- Collections can be further organized based on additional properties
  - Are the elements ordered?
  - Are duplicates allowed?
  - Are there constraints on how elements are added, removed?
- In the spirit of indirection, these are captured by interfaces that extend `Collection`
  - Interface `List` for ordered collections
  - Interface `Set` for collections without duplicates
  - Interface `Queue` for ordered collections with constraints on addition and deletion

# The List interface

- An ordered collection can be accessed in two ways
  - Through an iterator
  - By position — random access

# The List interface

- An ordered collection can be accessed in two ways
  - Through an iterator
  - By position — **random access**
- Additional functions for random access

```
public interface List<E>  
    extends Collection<E>{  
    void add(int index, E element);  
    void remove(int index);  
    E get(int index);  
    E set(int index, E element);  
}
```

# The List interface

- An ordered collection can be accessed in two ways
  - Through an iterator
  - By position — **random access**
- Additional functions for random access
- `ListIterator` extends `Iterator`
  - `void add(E element)` to insert an element before the current index
  - `void previous()` to go to previous element
  - `boolean hasPrevious()` checks that it is legal to go backwards

```
public interface List<E>
    extends Collection<E>{
    void add(int index, E element);
    void remove(int index);
    E get(int index);
    E set(int index, E element);

    ListIterator<E> listIterator();
}
```

# The List interface and random access

- Random access is not equally efficient for all ordered collections
  - In an array, can compute location of element at index *i*
  - In a linked list, must start at the beginning and traverse *i* links

```
public interface List<E>
    extends Collection<E>{
    void add(int index, E element);
    void remove(int index);
    E get(int index);
    E set(int index, E element);

    ListIterator<E> listIterator();
}
```



# The List interface and random access

- Random access is not equally efficient for all ordered collections
  - In an array, can compute location of element at index `i`
  - In a linked list, must start at the beginning and traverse `i` links
- **Tagging** interface `RandomAccess`
  - Tells us whether a `List` supports random access or not
  - Can choose algorithmic strategy based on this

```
public interface List<E>
    extends Collection<E>{
    void add(int index, E element);
    void remove(int index);
    E get(int index);
    E set(int index, E element);

    ListIterator<E> listIterator();
}

if (c instanceof RandomAccess) {
    // use random access algorithm
} else {
    // use sequential access algorithm
}
```

# The AbstractList interface

- Recall that `AbstractCollection` is the “usable” version of `Collection`

# The AbstractList interface

- Recall that `AbstractCollection` is the “usable” version of `Collection`
- Correspondingly, `AbstractList` extends `AbstractCollection`
  - Inherits default implementations

# The `AbstractList` interface

- Recall that `AbstractCollection` is the “usable” version of `Collection`
- Correspondingly, `AbstractList` extends `AbstractCollection`
  - Inherits default implementations
- `AbstractSequentialList` extends `AbstractList`
  - A further subclass to distinguish lists without random access

# The AbstractList interface

- Recall that `AbstractCollection` is the “usable” version of `Collection`
- Correspondingly, `AbstractList` extends `AbstractCollection`
  - Inherits default implementations
- `AbstractSequentialList` extends `AbstractList`
  - A further subclass to distinguish lists without random access
- Concrete generic class `LinkedList<E>` extends `AbstractSequentialList`
  - Internally, the usual flexible linked list
  - Efficient to add and remove elements at arbitrary positions

# The AbstractList interface

- Recall that `AbstractCollection` is the “usable” version of `Collection`
- Correspondingly, `AbstractList` extends `AbstractCollection`
  - Inherits default implementations
- `AbstractSequentialList` extends `AbstractList`
  - A further subclass to distinguish lists without random access
- Concrete generic class `LinkedList<E>` extends `AbstractSequentialList`
  - Internally, the usual flexible linked list
  - Efficient to add and remove elements at arbitrary positions
- Concrete generic class `ArrayList<E>` extends `AbstractList`
  - Flexible size array, supports random access

# Using concrete list classes

- Concrete generic class `LinkedList<E>`  
extends `AbstractSequentialList`
  - Not random access

# Using concrete list classes

- Concrete generic class `LinkedList<E>` extends `AbstractSequentialList`
  - Not random access
  - But random access methods of `AbstractList` are still available



# Using concrete list classes

- Concrete generic class `LinkedList<E>` extends `AbstractSequentialList`
  - Not random access
  - But random access methods of `AbstractList` are still available
  - This loop will execute a fresh scan from start to element `i` in each iteration!

```
LinkedList<String> list = new ...;  
  
for (int i = 0; i < list.size(); i++)  
    // do something with list.get(i);
```

# Using concrete list classes

- Concrete generic class `LinkedList<E>` extends `AbstractSequentialList`
  - Not random access
  - But random access methods of `AbstractList` are still available
  - This loop will execute a fresh scan from start to element `i` in each iteration!

```
LinkedList<String> list = new ...;
```

```
for (int i = 0; i < list.size(); i++)  
    // do something with list.get(i);
```

- Two versions of `add()` available
  - `add()` from `Collection` appends to the end of the list
  - `add()` from `ListIterator` inserts a value before current position of the iterator

# Using concrete list classes

- Concrete generic class `LinkedList<E>` extends `AbstractSequentialList`
  - Not random access
  - But random access methods of `AbstractList` are still available
  - This loop will execute a fresh scan from start to element `i` in each iteration!

```
LinkedList<String> list = new ...;
```

```
for (int i = 0; i < list.size(); i++)  
    // do something with list.get(i);
```

- Two versions of `add()` available
  - `add()` from `Collection` appends to the end of the list
  - `add()` from `ListIterator` inserts a value before current position of the iterator
- In `Collection`, `add()` returns `boolean` — did the add update the collection?
  - `add()` may not update a set, always works for lists

# Using concrete list classes

- Concrete generic class `LinkedList<E>` extends `AbstractSequentialList`
  - Not random access
  - But random access methods of `AbstractList` are still available
  - This loop will execute a fresh scan from start to element `i` in each iteration!

```
LinkedList<String> list = new ...;
```

```
for (int i = 0; i < list.size(); i++)  
    // do something with list.get(i);
```

- Two versions of `add()` available
  - `add()` from `Collection` appends to the end of the list
  - `add()` from `ListIterator` inserts a value before current position of the iterator
- In `Collection`, `add()` returns `boolean` — did the add update the collection?
  - `add()` may not update a set, always works for lists
- `add()` in `ListIterator` returns `void`

# The Set interface

- A set is a collection without duplicates

# The Set interface

- A set is a collection without duplicates
- `Set` interface is identical to `Collection`, but behaviour is more constrained
  - `add()` should have no effect, and return `false`, if the element already exists
  - `equals()` should return `true` if contents match after disregarding order

# The Set interface

- A set is a collection without duplicates
- `Set` interface is identical to `Collection`, but behaviour is more constrained
  - `add()` should have no effect, and return `false`, if the element already exists
  - `equals()` should return `true` if contents match after disregarding order
- Two interfaces, same signature?

# The Set interface

- A set is a collection without duplicates
- `Set` interface is identical to `Collection`, but behaviour is more constrained
  - `add()` should have no effect, and return `false`, if the element already exists
  - `equals()` should return `true` if contents match after disregarding order
- Two interfaces, same signature?
- Use `Set` to constrain values to satisfy additional constraints



# The Set interface

- A set is a collection without duplicates
- `Set` interface is identical to `Collection`, but behaviour is more constrained
  - `add()` should have no effect, and return `false`, if the element already exists
  - `equals()` should return `true` if contents match after disregarding order
- Two interfaces, same signature?
- Use `Set` to constrain values to satisfy additional constraints
- `Set` implementations typically designed to allow efficient membership tests

# The Set interface

- A set is a collection without duplicates
- `Set` interface is identical to `Collection`, but behaviour is more constrained
  - `add()` should have no effect, and return `false`, if the element already exists
  - `equals()` should return `true` if contents match after disregarding order
- Two interfaces, same signature?
- Use `Set` to constrain values to satisfy additional constraints
- `Set` implementations typically designed to allow efficient membership tests
- Ordered collections loop through a sequence to find an element

# The Set interface

- A set is a collection without duplicates
- `Set` interface is identical to `Collection`, but behaviour is more constrained
  - `add()` should have no effect, and return `false`, if the element already exists
  - `equals()` should return `true` if contents match after disregarding order
- Two interfaces, same signature?
- Use `Set` to constrain values to satisfy additional constraints
- `Set` implementations typically designed to allow efficient membership tests
- Ordered collections loop through a sequence to find an element
- Instead, map the value to its position
  - Hash function

# The Set interface

- A set is a collection without duplicates
- `Set` interface is identical to `Collection`, but behaviour is more constrained
  - `add()` should have no effect, and return `false`, if the element already exists
  - `equals()` should return `true` if contents match after disregarding order
- Two interfaces, same signature?
- Use `Set` to constrain values to satisfy additional constraints
- `Set` implementations typically designed to allow efficient membership tests
- Ordered collections loop through a sequence to find an element
- Instead, map the value to its position
  - Hash function
- Or arrange values in a two dimensional structure
  - Balanced search tree

# The Set interface

- A set is a collection without duplicates
- `Set` interface is identical to `Collection`, but behaviour is more constrained
  - `add()` should have no effect, and return `false`, if the element already exists
  - `equals()` should return `true` if contents match after disregarding order
- Two interfaces, same signature?
- Use `Set` to constrain values to satisfy additional constraints
- `Set` implementations typically designed to allow efficient membership tests
- Ordered collections loop through a sequence to find an element
- Instead, map the value to its position
  - Hash function
- Or arrange values in a two dimensional structure
  - Balanced search tree
- As usual, concrete set implementations extend `AbstractSet`, which extends `AbstractCollection`

# Concrete sets

- `HashSet` implements a **hash table**
  - Underlying storage is an array
  - Map value `v` to a position `h(v)`
  - If `h(v)` is unoccupied, store `v` at that position
  - Otherwise, **collision** — different strategies to handle this case

# Concrete sets

- `HashSet` implements a **hash table**
  - Underlying storage is an array
  - Map value `v` to a position `h(v)`
  - If `h(v)` is unoccupied, store `v` at that position
  - Otherwise, **collision** — different strategies to handle this case
- Checking membership is fast — check if `v` is at position `h(v)`

# Concrete sets

- `HashSet` implements a **hash table**
  - Underlying storage is an array
  - Map value `v` to a position `h(v)`
  - If `h(v)` is unoccupied, store `v` at that position
  - Otherwise, **collision** — different strategies to handle this case
- Checking membership is fast — check if `v` is at position `h(v)`
- Unordered, but supports `iterator()`



# Concrete sets

- `HashSet` implements a **hash table**
  - Underlying storage is an array
  - Map value `v` to a position `h(v)`
  - If `h(v)` is unoccupied, store `v` at that position
  - Otherwise, **collision** — different strategies to handle this case
- Checking membership is fast — check if `v` is at position `h(v)`
- Unordered, but supports `iterator()`
- Scan elements in **unspecified** order

# Concrete sets

- `HashSet` implements a **hash table**
  - Underlying storage is an array
  - Map value `v` to a position `h(v)`
  - If `h(v)` is unoccupied, store `v` at that position
  - Otherwise, **collision** — different strategies to handle this case
- Checking membership is fast — check if `v` is at position `h(v)`
- Unordered, but supports `iterator()`
- Scan elements in **unspecified** order
- Visit each element exactly once

# Concrete sets

- `HashSet` implements a **hash table**
  - Underlying storage is an array
  - Map value `v` to a position `h(v)`
  - If `h(v)` is unoccupied, store `v` at that position
  - Otherwise, **collision** — different strategies to handle this case
- Checking membership is fast — check if `v` is at position `h(v)`
- Unordered, but supports `iterator()`
- Scan elements in **unspecified** order
- Visit each element exactly once
- `TreeSet` uses a tree representation
  - Values are ordered
  - Maintains a sorted collection

# Concrete sets

- **HashSet** implements a **hash table**
  - Underlying storage is an array
  - Map value **v** to a position **h(v)**
  - If **h(v)** is unoccupied, store **v** at that position
  - Otherwise, **collision** — different strategies to handle this case
- Checking membership is fast — check if **v** is at position **h(v)**
- Unordered, but supports **iterator()**
- Scan elements in **unspecified** order
- Visit each element exactly once
- **TreeSet** uses a tree representation
  - Values are ordered
  - Maintains a sorted collection
- Iterator will visit elements in sorted order

# Concrete sets

- **HashSet** implements a **hash table**
  - Underlying storage is an array
  - Map value  $v$  to a position  $h(v)$
  - If  $h(v)$  is unoccupied, store  $v$  at that position
  - Otherwise, **collision** — different strategies to handle this case
- Checking membership is fast — check if  $v$  is at position  $h(v)$
- Unordered, but supports `iterator()`
- Scan elements in **unspecified** order
- Visit each element exactly once
- **TreeSet** uses a tree representation
  - Values are ordered
  - Maintains a sorted collection
- Iterator will visit elements in sorted order
- Insertion is more complex than a hash table
  - Time  $O(\log n)$  if the set has  $n$  elements

# The Queue interface

- Ordered, remove front, insert rear

# The Queue interface

- Ordered, remove front, insert rear
- `Queue` interface supports the following

```
boolean add(E element);  
E remove();
```

- If queue full, `add()` flags an error
- If queue empty, `remove()` flags an error

# The Queue interface

- Ordered, remove front, insert rear
- `Queue` interface supports the following

```
boolean add(E element);  
E remove();
```

- If queue full, `add()` flags an error
- If queue empty, `remove()` flags an error

- Gentler versions of `add()`, `remove()`

```
boolean offer(E element);  
E poll();
```

- Return `false` or `null`, respectively, if not possible



# The Queue interface

- Ordered, remove front, insert rear
- `Queue` interface supports the following

```
boolean add(E element);  
E remove();
```

- If queue full, `add()` flags an error
- If queue empty, `remove()` flags an error

- Gentler versions of `add()`, `remove()`

```
boolean offer(E element);  
E poll();
```

- Return `false` or `null`, respectively, if not possible

- Inspect the head, no update

```
E element(); // Throws exception  
E peek();    // Returns null
```

# The Queue interface

- Ordered, remove front, insert rear
- `Queue` interface supports the following

```
boolean add(E element);  
E remove();
```

- If queue full, `add()` flags an error
- If queue empty, `remove()` flags an error

- Gentler versions of `add()`, `remove()`

```
boolean offer(E element);  
E poll();
```

- Return `false` or `null`, respectively, if not possible

- Inspect the head, no update

```
E element(); // Throws exception  
E peek();    // Returns null
```

- Interface `Deque`, double ended queue

```
boolean addFirst(E element);  
boolean addLast(E element);  
boolean offerFirst(E element);  
boolean offerLast(E element);  
E pollFirst();  
E pollLast();  
E getFirst();  
E getLast();  
E peekFirst();  
E peekLast();
```

# The Queue interface

- Ordered, remove front, insert rear
- `Queue` interface supports the following

```
boolean add(E element);  
E remove();
```

- If queue full, `add()` flags an error
- If queue empty, `remove()` flags an error

- Gentler versions of `add()`, `remove()`

```
boolean offer(E element);  
E poll();
```

- Return `false` or `null`, respectively, if not possible

- Inspect the head, no update

```
E element(); // Throws exception  
E peek();    // Returns null
```

- Interface `Deque`, double ended queue

```
boolean addFirst(E element);  
boolean addLast(E element);  
boolean offerFirst(E element);  
boolean offerLast(E element);  
E pollFirst();  
E pollLast();  
E getFirst();  
E getLast();  
E peekFirst();  
E peekLast();
```

- Interface `PriorityQueue`

- `remove()` returns highest priority item

# The Queue interface

- Ordered, remove front, insert rear
- `Queue` interface supports the following

```
boolean add(E element);  
E remove();
```

- If queue full, `add()` flags an error
- If queue empty, `remove()` flags an error

- Gentler versions of `add()`, `remove()`

```
boolean offer(E element);  
E poll();
```

- Return `false` or `null`, respectively, if not possible

- Inspect the head, no update

```
E element(); // Throws exception  
E peek();    // Returns null
```

- Interface `Deque`, double ended queue

```
boolean addFirst(E element);  
boolean addLast(E element);  
boolean offerFirst(E element);  
boolean offerLast(E element);  
E pollFirst();  
E pollLast();  
E getFirst();  
E getLast();  
E peekFirst();  
E peekLast();
```

- Interface `PriorityQueue`

- `remove()` returns highest priority item

- Concrete implementations

- `LinkedList` — implements `Queue`
- `ArrayDeque` — circular array `Deque`

# Summary

- Different types of `Collection` are specified by subinterfaces
  - `List`, `Set`, `Queue`
- `List` allows random access, more functional `ListIterator`
- `Set` constrains collection to not have duplicates
- `Queue` supports restricted add and remove methods
- Each interface has corresponding version under `AbstractCollection`
- Concrete implementations extend `AbstractList`, `AbstractSet` and `AbstractQueue`