

# Python Recap – III

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python  
Week 1

# Computing gcd

- Both versions of `gcd` take time proportional to `min(m, n)`
- Can we do better?

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```

```
def gcd(m,n):  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            mrcf = i  
    return(mrcf)
```

# Computing gcd

- Both versions of `gcd` take time proportional to  $\min(m, n)$
- Can we do better?
- Suppose  $d$  divides  $m$  and  $n$ 
  - $m = ad, n = bd$
  - $m - n = (a - b)d$
  - $d$  also divides  $m - n$

```
def gcd(m,n):  
    cf = []    # List of common factors  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            cf.append(i)  
    return(cf[-1])
```

```
def gcd(m,n):  
    for i in range(1,min(m,n)+1):  
        if (m%i) == 0 and (n%i) == 0:  
            mrcf = i  
    return(mrcf)
```

# Computing gcd

- Both versions of `gcd` take time proportional to `min(m, n)`
- Can we do better?
- Suppose  $d$  divides  $m$  and  $n$ 
  - $m = ad, n = bd$
  - $m - n = (a - b)d$
  - $d$  also divides  $m - n$
- Recursively defined function
  - Base case:  $n$  divides  $m$ , answer is  $n$
  - Otherwise, reduce `gcd(m, n)` to `gcd(n, m - n)`

```
def gcd(m,n):  
    (a,b) = (max(m,n), min(m,n))  
    if a%b == 0:  
        return(b)  
    else  
        return(gcd(b,a-b))
```

# Computing gcd

- Unfortunately, this takes time proportional to  $\max(m, n)$

```
def gcd(m,n):  
    (a,b) = (max(m,n), min(m,n))  
    if a%b == 0:  
        return(b)  
    else  
        return(gcd(b,a-b))
```

# Computing gcd

- Unfortunately, this takes time proportional to  $\max(m, n)$
- Consider  $\text{gcd}(2, 9999)$ 
  - $\rightarrow \text{gcd}(2, 9997)$
  - $\rightarrow \text{gcd}(2, 9995)$
  - ...
  - $\rightarrow \text{gcd}(2, 3)$
  - $\rightarrow \text{gcd}(2, 1)$
  - $\rightarrow 1$

```
def gcd(m,n):  
    (a,b) = (max(m,n), min(m,n))  
    if a%b == 0:  
        return(b)  
    else  
        return(gcd(b,a-b))
```

# Computing gcd

- Unfortunately, this takes time proportional to  $\max(m, n)$
- Consider  $\text{gcd}(2, 9999)$ 
  - $\rightarrow \text{gcd}(2, 9997)$
  - $\rightarrow \text{gcd}(2, 9995)$
  - ...
  - $\rightarrow \text{gcd}(2, 3)$
  - $\rightarrow \text{gcd}(2, 1)$
  - $\rightarrow 1$
- Approximately 5000 steps

```
def gcd(m,n):  
    (a,b) = (max(m,n), min(m,n))  
    if a%b == 0:  
        return(b)  
    else  
        return(gcd(b,a-b))
```

# Computing gcd

- Unfortunately, this takes time proportional to  $\max(m, n)$
- Consider  $\text{gcd}(2, 9999)$ 
  - $\rightarrow \text{gcd}(2, 9997)$
  - $\rightarrow \text{gcd}(2, 9995)$
  - ...
  - $\rightarrow \text{gcd}(2, 3)$
  - $\rightarrow \text{gcd}(2, 1)$
  - $\rightarrow 1$
- Approximately 5000 steps
- Can we do better?

```
def gcd(m,n):  
    (a,b) = (max(m,n), min(m,n))  
    if a%b == 0:  
        return(b)  
    else  
        return(gcd(b,a-b))
```



# Euclid's algorithm

- Suppose  $n$  does not divide  $m$

# Euclid's algorithm

- Suppose  $n$  does not divide  $m$
- Then  $m = qn + r$

# Euclid's algorithm

- Suppose  $n$  does not divide  $m$
- Then  $m = qn + r$
- Suppose  $d$  divides both  $m$  and  $n$

# Euclid's algorithm

- Suppose  $n$  does not divide  $m$
- Then  $m = qn + r$
- Suppose  $d$  divides both  $m$  and  $n$
- Then  $m = ad$ ,  $n = bd$

# Euclid's algorithm

- Suppose  $n$  does not divide  $m$
- Then  $m = qn + r$
- Suppose  $d$  divides both  $m$  and  $n$
- Then  $m = ad, n = bd$
- $m = qn + r \rightarrow ad = q(bd) + r$

# Euclid's algorithm

- Suppose  $n$  does not divide  $m$
- Then  $m = qn + r$
- Suppose  $d$  divides both  $m$  and  $n$
- Then  $m = ad, n = bd$
- $m = qn + r \rightarrow ad = q(bd) + r$
- $r$  must be of the form  $cd$

# Euclid's algorithm

- Suppose  $n$  does not divide  $m$
- Then  $m = qn + r$
- Suppose  $d$  divides both  $m$  and  $n$
- Then  $m = ad, n = bd$
- $m = qn + r \rightarrow ad = q(bd) + r$
- $r$  must be of the form  $cd$
- Euclid's algorithm
  - If  $n$  divides  $m$ ,  $\text{gcd}(m, n) = n$
  - Otherwise, compute  $\text{gcd}(n, m \bmod n)$

```
def gcd(m,n):  
    (a,b) = (max(m,n), min(m,n))  
    if a%b == 0:  
        return(b)  
    else  
        return(gcd(b,a%b))
```

# Euclid's algorithm

- Suppose  $n$  does not divide  $m$
- Then  $m = qn + r$
- Suppose  $d$  divides both  $m$  and  $n$
- Then  $m = ad, n = bd$
- $m = qn + r \rightarrow ad = q(bd) + r$
- $r$  must be of the form  $cd$
- Euclid's algorithm
  - If  $n$  divides  $m$ ,  $\text{gcd}(m, n) = n$
  - Otherwise, compute  $\text{gcd}(n, m \bmod n)$

```
def gcd(m,n):  
    (a,b) = (max(m,n), min(m,n))  
    if a%b == 0:  
        return(b)  
    else  
        return(gcd(b,a%b))
```

- Can show that this takes time proportional to number of digits in  $\max(m, n)$



# Euclid's algorithm

- Suppose  $n$  does not divide  $m$
- Then  $m = qn + r$
- Suppose  $d$  divides both  $m$  and  $n$
- Then  $m = ad, n = bd$
- $m = qn + r \rightarrow ad = q(bd) + r$
- $r$  must be of the form  $cd$
- Euclid's algorithm
  - If  $n$  divides  $m$ ,  $\text{gcd}(m, n) = n$
  - Otherwise, compute  $\text{gcd}(n, m \bmod n)$

```
def gcd(m,n):  
    (a,b) = (max(m,n), min(m,n))  
    if a%b == 0:  
        return(b)  
    else  
        return(gcd(b,a%b))
```

- Can show that this takes time proportional to number of digits in  $\max(m, n)$
- One of the first non-trivial algorithms