

# Java generics at run time

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming Concepts using Java

Week 5

# Erasure of generic information

- Type erasure — Java does not keep record all versions of `LinkedList<T>` as separate types
  - Cannot write

```
if (s instanceof LinkedList<String>){ ... }
```

# Erasure of generic information

- Type erasure — Java does not keep record all versions of `LinkedList<T>` as separate types

- Cannot write

```
if (s instanceof LinkedList<String>){ ... }
```

- At run time, all type variables are promoted to `Object`

- `LinkedList<T>` becomes `LinkedList<Object>`

# Erasure of generic information

- Type erasure — Java does not keep record all versions of `LinkedList<T>` as separate types

- Cannot write

```
if (s instanceof LinkedList<String>){ ... }
```

- At run time, all type variables are promoted to `Object`

- `LinkedList<T>` becomes `LinkedList<Object>`

- Or, the **upper bound**, if one is available

- `LinkedList<? extends Shape>` becomes `LinkedList<Shape>`

# Erasure of generic information

- Type erasure — Java does not keep record all versions of `LinkedList<T>` as separate types

- Cannot write

```
if (s instanceof LinkedList<String>){ ... }
```

- At run time, all type variables are promoted to `Object`

- `LinkedList<T>` becomes `LinkedList<Object>`

- Or, the **upper bound**, if one is available

- `LinkedList<? extends Shape>` becomes `LinkedList<Shape>`

- Since no information about `T` is preserved, cannot use `T` in expressions like

```
if (o instanceof T) {...}
```

# Erasure and overloading

- Type erasure means the comparison in following code fragment returns **True**

```
o1 = new LinkedList<Employee>();  
o2 = new LinkedList<Date>();  
  
if (o1.getClass() == o2.getClass){  
    // True, so this block is executed  
}
```

# Erasure and overloading

- Type erasure means the comparison in following code fragment returns **True**

```
o1 = new LinkedList<Employee>();  
o2 = new LinkedList<Date>();  
  
if (o1.getClass() == o2.getClass){  
    // True, so this block is executed  
}
```

- As a consequence the following overloading is illegal

```
public class Example {  
    public void printlist(LinkedList<String> strList) { }  
    public void printlist(LinkedList<Date> dateList) { }  
}
```

# Erasure and overloading

- Type erasure means the comparison in following code fragment returns **True**

```
o1 = new LinkedList<Employee>();  
o2 = new LinkedList<Date>();  
  
if (o1.getClass() == o2.getClass){  
    // True, so this block is executed  
}
```

- As a consequence the following overloading is illegal

```
public class Example {  
    public void printlist(LinkedList<String> strList) { }  
    public void printlist(LinkedList<Date> dateList) { }  
}
```

- Both functions have the same signature after type erasure



# Arrays and generics

- Recall the covariance problem for arrays
  - If `S extends T` then `S[] extends T[]`

# Arrays and generics

- Recall the covariance problem for arrays
  - If `S extends T` then `S[] extends T[]`
- Can lead to run time type errors

```
ETicket[] elecarr = new ETicket[10];  
Ticket[] ticketarr = elecarr; // OK. ETicket[] is a subtype of Ticket[]  
...  
ticketarr[5] = new Ticket(); // Not OK. ticketarr[5] refers to an ETicket!
```

# Arrays and generics

- Recall the covariance problem for arrays
  - If `S extends T` then `S[] extends T[]`
- Can lead to run time type errors

```
ETicket[] elecarr = new ETicket[10];  
Ticket[] ticketarr = elecarr; // OK. ETicket[] is a subtype of Ticket[]  
...  
ticketarr[5] = new Ticket(); // Not OK. ticketarr[5] refers to an ETicket!
```

- To avoid similar problems, can declare a generic array, but cannot instantiate it

```
T[] newarray; // OK  
newarray = new T[100]; // Cannot create!
```

# Arrays and generics

- Recall the covariance problem for arrays
  - If `S extends T` then `S[] extends T[]`

- Can lead to run time type errors

```
ETicket[] elecarr = new ETicket[10];  
Ticket[] ticketarr = elecarr; // OK. ETicket[] is a subtype of Ticket[]  
...  
ticketarr[5] = new Ticket(); // Not OK. ticketarr[5] refers to an ETicket!
```

- To avoid similar problems, can declare a generic array, but cannot instantiate it

```
T[] newarray; // OK  
newarray = new T[100]; // Cannot create!
```

- An ugly workaround ...

```
T[] newarray;  
newarray = (T[]) new Object[100];
```

# Arrays and generics

- Recall the covariance problem for arrays
  - If `S extends T` then `S[] extends T[]`

- Can lead to run time type errors

```
ETicket[] elecarr = new ETicket[10];  
Ticket[] ticketarr = elecarr; // OK. ETicket[] is a subtype of Ticket[]  
...  
ticketarr[5] = new Ticket(); // Not OK. ticketarr[5] refers to an ETicket!
```

- To avoid similar problems, can declare a generic array, but cannot instantiate it

```
T[] newarray; // OK  
newarray = new T[100]; // Cannot create!
```

- An ugly workaround ... generates a compiler warning but works!

```
T[] newarray;  
newarray = (T[]) new Object[100];
```

# Wrapper classes

- Type erasure — at run time, all type variables are promoted to `Object`
  - `LinkedList<T>` becomes `LinkedList<Object>`

# Wrapper classes

- Type erasure — at run time, all type variables are promoted to `Object`
  - `LinkedList<T>` becomes `LinkedList<Object>`
- Basic types `int`, `float`, ... are not compatible with `Object`

# Wrapper classes

- Type erasure — at run time, all type variables are promoted to `Object`
  - `LinkedList<T>` becomes `LinkedList<Object>`
- Basic types `int`, `float`, ... are not compatible with `Object`
- Cannot use basic type in place of a generic type variable `T`
  - Cannot instantiate `LinkedList<T>` as `LinkedList<int>`, `LinkedList<double>`, ...



# Wrapper classes

- Type erasure — at run time, all type variables are promoted to `Object`
  - `LinkedList<T>` becomes `LinkedList<Object>`
- Basic types `int`, `float`, ... are not compatible with `Object`
- Cannot use basic type in place of a generic type variable `T`
  - Cannot instantiate `LinkedList<T>` as `LinkedList<int>`, `LinkedList<double>`, ...
- **Wrapper** class for each basic type:

Basic type	Wrapper Class
<code>byte</code>	<code>Byte</code>
<code>short</code>	<code>Short</code>
<code>int</code>	<code>Integer</code>
<code>long</code>	<code>Long</code>

Basic type	Wrapper Class
<code>float</code>	<code>Float</code>
<code>double</code>	<code>Double</code>
<code>boolean</code>	<code>Boolean</code>
<code>char</code>	<code>Character</code>

# Wrapper classes

- Type erasure — at run time, all type variables are promoted to `Object`
  - `LinkedList<T>` becomes `LinkedList<Object>`
- Basic types `int`, `float`, ... are not compatible with `Object`
- Cannot use basic type in place of a generic type variable `T`
  - Cannot instantiate `LinkedList<T>` as `LinkedList<int>`, `LinkedList<double>`, ...
- **Wrapper** class for each basic type:

Basic type	Wrapper Class
<code>byte</code>	<code>Byte</code>
<code>short</code>	<code>Short</code>
<code>int</code>	<code>Integer</code>
<code>long</code>	<code>Long</code>

Basic type	Wrapper Class
<code>float</code>	<code>Float</code>
<code>double</code>	<code>Double</code>
<code>boolean</code>	<code>Boolean</code>
<code>char</code>	<code>Character</code>

- All wrapper classes other than `Boolean`, `Character` extend the class `Number`

# Wrapper classes

- Converting from basic type to wrapper class and back

```
int x = 5;  
Integer myx = Integer(x);  
int y = myx.intValue();
```

# Wrapper classes

- Converting from basic type to wrapper class and back

```
int x = 5;  
Integer myx = Integer(x);  
int y = myx.intValue();
```

- Similarly, `byteValue()`, `doubleValue()`, ...

# Wrapper classes

- Converting from basic type to wrapper class and back

```
int x = 5;  
Integer myx = Integer(x);  
int y = myx.intValue();
```

- Similarly, `byteValue()`, `doubleValue()`, ...

- **Autoboxing** — implicit conversion between base types and wrapper types

```
int x = 5;  
Integer myx = x;  
int y = myx;
```

# Wrapper classes

- Converting from basic type to wrapper class and back

```
int x = 5;  
Integer myx = Integer(x);  
int y = myx.intValue();
```

- Similarly, `byteValue()`, `doubleValue()`, ...

- **Autoboxing** — implicit conversion between base types and wrapper types

```
int x = 5;  
Integer myx = x;  
int y = myx;
```

- Use wrapper types in generic data structures

# Summary

- Java generics come with some restrictions
- Information about type variables is erased at runtime
  - `LinkedList<T>` becomes `LinkedList<Object>`
  - `LinkedList<? extends Shape>` becomes `LinkedList<Shape>`
- Limits the use reflection on generic types — cannot write
  - `if (o instanceof LinkedList<String>) {...}`
  - `if (o instanceof T) {...}`
- Cannot overload function signatures using instantiation of generic types
- Cannot instantiate arrays of generic type
- Need to box built-in types using wrapper types