

Exceptions in Java

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming Concepts using Java

Week 7

Java's classification of errors

- All exceptions descend from class `Throwable`
 - Two branches, `Error` and `Exception`
- `Error` — relatively rare, “not the programmer’s fault”
 - Internal errors, resource limitations within Java runtime
 - No realistic corrective action possible, notify caller and terminate gracefully
- `Exception` — two sub branches
 - `RuntimeException`, `checked exceptions`
- `RuntimeException` — programming errors that should have been caught by code
 - Array index out of bounds, invalid hash key, ...
- Checked exceptions
 - Typically user-defined, code assumptions violated
 - In a list of orders, quantities should be positive integers

Catching and handling exceptions

■ try-catch

- Enclose code that may generate exception in a `try` block
- Exception handler in `catch` block
- Similar to Python

```
try {  
    ...  
    call a function that may  
        throw an exception  
    ..  
}  
catch (ExceptionType e){  
    ...  
    examine e and handle it  
    ...  
}
```

Catching and handling exceptions

■ try-catch

- Enclose code that may generate exception in a `try` block
 - Exception handler in `catch` block
 - Similar to Python
- If `try` encounters an exception, rest of the code in the block is skipped

```
try {  
    ...  
    call a function that may  
        throw an exception  
    ..  
}  
catch (ExceptionType e){  
    ...  
    examine e and handle it  
    ...  
}
```

Catching and handling exceptions

■ try-catch

- Enclose code that may generate exception in a `try` block
 - Exception handler in `catch` block
 - Similar to Python
- If `try` encounters an exception, rest of the code in the block is skipped
- If exception matches the type in `catch`, handler code executes

```
try {  
    ...  
    call a function that may  
        throw an exception  
    ..  
}  
catch (ExceptionType e){  
    ...  
    examine e and handle it  
    ...  
}
```

Catching and handling exceptions

■ try-catch

- Enclose code that may generate exception in a `try` block
 - Exception handler in `catch` block
 - Similar to Python
- If `try` encounters an exception, rest of the code in the block is skipped
 - If exception matches the type in `catch`, handler code executes
 - Otherwise, **uncaught** exception is passed back to the code that called this code

```
try {  
    ...  
    call a function that may  
        throw an exception  
    ..  
}  
catch (ExceptionType e){  
    ...  
    examine e and handle it  
    ...  
}
```

Catching and handling exceptions

■ try-catch

- Enclose code that may generate exception in a **try** block
 - Exception handler in **catch** block
 - Similar to Python
- If **try** encounters an exception, rest of the code in the block is skipped
 - If exception matches the type in **catch**, handler code executes
 - Otherwise, **uncaught** exception is passed back to the code that called this code
 - Top level uncaught exception — program crash

```
try {  
    ...  
    call a function that may  
        throw an exception  
    ..  
}  
catch (ExceptionType e){  
    ...  
    examine e and handle it  
    ...  
}
```

Catching and handling exceptions

- Can catch more than one type of exception
 - Multiple `catch` blocks

```
try {  
    code that might throw exceptions  
}  
catch (FileNotFoundException e) {  
    handle missing files  
}  
catch (UnknownHostException e) {  
    handle unknown hosts  
}  
catch (IOException e) {  
    handle all other I/O issues  
}
```


Catching and handling exceptions

- Can catch more than one type of exception
 - Multiple `catch` blocks
- Exceptions are classes in the Java class hierarchy
 - `catch (ExceptionType e)` matches any subtype of `ExceptionType`

```
try {  
    code that might throw exceptions  
}  
catch (FileNotFoundException e) {  
    handle missing files  
}  
catch (UnknownHostException e) {  
    handle unknown hosts  
}  
catch (IOException e) {  
    handle all other I/O issues  
}
```

Catching and handling exceptions

- Can catch more than one type of exception
 - Multiple `catch` blocks
- Exceptions are classes in the Java class hierarchy
 - `catch (ExceptionType e)` matches any subtype of `ExceptionType`
- Catch blocks are tried in sequence
 - Match exception type against each one in turn

```
try {  
    code that might throw exceptions  
}  
catch (FileNotFoundException e) {  
    handle missing files  
}  
catch (UnknownHostException e) {  
    handle unknown hosts  
}  
catch (IOException e) {  
    handle all other I/O issues  
}
```

Catching and handling exceptions

- Can catch more than one type of exception
 - Multiple `catch` blocks
- Exceptions are classes in the Java class hierarchy
 - `catch (ExceptionType e)` matches any subtype of `ExceptionType`
- Catch blocks are tried in sequence
 - Match exception type against each one in turn
- Order `catch` blocks by argument type, more specific to less specific
 - `IOException` would intercept `FileNotFoundException`

```
try {  
    code that might throw exceptions  
}  
catch (FileNotFoundException e) {  
    handle missing files  
}  
catch (UnknownHostException e) {  
    handle unknown hosts  
}  
catch (IOException e) {  
    handle all other I/O issues  
}
```

Generating exceptions

- When does a function generate an exception?

Generating exceptions

- When does a function generate an exception?
- **Error** — JVM runtime issue

Generating exceptions

- When does a function generate an exception?
- `Error` — JVM runtime issue
- `RuntimeException`
 - Array index out of bounds, invalid hash key, ...

Generating exceptions

- When does a function generate an exception?
- `Error` — JVM runtime issue
- `RuntimeException`
 - Array index out of bounds, invalid hash key, ...
- Code calls another function that generates an exception

Generating exceptions

- When does a function generate an exception?
- `Error` — JVM runtime issue
- `RuntimeException`
 - Array index out of bounds, invalid hash key, ...
- Code calls another function that generates an exception
- Your code detects an error and generates an exception
 - `throw` a checked exception

Notifying checked exceptions

- Example: you write a method `readData()`
 - Header line provides length of data
 - `Content-Length: 2048`
 - Actual data read is less than promised length

Notifying checked exceptions

- Example: you write a method `readData()`
 - Header line provides length of data
 - `Content-Length: 2048`
 - Actual data read is less than promised length
- Search Java documentation for suitable pre-defined exception
 - `EOFException`, subtype of `IOException`
 - “Signals that EOF has been reached unexpectedly during input”

Notifying checked exceptions

- Example: you write a method `readData()`
 - Header line provides length of data
 - `Content-Length: 2048`
 - Actual data read is less than promised length
- Search Java documentation for suitable pre-defined exception
 - `EOFException`, subtype of `IOException`
 - “Signals that EOF has been reached unexpectedly during input”
- Create an object of exception type and `throw` it
`throw new EOFException();`

Notifying checked exceptions

- Example: you write a method `readData()`
 - Header line provides length of data
 - `Content-Length: 2048`
 - Actual data read is less than promised length
- Search Java documentation for suitable pre-defined exception
 - `EOFException`, subtype of `IOException`
 - “Signals that EOF has been reached unexpectedly during input”
- Create an object of exception type and `throw` it

```
throw new EOFException();
```

- Can also pass a diagnostic message when constructing exception object

```
String errormsg = "Content-Length:" + contentlen + ", Received: " + rcvdlen;  
throw new EOFException(errormsg);
```

Throwing exceptions ...

- How does caller know that `readData()` generates `EOFException`?

Throwing exceptions ...

- How does caller know that `readData()` generates `EOFException`?
- Declare exceptions thrown in header

```
String readData(Scanner in)
    throws EOFException {
    ...
    while (...) {
        if (!in.hasNext()) {
            // EOF encountered
            if (n < len) {
                String errmsg = ...
                throw new EOFException(errmsg);
            }
            ...
        }
        return(s);
    }
}
```

Throwing exceptions ...

- How does caller know that `readData()` generates `EOFException`?
- Declare exceptions thrown in header
- Can throw multiple types of exceptions

```
String readFile(String filename)
    throws FileNotFoundException,
        EOFException { ... }
```

```
String readData(Scanner in)
    throws EOFException {
    ...
    while (...) {
        if (!in.hasNext()) {
            // EOF encountered
            if (n < len) {
                String errmsg = ...
                throw new EOFException(errmsg);
            }
        }
        ...
    }
    return(s);
}
```

Throwing exceptions ...

- How does caller know that `readData()` generates `EOFException`?

- Declare exceptions thrown in header

- Can throw multiple types of exceptions

```
String readFile(String filename)
    throws FileNotFoundException,
        EOFException { ... }
```

- Can throw any subtype of declared exception type

```
String readFile(String filename)
    throws IOException { ... }
```

- Can throw `FileNotFoundException`, `EOFException`, both subclasses of `IOException`

```
String readData(Scanner in)
    throws EOFException {
    ...
    while (...) {
        if (!in.hasNext()) {
            // EOF encountered
            if (n < len) {
                String errmsg = ...
                throw new EOFException(errmsg);
            }
        }
        ...
    }
    return(s);
}
```


Throwing exceptions ...

- Method declares the exceptions it throws

```
String readData(Scanner in)
    throws EOFException {
    ...
    while (...) {
        if (!in.hasNext()) {
            // EOF encountered
            if (n < len) {
                String errmsg = ...
                throw new EOFException(errmsg);
            }
            ...
        }
        return(s);
    }
}
```

Throwing exceptions ...

- Method declares the exceptions it throws
- If you call such a method, you must handle it

```
String readData(Scanner in)
    throws EOFException {
    ...
    while (...) {
        if (!in.hasNext()) {
            // EOF encountered
            if (n < len) {
                String errmsg = ...
                throw new EOFException(errmsg);
            }
        }
        ...
    }
    return(s);
}
```

Throwing exceptions ...

- Method declares the exceptions it throws
- If you call such a method, you must handle it
- ... or pass it on; your method should advertise that it throws the same exception

```
String readData(Scanner in)
    throws EOFException {
    ...
    while (...) {
        if (!in.hasNext()) {
            // EOF encountered
            if (n < len) {
                String errmsg = ...
                throw new EOFException(errmsg);
            }
        }
        ...
    }
    return(s);
}
```

Throwing exceptions ...

- Method declares the exceptions it throws
- If you call such a method, you must handle it
- ... or pass it on; your method should advertise that it throws the same exception
- Need not advertise unchecked exceptions
 - `Error`, `RuntimeException`

```
String readData(Scanner in)
    throws EOFException {
    ...
    while (...) {
        if (!in.hasNext()) {
            // EOF encountered
            if (n < len) {
                String errmsg = ...
                throw new EOFException(errmsg);
            }
            ...
        }
        return(s);
    }
}
```

Throwing exceptions ...

- Method declares the exceptions it throws
- If you call such a method, you must handle it
- ... or pass it on; your method should advertise that it throws the same exception
- Need not advertise unchecked exceptions
 - `Error`, `RuntimeException`
- Should not normally generate `RuntimeException`
 - Fix the error or report suitable checked exception

```
String readData(Scanner in)
    throws EOFException {
    ...
    while (...) {
        if (!in.hasNext()) {
            // EOF encountered
            if (n < len) {
                String errmsg = ...
                throw new EOFException(errmsg);
            }
            ...
        }
        return(s);
    }
}
```

Customized exceptions

- Don't want negative numbers in a `LinkedList`

Customized exceptions

- Don't want negative numbers in a `LinkedList`
- Define a new class extending `Exception`

```
public class NegativeException extends Exception{  
  
    private int error_value;  
    // Negative value that generated exception  
  
    public NegativeException(String message, int i){  
        super(message); // Appeal to superclass  
        error_value = i; // constructor to set message  
    }  
  
    public int report_error_value(){  
        return error_value;  
    }  
}
```

Customized exceptions

- Don't want negative numbers in a `LinkedList`
- Define a new class extending `Exception`
- Throw this from `LinkedList`
 - Note that `add` advertises the fact that it throws a `NegativeException`

```
public class NegativeException extends Exception{
    ...
}

public class LinkedList{
    ...
    public add(int i) throws NegativeException{
        ...
        if (i < 0){
            throw new NegativeException("Negative input",i);
        }
        ...
    }
}
```


More on catching exceptions

- Can extract information about the exception

```
try {  
    ...  
    call a function that may  
        throw an exception  
    ..  
}  
catch (ExceptionType e){  
    ...  
    String errormsg = e.getMessage();  
    ...  
}
```

More on catching exceptions

- Can extract information about the exception
- Chaining exceptions
 - Process and throw a new exception from `catch`

```
try {  
    ...  
    access database  
    ..  
}  
catch (SQLException e){  
    ...  
    String errormsg =  
        "database error" + e.getMessage();  
    throw new ServletException(errormsg);  
    ...  
}
```

More on catching exceptions

- Can extract information about the exception
- Chaining exceptions
 - Process and throw a new exception from `catch`
- `Throwable` has additional methods to track chain of exceptions
 - `getCause()`, `initCause()`

```
try {  
    ...  
    access database  
    ..  
}  
catch (SQLException e){  
    ...  
    String errormsg =  
        "database error" + e.getMessage();  
    throw new ServletException(errormsg);  
    ...  
}
```

More on catching exceptions

- Can extract information about the exception
- Chaining exceptions
 - Process and throw a new exception from `catch`
- `Throwable` has additional methods to track chain of exceptions
 - `getCause()`, `initCause()`
- Add information when you chain exceptions

```
try {  
    ...  
    access database  
    ..  
}  
catch (SQLException e){  
    ...  
    String errormsg =  
        "database error" + e.getMessage();  
    ServletException neue =  
        new ServletException(errormsg);  
    neue.initCause(e);  
    throw neue;  
    ...  
}
```

More on catching exceptions

- Can extract information about the exception
- Chaining exceptions
 - Process and throw a new exception from `catch`
- `Throwable` has additional methods to track chain of exceptions
 - `getCause()`, `initCause()`
- Add information when you chain exceptions
- Retrieve information when you catch exception

```
try {  
    ...  
}  
catch (ServletException e){  
    ...  
    Throwable original = e.getCause();  
    ...  
}
```

Cleaning up resources

- When exception occurs, rest of the `try` block is skipped

Cleaning up resources

- When exception occurs, rest of the `try` block is skipped
- May need to do some clean up (close files, deallocate resources, ...)

Cleaning up resources

- When exception occurs, rest of the `try` block is skipped
- May need to do some clean up (close files, deallocate resources, ...)
- Add a block labelled `finally`

```
try{  
    ...  
}  
  
catch (ExceptionType1 e){...}  
  
catch (ExceptionType2 e){...}  
  
finally{  
    ...  
    // Always executed, whether try  
    // terminates normally or  
    // exceptionally. Use for clean up.  
}
```


Cleaning up resources

- When exception occurs, rest of the `try` block is skipped
- May need to do some clean up (close files, deallocate resources, ...)
- Add a block labelled `finally`
- Different scenarios

```
FileInputStream in =  
    new FileInputStream(...);  
try {  
    // 1  
    code that might throw exceptions  
    // 2  
}  
catch (IOException e) {  
    // 3  
    show error message  
    // 4  
}  
finally {  
    // 5  
    in.close();  
}  
// 6
```

Cleaning up resources

- When exception occurs, rest of the `try` block is skipped
- May need to do some clean up (close files, deallocate resources, ...)
- Add a block labelled `finally`
- Different scenarios
 - No error — 1,2,5,6

```
FileInputStream in =  
    new FileInputStream(...);  
try {  
    // 1  
    code that might throw exceptions  
    // 2  
}  
catch (IOException e) {  
    // 3  
    show error message  
    // 4  
}  
finally {  
    // 5  
    in.close();  
}  
// 6
```

Cleaning up resources

- When exception occurs, rest of the `try` block is skipped
- May need to do some clean up (close files, deallocate resources, ...)
- Add a block labelled `finally`
- Different scenarios
 - No error — 1,2,5,6
 - `IOException` in `try`, no exception in `catch` — 1,3,4,5,6

```
FileInputStream in =  
    new FileInputStream(...);  
try {  
    // 1  
    code that might throw exceptions  
    // 2  
}  
catch (IOException e) {  
    // 3  
    show error message  
    // 4  
}  
finally {  
    // 5  
    in.close();  
}  
// 6
```

Cleaning up resources

- When exception occurs, rest of the `try` block is skipped
- May need to do some clean up (close files, deallocate resources, ...)
- Add a block labelled `finally`
- Different scenarios
 - No error — 1,2,5,6
 - `IOException` in `try`, no exception in `catch` — 1,3,4,5,6
 - `IOException` in `try`, chained exception in `catch` — 1,3,5

```
FileInputStream in =  
    new FileInputStream(...);  
try {  
    // 1  
    code that might throw exceptions  
    // 2  
}  
catch (IOException e) {  
    // 3  
    show error message  
    // 4  
}  
finally {  
    // 5  
    in.close();  
}  
// 6
```

Summary

- Use `try-catch` to safely call functions that may generate errors
- Can `throw` an exception — usually checked exception
- Must advertise checked exceptions that are thrown in function header
 - Java compiler enforces that code that calls such a function handles the exception or passes it on
- Can inspect exceptions and chain them with information about original source
- Use `finally` to clean up resources that may be left open when code is interrupted by an exception