

Subclasses and inheritance

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming Concepts using Java

Week 3

A Java class

■ An `Employee` class

```
public class Employee{
    private String name;
    private double salary;

    // Some Constructors ...

    // "mutator" methods
    public boolean setName(String s){ ... }
    public boolean setSalary(double x){ ... }

    // "accessor" methods
    public String getName(){ ... }
    public double getSalary(){ ... }

    // other methods
    public double bonus(float percent){
        return (percent/100.0)*salary;
    }
}
```

A Java class

- An `Employee` class
- Two private instance variables

```
public class Employee{  
    private String name;  
    private double salary;  
  
    // Some Constructors ...  
  
    // "mutator" methods  
    public boolean setName(String s){ ... }  
    public boolean setSalary(double x){ ... }  
  
    // "accessor" methods  
    public String getName(){ ... }  
    public double getSalary(){ ... }  
  
    // other methods  
    public double bonus(float percent){  
        return (percent/100.0)*salary;  
    }  
}
```

A Java class

- An `Employee` class
- Two private instance variables
- Some constructors to set up the object

```
public class Employee{
    private String name;
    private double salary;

    // Some Constructors ...

    // "mutator" methods
    public boolean setName(String s){ ... }
    public boolean setSalary(double x){ ... }

    // "accessor" methods
    public String getName(){ ... }
    public double getSalary(){ ... }

    // other methods
    public double bonus(float percent){
        return (percent/100.0)*salary;
    }
}
```

A Java class

- An `Employee` class
- Two private instance variables
- Some constructors to set up the object
- Accessor and mutator methods to set instance variables

```
public class Employee{
    private String name;
    private double salary;

    // Some Constructors ...

    // "mutator" methods
    public boolean setName(String s){ ... }
    public boolean setSalary(double x){ ... }

    // "accessor" methods
    public String getName(){ ... }
    public double getSalary(){ ... }

    // other methods
    public double bonus(float percent){
        return (percent/100.0)*salary;
    }
}
```

A Java class

- An `Employee` class
- Two private instance variables
- Some constructors to set up the object
- Accessor and mutator methods to set instance variables
- A public method to compute bonus

```
public class Employee{  
    private String name;  
    private double salary;  
  
    // Some Constructors ...  
  
    // "mutator" methods  
    public boolean setName(String s){ ... }  
    public boolean setSalary(double x){ ... }  
  
    // "accessor" methods  
    public String getName(){ ... }  
    public double getSalary(){ ... }  
  
    // other methods  
    public double bonus(float percent){  
        return (percent/100.0)*salary;  
    }  
}
```

Subclasses

- Managers are special types of employees with extra features

```
public class Manager extends Employee{  
    private String secretary;  
    public boolean setSecretary(name s){ ... }  
    public String getSecretary(){ ... }  
}
```

- Managers are special types of employees with extra features

```
public class Manager extends Employee{  
    private String secretary;  
    public boolean setSecretary(name s){ ... }  
    public String getSecretary(){ ... }  
}
```

- **Manager** objects inherit other fields and methods from **Employee**
 - Every **Manager** has a **name**, **salary** and methods to access and manipulate these.

Subclasses

- Managers are special types of employees with extra features

```
public class Manager extends Employee{  
    private String secretary;  
    public boolean setSecretary(name s){ ... }  
    public String getSecretary(){ ... }  
}
```

- **Manager** objects inherit other fields and methods from **Employee**
 - Every **Manager** has a **name**, **salary** and methods to access and manipulate these.
- **Manager** is a **subclass** of **Employee**
 - Think of subset

Subclasses

- **Manager** objects do not automatically have access to private data of parent class.
 - Common to extend a parent class written by someone else

Subclasses

- **Manager** objects do not automatically have access to private data of parent class.
 - Common to extend a parent class written by someone else
- How can a constructor for **Manager** set instance variables that are private to **Employee**?

Subclasses

- **Manager** objects do not automatically have access to private data of parent class.
 - Common to extend a parent class written by someone else
- How can a constructor for **Manager** set instance variables that are private to **Employee**?
- Some constructors for **Employee**

```
public class Employee{  
    ...  
    public Employee(String n, double s){  
        name = n; salary = s;  
    }  
    public Employee(String n){  
        this(n,500.00);  
    }  
}
```

Subclasses

- **Manager** objects do not automatically have access to private data of parent class.
 - Common to extend a parent class written by someone else
- How can a constructor for **Manager** set instance variables that are private to **Employee**?
- Some constructors for **Employee**
- Use parent class's constructor using **super**

```
public class Employee{  
    ...  
    public Employee(String n, double s){  
        name = n; salary = s;  
    }  
    public Employee(String n){  
        this(n,500.00);  
    }  
}
```

Subclasses

- **Manager** objects do not automatically have access to private data of parent class.
 - Common to extend a parent class written by someone else
- How can a constructor for **Manager** set instance variables that are private to **Employee**?
- Some constructors for **Employee**
- Use parent class's constructor using **super**
- A constructor for **Manager**

```
public class Employee{
    ...
    public Employee(String n, double s){
        name = n; salary = s;
    }
    public Employee(String n){
        this(n,500.00);
    }
}

public class Manager extends Employee{
    ..
    public Manager(String n, double s, String sn){
        super(n,s);    /* super calls
                        Employee constructor */
        secretary = sn;
    }
}
```

Inheritance

- In general, subclass has more features than parent class
 - Subclass **inherits** instance variables, methods from parent class

Inheritance

- In general, subclass has more features than parent class
 - Subclass **inherits** instance variables, methods from parent class
- Every **Manager** is an **Employee**, but not vice versa!

Inheritance

- In general, subclass has more features than parent class
 - Subclass **inherits** instance variables, methods from parent class
- Every **Manager** is an **Employee**, but not vice versa!
- Can use a subclass in place of a superclass

```
Employee e = new Manager(...)
```

Inheritance

- In general, subclass has more features than parent class
 - Subclass **inherits** instance variables, methods from parent class
- Every **Manager** is an **Employee**, but not vice versa!
- Can use a subclass in place of a superclass

```
Employee e = new Manager(...)
```
- But the following will not work

```
Manager m = new Employee(...)
```

Inheritance

- In general, subclass has more features than parent class
 - Subclass **inherits** instance variables, methods from parent class
- Every **Manager** is an **Employee**, but not vice versa!
- Can use a subclass in place of a superclass

```
Employee e = new Manager(...)
```
- But the following will not work

```
Manager m = new Employee(...)
```

■ Recall

- `int[] a = new int[100];`
- Why the seemingly redundant reference to `int` in `new`?

Inheritance

- In general, subclass has more features than parent class
 - Subclass **inherits** instance variables, methods from parent class
- Every **Manager** is an **Employee**, but not vice versa!
- Can use a subclass in place of a superclass

```
Employee e = new Manager(...)
```
- But the following will not work

```
Manager m = new Employee(...)
```

■ Recall

- `int[] a = new int[100];`
- Why the seemingly redundant reference to `int` in `new`?
- One can now presumably write

```
Employee[] e = new Manager(...)[100]
```

Summary

- A subclass extends a parent class
- Subclass inherits instance variables and methods from the parent class
- Subclass can add more instance variables and methods
 - Can also override methods — later
- Subclasses cannot see private components of parent class
- Use `super` to access constructor of parent class