

# Greedy Algorithms: Interval Scheduling

Madhavan Mukund

<https://www.cmi.ac.in/~madhavan>

Programming, Data Structures and Algorithms using Python

Week 7

# Greedy Algorithms

- Need to make a sequence of choices to achieve a global optimum

# Greedy Algorithms

- Need to make a sequence of choices to achieve a global optimum
- At each stage, make the next choice based on some local criterion

# Greedy Algorithms

- Need to make a sequence of choices to achieve a global optimum
- At each stage, make the next choice based on some local criterion
- Never go back and revise an earlier decision

# Greedy Algorithms

- Need to make a sequence of choices to achieve a global optimum
- At each stage, make the next choice based on some local criterion
- Never go back and revise an earlier decision
- Drastically reduces space to search for solutions

# Greedy Algorithms

- Need to make a sequence of choices to achieve a global optimum
- At each stage, make the next choice based on some local criterion
- Never go back and revise an earlier decision
- Drastically reduces space to search for solutions
- How to prove that local choices achieve global optimum?

# Greedy Algorithms

- Need to make a sequence of choices to achieve a global optimum
- At each stage, make the next choice based on some local criterion
- Never go back and revise an earlier decision
- Drastically reduces space to search for solutions
- How to prove that local choices achieve global optimum?

## Examples

- Dijkstra's algorithm
  - Local rule: freeze the distance to nearest unvisited vertex
  - Global optimum: distance assigned to each vertex is shortest distance from source

# Greedy Algorithms

- Need to make a sequence of choices to achieve a global optimum
- At each stage, make the next choice based on some local criterion
- Never go back and revise an earlier decision
- Drastically reduces space to search for solutions
- How to prove that local choices achieve global optimum?

## Examples

- Prim's algorithm
  - Local rule: add to the spanning tree nearest non-tree vertex
  - Global optimum: final spanning tree is minimum cost spanning tree



# Greedy Algorithms

- Need to make a sequence of choices to achieve a global optimum
- At each stage, make the next choice based on some local criterion
- Never go back and revise an earlier decision
- Drastically reduces space to search for solutions
- How to prove that local choices achieve global optimum?

## Examples

- Kruskal's algorithm
  - Local rule: add to the current set of edges the smallest edge that does not form a cycle
  - Global optimum: final spanning tree is minimum cost spanning tree

# Interval scheduling

- IIT Madras has a special video classroom for delivering online lectures

# Interval scheduling

- IIT Madras has a special video classroom for delivering online lectures
- Different teachers want to book the classroom

# Interval scheduling

- IIT Madras has a special video classroom for delivering online lectures
- Different teachers want to book the classroom
- Slot for instructor  $i$  starts at  $s(i)$  and finishes at  $f(i)$

# Interval scheduling

- IIT Madras has a special video classroom for delivering online lectures
- Different teachers want to book the classroom
- Slot for instructor  $i$  starts at  $s(i)$  and finishes at  $f(i)$
- Slots may overlap, so not all bookings can be honoured

# Interval scheduling

- IIT Madras has a special video classroom for delivering online lectures
- Different teachers want to book the classroom
- Slot for instructor  $i$  starts at  $s(i)$  and finishes at  $f(i)$
- Slots may overlap, so not all bookings can be honoured
- Choose a subset of bookings to maximize the number of teachers who get to use the room

# Interval scheduling

- IIT Madras has a special video classroom for delivering online lectures
- Different teachers want to book the classroom
- Slot for instructor  $i$  starts at  $s(i)$  and finishes at  $f(i)$
- Slots may overlap, so not all bookings can be honoured
- Choose a subset of bookings to maximize the number of teachers who get to use the room

## Greedy approach

- Pick the next booking to allot based on a local strategy

# Interval scheduling

- IIT Madras has a special video classroom for delivering online lectures
- Different teachers want to book the classroom
- Slot for instructor  $i$  starts at  $s(i)$  and finishes at  $f(i)$
- Slots may overlap, so not all bookings can be honoured
- Choose a subset of bookings to maximize the number of teachers who get to use the room

## Greedy approach

- Pick the next booking to allot based on a local strategy
- Remove all bookings that overlap with the chosen slot



# Interval scheduling

- IIT Madras has a special video classroom for delivering online lectures
- Different teachers want to book the classroom
- Slot for instructor  $i$  starts at  $s(i)$  and finishes at  $f(i)$
- Slots may overlap, so not all bookings can be honoured
- Choose a subset of bookings to maximize the number of teachers who get to use the room

## Greedy approach

- Pick the next booking to allot based on a local strategy
- Remove all bookings that overlap with the chosen slot
- Argue that this sequence of bookings will maximize the number of teachers who get to use the room

# Interval scheduling

- IIT Madras has a special video classroom for delivering online lectures
- Different teachers want to book the classroom
- Slot for instructor  $i$  starts at  $s(i)$  and finishes at  $f(i)$
- Slots may overlap, so not all bookings can be honoured
- Choose a subset of bookings to maximize the number of teachers who get to use the room

## Greedy approach

- Pick the next booking to allot based on a local strategy
- Remove all bookings that overlap with the chosen slot
- Argue that this sequence of bookings will maximize the number of teachers who get to use the room
- What is a sound local strategy?

# Greedy strategies for interval scheduling

## ■ Strategy 1


Choose the booking whose starting time is earliest

# Greedy strategies for interval scheduling

## ■ Strategy 1

Choose the booking whose starting time is earliest

### Counterexample



# Greedy strategies for interval scheduling

- Strategy 1

Choose the booking whose starting time is earliest

- Strategy 2

Choose the booking spanning the shortest interval

# Greedy strategies for interval scheduling

## ■ Strategy 1

Choose the booking whose starting time is earliest

## ■ Strategy 2

Choose the booking spanning the shortest interval

## Counterexample



# Greedy strategies for interval scheduling

- Strategy 1

Choose the booking whose starting time is earliest

- Strategy 2

Choose the booking spanning the shortest interval

- Strategy 3

Choose the booking that overlaps with minimum number of other bookings

# Greedy strategies for interval scheduling

## ■ Strategy 1

Choose the booking whose starting time is earliest

## ■ Strategy 2

Choose the booking spanning the shortest interval

## ■ Strategy 3

Choose the booking that overlaps with minimum number of other bookings

## Counterexample





# Greedy strategies for interval scheduling

- Strategy 1

Choose the booking whose starting time is earliest

- Strategy 2

Choose the booking spanning the shortest interval

- Strategy 3

Choose the booking that overlaps with minimum number of other bookings

- Strategy 4

Choose the booking whose finish time is the earliest

# Greedy strategies for interval scheduling

## ■ Strategy 1

Choose the booking whose starting time is earliest

## ■ Strategy 2

Choose the booking spanning the shortest interval

## ■ Strategy 3

Choose the booking that overlaps with minimum number of other bookings

## ■ Strategy 4

Choose the booking whose finish time is the earliest

- Counterexample? Proof of correctness?

# Greedy algorithm for interval scheduling

- $B$  is the set of bookings

# Greedy algorithm for interval scheduling

- $B$  is the set of bookings
- $A$  is the set of accepted bookings
  - Initially,  $A$  is empty


# Greedy algorithm for interval scheduling

- $B$  is the set of bookings
- $A$  is the set of accepted bookings
  - Initially,  $A$  is empty
- While  $B$  is not empty
  - Pick  $b \in B$  with earliest finishing time
  - Add  $b$  to  $A$
  - Remove from  $B$  all bookings that overlap with  $b$

# Greedy algorithm for interval scheduling

- $B$  is the set of bookings
- $A$  is the set of accepted bookings
  - Initially,  $A$  is empty
- While  $B$  is not empty
  - Pick  $b \in B$  with earliest finishing time
  - Add  $b$  to  $A$
  - Remove from  $B$  all bookings that overlap with  $b$


The algorithm in action



# Greedy algorithm for interval scheduling

- $B$  is the set of bookings
- $A$  is the set of accepted bookings
  - Initially,  $A$  is empty
- While  $B$  is not empty
  - Pick  $b \in B$  with earliest finishing time
  - Add  $b$  to  $A$
  - Remove from  $B$  all bookings that overlap with  $b$


The algorithm in action



# Greedy algorithm for interval scheduling

- $B$  is the set of bookings
- $A$  is the set of accepted bookings
  - Initially,  $A$  is empty
- While  $B$  is not empty
  - Pick  $b \in B$  with earliest finishing time
  - Add  $b$  to  $A$
  - Remove from  $B$  all bookings that overlap with  $b$

The algorithm in action






# Greedy algorithm for interval scheduling

- $B$  is the set of bookings
- $A$  is the set of accepted bookings
  - Initially,  $A$  is empty
- While  $B$  is not empty
  - Pick  $b \in B$  with earliest finishing time
  - Add  $b$  to  $A$
  - Remove from  $B$  all bookings that overlap with  $b$


The algorithm in action



# Greedy algorithm for interval scheduling

- $B$  is the set of bookings
- $A$  is the set of accepted bookings
  - Initially,  $A$  is empty
- While  $B$  is not empty
  - Pick  $b \in B$  with earliest finishing time
  - Add  $b$  to  $A$
  - Remove from  $B$  all bookings that overlap with  $b$

The algorithm in action



# Correctness

- Our algorithm produces a solution  $A$

# Correctness

- Our algorithm produces a solution  $A$
- Let  $O$  be an optimal set of accepted bookings

# Correctness

- Our algorithm produces a solution  $A$
- Let  $O$  be an optimal set of accepted bookings
- $A$  and  $O$  need not be identical
  - Could have multiple allocations of the same size

# Correctness

- Our algorithm produces a solution  $A$
- Let  $O$  be an optimal set of accepted bookings
- $A$  and  $O$  need not be identical
  - Could have multiple allocations of the same size
- Just show that  $|A| = |O|$ 
  - Both sets of bookings are of the same size

# Correctness

- Our algorithm produces a solution  $A$
- Let  $O$  be an optimal set of accepted bookings
- $A$  and  $O$  need not be identical
  - Could have multiple allocations of the same size
- Just show that  $|A| = |O|$ 
  - Both sets of bookings are of the same size
- Let  $A = \{i_1, i_2, \dots, i_k\}$ 
  - Assume sorted
  - $f(i_1) \leq s(i_2), f(i_2) \leq s(i_3), \dots$

# Correctness

- Our algorithm produces a solution  $A$
- Let  $O$  be an optimal set of accepted bookings
- $A$  and  $O$  need not be identical
  - Could have multiple allocations of the same size
- Just show that  $|A| = |O|$ 
  - Both sets of bookings are of the same size
- Let  $A = \{i_1, i_2, \dots, i_k\}$ 
  - Assume sorted
  - $f(i_1) \leq s(i_2), f(i_2) \leq s(i_3), \dots$
- Let  $O = \{j_1, j_2, \dots, j_m\}$ 
  - Also sorted
  - $f(j_1) \leq s(j_2), f(j_2) \leq s(j_3), \dots$



# Correctness

- Our algorithm produces a solution  $A$
- Let  $O$  be an optimal set of accepted bookings
- $A$  and  $O$  need not be identical
  - Could have multiple allocations of the same size
- Just show that  $|A| = |O|$ 
  - Both sets of bookings are of the same size
- Let  $A = \{i_1, i_2, \dots, i_k\}$ 
  - Assume sorted
  - $f(i_1) \leq s(i_2), f(i_2) \leq s(i_3), \dots$
- Let  $O = \{j_1, j_2, \dots, j_m\}$ 
  - Also sorted
  - $f(j_1) \leq s(j_2), f(j_2) \leq s(j_3), \dots$
- Our goal is to show that  $k = m$

# Greedy algorithm stays ahead

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$

# Greedy algorithm stays ahead

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- **Claim** For each  $\ell \leq k$ ,  $f(i_\ell) \leq f(j_\ell)$

# Greedy algorithm stays ahead

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- **Claim** For each  $\ell \leq k$ ,  $f(i_\ell) \leq f(j_\ell)$
- **Proof** By induction of  $\ell$

# Greedy algorithm stays ahead

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- **Claim** For each  $\ell \leq k$ ,  $f(i_\ell) \leq f(j_\ell)$
- **Proof** By induction of  $\ell$
- Base case:  $\ell = 1$

By greedy strategy,  $i_1$  has earliest overall finish time

# Greedy algorithm stays ahead

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- **Claim** For each  $\ell \leq k$ ,  $f(i_\ell) \leq f(j_\ell)$
- **Proof** By induction of  $\ell$
- Base case:  $\ell = 1$

By greedy strategy,  $i_1$  has earliest overall finish time

- Induction step: Assume  $f(i_{\ell-1}) \leq f(j_{\ell-1})$

# Greedy algorithm stays ahead

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- **Claim** For each  $\ell \leq k$ ,  $f(i_\ell) \leq f(j_\ell)$
- **Proof** By induction of  $\ell$
- Base case:  $\ell = 1$

By greedy strategy,  $i_1$  has earliest overall finish time

- Induction step: Assume  $f(i_{\ell-1}) \leq f(j_{\ell-1})$ 
  - $f(i_{\ell-1}) \leq f(j_{\ell-1}) \leq s(j_\ell)$

# Greedy algorithm stays ahead

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- **Claim** For each  $\ell \leq k$ ,  $f(i_\ell) \leq f(j_\ell)$
- **Proof** By induction of  $\ell$
- Base case:  $\ell = 1$

By greedy strategy,  $i_1$  has earliest overall finish time

- Induction step: Assume  $f(i_{\ell-1}) \leq f(j_{\ell-1})$ 
  - $f(i_{\ell-1}) \leq f(j_{\ell-1}) \leq s(j_\ell)$
  - If  $f(j_\ell) < f(i_\ell)$ , greedy strategy would pick  $j_\ell$



# Greedy algorithm stays ahead

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- **Claim** For each  $\ell \leq k$ ,  $f(i_\ell) \leq f(j_\ell)$
- **Proof** By induction of  $\ell$
- Base case:  $\ell = 1$

By greedy strategy,  $i_1$  has earliest overall finish time

- Induction step: Assume  $f(i_{\ell-1}) \leq f(j_{\ell-1})$ 
  - $f(i_{\ell-1}) \leq f(j_{\ell-1}) \leq s(j_\ell)$
  - If  $f(j_\ell) < f(i_\ell)$ , greedy strategy would pick  $j_\ell$
  - We must have  $f(i_\ell) \leq f(j_\ell)$

# Greedy strategy is optimal

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$

# Greedy strategy is optimal

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- Suppose  $m > k$

# Greedy strategy is optimal

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- Suppose  $m > k$
- We know  $f(i_k) \leq f(j_k)$

# Greedy strategy is optimal

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- Suppose  $m > k$
- We know  $f(i_k) \leq f(j_k)$
- Greedy strategy stops when  $B$  is empty

# Greedy strategy is optimal

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- Suppose  $m > k$
- We know  $f(i_k) \leq f(j_k)$
- Greedy strategy stops when  $B$  is empty
  - Consider request  $j_{k+1}$
  - Since  $f(i_k) \leq f(j_k) \leq s(j_{k+1})$ , this request is compatible with  $A$

# Greedy strategy is optimal

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- Suppose  $m > k$
- We know  $f(i_k) \leq f(j_k)$
- Greedy strategy stops when  $B$  is empty
  - Consider request  $j_{k+1}$
  - Since  $f(i_k) \leq f(j_k) \leq s(j_{k+1})$ , this request is compatible with  $A$
  - $j_{k+1}$  must still be in  $B$

# Greedy strategy is optimal

- $A = \{i_1, i_2, \dots, i_k\}$
- $O = \{j_1, j_2, \dots, j_m\}$
- Suppose  $m > k$
- We know  $f(i_k) \leq f(j_k)$
- Greedy strategy stops when  $B$  is empty
  - Consider request  $j_{k+1}$
  - Since  $f(i_k) \leq f(j_k) \leq s(j_{k+1})$ , this request is compatible with  $A$
  - $j_{k+1}$  must still be in  $B$
  - $B$  is not empty after choosing  $A$ , contradiction!



# Implementation

- Initially, sort  $n$  bookings by finish time —  $O(n \log n)$ 
  - Renumber bookings to reflect this sorted order

# Implementation

- Initially, sort  $n$  bookings by finish time —  $O(n \log n)$ 
  - Renumber bookings to reflect this sorted order
- Record start and finish times in array/dictionary
  - $S[i]$  is starting time of request  $i$
  - $F[i]$  is finish time of request  $i$

# Implementation

- Initially, sort  $n$  bookings by finish time —  $O(n \log n)$ 
  - Renumber bookings to reflect this sorted order
- Record start and finish times in array/dictionary
  - $S[i]$  is starting time of request  $i$
  - $F[i]$  is finish time of request  $i$
- Add first booking to  $A$

# Implementation

- Initially, sort  $n$  bookings by finish time —  $O(n \log n)$ 
  - Renumber bookings to reflect this sorted order
- Record start and finish times in array/dictionary
  - $S[i]$  is starting time of request  $i$
  - $F[i]$  is finish time of request  $i$
- Add first booking to  $A$
- In general, after adding booking  $j$  to  $A$ , Find the smallest  $r$  with  $S[r] > F[j]$ 
  - Single scan,  $O(n)$  overall

# Summary

- A greedy algorithm makes a sequence of locally optimal choices to achieve a global optimum

# Summary

- A greedy algorithm makes a sequence of locally optimal choices to achieve a global optimum
- The algorithm never goes back and reconsiders on a choice

# Summary

- A greedy algorithm makes a sequence of locally optimal choices to achieve a global optimum
- The algorithm never goes back and reconsiders on a choice
- Drastically reduces space to search for solutions, but need to show prove that local strategy is globally optimal

# Summary

- A greedy algorithm makes a sequence of locally optimal choices to achieve a global optimum
- The algorithm never goes back and reconsiders on a choice
- Drastically reduces space to search for solutions, but need to show prove that local strategy is globally optimal
- Interval scheduling — many “natural” greedy strategies



# Summary

- A greedy algorithm makes a sequence of locally optimal choices to achieve a global optimum
- The algorithm never goes back and reconsiders on a choice
- Drastically reduces space to search for solutions, but need to show prove that local strategy is globally optimal
- Interval scheduling — many “natural” greedy strategies
- Most of them are wrong!

# Summary

- A greedy algorithm makes a sequence of locally optimal choices to achieve a global optimum
- The algorithm never goes back and reconsiders on a choice
- Drastically reduces space to search for solutions, but need to show prove that local strategy is globally optimal
- Interval scheduling — many “natural” greedy strategies
- Most of them are wrong!
- Correct strategy needs a proof

# Summary

- A greedy algorithm makes a sequence of locally optimal choices to achieve a global optimum
- The algorithm never goes back and reconsiders on a choice
- Drastically reduces space to search for solutions, but need to show prove that local strategy is globally optimal
- Interval scheduling — many “natural” greedy strategies
- Most of them are wrong!
- Correct strategy needs a proof
- One way is to show that greedy solution “stays ahead”, step by step, of any optimal solutions