CHAPTER 1

INTRODUCTION

1.1 DEFINITION OF HYPOTHERMIA

Hypothermia is a medical emergency condition that can lead to death. This condition occurs when the body baseline temperature drops below 95°F (35°C) due to loss of heat. Shivers, confusion, slurs, as well as movements become difficult, and it's just the beginning – in a matter of time, breathing and pulse rates decrease, and the desire to shiver fades. There are three different stages of hypothermia, mild, moderate, and severe, which occur at a baseline base line of 95°F, 90°F and 82°F respectively. Enduring subzero temperatures is one of the main causes of frostbite, especially in extreme wet conditions, even people indoors tend to get this condition, and without any form of treatment they might end up with heart failure.

1.2 CAUSES OF HYPOTHERMIA

Core body temperature drops below 95°F (35°C) when your body loses heat faster than it can produce it. This happens through several mechanisms:

Environmental Exposure:

- Cold temperatures, especially when combined with wind (wind chill), Cold water immersion (water conducts heat away 25 times faster than air)
- Inadequate clothing or shelter for conditions, or wet clothing, which loses its insulating properties

Medical Conditions:

- Age extremes (very young and elderly are more susceptible)
- Certain medications that affect body temperature regulation
- Endocrine problems (hypothyroidism, diabetes)
- Severe trauma or illness and malnutrition
- Spinal cord injuries affecting temperature regulation

Behavioral/Situational:

- Alcohol or drug use (impairs judgment and reduces sensation of cold)
- Exhaustion and dehydration
- Remaining immobile for long periods in cold conditions
- Getting lost or stranded in cold environments

1.3 SYMPTOMS OF HYPOTHERMIA

1. Mild Hypothermia's (Early Symptoms Mortal Range): 95-89.6°F / 35-32°C.

- Intense feeling of shivering that is unrestrainable.
- The skin becomes pale and loses heat.
- Words become slurred during speech.
- One of the early signs can include difficulty to think rationally or confuses easily.
- Coordination becomes poorly maintained and movement turns more clumsy. Rapid inhalation occurs.
- Lethargy and tiredness.

2. Moderate Hypothermia (89.6-82.4°F / 32-28°C):

- shivering may stop
- Increased muscle stiffness
- Slower, shallow breathing
- Further confusion and disorientation
- Drowsiness
- Weak pulse
- Poor judgment and irrational behavior (like paradoxical undressing)

3. Severe Hypothermia (Below 82.4°F / 28°C):

- No shivering
- Blue-gray or very pale skin
- Loss of consciousness
- Little or no breathing
- Weak or difficult to find pulse
- Pupils may be dilated
- Rigid muscles
- May appear dead but could still be revived

4. Critical Warning Signs Requiring Immediate Medical Attention:

- Stopped shivering despite being very cold
- Severe confusion or unusual behavior
- Loss of consciousness
- Very shallow or no breathing
- Weak or absent pulse

1.4 CASE STUDY OF HYPOTHERMIA

A 23-year-old male soldier experienced severe hypothermia during a winter mountain warfare training exercise at 8,500 feet elevation. The incident occurred when he became separated from his unit during a snowstorm and was found unresponsive after four hours of exposure. Upon initial field assessment, the soldier's core temperature was 86°F (30°C), with a pulse of 45 beats per minute and a respiratory rate of 10 breaths per minute. He was unconscious but responsive to painful stimuli, exhibiting severe muscle rigidity. His clothing was wet from both snow and sweat, though notably, he showed no signs of frostbite.

Several factors contributed to his condition, including intense physical exertion that led to sweating, wearing a cotton base layer that retained moisture, separation from his unit during whiteout conditions, and significant dehydration from extended exercise. The situation was further complicated by exhaustion from a 12-hour training mission and inadequate caloric intake during the operation.

Field treatment was initiated immediately, beginning with the removal of wet clothing and insulation with dry blankets and a vapor barrier. Chemical heat packs were applied to core areas, along with hot water bottles placed in the axilla and groin regions. A field shelter was established using group body heat, and once conscious, the soldier was given warm, sweet liquids.

A helicopter evacuation was initiated within 30 minutes, during which careful immobilization was maintained to prevent after-drop, and active external rewarming continued. Upon reaching the hospital, treatment included warmed IV fluids, continued active external rewarming, cardiac monitoring, treatment of mild rhabdomyolysis, and careful electrolyte monitoring and correction.

During recovery, the soldier experienced several complications, including transient cardiac arrhythmias during rewarming, mild muscle breakdown, short-term memory issues, and

heightened cold sensitivity that persisted for several months. However, his core temperature normalized after six hours, and he was discharged after three days. He returned to light duty after one week and resumed full duty status after three weeks, ultimately suffering no long-term complications.

This incident led to several important training improvements, including enhanced buddy system protocols, mandatory proper cold-weather gear checks, improved hydration and nutrition protocols, additional cold-weather survival training, and updated emergency response procedures. The case served as a valuable learning experience, highlighting the critical importance of proper cold-weather gear, strict adherence to the buddy system, proper nutrition and hydration, rapid field response, and specialized cold-weather training in military operations.

1.5 MOTIVATION

- The project titled "Bridging Distance to Fight Hypothermia" stems from the worry of how to safeguard the weak between cold bordering soldiers and colder place tourists.
- Unfortunately, many of us underestimate someone's hypothermia condition and how such medical problems can be so extreme.
- This project has an aim to mitigate the illness by emphasizing the symptoms, treatment and preventive measures that can be taken.
- In addition, soldiers and tourists are common people who need to have proper information about the indication so that they can act in time to prevent severe damage from occuring.
- Most importantly, we are trying to ensure the people that travel are not susceptible to these medical conditions and are protected adequately when carrying out their duties.

1.6 PROBLEM STATEMENT

- **Accidents Involving Water and Having a Cold Climate Setting:** Rescue operations in cold environments and in water related accidents are notably difficult to accomplish. Rescuing someone in these types of accidents is considered dangerous, which may lead to fatal consequences
- **Limitations of Current Rescue System**: The lack of technology for real-time tracking and communication serves as a hindrance to current rescue systems. The major known systems also

exhibit an inability to adapt to various environmental factors, such as extreme weather, dense terrains, or open water conditions.

- **Healthcare Access and Delayed Diagnoses:** In reality, the limited access to any form of medication and poor connectivity in some geographically isolated, rural areas really delay diagnoses such that patients lose the window that would have let them seek actual medical attention well.

1.7 OBJECTIVE

- Develop a system for real-time location tracking and communication to enhance rescue operations in harsh environments like cold climates and water-related emergencies.
- Ensure accessibility to advanced diagnostic tools in remote and underserved regions to reduce healthcare disparities and enable timely interventions.
- Integrate wearable health monitoring devices, advanced sensors, and robust communication networks to streamline rescue and healthcare delivery.
- Enhance safety and reduce fatalities by minimizing delays in emergency responses and medical diagnoses for at-risk individuals.

CHAPTER 2

LITERATURE SURVEY

This chapter confers about the literature survey which helps in establishing and developing familiarity with other people's work relevant to our field of study. It provides an overview of current knowledge, allowing us to identify relevant theories, methods and the gaps in the existing research.

2.1 Literature Review

[1] IoT-Based Smart Life Jacket for Water Safety:

The IoT-Based Smart Life Jacket enhances the safety of water tourist spots through health monitoring and alert features. It sends real-time health data to a server via HTTP for emergency alerts. However, the system lacks detailed implementation and raises scalability concerns in high-user scenarios. Moreover, real-world validation is required to evaluate its practicality and reliability. Although promising, further testing and refinement are necessary to establish it as an effective and robust water safety solution.

[2] LoRa-Based Intelligent Jacket for Worker Safety:

The IoT-Based Smart Life Jacket enhances the safety of water tourist spots through health monitoring and alert features. It sends real-time health data to a server via HTTP for emergency alerts. However, the system lacks detailed implementation and raises scalability concerns in high-user scenarios. Moreover, real-world validation is required to evaluate its practicality and reliability. Although promising, further testing and refinement are necessary to establish it as an effective and robust water safety solution.

[3] Energy-Efficient Wearable System:

The Energy-Efficient Wearable System combines many forms of energy-harvesting technologies to supply wearable gadgets. These energy-harvesting technologies may be solar panels, piezoelectric shoes, and even thermoelectric fabric. Using environmental sources of sunlight, movements, and heat, the wearable device is designed to generate this power. As flexible battery choices are not possible in this device, lithium polymer and lithium-ion are the batteries available for this system for storage purposes. Although the approach may promise sustainability, with prolonged life for the batteries, the very system's basis on traditional types of batteries prevents flexibility and even requires further innovation in energy storage to fully harness the wearable device's potential.

[4] LoRa-Based IoT Monitoring for Military Operations:

Soldier health monitoring and location tracking use case rely on low-data-rate, long-distance signal transmission, ensuring reliable military communications. Such an approach is especially useful in rugged, remote environments where traditional communication networks might be unreliable or unavailable. The system allows for continuous monitoring of health parameters and real-time location tracking of soldiers without overloading the network with excessive data by using technologies such as LoRa or other LPWAN. Although promising, challenges remain in ensuring data security, real-time processing, and seamless integration with military operations, requiring further research and development for deployment in real-world scenarios.

[5] LoRa Technology in Remote Areas:

Long-range capabilities with low power consumption, LoRa technology is very appropriate for use in remote areas especially where the challenging environment of water bodies would prevent the proper communication networks. With its minimal energy usage and its ability to send data for miles, LoRa technology makes continuous monitoring and communication possible in underserved areas. This makes LoRa particularly useful for applications like water safety, environmental monitoring, and remote worker health tracking. However, it still needs further development to address data security, real-time communication in such specific environments, and scalability of networks.

[6] Solar Energy Harvesting for Sustainable Wearables:

It uses the possibilities that solar harvesting energy technology opens to develop the capability of wearables as an uninterrupted, continuously health-monitoring technology with potential as a solution towards sustainability. Thus, for a wearable integrating a solar panel in its infrastructure, ambient light will be collected, and solar power will allow these sensors-sensing vital signs to be functional continuously. This approach reduces the need for frequent battery replacements and enhances the convenience and sustainability of long-term health monitoring. However, the efficiency of energy harvesting is still an issue, especially in low-light conditions, and the reliability of the system in continuous monitoring without interruptions. Further research is required to overcome these limitations and improve the practicality of solar-powered wearable devices.

[7] LoRa-Based System for Remote Location Tracking:

The LoRa-based system is significantly more advantageous than GSM-based systems since it autonomously identifies and localizes victims in remote areas where GSM coverage is unavailable. It is especially useful for applications in regions such as remote rural areas or water bodies, where traditional communication networks fail to provide reliable connectivity. The system ensures continuous communication and real-time location tracking through the long-range, low-power capabilities of LoRa, thus improving emergency response efforts. However, the effective deployment of such networks in areas still requires an answer to network infrastructure and the necessity of integration into existing systems.

[8] Challenges with Wearable Smart Jackets for Underground Miners:

The challenges of using wearable smart jackets for underground miners are numerous and deter their effectiveness. Major disadvantages include unavailability of a few vital sensors, like pulse sensors, that may be very much required for observing the health condition of miners in real time. Besides, the complicated algorithms used in the ubiquitous computing method for processing the data may not be practical and sometimes unreliable in such a hostile environment underground. This is yet another significant limitation in the sense that miners have to have smartphones for communication purposes, which is impractical under some situations because it may cause problems with networks and has battery limitations, which the environment does not respect. These pose a challenge towards further advancements in sensor technology, optimization of the algorithm, and alternative communication methods to enhance the usability and reliability of wearable safety systems for underground miners.

[9] Optimizing Data Processing in Water-Based Accident Scenarios:

The techniques discussed in optimizing energy consumption and enhancing real-time data retrieval in water-based accident scenarios include Map Reduce infrastructure, data segregation algorithms, and query processing optimization. These methods aim to efficiently process and manage large volumes of data in real-time, ensuring timely decision-making during emergencies. In addition, the use of fuzzy logic and mobile cloud resource allocation is applied in improving the efficiency of the system and minimizing latency, allowing quick response in emergency situations.

[10] Disadvantages of Solar-Powered Wearable Systems:

The other techniques discussed involve optimizing energy consumption. One of the major challenges of these systems is the complexity, which can deter further implementation and scalability. Integration of multiple components such as sensors, processing data algorithms, and communication networks calls for proper coordination and this may introduce potential points of failure. It may also hinder the execution by creating undue dependence on specific components like smartphones for communication. In areas where phones are not accessible, available, or practical—for example, in distant or high-risk environments—this reliance is a severe limitation. Such factors make it difficult to deploy the system initially and sustain it over time, which again points to a need for stronger, independent communications solutions and simpler, more robust designs.

CHAPTER 3

PROPOSED WORK

3.1 PROJECT SETUP:

The proposed model is a unique system which helps in fighting against hypothermia in cold harsh environments. Based on this, the temperature of a person is monitored continuously along with other provided facilities and supplies heat to the body in order to prevent hypothermia. These vital data of the user is monitored easily through the different deciding factors that can lead to hypothermia or severe injury to a person due to fall.

BLOCK DIAGRAM




Fig.3.1.1 Block Diagram of Transmitter & Receiver Side of the LoRa-Based Life Jacket

The Fig.3.1.1 consists of all the components embedded in the Lo-Ra Based Life Jacket. The transmitter which will be present within the "Jacket" consists of components such as Pulse Rate Sensor, Temperature Sensor, GPS Module, Peltier Modules, Accelerometer Sensor and the receiver which is placed in the rescue team centre and or the Control Office consists of components such as a Buzzer and 16x2 LCD with I2C is connected to display the readings.

Communication between the transmitter and receiver is seamlessly implemented using **LoRa Technology**, which ensures reliable long-range data transmission even in challenging environments. All the components are interfaced with a **Raspberry Pi Pico microcontroller**, which serves as the central processing unit for data collection, analysis, and transmission.

The primary objective of this system is to detect early symptoms of **hypothermia** and provide timely intervention. The system continuously monitors the wearer's body temperature, and if it drops below a predefined threshold, the **Peltier module** is activated to deliver heat, thereby preventing the onset of severe hypothermia. This proactive approach not only safeguards the individual's health but also enhances their chances of survival in extreme conditions.

By integrating advanced sensors, reliable communication technology, and effective heating mechanisms, the LoRa-based life jacket offers a comprehensive solution for monitoring and protecting individuals in potentially life-threatening situations.

3.2 SYSTEM ARCHITECTURE

The whole system can be divided into two main categories: the Hardware and the Software.

HARDWARE

- Power Supply
- Pulse Rate Sensor
- Accelerometer Sensor
- Temperature Sensor
- GPS Module
- Peltier Module
- Lora Transmitter/Receiver
- Raspberry Pi Pico
- LCD Display

SOFTWARE

- Arduino IDE

3.2.1 HARDWARE DESIGN

1. Raspberry Pi Pico

The Raspberry Pi Pico is used as the microcontroller for both the transmitter and receiver due to its affordability, compact size, and power efficiency. It offers sufficient GPIO pins to interface with peripherals like LoRa modules and sensors.

With its dual-core ARM Cortex-M0+ processor, it can handle communication and data processing efficiently.



Fig. 3.2.1.1 Raspberry Pi Pico

Table.3.2.1.1 Raspberry Pi Pico and its comparison with other boards

Feature	Raspberry Pi Pico	Arduino Uno	ESP32	Raspberry Pi 4
Processing Power	Dual core ARM	16Mhz	Dual core Xtensa LX6	Quad core cortex-A72
Power consumption	Low	Low	Moderate	High
GPIO pins	26	14	38	40
Cost	Very affordable	Affordable	Moderate	Expensive
Programming Environment	C, MicroPython	C, Arduino IDE	C, MicroPython, Arduino IDE	Linus based

2. Power Supply

Currently, the power supply to all the components except for the Peltier module is supplied through the Raspberry Pi Pico's 3.3V and the microcontroller itself is supplied a 5V through a power bank.

3. Pulse Rate Sensor

The Pulse Rate Sensor (SEN11574) (Fig. 3.1.1.2) is a heartbeat-detecting and biometric pulse rate sensor. It operates at a voltage range of +3.3V and consumes 4mA current. However, it is not FDA-approved and is intended for student-level projects rather than commercial or medical applications.

The sensor operates by positioning the LED over a vein, typically on the fingertip or earlobe, directly above the skin layer. The LED emits light, which interacts with the blood flowing through the veins. As the heart pumps, the flow of blood changes. These changes affect the amount of light reflected or absorbed, and the ambient light sensor detects these variations. The data is then processed to calculate the pulse rate.

This compact and easy-to-use sensor allows users to measure heart rates effectively for non-critical applications, making it a popular choice for educational and experimental purposes.

4. Accelerometer Sensor

An accelerometer sensor (Gy61AD XL335) is a tool that measures the acceleration of any body or object in its instantaneous rest frame. The force caused by vibration or a change in motion (acceleration) causes the mass to **"squeeze"** the piezoelectric material which produces an electrical charge that is proportional to the force exerted upon it.

The ADXL335 measures acceleration in three orthogonal axes: X, Y, and Z, allowing it to detect movement and orientation in three-dimensional space. We calculate the resultant acceleration using the formula mentioned and then define a threshold acceleration which when satisfies the condition that a person is falling and has hit the ground alerts the rescue team.

$$A_{Resultant}=\sqrt{x_{acc}^2+y_{acc}^2+z_{acc}^2}$$



Fig. 3.2.1.3 SEN11574 Pulse Rate Sensor




Fig. 3.2.1.4 Gy61AD XL335 Accelerometer Sensor

5. **Temperature Sensor**

This Maxim-made item is a digital thermo probe or sensor that employs DALLAS DS18B20. Its unique 1-wire interface makes it easy to communicate with devices. Besides, it can measure temperatures from -55°C to +125°C (-67F to +257F). In addition, this thermo probe doesn't require any external power supply since it draws power from data line.

This works along with the Peltier module to ensure that whenever the user's body temperature drops below 30°-35°C it triggers the Peltier module to **'Switch ON'** thereby heating the user's body bringing it back to the normal temperature (i.e. above 37° C).

6. **GPS Module**

A GPS module (NEO-6M) uses a receiver chip, antenna, and CPU to receive signals from satellites and calculate a location. The module uses a process called trilateration,

Trilateration: Trilateration uses the distance from at least three known points to calculate the position of a target. The distance is calculated using the rate and time, where

Distance = Rate × Time.

With the help of this module, we can obtain the exact coordinates of the user in the form of latitude and longitude.

7. **Peltier Module**

Peltier module (thermoelectric module) is a thermal control module that has both "warming" and "cooling" effects. But in our project, we are mainly focusing on the usage of "warming" side. By passing an electric current through the module, it is possible to change the surface temperature and keep it at the desired temperature.

The Peltier module is a high-current device, so it can't be driven directly by the Pico's GPIO pins. Instead, it is connected using a relay module to control it. The Peltier is controlled using a decision tree and is turned on only in the case of low temperature measured by the temperature sensor.



Fig. 3.2.1.5 DS18B20 Temperature Sensor



Fig. 3.2.1.6 NEO-6M GPS Module

8. Lora Transmitter/Receiver

The connection between the transmitter and receiver has been successfully established using LoRa technology, which is specifically designed for long-range communication. This system ensures reliable data transmission over extended distances without relying on internet connectivity, making it highly efficient for remote applications.

By utilizing LoRa, the setup becomes cost-effective, energy-efficient, and suitable for scenarios where internet access is limited or unavailable. This robust communication method enhances the reliability and functionality of the entire system.



Fig. 3.2.1.7 TEC1-12706 Peltier Module




Fig. 3.2.1.8 LoRa RA-02 Module

9. LCD Display

We are using a **16x2 LCD display** with I2C to show all the user's vitals in a rotating system for better readability. The display will also indicate whether the Peltier module is currently active or not.

Additionally, it will provide alerts if the accelerometer detects a fall, ensuring the user's safety. This system combines vital monitoring, fall detection, and heating status in a compact and efficient display, enhancing the functionality and usability of the overall setup.




Fig. 3.2.1.9 Raspberry Pi Pico

3.2.2 COMMUNICATION MODULE DESIGN

The communication module is designed using LoRa (433 MHz) technology, which is highly suitable for long-range, low-power applications such as IoT. LoRa operates effectively over distances of up to 10–15 km in rural areas and approximately 210 m in urban environments. However, in urban areas, the coverage is reduced due to increased noise, interference, and the presence of jammers. These factors impact signal propagation, requiring careful planning in dense city deployments.

This module's extremely low power consumption makes it ideal for battery-operated devices. Though the data rate is limited to 0.3–50 kbps, it is sufficient for small data packets typical in IoT use cases. LoRa's high resistance to interference ensures reliable communication in noisy conditions.

The technology's low cost, energy efficiency, and ability to function without internet connectivity make it an optimal choice for scalable, long-range communication in both rural and urban areas.

Fig. 3.1.1.9 represents a brief comparison of different communication technologies and why LoRa Module is preferred.

Table 3.1 shows a brief comparison of LoRa with all other technologies and why it is much preferred.




Fig. 3.2.2 Comparison of different communication technologies

Table.3.1. Comparison of LoRa with other Technologies

Feature	LoRa(433Mhz)	Wi-Fi	GSM (Mobile networks)	Bluetooth
Range	Up to 10-15km in rural areas, ~210m in urban areas (as tested by us)	~50-100m indoors, ~300m outdoors	Several kilometers, depending on the network availability	~10-100m, depending on the version
Connectivity	No internet required direct device-to -device	Requires an internet router	Requires cellular network coverage	Required paired devices in close proximity
Power consumption	Extremely low	high	high	low
Cost	low	medium	high	low
Data rate	Low (0.3-50kbps)	High (up to several Mbps)	Medium to high	high
Inference resistance	High (resilient in noisy environments)	Moderate	High	Low to moderate
Use case Suitability	Ideal for long range low power applications like IOT	Suitable for short-range, high bandwidths	Good for voice and data, but requires infrastructure	Best for short range, low-bandwidth applications

3.3 USER APPLICATION

BLOCK DIAGRAM:




Fig.3.2.1 Block Diagram of User Application

The block diagram of the user application is shown in Fig. 3.2.1. First, the system is initialized, during which it sets up the LoRa connection. The jacket, designed for user convenience, houses multiple sensors, including a pulse rate sensor, temperature sensor, accelerometer, Peltier pads, and a GPS module. These sensors continuously collect vital data about the user. The LoRa transmitter sends the collected data to the receiver in the form of packets. Additionally, the signal strength of the communication is displayed on the Arduino IDE Serial Monitor, along with the monitored vital parameters.

The decision-making system uses a predefined decision tree to monitor temperature, pulse rate, and resultant acceleration. These parameters are evaluated continuously to determine the user's condition. When specific conditions are satisfied based on the decision tree logic, the Peltier pads and buzzer are activated.

For example, the Peltier pads may provide heating or cooling based on the detected temperature, while the buzzer can signal critical health alerts or unsafe conditions.

This monitoring system ensures that the user receives timely feedback and interventions to maintain their comfort and safety. The following subsections provide a detailed explanation of the working principles and the integration of the various components in this model.

3.3.1 BODY TEMPERATURE CONTROL

The regular human body temperature is typically above 37°C. However, when the body temperature falls between 32°C and 35°C, it signals the early stages of hypothermia. Hypothermia's foremost and most critical symptom is a significant drop in body temperature, often followed by dizziness and fatigue. To address this, our model incorporates an all-time temperature monitoring system alongside Peltier pads to provide effective intervention.

When the body temperature falls below 30°C, the Peltier module is automatically activated to help restore normal body temperature. The Peltier operates using a power supply rated at 12-15V, which cannot be directly connected to the Raspberry Pi Pico due to its 3.3-5V voltage rating. To overcome this limitation, a relay module is employed, allowing the Raspberry Pi Pico to safely control the Peltier module.

The Peltier pad can reach temperatures of up to 90°C, with the heating speed adjustable to suit the user's needs. This feature helps in gradually increasing body temperature to safe levels. Once the temperature rises above 30°C, the Peltier module automatically switches off, ensuring the user's safety and preventing overheating.

Additionally, the activation and deactivation of the Peltier module are reported to the Rescue Operation Team, enabling continuous monitoring and timely responses to critical situations. This ensures comprehensive safety and care for the user.

3.3.2 BODY VITALS MONITORING

Another notable feature of the model is the inclusion of an accelerometer, which measures the user's body acceleration in three dimensions—x-axis, y-axis, and z-axis. To simplify the rescue operation's analysis of acceleration data, we calculate the resultant acceleration using the formula:

$$A_{Resultant} = \sqrt{x_{acc}^2 + y_{acc}^2 + z_{acc}^2}$$

The resultant acceleration provides a clearer understanding of the user's movement and is instrumental in detecting falls or injuries. However, relying solely on a single threshold for resultant acceleration can lead to false positives, such as mistaking a minor trip or stumble for a fall.

To address this limitation, the system evaluates two critical factors:

1. The resultant acceleration caused during free fall, where acceleration is primarily dependent on gravity.
2. The acceleration generated when the user's body impacts the ground.

   A pre-defined delay is used to analyze these two events sequentially, ensuring accurate detection of a true fall while avoiding false alerts.

   In the event of a confirmed fall, the system activates a buzzer located at the receiver's end with the rescue team. This immediate notification allows the rescue team to respond promptly, providing first aid and necessary assistance to the injured user. This dual-sensor integration ensures enhanced safety, offering both accurate fall detection and timely alerts to rescue operations.

3.3.3 USER TRACKING

Having a user's precise coordinates is highly advantageous, especially during emergencies when immediate attention is required. With the integration of a GPS module, the exact location of the user can be determined in real time using latitude and longitude coordinates. These coordinates are continuously transmitted to the rescue team, enabling them to locate the user swiftly and efficiently.

The GPS module, when connected to a satellite, provides highly accurate and reliable location data. This precision is crucial in scenarios where every second matters, such as in the case of severe injuries, falls, or medical emergencies.

Tracking the user's location is particularly beneficial in situations where early symptoms of hypothermia are detected. Hypothermia can escalate quickly if not addressed promptly, making it vital for the rescue team to pinpoint the user's location without delay. By receiving the user's coordinates in real time, medical assistance can be directed to the affected individual more efficiently, potentially saving lives.

This seamless integration of location tracking ensures a higher level of safety and responsiveness, especially in challenging environments where the user may be isolated or difficult to locate manually. The GPS module, therefore, serves as a critical component of the rescue operation, enhancing both efficiency and effectiveness in emergency scenarios.

CHAPTER 4

RESULT

4.1 OUTCOMES

4.1.1 BODY TEMPERATURE CONTROL

To implement body temperature control, we utilized the **DS18B20 temperature sensor** to monitor the body temperature in real time. The DS18B20 is a digital thermometer with an accuracy of ±0.5°C, over the range of -55°C to +125°C. Its small size and precise readings made it ideal for this application.

We integrated the sensor with a **Peltier module**, a thermoelectric device capable of both heating and cooling. The specific Peltier module used in our system has a heating capability of up to **90°C**, ensuring it can provide adequate thermal energy when required. The module is powered by an external DC power source to handle its energy-intensive operation.

A **relay module** was employed to control the operation of the Peltier module. The relay acts as an electronic switch, toggling the module on or off based on temperature readings from the DS18B20 sensor.

Our system was designed to maintain a target temperature of **30°C (just for testing purposes)**, with the following control logic:

- **When the temperature exceeds 30°C**, the relay turns the Peltier module **off**, preventing overheating.
- **When the temperature falls below 30°C**, the relay activates the Peltier module to provide heat and maintain the desired range.

The system was tested for its efficiency and responsiveness:

- The DS18B20 accurately tracked temperature fluctuations.
- The relay-controlled Peltier module ensured smooth and automated thermal management, capable of adapting to real-time temperature changes.

This configuration successfully achieved a balance between maintaining comfort and ensuring the safe operation of the components.

4.1.2 BODY VITAL MONITORING

The body vital monitoring system is designed to track key physiological parameters of an individual. For this purpose, we incorporated a **pulse rate sensor** and a **temperature sensor** to monitor the person's body condition.

4.1.2.1 Pulse Rate Monitoring

The pulse rate sensor utilized in our setup measures the heart rate by detecting changes in blood volume through a photoplethysmogram (PPG) technique.

The pulse rate sensor in our system works based on **Photoplethysmogram (PPG)** technology. PPG is a non-invasive optical technique that measures changes in blood volume in the microvascular bed of tissue. It works by shining a light, typically from an LED, onto the skin and measuring the amount of light reflected or transmitted. Changes in blood volume caused by the heartbeat result in corresponding changes in the light intensity, which are captured by a photodetector to calculate the pulse rate.

While it provides basic functionality for real-time monitoring, it is **important to note that the sensor is not as accurate as clinical-grade heart rate monitors**. Despite this limitation, it serves as an effective, low-cost solution for applications where precise medical accuracy is not critical.

4.1.2.2 Temperature Monitoring

The **DS18B20 temperature sensor** was used to monitor body temperature. It offers a digital interface, high precision (±0.5°C), and a wide temperature range of -55°C to +125°C, making it suitable for detecting changes in body temperature.

Together, these sensors allow for continuous monitoring of vital signs, providing valuable insights into the individual's condition. While the system's accuracy is sufficient for general-purpose monitoring, future improvements could involve integrating higher-grade sensors for enhanced reliability and precision.

4.1.3 USER TRACKING

The user tracking system is designed to monitor a person's location and motion in real time, enabling immediate response in emergency situations. This system integrates a **GPS module** and an **accelerometer sensor** to achieve comprehensive tracking.

4.1.3.1 GPS Tracking

We used the **NEO-6M GPS module** to extract the person's latitude and longitude coordinates. The module is highly efficient and capable of quickly locking onto satellites, especially in low-disturbance environments such as open or remote areas. This makes the system particularly well-suited for usage in rural or isolated regions where other location-tracking solutions might struggle. Continuous GPS updates ensure precise, real-time location monitoring, which is critical for performing timely rescue operations.

4.1.3.2 Motion Detection and Fall Identification

An **accelerometer sensor** is employed to monitor the user's motion. By calculating the **resultant acceleration** using the formula:

$$A_{resultant} = \sqrt{x_{acc}^2 + y_{acc}^2 + z_{acc}^2}$$

The accelerations along the X, Y, and Z axes, we can detect patterns indicative of unusual movements or impacts.

- **Free Fall Detection**: A significant drop in the resultant acceleration below a threshold indicates a free fall.
- **High Impact Detection**: Sudden spikes in the resultant acceleration exceeding a predefined threshold suggest a high-impact event, such as a fall.


When these conditions are detected, it is assumed that the person may have fallen unconscious.

SYSTEM ADVANTAGES

- The GPS module's quick satellite locking and consistent updates make it highly reliable for continuous location tracking, particularly in remote areas.
- The accelerometer-based motion analysis provides an effective way to detect falls and other critical events.

This system offers an efficient solution for real-time user monitoring and enhances rescue operations through precise tracking and fall detection capabilities.

Fig. 4.1.1 The output of the Serial Monitor at the Receiver Side



4.2 COMMUNICATION MODULE DESIGN

The communication module is designed to ensure reliable and efficient data transmission between devices. For this purpose, we utilized LoRa (Long Range) technology due to its low-power consumption, long-range capabilities, and robust performance in remote areas.

4.2.1 LoRa Communication

We implemented LoRa modules for transmitting and receiving data packets. The system operates on a frequency of 433 MHz, which is well-suited for long-range communication in environments with minimal interference.

- **Data Transmission:** The data, such as location, motion, and temperature readings, is transmitted wirelessly from the sender module.
- **Data Reception:** The receiver LoRa module ensures that the exact packet of data sent by the transmitter is received without loss or corruption.

4.2.2 Limitations Observed During Experimentation

While LoRa performed well in open and rural environments, our experimentation revealed certain limitations in urban areas:

- Reduced Range: In densely populated urban settings with multiple obstructions such as buildings, the range of LoRa communication was significantly reduced. The signal could only reliably cover distances of up to 210 meters. Beyond this range, the signal was either weak or completely lost.
- Interference Sensitivity: High levels of radio frequency interference in urban areas also impacted the signal quality and reliability.

These findings suggest that while LoRa is an excellent choice for rural and remote applications, its effectiveness in urban environments may be limited. Future enhancements could explore alternative communication technologies or hybrid systems to overcome these challenges.

4.3 APPLICATION

The project has a wide range of applications, focusing on combating hypothermia, health monitoring, and ensuring safety in extreme environments. Below are the key applications:

4.3.1 Combating Hypothermia in Harsh Weather Conditions:

- **Indian Soldiers and Army Personnel**: Indian soldiers posted in regions with extreme cold weather, such as the Siachen Glacier or other high-altitude areas, face a constant risk of hypothermia. Our project can monitor their body temperature in real time and provide heat using the Peltier module to maintain a safe body temperature. This technology enhances their survivability and operational effectiveness in harsh climates.

- **Tourists and Adventurers:** Tourists and adventure enthusiasts who explore cold regions such as the Himalayas or participate in winter sports often encounter sub-zero temperatures. This system can serve as a portable device to monitor vital signs and provide necessary warmth, ensuring their safety during such activities.

4.3.2 Health Monitoring:

- **General Health Monitoring:** The integration of pulse rate and temperature sensors allows this system to monitor vital health parameters, making it useful for elderly individuals, patients recovering from illness, or individuals in remote areas without access to advanced medical facilities.

- **Emergency Fall Detection**: The system's ability to detect falls and provide precise GPS location information makes it invaluable for health monitoring, particularly for individuals prone to falls, such as senior citizens or people with certain medical conditions.

4.3.3 Search and Rescue Operations:

The GPS tracking system can be used to locate individuals in emergencies, such as avalanches, mountain accidents, or other critical situations in remote or extreme weather regions.

4.3.4 Outdoor Safety for Remote Workers:

Workers in cold regions, such as miners, forest officials, or engineers stationed in remote areas, can benefit from this system to ensure their safety and maintain optimal body temperature.

4.4 ADVANTAGES

4.4.1 LoRa for Communication in the Absence of Wi-Fi or Internet

One of the most significant advantages of our project is the use of **LoRa (Long Range)** communication. Unlike systems that rely on Wi-Fi, mobile networks, or internet connectivity, LoRa enables seamless data transmission over long distances in areas with no network coverage. This makes the system highly reliable in remote regions, such as:

- High-altitude military postings (e.g., Indian Army personnel in Siachen Glacier).
- Isolated villages and forests.
- Emergency situations where traditional networks might fail.

By transmitting vital data such as GPS coordinates, body temperature, and motion status using LoRa, rescue operations and monitoring systems can continue functioning uninterrupted in critical conditions.

4.4.2 Comprehensive Sensor Integration

Our project combines multiple sensors to provide a holistic approach to body vital monitoring and fall detection:

- **DS18B20 Temperature Sensor**: Ensures precise body temperature readings to combat hypothermia effectively.
- **Pulse Rate Sensor**: Offers real-time heart rate monitoring, which, although not as accurate as clinical devices, provides vital health insights in the absence of professional medical equipment.
- **Accelerometer Sensor**: Detects free falls and high impacts, enabling timely alerts for emergencies.
- **GPS Module (NEO-6M)**: Provides real-time location tracking to enhance safety and facilitate rescue operations.

This integration of sensors ensures that the system is equipped to handle a wide range of scenarios, offering functionality beyond what most existing single-purpose devices provide.

4.4.3 Superior to Existing Methodologies

Compared to existing methods, our project offers several unique advantages:

- **Portability and Versatility**: Unlike large and cumbersome equipment, our system is compact and can be used by soldiers, adventurers, tourists, and individuals in remote areas.
- **Real-Time Data Processing**: The system continuously monitors health parameters and environmental conditions, providing immediate feedback and response.
- **Cost-Effectiveness**: By using components like LoRa and affordable sensors, our solution is more budget-friendly than high-end systems that require constant connectivity or advanced infrastructure.
- **Rescue Optimization**: The combination of GPS tracking and fall detection enables faster rescue operations, which is a critical improvement over traditional systems that lack integrated tracking.

4.4.4 Designed for Extreme Conditions

The system's robust performance in extreme cold and remote areas makes it ideal for applications where traditional devices fail, such as high-altitude postings, harsh weather expeditions, and isolated rural setups.

4.4.5 Energy Efficiency

The low power consumption of LoRa and efficient sensors ensures that the system can operate for extended periods without frequent recharging, making it highly practical for field use.

4.4.6 Multipurpose Application

This project is not limited to hypothermia prevention but also addresses health monitoring, safety tracking, setting it apart from existing single-function solutions.

4.5 DRAWBACKS

4.5.1 LoRa Limitations

- **Reduced Range in Urban Areas**: During experimentation, it was observed that the range of LoRa communication drops significantly in urban areas due to interference and obstructions such as buildings. The reliable range was limited to around **210 meters**, which may not be sufficient for certain applications.
- **Limited Bandwidth**: LoRa's low data rate is suitable for transmitting small packets of data, such as temperature or GPS coordinates. However, it is not ideal for applications requiring high-bandwidth communication, such as video or audio streaming.
- **Dependency on Specific Frequencies**: LoRa's performance depends on using specific frequencies (e.g., 433 MHz in this project), which may face interference or regulatory restrictions in some regions.

4.5.2 Sensor Drawbacks

- **DS18B20 Temperature Sensor**:
  - **Lag in Response Time**: While accurate, this sensor can have a slight delay in reflecting sudden temperature changes, which may affect real-time responsiveness in critical scenarios.
  - **Limited Temperature Range**: The sensor is suitable for measuring human body temperature but may not be effective for extreme conditions outside its range.
- **Pulse Rate Sensor**:
  - **Accuracy Concerns**: The pulse rate sensor used is not as precise as clinical-grade equipment, which may lead to occasional inaccuracies in readings.
  - **Sensitivity to Noise**: Environmental factors such as movement or poor sensor placement can cause fluctuations in pulse data, reducing reliability in active scenarios.
- **Accelerometer Sensor**:
  - **False Positives**: Sudden movements, such as jumping or running, may occasionally trigger false fall detections, leading to unnecessary alerts.
  - **Threshold Tuning**: Proper threshold values must be set for accurate fall detection, which may vary based on user conditions and usage scenarios.

4.5.3 Dependency on External Power

Some components, such as the Peltier module, require an external power source, which may limit portability or operation in areas without reliable power access.

4.5.4 Environmental Interference

- **GPS Module**: Performance can degrade in dense forests, caves, or urban areas with tall buildings, where satellite signals are obstructed, leading to reduced accuracy in location tracking.
- **LoRa Signal**: Interference from other devices operating at the same frequency can cause packet loss or delays.

CHAPTER 5

CONCLUSION

5.1 CONCLUSION

The LoRa-based life jacket system is a comprehensive safety solution designed to monitor and protect individuals in emergency situations. By integrating a Raspberry Pi Pico microcontroller with sensors such as the Pulse Rate Sensor, Temperature Sensor, Accelerometer, and GPS module, it ensures continuous monitoring of vital parameters. The use of a Peltier module provides timely heat to prevent hypothermia, while the accelerometer alerts the rescue team in case of a fall. LoRa technology ensures long-range communication between the life jacket and the rescue team, and real-time data is displayed on a 16x2 LCD with I2C for immediate access. This system effectively addresses critical safety needs, enhancing survival chances in adverse conditions.

5.2 OUR PROJECT




Fig. 5.2.1 The Transmitter




Fig. 5.2.2 The Receiver

5.3 FUTURE SCOPE

1. **Enhanced Sensor Integration:** Incorporating advanced medical-grade sensors to increase accuracy and reliability for commercial applications.
2. **Energy Optimization:** Utilizing solar panels or energy-harvesting technologies to extend battery life.
3. **IoT Connectivity:** Expanding functionality by integrating cloud-based dashboards for real-time global monitoring.
4. **Wearable Technology:** Miniaturizing components for enhanced comfort and usability in real-life scenarios.

This innovative solution can evolve into a vital tool for ensuring safety in various high-risk environments.

REFERENCES

[1] D. B. Nguyen, T. Le Minh, N. Van Truc and H. Vu Tran, "Building a Smart Life Jacket Based on the IoT Platform," 2023 International Conference on Advanced Technologies for Communications (ATC),Da Nang, Vietnam, 2023, pp. 527-533, 2023.

[2] Khan, Aman Ul Azam, Aurghya Kumar Saha, Zarin Tasnim, T. T. Bristy, A. Baqui, and B. Dev, 2023, Development of the Smart Jacket Featured With Medical, Sports, and Defense Attributes Using Conductive Thread and ThermoelectricFabric Engineering Proceedings 30, vol. 1, p. 18

[3] Dr. Ch.Rajasekhara Rao, P.Ganesh Kumar, N.Viveka Vardhini, V.Pavan Kumar, T.Gnana Bhaskar, ”Smart Jacket For Workers using Lora Technology”, Journal of Emerging Technologies and Innovative Research(JETIR), 2023.

[4] Kruthikaran, Nandhu, S. Krishnan, and S. P. Philip, “Lora based soldier tracking and health monitoring device,” Int. Res. J. Eng. Technol(IRJET), 2023.

[5] R. Sharma, “D,Raghuwanshi, R.R,” Chandak.T,Ramdasi.D,”LoRa- based IoT system for emergency assistance and safety in mountaineering”. International Information and Engineering Technology Association (IIETA), 2023.

[6] S. Khan and F. U. Khan,“A wearable solar energy harvesting based jacket with maximum PowerPoint tracking for vital health monitoring systems,” in IEEE Access, vol. 10, pp. 119475–119495, 2022.

[7] Gaby Bou Tayeh, Joseph Azar, Abdallah Makhoul, Christophe Guyeux, Jacques Demerjian,”A Wearable LoRa- Based Emergency System for Remote Safety Monitoring”,International Wireless Communications and Mobile Computing Conference,2020.

[8] M. Abro, G. Abid, S. Ahmed, and K. Kumar,” Prototyping IOT Based Smart Wearable Jacket Design for Securing the Life of Coal Miners”, International Conference on Computing, Electronics & Communications Engineering (iCCECE), 201[9] S. Abiodun, M. H. Anisi, and M. K. Khan, “Cloud-based wireless body area networks: Managing data for better health care,” IEEE Con. Electron. Mag., vol. 8, no. 3, pp. 55–59, 2019.

[9] S. Khan and F. U. Khan,“A wearable solar energy harvesting based jacket with maximum PowerPoint tracking for vital health monitoring systems,” in IEEE Access, vol. 10, pp. 119475–119495, 2022.

[10] Juyiuy S. A. Shaik and M. Abro, “Prototyping IOT based smart wearable jacket design for securing the life,” in IEEE Access, vol. 10, pp. 119475– 119495, 2019.