C:\hpc-23-feb-2026\.\33\eg211.cpp

```
#include<iostream>
#include<string>
#include<chrono>
#include<cstring>
#include<stdlib.h>
using namespace std;
#define isdigit(c) (c >= '0' && c <= '9')
int main()
{
  double a;
  int e;
  int c;
char buffer[1024];
strcpy(buffer,"1231312.2334");
int x;
int index;
double value;
auto start=chrono::high_resolution_clock::now();
x=1;
while(x<50)
{
 a=0.0;
 e=0;
 index=0;
 while ((c = buffer[index++]) != '\0' && isdigit(c)) {
  a = a*10.0 + (c - '0');
 }
 if (c == '.') {
  while ((c = buffer[index++]) != '\0' && isdigit(c)) {
   a = a*10.0 + (c - '0');
   e = e-1;
  }
 }
 if (c == 'e' || c == 'E') {
  int sign = 1;
  int i = 0;
  c = buffer[index++];
  if (c == '+')
   c = buffer[index++];
  else if (c == '-') {
   c = buffer[index++];
   sign = -1;
  }
  while (isdigit(c)) {
   i = i*10 + (c - '0');
   c = buffer[index++];
  }
  e += i*sign;
```

```
  }
  while (e > 0) {
    a *= 10.0;
    e--;
  }
  while (e < 0) {
    a *= 0.1;
    e++;
  }
cout<<x<<")"<<a<<endl;
x++;
}
auto end=chrono::high_resolution_clock::now();
auto d=chrono::duration_cast<chrono::milliseconds>(end-start);
cout<<d.count()<<" milliseconds"<<endl;
return 0;
}
```

Thinking Machines Classroom Codes