C:\hpc-23-feb-2026\.\26\eg194.cpp

```
#include<oneapi/tbb.h>
#include<vector>
#include<iostream>
using namespace std;
using namespace oneapi::tbb;
int main()
{
vector<int> v={1,2,3,4,5,6,7,8,9,10};
parallel_for(blocked_range<size_t>(0,v.size()),[&](blocked_range<size_t> &range){
for(auto i=range.begin();i!=range.end();++i) v[i]*=v[i];
});
for(auto x:v) cout<<x<<endl;
return 0;
}
```

Thinking Machines Classroom Codes

C:\hpc-23-feb-2026\.\26\eg195.cpp

```
#include<oneapi/tbb.h>
#include<vector>
#include<iostream>
using namespace std;
using namespace oneapi::tbb;
int main()
{
vector<int> v={1,2,3,4,5,6,7,8,9,10};
parallel_for((size_t)0,v.size(),[&](int index){
v[index]*=v[index];
});
for(auto x:v) cout<<x<<endl;
return 0;
}
```

Thinking Machines Classroom Codes

C:\hpc-23-feb-2026\.\26\eg196.cpp

```
#include<iostream>
using namespace std;
int main()
{
int x=(int)5.44;
int y=int(5.44); // functional style used for typecasting
cout<<x<<endl;
cout<<y<<endl;
return 0;
}
```

Thinking Machines Classroom Codes

C:\hpc-23-feb-2026\.\26\eg197.cpp

```
#include<oneapi/tbb.h>
#include<iostream>
using namespace std;
using namespace oneapi::tbb;
void sam()
{
for(int e=0;e<=10;e++) cout<<e<<" ";
}
int main()
{
parallel_invoke([](){
for(int j=403;j<=530;++j) cout<<j<<" ";
},sam,[](){
for(int k=703;k<=870;++k) cout<<k<<" ";
});
return 0;
}
```

C:\hpc-23-feb-2026\.\26\eg198.cpp

```
#include<iostream>
#include<fstream>
using namespace std;
int main()
{
ifstream file("fhaltu.csv");
string line;
while(getline(file,line))
{
cout<<line<<endl;
}
file.close();
return 0;
}
```