C:\hpc-23-feb-2026\.\scaler\create_random_csv.c

```
#include<stdio.h>
#include<time.h>
#include<stdlib.h>
#define FILES_COUNT 5000
int main()
{
int x,rows,columns,r,c;
char file_name[51];
FILE *file;
int min,max;
int value;
srand(time(NULL));
for(x=1;x<=FILES_COUNT;++x)
{
sprintf(file_name,"source/data_%d.csv",x);
file=fopen(file_name,"wb");
min=3; max=45;
columns=rand()%(max-min)+min;
min=1000; max=9000;
rows=rand()%(max-min)+min;
min=1;
max=1000000;
for(r=1;r<=rows;++r)
{
for(c=1;c<columns;++c)
{
value=rand()%(max-min)+min;
fprintf(file,"%d,",value);
}
value=rand()%(max-min)+min;
fprintf(file,"%d\n",value);
}
fclose(file);
printf("File %s created with %d rows and %d columns\n",file_name,rows,columns);
}
return 0;
}
```

C:\hpc-23-feb-2026\.\scaler\list_of_csvs.c

```
#include<stdio.h>
#include<dirent.h>
#include<string.h>
int main()
{
DIR *directory;
struct dirent *directory_entry;
char *ptr;
directory=opendir("source");
if(directory==NULL)
{
printf("Unable to access source directory\n");
return 1;
}
while(1)
{
directory_entry=readdir(directory);
if(directory_entry==NULL) break;
ptr=strrchr(directory_entry->d_name,'.');
if(ptr && strcmp(ptr,".csv")==0)
{
printf("%s\n",directory_entry->d_name);
}
}
closedir(directory);
return 0;
}
```

Thinking Machines Classroom Codes

C:\hpc-23-feb-2026\.\scaler\read_contents.c

```
#include<stdio.h>
#include<string.h>
#include<stdlib.h>
//#define BUFFER_SIZE 1024*1024
#define BUFFER_SIZE 1024
int main()
{
char file_name[51];
FILE *file;
unsigned char *buffer;
size_t read_count;
int i;
buffer=(unsigned char *)malloc(BUFFER_SIZE);
if(buffer==NULL)
{
printf("Low memory\n");
return 1;
}
strcpy(file_name,"source/data_1.csv");
file=fopen(file_name,"rb");
if(file==NULL)
{
printf("Unable to access %s\n",file_name);
return 1;
}
while(1)
{
read_count=fread(buffer,1,BUFFER_SIZE,file);
if(read_count==0) break;
printf("Bytes extracted %lu\n",read_count);
//for(i=0;i<read_count;++i) printf("%c",buffer[i]);
}
fclose(file);
free(buffer);
return 0;
}
```