

**Open Elective Course [OE]**

Course Code: CSO507


Winter 2023-24

Lecture#

# Deep Learning

Unit-7: Structured Probabilistic Models (Part-II)

Unit-8: Generative Models (Part-I)

**Course Instructor:**


Dr. Monidipa Das

Assistant Professor


Department of Computer Science and Engineering

Indian Institute of Technology (Indian School of Mines) Dhanbad, Jharkhand 826004, India

## Undirected Models



- Markov random fields (MRFs) or Markov networks:




- Formally, an undirected graphical model is a structured probabilistic model defined on an undirected graph  $G$ .

# Undirected Models




- For each clique  $C$  in the graph,  $\phi(C)$  is a factor (called clique potential)
  - measures the affinity of the variables in that clique for being in each of their possible joint states.



- The factors are constrained to be non-negative.
- Together they define an **unnormalized** probability distribution:  $\tilde{p}(\mathbf{x}) = \prod_{C \in \mathcal{G}} \phi(C)$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# Partition Function



- Normalized Probability Distribution

$$p(\mathbf{x}) = \frac{1}{Z} \tilde{p}(\mathbf{x})$$

where  $Z$  is the value that results in the probability distribution summing or integrating to 1:

$$Z = \int \tilde{p}(\mathbf{x}) d\mathbf{x}$$

**Normalizing constant**  
Also called **partition function**

It is possible to specify the factors in such a way that  $Z$  does not exist.

Choice of factors is important!

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# Energy-Based Models (EBMs)




- $\tilde{p}(x) = \exp(-E(x))$  — **Energy function**
- enforces  $\forall x, \tilde{p}(x) > 0$

**Boltzmann distribution**

- Unconstrained optimization.
- The probabilities in an energy-based model can approach arbitrarily close to zero but never reach it.
- Many energy-based models are called **Boltzmann machines**

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# Energy-based Models



$$E(a, b, c, d, e, f) = E_{a,b}(a, b) + E_{b,c}(b, c) + E_{a,d}(a, d) + E_{b,e}(b, e) + E_{e,f}(e, f)$$

$$p(a, b, c, d, e, f) = \frac{1}{Z} \phi_{a,b}(a, b) \phi_{b,c}(b, c) \phi_{a,d}(a, d) \phi_{b,e}(b, e) \phi_{e,f}(e, f)$$

Different cliques in undirected graph correspond to different terms of the energy function

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# Free Energy instead of Probability



- Algorithms don't need  $p_{\text{model}}(\mathbf{x})$  but only


$$\log \tilde{p}_{\text{model}}(\mathbf{x}) \quad \text{where} \quad \tilde{p}(\mathbf{x}) = \exp(-E(\mathbf{x}))$$

- EBMs with hidden units  $\mathbf{h}$  use the negative of this quantity, called the *free energy*


$$F(\mathbf{x}) = -\log \sum_{\mathbf{h}} \exp(-E(\mathbf{x}, \mathbf{h}))$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


## Separation




### Conditional independence in undirected models




When  $s$  is not observed, influence can flow from  $a$  to  $b$  and vice versa through  $s$ .



When  $s$  is observed, it blocks the flow of influence between  $a$  and  $b$ : they are *separated*



$a$  and  $c$  are separated given  $b$   
 $a$  and  $d$  are not separated given  $b$




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# D-Separation




## Separation concept in case of directed models

The flow of influence is more complicated for directed models




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# Converting directed to undirected





Resulting undirected model implies exactly the same set of independences and conditional independences




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


# Converting undirected to directed



No loops of length greater than three allowed!




Add edges to triangulate long loops



Assign directions to edges. No directed cycles allowed.


Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# Sampling from graphical models



- Sampling from directed models (BNs)

- Ancestral Sampling




To generate one sample:

- |  |  |
|--|--|
| 1. Sample $x_1^*$ from $\Pr(x_1)$                | 4. Sample $x_3^*$ from $\Pr(x_3   x_2^*, x_4^*)$ |
| 2. Sample $x_2^*$ from $\Pr(x_2   x_1^*)$        | 5. Sample $x_5^*$ from $\Pr(x_5   x_3^*)$        |
| 3. Sample $x_4^*$ from $\Pr(x_4   x_1^*, x_2^*)$ |  |

- Without topological sorting, we might attempt to sample a variable before its parents are available

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


# Sampling from graphical models



- Sampling from undirected models (MNs)
  - Gibbs Sampling
    - Simplest approach for sampling from an MN
  - Gibbs Sampling with M variables
    - Initialize first sample:  $\{z_i, i = 1, \dots, M\}$
    - For  $t=1, \dots, T$ ,  $T = \text{no of samples}$ 
      - Sample  $z_1^{(\tau+1)} \sim p(z_1 | z_2^{(\tau)}, z_3^{(\tau)}, \dots, z_M^{(\tau)})$
      - Sample  $z_2^{(\tau+1)} \sim p(z_2 | z_1^{(\tau+1)}, z_3^{(\tau)}, \dots, z_M^{(\tau)})$
      - .....
      - Sample  $z_j^{(\tau+1)} \sim p(z_j | z_1^{(\tau+1)}, \dots, z_{j-1}^{(\tau+1)}, z_{j+1}^{(\tau)}, \dots, z_M^{(\tau)})$
      - .....
      - Sample  $z_M^{(\tau+1)} \sim p(z_M | z_1^{(\tau+1)}, z_2^{(\tau+1)}, \dots, z_{M-1}^{(\tau+1)})$
    - $p(z_j | z_{-j})$  is called a *full conditional* for variable  $j$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


# Advantages of Structured Modeling



- Reduce cost of representing distributions
- Operations use less runtime and memory
- Convey information by leaving edges out
- Sampling accelerated for directed models

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


## Deep learning approach to structured models



- **PGM: Probabilistic Graphical Model**
- **Traditional PGMs vs. PGMs in deep learning**
  - 1. Depth
  - 2. Proportion of observed to latent variables
  - 3. Latent semantics (meaning of a latent variable)
  - 4. Connectivity and inference algorithm
  - 5. Intractability and approximation

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

## Deep learning approach to structured models




- PGMs in deep learning are not deep PGMs
- Deep Learning has more latent variables than observed variables
- Deep Learning does not take any specific semantics ahead of time
- Deep learning PGMs have large groups of units connected other large groups of units


Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad




# Example: RBMs



- **Restricted Boltzmann machine (RBM)**
  - quintessential example of how graphical models are used for deep learning.
- RBM is a bipartite graph
- RBM is a special case of Boltzmann machines and Markov networks
- **RBM itself is not a deep model**





General BM




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


# Models constructed using RBMs



RBM




Deep belief network



Deep Boltzmann Machine

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


# Properties of RBMs



- Restrictions of RBM structure yields nice properties:

$$p(\mathbf{h}|\mathbf{v}) = \prod_i p(h_i|\mathbf{v}) \text{ and } p(\mathbf{v}|\mathbf{h}) = \prod_i p(v_i|\mathbf{h})$$


Since nodes at same level are independent



- Individual conditionals are simple to compute

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# RBM: an energy-based model



- Joint-probability distribution is specified by the energy function:

$$P(\mathbf{v}=\mathbf{v}, \mathbf{h}=\mathbf{h}) = (1/Z) \exp(-E(\mathbf{v}, \mathbf{h}))$$


– The energy function for an RBM is

$$-E(\mathbf{v}, \mathbf{h}) = -\mathbf{b}^T \mathbf{v} - \mathbf{c}^T \mathbf{h} - \mathbf{v}^T \mathbf{W} \mathbf{h}$$

–  $Z$  is the partition function


$$Z = \sum_{\mathbf{v}} \sum_{\mathbf{h}} \exp(-E(\mathbf{v}, \mathbf{h}))$$

– Since  $Z$  is intractable  $P(\mathbf{v})$  is also intractable



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# RBM conditionals are tractable



- Although  $P(\mathbf{v})$  is intractable,
  - Conditionals  $P(\mathbf{h}|\mathbf{v})$ ,  $P(\mathbf{v}|\mathbf{h})$  are factorial & easily computed:

$$P(\mathbf{h} | \mathbf{v}) = \frac{P(\mathbf{h}, \mathbf{v})}{P(\mathbf{v})} = \frac{1}{P(\mathbf{v})} \frac{1}{Z} \exp\{\mathbf{b}^T \mathbf{v} + \mathbf{c}^T \mathbf{h} + \mathbf{v}^T \mathbf{W} \mathbf{h}\} = \frac{1}{Z'} \exp\{\mathbf{c}^T \mathbf{h} + \mathbf{v}^T \mathbf{W} \mathbf{h}\}$$

$$= \frac{1}{Z'} \exp\left\{\sum_{j=1}^{n_h} c_j h_j + \sum_{j=1}^{n_h} \mathbf{v}^T \mathbf{W}_{:,j} h_j\right\} = \frac{1}{Z'} \prod_{j=1}^{n_h} \exp\{c_j h_j + \mathbf{v}^T \mathbf{W}_{:,j} h_j\}$$

- Normalizing the distributions over individual binary  $\mathbf{h}$


$$P(h_j = 1 | \mathbf{v}) = \frac{\tilde{P}(h_j = 1 | \mathbf{v})}{\tilde{P}(h_j = 0 | \mathbf{v}) + \tilde{P}(h_j = 1 | \mathbf{v})} = \frac{\exp\{c_j + \mathbf{v}^T \mathbf{W}_{:,j}\}}{\exp\{0\} + \exp\{c_j + \mathbf{v}^T \mathbf{W}_{:,j}\}} = \sigma(c_j + \mathbf{v}^T \mathbf{W}_{:,j})$$

- We now express full conditional as a factorial distribution

$$P(\mathbf{h} | \mathbf{v}) = \prod_{j=1}^{n_h} \sigma((2h_j - 1) \odot (c + \mathbf{W}^T \mathbf{v})) \quad \text{and similarly} \quad P(\mathbf{v} | \mathbf{h}) = \prod_{j=1}^{n_v} \sigma((2v_j - 1) \odot (b + \mathbf{W}^T \mathbf{h}))$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# Training RBM



- RBM properties allow for block Gibbs sampling
  - Alternate between sampling all  $\mathbf{h}$  simultaneously and all  $\mathbf{v}$  simultaneously
- Energy function:  $E(\mathbf{v}, \mathbf{h}) = -\mathbf{b}^T \mathbf{v} - \mathbf{c}^T \mathbf{h} - \mathbf{v}^T \mathbf{W} \mathbf{h}$ 
  - where  $\mathbf{b}$ ,  $\mathbf{c}$  and  $\mathbf{W}$  are unconstrained, real-valued learnable parameters
- Since the energy function is a linear function of its parameters, it is easy to take derivatives

$$\frac{\partial}{\partial W_{i,j}} E(\mathbf{v}, \mathbf{h}) = -v_i h_j$$

- These two properties, efficient Gibbs sampling and efficient derivatives make training convenient

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# Training RBM



- Joint configuration  $(\mathbf{v}, \mathbf{h})$

$$E(\mathbf{v}, \mathbf{h}) = - \sum_{i \in \text{visible}} a_i v_i - \sum_{j \in \text{hidden}} b_j h_j - \sum_{i,j} v_i h_j w_{ij}$$

$$p(\mathbf{v}, \mathbf{h}) = \frac{1}{Z} e^{-E(\mathbf{v}, \mathbf{h})}$$

$$Z = \sum_{\mathbf{v}, \mathbf{h}} e^{-E(\mathbf{v}, \mathbf{h})}$$

$$p(\mathbf{v}) = \frac{1}{Z} \sum_{\mathbf{h}} e^{-E(\mathbf{v}, \mathbf{h})}$$

- Changing probability of  $\mathbf{v}$

Likelihood:  $P(\{\mathbf{v}^{(1)}, \dots, \mathbf{v}^{(M)}\}) = \prod_m p(\mathbf{v}^{(m)})$

Log-likelihood:

$$\ln P(\{\mathbf{v}^{(1)}, \dots, \mathbf{v}^{(M)}\}) = \sum_m \ln p(\mathbf{v}^{(m)}) = \sum_m \ln \left( \frac{1}{Z} \sum_{\mathbf{h}} e^{-E(\mathbf{v}^{(m)}, \mathbf{h})} \right) = \sum_m \ln \left( \sum_{\mathbf{h}} e^{-E(\mathbf{v}^{(m)}, \mathbf{h})} \right) - \sum_m \ln \left( \sum_{\mathbf{v}, \mathbf{h}} e^{-E(\mathbf{v}, \mathbf{h})} \right)$$

Derivative of the log-probability of a training vector wrt a weight:


$$\frac{\partial \ln p(\mathbf{v})}{\partial w_{ij}} = \mathbb{E}_{\text{data}}(v_i h_j) - \mathbb{E}_{\text{model}}(v_i h_j)$$

Learning rule for stochastic steepest ascent

$$\Delta w_{ij} = \varepsilon \left( \mathbb{E}_{\text{data}}(v_i h_j) - \mathbb{E}_{\text{model}}(v_i h_j) \right), \text{ where } \varepsilon \text{ is the learning rate}$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

## Samples for Computing Expectations



- Getting unbiased samples for  $E_{\text{data}}(v_i h_j)$

- $h_j$ : Given random training image  $\mathbf{v}$ , the binary state  $h_j$  for each hidden unit is set to 1 with probability

$$p(h_j = 1 | \mathbf{v}) = \sigma \left( b_j + \sum_i v_i w_{ij} \right)$$

- $v_i$ : Given a random training image  $\mathbf{v}$ , the binary state  $v_i$  for a visible unit is set to 1 with probability


$$p(v_i = 1 | \mathbf{v}) = \sigma \left( a_i + \sum_j h_j w_{ij} \right)$$

- Getting unbiased samples for  $E_{\text{model}}(v_i h_j)$

– Can be done by starting at a random state of visible units and performing Gibbs sampling for a long time

- One iteration of alternating Gibbs sampling consists of updating all hidden units in parallel followed by updating all visible units

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad



# Questions?

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad