
#### **Open Elective Course** [OE]

Course Code: CSO507 Winter 2023-24

### Lecture#

# **Deep Learning**

**Unit-4: Convolutional Neural Networks (Part-V)** 




#### **Course Instructor:**

Dr. Monidipa Das

**Assistant Professor** 

**Department of Computer Science and Engineering** 


Indian Institute of Technology (Indian School of Mines) Dhanbad, Jharkhand 826004, India





Once we have Batch Normalization, we can train networks with 10+ layers. What happens as we go deeper?

Deeper model does worse than shallow model!





Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# **Residual Networks**



Once we have Batch Normalization, we can train networks with 10+ layers. What happens as we go deeper?






In fact the deep model seems to be **underfitting** since it also performs worse than the shallow model on the training set! It is actually **underfitting** 


Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad








Non-nested function does not guarantee better expressive power of the network.






Every additional layer should more easily contain the identity function as one of its elements.

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbac

# Residual Block






Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

# Residual Networks (ResNet)




#### Residual Networks


- A residual network is a stack of many residual blocks
- Regular design, like VGG: each residual block has two 3x3 conv
- Network is divided into stages: the first block of each stage halves the resolution (with stride-2 conv) and doubles the number of channels



Prof. Monidipa Das. Department of CSE, IIT (ISM) Dhanba

# Residual Networks (ResNet) Solum 158 3x3 colm, 168 3x3 colm, 164 3x3 colm, 64 3x3 colm, 188 3x3 col







#### ResNet-18:

Stem: 1 conv layer

Stage 1 (C=64): 2 res. block = 4 conv Stage 2 (C=128): 2 res. block = 4 conv Stage 3 (C=256): 2 res. block = 4 conv Stage 4 (C=512): 2 res. block = 4 conv

Linear

ImageNet top-5 error: 10.92

GFLOP: 1.8

#### ResNet-34:

Stem: 1 conv layer

Stage 1: 3 res. block = 6 conv Stage 2: 4 res. block = 8 conv

Stage 3: 6 res. block = 12 conv Stage 4: 3 res. block = 6 conv

Linear

ImageNet top-5 error: 8.58


GFLOP: 3.6

#### VGG-16:


ImageNet top-5 error: 9.62

GFLOP: 13.6

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbac



#### **Residual Networks** More layers, less computational cost! Conv(1x1, C->4C) FLOPs: 4HWC<sup>2</sup> Conv(3x3, C->C) FLOPs: 9HWC<sup>2</sup> FLOPs: 9HWC<sup>2</sup> Conv(3x3, C->C) FLOPs: 9HWC<sup>2</sup> Conv(3x3, C->C) FLOPs: 4HWC<sup>2</sup> Conv(1x1, 4C->C) "Basic" Total FLOPs: 18HWC<sup>2</sup> Residual block "Bottleneck" **Total FLOPs:** 17HWC<sup>2</sup> Residual block






layer name	output size	18-layer	34-layer	50-layer	101-layer	152-layer
conv1	112×112	7×7, 64, stride 2				
	56×56	3×3 max pool, stride 2				
conv2_x		$\left[\begin{array}{c} 3\times3,64\\ 3\times3,64 \end{array}\right]\times2$	$\left[\begin{array}{c} 3\times3,64\\ 3\times3,64 \end{array}\right]\times3$	$\begin{bmatrix} 1 \times 1, 64 \\ 3 \times 3, 64 \\ 1 \times 1, 256 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 64 \\ 3 \times 3, 64 \\ 1 \times 1, 256 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 64 \\ 3 \times 3, 64 \\ 1 \times 1, 256 \end{bmatrix} \times 3$
conv3_x				$ \begin{bmatrix} 1 \times 1, 128 \\ 3 \times 3, 128 \\ 1 \times 1, 512 \end{bmatrix} \times 4 $	[ 1×1 129 ]	$\begin{bmatrix} 1 \times 1, 128 \\ 3 \times 3, 128 \\ 1 \times 1, 512 \end{bmatrix} \times 8$
conv4_x		L , , , ,	L ,	$\begin{bmatrix} 1 \times 1, 256 \\ 3 \times 3, 256 \\ 1 \times 1, 1024 \end{bmatrix} \times 6$	[ 1×1, 1024 ]	$\begin{bmatrix} 1 \times 1, 256 \\ 3 \times 3, 256 \\ 1 \times 1, 1024 \end{bmatrix} \times 36$
conv5_x	7×7	$\left[\begin{array}{c} 3\times3,512\\ 3\times3,512 \end{array}\right]\times2$	$\left[\begin{array}{c} 3\times3,512\\ 3\times3,512 \end{array}\right]\times3$	$\begin{bmatrix} 1 \times 1, 512 \\ 3 \times 3, 512 \\ 1 \times 1, 2048 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 512 \\ 3 \times 3, 512 \\ 1 \times 1, 2048 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 512 \\ 3 \times 3, 512 \\ 1 \times 1, 2048 \end{bmatrix} \times 3$
	1×1	average pool, 1000-d fc, softmax				
FLOPs		$1.8 \times 10^{9}$	$3.6 \times 10^{9}$	$3.8 \times 10^9$	$7.6 \times 10^9$	$11.3 \times 10^9$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbac



#### Original ResNet block




#### Note ReLU after residual:

Cannot actually learn identity function since outputs are nonnegative!

Note ReLU inside residual:

Can learn true identity function by setting Conv weights to zero!



"Pre-Activation" ResNet Block

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbac

# Tiny Neural Networks for Mobile Devices




Instead of pushing for the largest network with biggest accuracy, consider tiny networks and accuracy / complexity tradeoff

#### Compare families of models:

One family is better than another if it moves the whole curve up and to the left

#### Accuracy



# Model Complexity (FLOPs, #params, runtime speed)


Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbac

# MobileNets: Tiny Networks (For Mobile Devices)



#### **Standard Convolution Block**


Total cost: 9C2HW



Speedup = 
$$9C^2/(9C+C^2)$$
  
=  $9C/(9+C)$   
=> 9 (as C->inf)

#### **Depthwise Separable Convolution**

Total cost:  $(9C + C^2)HW$ 



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbac

#### MobileNetV2: Inverted Bottleneck, Linear Residual No nonlinearity after last Nonlinearity ReLU conv! (linear residual) outside residual Ŧ Total FLOP: 17HWC<sup>2</sup> Total FLOP: 2tHWC<sup>2</sup> + 9tHWC **Batch Norm** 1x1 conv reduces **Batch Norm** Conv(1x1, tC->C) ResNet Bottleneck Block 1x1 conv expands channels before output MobileNetV2 Block channels output (tHWC<sup>2</sup> FLOP) Conv(1x1, C->4C) ReLU6 (4HWC<sup>2</sup> FLOP) ReLU **Batch Norm** 3x3 Depthwise conv with **Batch Norm** Conv(3x3, tC->tC, more channels than input 3x3 conv uses fewer groups=tC) (9tHWC FLOP) channels than input Conv(3x3, C->C) (9HWC<sup>2</sup> FLOP) ReLU6 ReLU 1x1 conv increases **Batch Norm Batch Norm** channels before 3x3 conv 1x1 conv reduces Conv(1x1, C->tC) (inverted bottleneck) Conv(1x1, 4C->C) channels before 3x3 (tHWC<sup>2</sup> FLOP) conv (4HWC2 FLOP) Sandler et al, "MobileNetV2: Inverted Residuals and Linear Bottlenecks", CVPR 2018

