

Open Elective Course [OE]

Course Code: CSO507

Winter 2023-24

Lecture#

Deep Learning

Unit-8: Few more GAN variants

Unit-9: Graph Neural Networks


Course Instructor:

Dr. Monidipa Das


Assistant Professor

Department of Computer Science and Engineering


Indian Institute of Technology (Indian School of Mines) Dhanbad, Jharkhand 826004, India




Deep Convolutional GANs (DCGANs)



Generator Architecture

**Key ideas:**

- Replace FC hidden layers with Convolutions
 - **Generator:** Fractional-Strided convolutions
- Use Batch Normalization after each layer
- **Inside Generator**
 - Use ReLU for hidden layers
 - Use Tanh for the output layer



Radford, Alec, Luke Metz, and Soumith Chintala. "Unsupervised representation learning with deep convolutional generative adversarial networks." arXiv:1511.06434 (2015).

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

LSGAN



- proposes to use the least-squares loss function for the discriminator.

Vanilla GAN:


$$\min_G \max_D V_{\text{GAN}}(D, G) = \mathbb{E}_{\mathbf{x} \sim p_{\text{data}}(\mathbf{x})} [\log D(\mathbf{x})] + \mathbb{E}_{\mathbf{z} \sim p_{\mathbf{z}}(\mathbf{z})} [\log(1 - D(G(\mathbf{z})))]$$

LSGAN:

$$\min_D V_{\text{LSGAN}}(D) = \frac{1}{2} \mathbb{E}_{\mathbf{x} \sim p_{\text{data}}(\mathbf{x})} [(D(\mathbf{x}) - b)^2] + \frac{1}{2} \mathbb{E}_{\mathbf{z} \sim p_{\mathbf{z}}(\mathbf{z})} [(D(G(\mathbf{z})) - a)^2]$$

$$\min_G V_{\text{LSGAN}}(G) = \frac{1}{2} \mathbb{E}_{\mathbf{z} \sim p_{\mathbf{z}}(\mathbf{z})} [(D(G(\mathbf{z})) - c)^2],$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad




Unit-9: Graph Neural Networks


Acknowledgement: Prof. E. Knag et al., Prof. J. Leskovec

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Graphs in the World



phenylalanine




Map of Manhattan



Social Network


Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Graph Definitions




$$G = (V, E)$$

- V is a set of nodes
- E is a set of tuples of form (u, v) , where there is an edge between u and v
- G is a graph



Undirected edge



Directed edge

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


Graph encoding as a matrix



Adjacency Matrix: $\mathbf{A} \in \mathbb{R}^{|V| \times |V|}$

- In this example, binary matrix encoding of a unweighted graph
- Rows/columns number the nodes, matrix elements encode edges

$V = \{u, v, w, x\}$; $E = \{(w, u), (x, u), (u, v)\}$




$\mathbf{A} =$

(to)				
u	v	w	x	
0	1	0	0	\sqsubset
0	0	0	0	$<$
1	0	0	0	\sqsupset
1	0	0	0	\times

(from)

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Do the matrices encode the same graph?



0	1	0	0
0	0	0	0
1	0	0	0
1	0	0	0

0	0	0	0
0	0	1	0
1	0	0	0
0	0	1	0

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Do the matrices encode the same graph?



0	1	0	0
0	0	0	0
1	0	0	0
1	0	0	0

u v w x

0	1	0	0
0	0	0	0
1	0	0	0
1	0	0	0

⊂
<
≅
×

0	0	0	0
0	0	1	0
1	0	0	0
0	0	1	0


v w u x

0	0	0	0
0	0	1	0
1	0	0	0
0	0	1	0

<
≅
⊂
×

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Do the matrices encode the same graph?



u	v	w	x
0	1	0	0
0	0	0	0
1	0	0	0
1	0	0	0


⊂
<
≅
×

v	w	u	x
0	0	0	0
0	0	1	0
1	0	0	0
0	0	1	0

<
≅
⊂
×

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Considerations for GNN



- Nodes are not i.i.d
- A NN modeling a graph should be permutation invariant and equivariant o Adjacency matrix orders nodes arbitrarily


For permutation matrix \mathbf{P} , function f that takes in an adjacent matrix \mathbf{A} :

Permutation Invariance Property: $f(\mathbf{PAP}^T) = f(\mathbf{A})$


Permutation Equivariance Property: $f(\mathbf{PAP}^T) = \mathbf{P}f(\mathbf{A})$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Considerations for GNN




- 3) Find an encoding that preserves the graph structure



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Neural Message Passing



Graph

$$G = (V, E)$$

Node Features

$$X \in \mathbb{R}^{d \times |V|}$$

Hidden embedding:

$$\mathbf{h} = \{\vec{h}_1, \vec{h}_2, \dots, \vec{h}_N\}$$

Node Embeddings

$$\mathbf{z}_u, \forall u \in V$$



Node vs Edge embeddings:

$$h_u^{(k)}, u \in V$$

$$h_{(u,v)}^{(k)}, (u, v) \in E$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Message Passing Framework




$$h_u^{(k+1)} = \text{UPDATE}^{(k)} \left(h_u^{(k)}, \text{AGGREGATE}^{(k)} \left(\{h_v^{(k)}, \forall v \in \mathcal{N}(u)\} \right) \right)$$

$$h_u^{(k+1)} = \text{UPDATE}^{(k)} \left(h_u^{(k)}, m_{\mathcal{N}(u)}^{(k)} \right)$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Message Passing Framework




AT EACH ITERATION k OF THE GNN:

- *AGGREGATE* all embeddings from u 's neighbors to generate a message $m_{\mathcal{N}(u)}^{(k)}$ based on this aggregated neighborhood information
- *UPDATE* the embedding $h_u^{(k+1)}$ of node u by combining information from the previous embedding $h_u^{(k)}$ and with the message $m_{\mathcal{N}(u)}^{(k)}$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Message Passing Framework




AFTER RUNNING K ITERATIONS:

- Use the output of the final layer to define the embeddings for each node:

$$z_u = h_u^{(K)}, \forall u \in V$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

The Basic GNN




$$h_u^{(k)} = \sigma \left(W_{\text{self}}^{(k)} h_u^{(k-1)} + W_{\text{neigh}}^{(k)} \sum_{v \in N_u} h_v^{(k-1)} + b^{(k)} \right)$$

- $h_u^{(k-1)} \in \mathbb{R}^{d^{(k-1)}}$: Node embeddings
- $W_{\text{self}}^{(k)}, W_{\text{neigh}}^{(k)} \in \mathbb{R}^{d^{(k)} \times d^{(k-1)}}$: Learnable parameters
- $b^{(k)} \in \mathbb{R}^{d^{(k)}}$: Bias term
- σ : Elementwise non-linearity (e.g., a tanh or ReLU)

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad



Summary



1. Sum the messages incoming from the neighbors
2. Combine the neighborhood information with the node's previous embedding using a linear combination
3. Apply an elementwise non-linearity


Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Traditional Machine Learning on Graphs




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Learning Tasks




- Node-level prediction
- Link-level prediction
- Graph-level prediction



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


Node-Level Prediction Tasks



Node classification

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


Example



- Predict a protein's 3D structure based solely on its amino acid sequence




T1037 / 6vr4
90.7 GDT
(RNA polymerase domain)



T1049 / 6y4f
93.3 GDT
(adhesin tip)


Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Link-Level Prediction Tasks




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Example-1




- Recommender Systems




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Example-2




- Given a pair of drugs predict adverse side effects




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Graph-Level Tasks




- Graph/Sub-graph Classification



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Example-1



- Predicting Arrival Time














Image credit: [DeepMind](#)

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Example-2





- Drug Discovery





Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Graph Representation Learning



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Graph Representation Learning





Tasks

- Node classification
- Link prediction
- Graph classification
- Anomalous node detection
- Clustering
-

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Example: Node Embedding




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Node Embedding




Goal: $\text{similarity}(u, v) \approx \mathbf{z}_v^T \mathbf{z}_u$

Need to define!



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Learning Node Embedding



1. **Encoder** maps from nodes to embeddings
2. **Define a node similarity function** (i.e., a measure of similarity in the original network)
3. **Decoder DEC** maps from embeddings to the similarity score
4. **Optimize the parameters of the encoder so that:**


$$\text{similarity}(u, v) \approx \mathbf{z}_v^T \mathbf{z}_u$$

in the original network Similarity of the embedding


$$\text{DEC}(\mathbf{z}_v^T \mathbf{z}_u)$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Simplest Embedding




Simplest encoding approach: **Encoder is just an embedding-lookup**



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


Limitation



- **Limitations of shallow embedding methods:**
 - Large number of parameters are needed
 - No sharing of parameters between nodes
 - Every node has its own unique embedding
 - Inherently “transductive”
 - Cannot generate embeddings for nodes that are not seen during training
 - Do not incorporate node features
 - Nodes in many graphs have features that we can and should leverage

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Deep Graph Encoders




- Based on deep learning for graphs (using **Graph Neural Networks**)

$$\text{ENC}(v) = \begin{array}{l} \text{multiple layers of} \\ \text{non-linear transformations} \\ \text{based on graph structure} \end{array}$$


Why GNNs?

**The CNNs and RNNs are designed for simple sequences & grids.
Difficult to handle graphs!**



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Problems with Approaches Learnt So Far




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


Problems with Approaches Learnt So Far




CNN on an image:



But our graphs look like this:




or this:




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


Graph Convolutional Networks



- Idea:** Node's neighborhood defines a computation graph






Determine node
computation graph



Propagate and
transform information

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad



Aggregate Neighbors




Neural networks

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Aggregate Neighbors




INPUT GRAPH




Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Node Aggregation: Basic Approach



Average neighbor messages and apply a neural network



Initial 0-th layer embeddings are equal to node features

$$h_v^0 = x_v$$

embedding of v at layer k

$$h_v^{(k+1)} = \sigma \left(W_k \sum_{u \in N(v)} \frac{h_u^{(k)}}{|N(v)|} + B_k h_v^{(k)} \right), \forall k \in \{0, \dots, K-1\}$$

Average of neighbor's previous layer embeddings

Non-linearity (e.g., ReLU)

Embedding after K layers of neighborhood aggregation


Total number of layers

Notice summation is a permutation invariant pooling/aggregation.

Graph Convolutional Networks (GCN)

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

GraphSAGE



$$\mathbf{h}_v^{(l)} = \sigma \left(\mathbf{W}^{(l)} \cdot \text{CONCAT} \left(\mathbf{h}_v^{(l-1)}, \text{AGG} \left(\left\{ \mathbf{h}_u^{(l-1)}, \forall u \in N(v) \right\} \right) \right) \right)$$

- **How to write this as Message + Aggregation?**

- **Message** is computed within the **AGG(·)**

- **Two-stage aggregation**

- **Stage 1:** Aggregate from node neighbors


$$\mathbf{h}_{N(v)}^{(l)} \leftarrow \text{AGG} \left(\left\{ \mathbf{h}_u^{(l-1)}, \forall u \in N(v) \right\} \right)$$

- **Stage 2:** Further aggregate over the node itself

$$\mathbf{h}_v^{(l)} \leftarrow \sigma \left(\mathbf{W}^{(l)} \cdot \text{CONCAT}(\mathbf{h}_v^{(l-1)}, \mathbf{h}_{N(v)}^{(l)}) \right)$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

GraphSAGE



- **Mean:** Take a weighted average of neighbors

$$\text{AGG} = \sum_{u \in N(v)} \frac{\mathbf{h}_u^{(l-1)}}{|N(v)|} \quad \text{Aggregation} \quad \text{Message computation}$$

- **Pool:** Transform neighbor vectors and apply symmetric vector function Mean(·) or Max(·)

$$\text{AGG} = \text{Mean}(\{\text{MLP}(\mathbf{h}_u^{(l-1)}), \forall u \in N(v)\})$$

Aggregation Message computation


- **LSTM:** Apply LSTM to reshuffled of neighbors

$$\text{AGG} = \text{LSTM}([\mathbf{h}_u^{(l-1)}, \forall u \in \pi(N(v))])$$

Aggregation

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

GraphSAGE




■ ℓ_2 Normalization:


- **Optional:** Apply ℓ_2 normalization to $\mathbf{h}_v^{(l)}$ at every layer
- $\mathbf{h}_v^{(l)} \leftarrow \frac{\mathbf{h}_v^{(l)}}{\|\mathbf{h}_v^{(l)}\|_2} \forall v \in V$ where $\|u\|_2 = \sqrt{\sum_i u_i^2}$ (ℓ_2 -norm)
- Without ℓ_2 normalization, the embedding vectors have different scales (ℓ_2 -norm) for vectors
- In some cases (not always), normalization of embedding results in performance improvement
- After ℓ_2 normalization, all vectors will have the same ℓ_2 -norm

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Constructing Graph Neural Network



• Stacking GNN Layers




Acknowledgement: Prof. Jure Leskovec

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Over-Smoothing Problem




- All the node embeddings converge to the same value
 - Over-smoothing can be explained via the notion of the receptive field
 - **Receptive field:** the set of nodes that determine the embedding of a node of interest
 - If two nodes have highly-overlapped receptive fields, then their embeddings are highly similar





Acknowledgement: Prof. Jure Leskovec

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Over-Smoothing Problem




- Do not set GNN layers to be unnecessarily large!
 - **Step 1:** Analyze the necessary receptive field to solve your problem
 - **Step 2:** Set number of GNN layers L to be a bit more than the receptive field we like.
- How to enhance the expressive power of a GNN, if the number of GNN layers is small?
 - **Solution 1:** Increase the expressive power within each GNN layer
 - **Solution 2:** Add layers that do not pass messages



Acknowledgement: Prof. Jure Leskovec

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad




Over-Smoothing Problem



- What if we still need many GNN layers?

- Add skip connections in GNNs


N skip connections $\rightarrow 2^N$ possible paths



Acknowledgement: Prof. Jure Leskovec

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

GCN with Skip Connection



- A standard GCN layer

$$\mathbf{h}_v^{(l)} = \sigma \left(\sum_{u \in N(v)} \mathbf{W}^{(l)} \frac{\mathbf{h}_u^{(l-1)}}{|N(v)|} \right)$$


- A GCN layer with skip connection

$$\mathbf{h}_v^{(l)} = \sigma \left(\sum_{u \in N(v)} \mathbf{W}^{(l)} \frac{\mathbf{h}_u^{(l-1)}}{|N(v)|} + \mathbf{h}_v^{(l-1)} \right)$$

Acknowledgement: Prof. Jure Leskovec

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

GNN Training



Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Acknowledgement: Prof. Jure Leskovec

GNN Training: Prediction Head



- Node-level prediction:**

$$\hat{y}_v = \text{Head}_{\text{node}}(\mathbf{h}_v^{(L)}) = \mathbf{W}^{(H)} \mathbf{h}_v^{(L)}$$

▪ $\mathbf{W}^{(H)} \in \mathbb{R}^{k \times d}$: We map node embeddings from $\mathbf{h}_v^{(L)} \in \mathbb{R}^d$ to $\hat{y}_v \in \mathbb{R}^k$ so that we can compute the loss

- Edge-level prediction:**

$$\hat{y}_{uv} = \text{Head}_{\text{edge}}(\mathbf{h}_u^{(L)}, \mathbf{h}_v^{(L)})$$

$$\hat{y}_{uv} = \text{Linear}(\text{Concat}(\mathbf{h}_u^{(L)}, \mathbf{h}_v^{(L)}))$$

$$\hat{y}_{uv} = (\mathbf{h}_u^{(L)})^T \mathbf{h}_v^{(L)}$$

- Graph-level prediction:**

$$\hat{y}_G = \text{Head}_{\text{graph}}(\{\mathbf{h}_v^{(L)} \in \mathbb{R}^d, \forall v \in G\})$$

- **(1) Global mean pooling**

$$\hat{y}_G = \text{Mean}(\{\mathbf{h}_v^{(L)} \in \mathbb{R}^d, \forall v \in G\})$$

- **(2) Global max pooling**

$$\hat{y}_G = \text{Max}(\{\mathbf{h}_v^{(L)} \in \mathbb{R}^d, \forall v \in G\})$$


- **(3) Global sum pooling**

$$\hat{y}_G = \text{Sum}(\{\mathbf{h}_v^{(L)} \in \mathbb{R}^d, \forall v \in G\})$$

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Acknowledgement: Prof. Jure Leskovec

GNN Training: Ground-Truth




- Supervised:
 - Node labels y_v : in a citation network, which subject area does a node belong to
 - Edge labels y_{uv} : in a transaction network, whether an edge is fraudulent
 - Graph labels y_G : among molecular graphs, the drug likeness of graphs
- Unsupervised:
 - Node-level y_v . Node statistics: such as clustering coefficient, PageRank, ...
 - Edge-level y_{uv} . Link prediction: hide the edge between two nodes, predict if there should be a link
 - Graph-level y_G . Graph statistics: for example, predict if two graphs are isomorphic

Acknowledgement: Prof. Jure Leskovec

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

GNN Training: Loss



- **Classification:** Cross Entropy Loss

$$\text{CE}(\underbrace{\mathbf{y}^{(i)}}_{\text{Label}}, \underbrace{\hat{\mathbf{y}}^{(i)}}_{\text{Prediction}}) = - \sum_{j=1}^K y_j^{(i)} \log(\hat{y}_j^{(i)}) \quad \begin{matrix} i\text{-th data point} \\ j\text{-th class} \end{matrix} \quad \text{Loss} = \sum_{i=1}^N \text{CE}(\mathbf{y}^{(i)}, \hat{\mathbf{y}}^{(i)})$$


- **Regression:** Mean Squared Loss

$$\text{MSE}(\mathbf{y}^{(i)}, \hat{\mathbf{y}}^{(i)}) = \sum_{j=1}^K (y_j^{(i)} - \hat{y}_j^{(i)})^2 \quad \begin{matrix} i\text{-th data point} \\ j\text{-th target} \end{matrix} \quad \text{Loss} = \sum_{i=1}^N \text{MSE}(\mathbf{y}^{(i)}, \hat{\mathbf{y}}^{(i)})$$

Acknowledgement: Prof. Jure Leskovec

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

GNN Training: Evaluation Metrics



Regression

- Root mean square error (RMSE)

$$\sqrt{\sum_{i=1}^N \frac{(y^{(i)} - \hat{y}^{(i)})^2}{N}}$$

- Mean absolute error (MAE)

$$\frac{\sum_{i=1}^N |y^{(i)} - \hat{y}^{(i)}|}{N}$$




Image Credit: Wikipedia

$$TPR = \text{Recall} = \frac{TP}{TP + FN}$$

$$FPR = \frac{FP}{FP + TN}$$

Classification

- (1) Multi-class classification

- We simply report the accuracy

$$\frac{1}{N} \sum_{i=1}^N \mathbb{1}[\text{argmax}(\hat{y}^{(i)}) = y^{(i)}]$$

- (2) Binary classification

- Metrics sensitive to classification threshold

- Accuracy

- Precision / Recall

- If the range of prediction is $[0,1]$, we will use 0.5 as threshold


- Metric Agnostic to classification threshold

- ROC AUC

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


Acknowledgement: Prof. Jure Leskovec

GNN Training: Dataset Split




- Node classification:

Training
Validation
Test




Transductive setting



Inductive setting

- Graph Classification:



Training

Validation

Test


Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Acknowledgement: Prof. Jure Leskovec

GNN Training: Dataset Split





- Link Prediction:



Acknowledgement: Prof. Jure Leskovec

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Spatial based Filtering



h_i : The hidden features

l_i : The input features

$$h_i^{(k+1)} = \sum_{v_j \in N(v_i)} f(l_i, h_j^{(k)}, l_j), \quad \forall v_i \in V.$$


$N(v_i)$: Neighbors of the node v_i .

$f(\cdot)$: Feedforward neural network.


Ack: Yiqi Wang, Wei Jin, Yao Ma, and Biliang Tang

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Spectral based Filtering



- “**Spectral**” in the graph domain denotes the **eigendecomposition of the graph Laplacian matrix into simpler orthonormal basis components**



Adjacency Matrix: $A[i, j] = 1$ if v_i is adjacent to v_j
 $A[i, j] = 0$, otherwise


Degree Matrix: $\mathbf{D} = \text{diag}(\text{degree}(v_1), \dots, \text{degree}(v_N))$

$$\begin{array}{ccc}
 \text{Degree Matrix} & & \text{Adjacency Matrix} \\
 \begin{pmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 3 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 4 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 2 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 2 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 4 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 3 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \end{pmatrix} & - & \begin{pmatrix} 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 1 & 0 & 0 & 1 & 0 & 0 \\ 0 & 1 & 0 & 1 & 0 & 1 & 1 & 0 \\ 0 & 0 & 1 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 1 & 0 & 0 \\ 0 & 1 & 1 & 0 & 1 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 & 0 & 1 & 0 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \end{pmatrix} \\
 \mathbf{D} & & \mathbf{A}
 \end{array} = \begin{array}{ccc}
 \text{Laplacian Matrix} \\
 \begin{pmatrix} 1 & -1 & 0 & 0 & 0 & 0 & 0 & 0 \\ -1 & 3 & -1 & 0 & 0 & -1 & 0 & 0 \\ 0 & -1 & 4 & -1 & 0 & -1 & -1 & 0 \\ 0 & 0 & -1 & 2 & -1 & 0 & 0 & 0 \\ 0 & 0 & 0 & -1 & 2 & -1 & 0 & 0 \\ 0 & -1 & -1 & 0 & -1 & 4 & -1 & 0 \\ 0 & 0 & -1 & 0 & 0 & -1 & 3 & -1 \\ 0 & 0 & 0 & 0 & 0 & 0 & -1 & 1 \end{pmatrix} \\
 \mathbf{L}
 \end{array}$$

Ack: Yiqi Wang, Wei Jin, Yao Ma, and Jiliang Tang

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Spectral based Filtering



Laplacian matrix has a complete set of orthonormal eigenvectors:

$$\mathbf{L} = \begin{bmatrix} | & & | \\ \mathbf{u}_0 & \cdots & \mathbf{u}_{N-1} \\ | & & | \end{bmatrix} \begin{bmatrix} \lambda_0 & & 0 \\ & \ddots & \\ 0 & & \lambda_{N-1} \end{bmatrix} \begin{bmatrix} \text{---} & \mathbf{u}_0 & \text{---} \\ & \vdots & \\ \text{---} & \mathbf{u}_{N-1} & \text{---} \end{bmatrix}$$

$\mathbf{U} \qquad \qquad \mathbf{\Lambda} \qquad \qquad \mathbf{U}^T$

Eigenvalues are sorted non-decreasingly:


$$0 = \lambda_0 < \lambda_1 \leq \cdots \lambda_{N-1}$$

The frequency of an eigenvector of Laplacian matrix is its corresponding eigenvalue


Ack: Yiqi Wang, Wei Jin, Yao Ma, and Jiliang Tang

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Spectral based Filtering



- Graphs and Graph Signals



Graph Signal: $f : \mathcal{V} \rightarrow \mathbb{R}^N$

$$\mathcal{V} = \{v_1, \dots, v_N\}$$

$$\mathcal{E} = \{e_1, \dots, e_M\}$$


$$\mathcal{G} = \{\mathcal{V}, \mathcal{E}\}$$

$$\mathcal{V} \rightarrow \begin{bmatrix} f(1) \\ f(2) \\ f(3) \\ f(4) \\ f(5) \\ f(6) \\ f(7) \\ f(8) \end{bmatrix}$$


Ack: Yiqi Wang, Wei Jin, Yao Ma, and Jiliang Tang

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Spectral based Filtering




- Graph Fourier Transform (GFT)



Spatial domain: f

$$\hat{f} = U^T f$$

Decompose signal f




Spectral domain: \hat{f}


Ack: Yiqi Wang, Wei Jin, Yao Ma, and Jiliang Tang

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad

Spectral based Filtering




- Inverse Graph Fourier Transform (IGFT)



Spatial domain: f

$$f = U\hat{f}$$

Reconstruct signal f




Spectral domain: \hat{f}


Ack: Yiqi Wang, Wei Jin, Yao Ma, and Jiliang Tang

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad


Spectral based Filtering



Filter a graph signal f :




$$\hat{g}(\Lambda) = \begin{bmatrix} \hat{g}(\lambda_0) & & 0 \\ & \ddots & \\ 0 & & \hat{g}(\lambda_{N-1}) \end{bmatrix}$$



Ack: Yiqi Wang, Wei Jin, Yao Ma, and Jiliang Tang

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad



Questions?

Prof. Monidipa Das, Department of CSE, IIT (ISM) Dhanbad