

Four State Model

State1 is with 0 e-h pair, state2 is with one e-h pair, state3 is with 2 e-h pairs, state4 is the trap state

Version-1

In this model the increment in time(t_{inc}) in each state is given by $1/\Sigma rates$. The probability of electron for going in a particular state is $rate/\Sigma rates$.

Code:

```
clear;
clc;
close all;
tic
tau1=4e-9; %for transition from state 2 to 1
tau2=1e-9; %for transition from state 3 to 2
tau=0.8; %for transition from state 4 to 1
taua=10e-9; %for transition from state 3 to 4
s1=1e-15; %cross section of NC
s2=1e-15; %cross section of NC
h=2.5*1.6e-19;
I=0.08e3; %intensity
W1=s1*I/h; %rate of transition from state 1 to 2
W2=s2*I/h; %rate of transition from state 2 to 3
bin_size=10e-3;
trap=0; %count total number of trap states(3 to 4)
on=0; %count total number of on states(2 to 1)
i=3; %index for array
n=800000; %total number of iterations
t(1)=0; %time array
next(1)=1; %stores the sequence of states with initial state as 1
on(1)=0;
[next(2), tinc(1), tr, on1]=state(next(1), W1, W2, tau1, tau2, taua, tau); %next state is determined
on(2)=on1;
t(2)=t(1)+tinc(1);
while i<=n
    [next(i), tinc(i-1), tr, on1]=state(next(i-1), W1, W2, tau1, tau2, taua, tau); %iteratively next state is determined
    trap=trap+tr;
    on(i)=on1;
    t(i)=t(i-1)+tinc(i-1);
    i=i+1;
end
n2=fix(max(t)/bin_size); %number of bins formed
binranges=0:bin_size:max(t); %stores the various bins
[bincounts, ind]=histc(t, binranges); % bincounts stores the number of indices of t array in each bin
sr=1;
for y=1:n2 %binning method
```

```

on2(y)= sum(on(sr:bincounts(y)+sr));
st=bincounts(y)+1;
end
t1 = 0:bin_size:(n2-1)*bin_size;
c = [[0,0,0];[0.7,0.7,0.7];[1,0,0];[0,1,0];[0,0,1]];
line_style = {'-','--','-','-'};
plot(t1,on2,'Color', [c(3,:)],'LineStyle',line_style{1});
xlim([0, max(t)]);

%h_legend = legend('3 level','Location','NorthEast');
title(['I=',num2str(I),' taua=',num2str(taua),' Noff=',num2str(trap)],'fontsize',16);
% set(h_legend,'fontsize',16, 'box', 'off');
xlabel('time (s)','fontsize',24);
ylabel('Intensity (a.u.)','fontsize',24);
set(gca, 'FontSize',24);

figname_png = ['Intensity and time for 4 state model 4.png'];
figname = ['Intensity and time for 4 state model 4'];
width = 30;
height = 10;
set(gcf, 'PaperPositionMode', 'manual');
set(gcf, 'PaperSize', [width height]);
set(gcf, 'PaperPosition', [0 0 width height]);
set(gca,'position',[0.1 0.19 .85 .7]);% specify these as the fraction of the total.. between 0 and 1

print('-dpng','-r125',figname_png);
toc
Function:
function [next, tinc,tr,on1] =state(st, W1,W2,tau1,tau2,taua,tau)
tr=0;
on1=0;
if st==1
    tinc=1/(W1);
    num=rand();
    if(num<W1*tinc)
        next=2;
    end
end
if st==2
    tinc=1/(W2+(1/tau1));
    num=rand();
    if(num<W2*tinc)
        next=3;
    else
        next=1;
        on1=1;
    end
end

```

```

end
if st==3
    tinc=1/((1/tau2)+(1/taua));
    num=rand();
    if(num<(1/tau2)*tinc)
        next=2;
    else
        next=4;
        tr=1;
    end
end
if st==4
    tinc=1/(1/tau);
    num=rand();
    if(num<(1/tau)*tinc)
        next=2;
    end
end
end
end

```

Results:



