

AS

EXPLORE

TRACKS

MY COURSES

EDPRESSO

TEACH

< educative

Q Search Course

Grokking the System Design Interview

74% COMPLETED

Glossary of System Design Ba...

Appendix

System Design Basics

Key Characteristics of Distributed Systems

Load Balancing

Caching

Data Partitioning

Indexes

Proxies

Redundancy and Replication

SQL vs. NoSQL

CAP Theorem

Consistent Hashing

Long-Polling vs WebSockets vs Server-Sent Events

Contact Us


Other courses

OPTIONS

CAP Theorem

CAP theorem states that it is impossible for a distributed software system to simultaneously provide more than two out of three of the following guarantees (CAP): **Consistency, Availability, and Partition tolerance**. When we design a distributed system, trading off among CAP is almost the first thing we want to consider. CAP theorem says while designing a distributed system we can pick only two of the following three options:

- Consistency:** All nodes see the same data at the same time. Consistency is achieved by updating several nodes before allowing further reads.
- Availability:** Every request gets a response on success/failure. Availability is achieved by replicating the data across different servers.
- Partition tolerance:** The system continues to work despite message loss or partial failure. A system that is partition-tolerant can sustain any amount of network failure that doesn't result in a failure of the entire network. Data is sufficiently replicated across combinations of nodes and networks to keep the system up through intermittent outages.



We cannot build a general data store that is continually available, sequentially consistent, and tolerant to any partition failures. We can only build a system that has any two of these three properties. Because, to be consistent, all nodes should see the same set of updates in the same order. But if the network suffers a partition, updates in one partition might not make it to the other partitions before a client reads from the out-of-date partition after having read from the up-to-date one. The only thing that can be done to cope with this possibility is to stop serving requests from the out-of-date partition, but then the service is no longer 100% available.

Have questions?

Get help on educative

← Previous
SQL vs. NoSQL

Completed

Next →
Consistent Hashing