

Eaze Referral Program — Database Schema Reference

eaze-referral-service · PostgreSQL · every table the referral program tracks, one row each

All timestamp columns are recorded in IST (Asia/Kolkata). Every table also has at least one creation timestamp not listed under “Key columns” unless it's the table's defining field (e.g. `login_logs.first_seen_at`). `users` and `recharges` are stand-ins for tables the real Eaze backend already owns; every other table is specific to the referral program. Full column-level types/constraints live in `eaze-referral-service/app/models.py`.

Category	Table	Purpose	Key columns	Grows
Core (stand-in)	<code>users</code>	Minimal stand-in for the real Eaze backend's user table.	<code>id</code> (PK) · <code>phone_e164</code> (unique) · <code>external_ref</code> (unique) · <code>status</code> · <code>wallet_balance</code> · <code>created_at</code>	Per user
Core (stand-in)	<code>recharges</code>	Minimal stand-in for the real Eaze backend's recharge/payment table.	<code>id</code> (PK) · <code>user_id</code> → <code>users</code> · <code>amount_paise</code> · <code>status</code> (SUCCESS/FAILED/REFUNDED) · <code>created_at</code>	Per recharge
Referral pipeline	<code>referral_codes</code>	One durable shareable code per referrer, for the share link and its click analytics.	<code>id</code> (PK) · <code>user_id</code> → <code>users</code> (unique) · <code>code</code> (unique) · <code>is_active</code> · <code>created_at</code>	Per referrer
Referral pipeline	<code>referral_intents</code>	A phone number a referrer submitted — the SOLE attribution mechanism.	<code>id</code> (PK) · <code>referrer_user_id</code> → <code>users</code> · <code>phone_e164</code> (unique) · <code>status</code> (PENDING/MATCHED/EXPIRED) · <code>matched_user_id</code> , <code>matched_at</code>	Per submitted number
Referral pipeline	<code>referral_clicks</code>	Click tracking on the <code>/r/:code</code> share link — funnel visibility only, never attribution.	<code>id</code> (PK) · <code>referral_code_id</code> → <code>referral_codes</code> · <code>ip_address</code> · <code>user_agent</code> · <code>clicked_at</code>	Per link click
Referral pipeline	<code>referrals</code>	The referral relationship and its reward lifecycle.	<code>id</code> (PK) · <code>referrer_user_id</code> , <code>referred_user_id</code> (unique) → <code>users</code> · <code>referral_intent_id</code> (mandatory) · <code>status</code> (SIGNED_UP/REWARDED/REVERSED) · <code>signup_rewarded_at</code> , <code>recharge_rewarded_at</code>	Per matched referral
Coin ledger	<code>wallet_transactions</code>	The coin ledger — every signup and recharge bonus, idempotent.	<code>id</code> (PK) · <code>user_id</code> → <code>users</code> · <code>amount</code> · <code>type</code> (SIGNUP/RECHARGE/REVERSAL) · <code>reference_id</code> — UNIQUE(<code>user_id</code> , <code>type</code> , <code>reference_id</code>)	Per coin credit
Activity logs	<code>login_logs</code>	First-seen visit per <code>user_id</code> , recorded once, ever.	<code>id</code> (PK) · <code>user_id</code> (unique) · <code>first_seen_at</code> (IST) — ON CONFLICT DO NOTHING	Per user, once
Activity logs	<code>referral_logs</code>	Append-only audit trail of every phone number submitted — no dedup.	<code>id</code> (PK) · <code>user_id</code> (indexed) · <code>phone_e164</code> · <code>recorded_at</code> (IST)	Per submission
Activity logs	<code>message_copy_logs</code>	One row per "Copy message" tap — count = COUNT(*) GROUP BY <code>user_id</code> .	<code>id</code> (PK) · <code>user_id</code> (indexed) · <code>copied_at</code> (IST)	Per click