

Code Sample

Selected Replication Code

Anonymous

CODING SAMPLE: SHORT COPY

These excerpts are selected from the replication code for the paper. Selected outputs appear at the end of the document.

Survey-weighted enrollment model

File: R/selection/estimate_selection_probit.R

```
selection_probit_variables <- function(selection_data) {
  controls <- c("AGE", "age", "SEX", "HH_SIZE", "RELIGION", "SOCIAL_GROUP", "SECTOR")
  exclusion_all_kids <- c("DIST_FROM_NEAREST_PRIMARY_CLASS", "father_educ")
  exclusion_district <- c(
    "dmean_num_IS_EDU_FREE", "dmean_num_TUTION_FEE_WAIVED",
    "dmean_num_RECD_SCHOLARSHIP_STIPEND", "dmean_num_RECD_TXT_BOOKS",
    "dmean_num_RECD_STATIONERY", "dmean_num_MID_DAY_MEAL_ETC_RECD",
    "dmean_num_ENROLLMENT_COST"
  )
  intersect(c(controls, exclusion_all_kids, exclusion_district), names(selection_data))
}

#' project the selection sample to the model's actual dependency surface
#'
#' Keeping unrelated Block-5 schooling attributes in the fitted survey design makes
#' the serialized model change whenever those attributes change, even though they
#' are absent from the probit formula. A narrow model frame lets {targets} skip the
#' expensive AME branch when upstream changes do not affect estimation.
project_selection_model_data <- function(selection_data) {
  selection_data <- safe_df(selection_data)
  design <- c("enrolled", "FSU_SL_NO", "weight", "STATE", "STRATUM", "SUB_STRATUM_NO")
  keep <- unique(c(design, selection_probit_variables(selection_data)))
  selection_data[intersect(keep, names(selection_data))]
}

#' estimate selection probit
#'
estimate_selection_probit <- function(selection_data, cfg) {
```

```

if (!"enrolled" %in% names(selection_data) || all(is.na(selection_data$enrolled))) {
  return(list(status = "out_of_active_pipeline", reason = "No enrolled variable. "))
}
covars <- selection_probit_variables(selection_data)
if (!length(covars)) {
  return(list(status = "out_of_active_pipeline", reason = "No probit covariates. "))
}
f_probit <- stats::reformulate(covars, response = "enrolled")
if (identical(cfg$mode, "final") && requireNamespace("survey", quietly = TRUE)) {
  old_options <- options(survey.lonely.psu = "average")
  on.exit(options(old_options), add = TRUE)

  design <- build_survey_design_selection(selection_data)
  if (!is.null(design)) {
    out <- fit_selection_probit(design, f_probit)
    return(stabilize_selection_model_formula(out, f_probit))
  }
}
out <- stats::glm(f_probit, data = selection_data, family = stats::binomial(link = "probit"))
stabilize_selection_model_formula(out, f_probit)
}

#' store a durable selection-model formula
#'
#' Programmatically fitted models otherwise retain a call to the local symbol
#' `f_probit`. Packages which reconstruct model data from the saved call cannot
#' resolve that symbol after the model is serialized by targets. Embed the
#' formula object in the call and retain the existing audit attribute.
stabilize_selection_model_formula <- function(model, formula) {
  if (!inherits(formula, "formula")) {
    stop("Selection model formula must inherit from formula.", call. = FALSE)
  }
  if (!is.null(model$call)) model$call$formula <- formula
  attr(model, "selection_probit_formula") <- formula
  model
}

#' build survey design selection
#'
build_survey_design_selection <- function(selection_df) {
  psu <- first_col(selection_df, c("FSU_SL_NO", "fsu", "PSU", "psu"))
  weight <- first_col(selection_df, c("weight", "WEIGHT", "Multiplier", "multiplier"))
  strata_cols <- intersect(c("STATE", "STRATUM", "SUB_STRATUM_NO"), names(selection_df))
  if (is.null(psu) || is.null(weight) || !length(strata_cols)) return(NULL)
  selection_df$survey_strata <- interaction(selection_df[strata_cols], drop = TRUE)
  survey::svydesign(
    ids = stats::as.formula(paste0("~", psu)),
    strata = ~.survey_strata,
    weights = stats::as.formula(paste0("~", weight)),
    data = selection_df,

```

```

    nest = TRUE
  )
}

#' fit selection probit
#'
fit_selection_probit <- function(selection_design, f_probit) {
  survey::svyglm(f_probit, design = selection_design, family = stats::quasibinomial(link = "probit"))
}

```

Average marginal effects on the model estimation sample

File: R/selection/compute_average_marginal_effects.R

```

ame_model_weight <- function(model_data, model_weights = NULL) {
  weight_cols <- intersect(c("weight", "WEIGHT", "Multiplier", "multiplier", "(weights)"), names(model_data))
  if (length(weight_cols)) {
    return(suppressWarnings(as.numeric(model_data[[weight_cols[[1]]]])))
  }

  if (!is.null(model_weights) && length(model_weights) == nrow(model_data)) {
    return(suppressWarnings(as.numeric(model_weights)))
  }

  NULL
}

#' build marginaleffects newdata and weights
#'
#' @return List with `data`, `wts`, and `has_explicit_weights`.
ame_model_data_and_weights <- function(model) {
  model_data <- as.data.frame(stats::model.frame(model))
  model_weights <- tryCatch(stats::weights(model), error = function(e) NULL)
  weight <- ame_model_weight(model_data, model_weights)

  if (!is.null(weight) && length(weight) == nrow(model_data) && any(is.finite(weight) & weight != 0)) {
    model_data$.ame_weight <- weight
    return(list(data = model_data, wts = ".ame_weight", has_explicit_weights = TRUE))
  }

  list(data = model_data, wts = FALSE, has_explicit_weights = FALSE)
}

#' run marginaleffects while muffling only a redundant explicit-weight warning
#'
run_avg_slopes <- function(model, model_data, wts, numderiv = NULL) {
  args <- list(

```

```

    model = model,
    newdata = model_data,
    wts = wts,
    vcov = TRUE,
    type = "response"
  )
  if (!is.null(numderiv)) args$numderiv <- numderiv

  withCallingHandlers(
    do.call(marginaleffects::avg_slopes, args),
    warning = function(w) {
      msg <- conditionMessage(w)
      explicit_weight_warning <- grepl(
        "normally good practice to specify weights using the `wts` argument",
        msg,
        fixed = TRUE
      )
      if (explicit_weight_warning && !identical(wts, FALSE)) {
        invokeRestart("muffleWarning")
      }
    }
  )
}

#' compute ames autodiff
#'
compute_ames_autodiff <- function(model) {
  # Use the exact estimation sample retained by glm/svyglm. Passing the full
  # pre-model selection_data can have extra rows omitted during model fitting,
  # which makes marginaleffects recycle weights/covariates silently.
  amed <- ame_model_data_and_weights(model)
  run_avg_slopes(model, amed$data, amed$wts)
}

```

Montiel Olea–Pflueger effective-F calculation

File: R/iv/weak_identification.R

```

mop_effective_f <- function(
  model, analysis_data, tau = 0.10, size = 0.05) {
  unavailable <- function(reason) {
    list(
      statistic = NA_real_, critical_value = NA_real_, p.value = NA_real_,
      effective_df = NA_real_, tau = tau, size = size,
      status = "not_estimated", reason = reason
    )
  }

  if (!inherits(model, "ivreg")) {

```

```

    return(unavailable("Montiel Olea-Pflueger effective F requires an ivreg model."))
  }
  if (!requireNamespace("momentfit", quietly = TRUE)) {
    return(unavailable("Package 'momentfit' is not installed."))
  }
  if (!is.finite(tau) || tau <= 0 || !is.finite(size) || size <= 0 || size >= 1) {
    return(unavailable("Montiel Olea-Pflueger tau and size must be valid probabilities."))
  }

  terms <- parse_iv_formula_terms(model)
  if (is.null(terms)) {
    return(unavailable("Could not parse IV formula for Montiel Olea-Pflueger effective F."))
  }
  endogenous <- setdiff(terms$regressors, terms$instruments)
  if (length(endogenous) != 1L) {
    return(unavailable("Montiel Olea-Pflueger effective F requires exactly one endogenous regressor."))
  }

  formula <- stats::formula(model)
  regression_formula <- stats::as.formula(
    call("~", formula[[2L]], formula[[3L]][[2L]]),
    env = environment(formula)
  )
  instrument_formula <- stats::as.formula(
    call("~", formula[[3L]][[3L]]),
    env = environment(formula)
  )
  needed <- unique(c(all.vars(regression_formula), all.vars(instrument_formula)))
  data <- iv_analysis_frame(analysis_data, needed)
  missing <- setdiff(needed, names(data))
  if (length(missing)) {
    return(unavailable(paste(
      "Missing variables for Montiel Olea-Pflueger effective F:",
      paste(missing, collapse = ", ")
    )))
  }
  moment_data <- data[needed]
  if (any(!stats::complete.cases(moment_data))) {
    return(unavailable("Montiel Olea-Pflueger analysis data contain incomplete model rows."))
  }

  stored_cluster <- attr(model, "cluster_state", exact = TRUE)
  cluster <- if (
    length(stored_cluster) == stats::nobs(model) &&
    !anyNA(stored_cluster) && length(unique(stored_cluster)) >= 2L
  ) {
    as.vector(stored_cluster)
  } else {
    iv_model_cluster(model, data)
  }

```

```

covariance <- if (is.null(cluster)) "MDS" else "CL"
covariance_options <- if (is.null(cluster)) {
  list(type = "HCO")
} else {
  # momentfit's clustered moment covariance is based on sandwich::meatCL()
  # and supports HCO. Keep its package-native finite-cluster correction
  # rather than altering the existing HCl Wald-F diagnostic to force equality.
  list(
    cluster = data.frame(cluster = cluster),
    type = "HCO", cadjust = TRUE, multi0 = FALSE
  )
}

result <- tryCatch({
  moment_model <- momentfit::momentModel(
    regression_formula,
    instrument_formula,
    data = moment_data,
    vcov = covariance,
    vcovOptions = covariance_options
  )
  momentfit::MOPtest(
    moment_model,
    tau = tau,
    size = size,
    estMethod = "TSLS",
    simplified = TRUE,
    print = FALSE
  )
}, error = function(e) e)
if (inherits(result, "error")) return(unavailable(conditionMessage(result)))

values <- suppressWarnings(as.numeric(result[c("Feff", "critValue", "pvalue", "Keff")]))
names(values) <- c("statistic", "critical_value", "p.value", "effective_df")
if (length(values) != 4L || any(!is.finite(values))) {
  return(unavailable("momentfit::MOPtest() did not return finite effective-F diagnostics."))
}

c(
  as.list(values),
  list(tau = tau, size = size, status = "estimated", reason = NA_character_)
)
}

```

Linked state-sector price series

File: R/prices/build_temporal_price_series.R

```

build_temporal_price_series <- function(
  price_sources,
  switch_date = as.Date("2013-01-01"),
  overlap_start = as.Date("2013-01-01"),
  overlap_end = as.Date("2014-12-01"),
  minimum_link_months = 6L,
  pre_switch_start = NULL,
  pre_switch_end = NULL) {
  switch_date <- price_boundary(switch_date)
  old <- select_pre_2013_price_series(price_sources)
  new <- select_post_2013_price_series(price_sources)
  links <- summarise_price_links(old, new, overlap_start, overlap_end)

  minimum_link_months <- as.integer(minimum_link_months)
  if (length(minimum_link_months) != 1L || is.na(minimum_link_months) || minimum_link_months < 1L)
    stop("minimum_link_months must be one positive integer.", call. = FALSE)
}

old_groups <- unique(old[old$period < switch_date, c("state_code", "sector"), drop = FALSE])
linked_groups <- links[links$link_months >= minimum_link_months, c("state_code", "sector"), drop = FALSE]
linked_key <- paste(linked_groups$state_code, linked_groups$sector, sep = "\r")
missing_key <- !paste(old_groups$state_code, old_groups$sector, sep = "\r") %in% linked_key
if (any(missing_key)) {
  bad <- old_groups[missing_key, , drop = FALSE]
  stop(
    "Pre-2013 price series lack a sufficient direct link to CPI-R/U: ",
    paste(paste(bad$state_code, bad$sector, sep = "/"), collapse = ", "),
    call. = FALSE
  )
}

old <- merge(old, links, by = c("state_code", "sector"), all.x = TRUE, sort = FALSE)
old <- old[old$period < switch_date, , drop = FALSE]
if (!is.null(pre_switch_start) || !is.null(pre_switch_end)) {
  if (is.null(pre_switch_start) || is.null(pre_switch_end)) {
    stop("Both pre_switch_start and pre_switch_end are required when trimming the old price series.")
  }
  pre_switch_start <- price_boundary(pre_switch_start)
  pre_switch_end <- price_boundary(pre_switch_end)
  if (pre_switch_end < pre_switch_start || pre_switch_end >= switch_date) {
    stop("The pre-switch production window must end before the switch date.", call. = FALSE)
  }
  old <- old[old$period >= pre_switch_start & old$period <= pre_switch_end, , drop = FALSE]
}
old$index_unlinked <- old$index
old$link_factor <- num(old$index) * num(old$link_factor)

new <- new[new$period >= switch_date, , drop = FALSE]
new$link_factor <- 1
new$link_months <- NA_integer_

```

```

new$link_ratio_mad <- NA_real_
new$link_ratio_min <- NA_real_
new$link_ratio_max <- NA_real_
new$index_unlinked <- new$index

columns <- c(
  "state_code", "sector", "period", "index", "index_unlinked", "price_source",
  "link_factor", "link_months", "link_ratio_mad", "link_ratio_min", "link_ratio_max"
)
index <- rbind(old[columns], new[columns])
index$year <- as.integer(format(index$period, "%Y"))
index$month <- as.integer(format(index$period, "%m"))
index <- index[order(index$state_code, index$sector, index$period), , drop = FALSE]
rownames(index) <- NULL
validate_temporal_price_chain(index, switch_date)

structure(
  list(index = index, links = links, switch_date = switch_date),
  class = "emi_temporal_price_series"
)
}

```

Selected Outputs

The tables and figures below are generated by the analyses from which the preceding excerpts are drawn.

Selected enrollment-model average marginal effects

Selected average slopes and discrete comparisons from the survey-weighted enrollment model.

Covariate or comparison	Estimate	SE
Religion: Muslim (ref: Hindu)	-0.125	0.013
Social group: Scheduled Tribe (ref: Other)	-0.101	0.019
Social group: Scheduled Caste	-0.074	0.015
Social group: Other Backward Class	-0.029	0.012
Distance 1–2km (ref: <1km)	-0.076	0.044

Weak-instrument-robust long-run inference

Long-run IV estimates, effective first-stage F statistics, and Anderson–Rubin acceptance sets.

Outcome	2SLS estimate	SE	Effective F	AR 95% set
2022-23 long change	0.117	0.152	0.686	[grid<= -0.193146, -0.0714641] U [0.025109, 0.193146 <=grid]

Outcome	2SLS estimate	SE	Effective F	AR 95% set
2023-24 long change	0.137	0.234	0.414	[grid<= -0.185982, -0.0511449] U [0.0148785, 0.185982 <=grid]

Consumption-series consistency

Validation of the harmonized consumption series used in the later-outcome analysis.

