

LeetCode

Problems

Author
Srinivas Dande





Java Learning Center

No.1 In Java Training & placement

344. Reverse String

Description:

- ✓ Write a function that reverses a string.
- ✓ The input string is given as an array of characters **chArr**.
- ✓ You must do this by modifying the input array in-place with $O(1)$ extra memory.

Example 1:

Input: s = ["h","e","l","l","o"]

Output: ["o","l","l","e","h"]

Example 2:

Input: s = ["H","a","n","n","a","h"]

Output: ["h","a","n","n","a","H"]

Constraints:

- $1 \leq s.length \leq 105$
- $s[i]$ is a printable ascii character.

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Apple 5

Microsoft 2

Amazon 2

Facebook 2

Google 2

Arista Networks 2

Companies

0 - 6 months 6 months - 1 year 1 year - 2 years

Adobe 7

tcs 3

Intel 2

Companies

0 - 6 months 6 months - 1 year 1 year - 2 years

Goldman Sachs 3

Oracle 3

Cisco 2

Paypal 2

Bloomberg 2

Spotify 2

Cognizant 2

344.Reverse String - Solution

```
/*
 * @Author : Srinivas Dande
 * @Company: Java Learning Center
 */
class Solution {
    public void reverseString(char chArr[]) {

        int start=0;
        int end=chArr.length-1;

        while(start<end) {
            char temp = chArr[start];
            chArr[start]=chArr[end];
            chArr[end]=temp;

            start++;
            end--;
        }
    }
}
```

345. Reverse Vowels of a String

Description:

- ✓ Given a string str, reverse only all the vowels in the string and return it.
- ✓ The vowels are 'a', 'e', 'i', 'o', and 'u', and they can appear in both lower and upper cases, more than once.

Example 1:

Input: str = "hello"

Output: "holle"

Example 2:

Input: str = "leetcode"

Output: "leotcede"

Constraints:

- c) $1 \leq s.length \leq 3 * 10^5$
- d) s consist of printable ASCII characters.

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Apple **3**



Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Bloomberg 3

Yahoo 3

Uber 2

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Google 4

Facebook 4

Amazon 4

Adobe 2

345. Reverse Vowels of a String - Solution

```
/*
 * @Author : Srinivas Dande
 * @Company: Java Learning Center
 */

class Solution {
    public boolean isVowel(char c) {
        return c == 'a' || c == 'i' || c == 'e' || c == 'o' || c == 'u' || c == 'A' || c
            == 'I' || c == 'E' || c == 'O' || c == 'U';
    }

    public String reverseVowels(String str) {

        int n = str.length();
        char chArr[] = str.toCharArray();

        int start = 0;
        int end = chArr.length - 1;
```



```
while (start < end) {  
  
    while (start < n && !isVowel(chArr[start])) {  
        start++;  
    }  
  
    while (end >= 0 && !isVowel(chArr[end])) {  
        end--;  
    }  
  
    if (start < end) {  
        char temp = chArr[start];  
        chArr[start] = chArr[end];  
        chArr[end] = temp;  
    }  
  
    start++;  
    end--;  
  
}  
String resultStr = new String(chArr);  
return resultStr;  
}
```



151. Reverse Words in a String

Description:

- ✓ Given an input string **str**, reverse the order of the words.
- ✓ A word is defined as a sequence of non-space characters. The words in **str** will be separated by at least one space.
- ✓ Return a string of the words in reverse order concatenated by a single space.

Note that `str` may contain leading or trailing spaces or multiple spaces between two words. The returned string should only have a single space separating the words. Do not include any extra spaces.

Example 1:

Input: `str = "the sky is blue"`

Output: `"blue is sky the"`

Example 2:

Input: `str = " hello world "`

Output: `"world hello"`

Explanation: Your reversed string should not contain leading or trailing spaces.

Example 3:

Input: `str = "a good example"`

Output: `"example good a"`

Explanation: You need to reduce multiple spaces between two words to a single space in the reversed string.

Constraints:

- $1 \leq s.length \leq 104$
- `str` contains English letters (upper-case and lower-case), digits, and spaces `"`.
- There is at least one word in `str`.

Companies

0 - 6 months 6 months - 1 year 1 year - 2 years

Apple 5 Microsoft 4 Amazon 2 Bloomberg 2

Companies

0 - 6 months 6 months - 1 year 1 year - 2 years

Google 4 VMware 3 Visa 3 Facebook 2 Uber 2 Nvidia 2

Companies

0 - 6 months 6 months - 1 year 1 year - 2 years

LinkedIn 5 Salesforce 4 Oracle 4 Cisco 3 ByteDance 3
 Paypal 2 Citrix 2 Qualcomm 2 Adobe 2 PayTM 2
 Deutsche Bank 2 Cognizant 2 Snapchat Yelp

151. Reverse Words in a String - Solution

```
/*
```

```
* @Author : Srinivas Dande
```

```
* @Company: Java Learning Center
```

```
**/
```

```
class Solution {
```

```
    public String trimSpaces(String s) {
```

```
        int left = 0, right = s.length() - 1;
```

```
        while (left <= right && s.charAt(left) == ' '){
```

```
            ++left;
```

```
        }
```



```
while (left <= right && s.charAt(right) == ' '){
    --right;
}

StringBuilder sb = new StringBuilder();
while (left <= right) {
    char c = s.charAt(left);

    if (c != ' ') sb.append(c);
    else if (sb.charAt(sb.length() - 1) != ' ') sb.append(c);

    ++left;
}
return sb.toString();
}
```

```
public void reverse(char chArr[], int start, int end) {
```

```
    while (start < end) {
        char temp = chArr[start];
        chArr[start] = chArr[end];
        chArr[end] = temp;

        start++;
        end--;
    }
}
```

```
public String reverseWords(String str) {
```

```
    str=trimSpaces(str);
    char chArr[] = str.toCharArray();
    int n = chArr.length;

    int start = 0;
    int end=0;
```



```
        for (; end < n; end++) {  
            if (chArr[end] == ' ') {  
                reverse(chArr, start, end - 1);  
                start = end + 1;  
            }  
        }  
  
        reverse(chArr, start, end - 1);  
        reverse(chArr, 0, n - 1);  
  
        String revStr = new String(chArr);  
        return revStr;  
    }  
}
```



125. Valid Palindrome

Description:

- ✓ A phrase is a palindrome if, after converting all uppercase letters into lowercase letters and removing all non-alphanumeric characters, it reads the same forward and backward. Alphanumeric characters include letters and numbers.
- ✓ Given a string `str`, return `true` if it is a palindrome, or `false` otherwise.

Example 1:

Input: `str = "A man, a plan, a canal: Panama"`

Output: `true`

Explanation: "amanaplanacanalpanama" is a palindrome.

Example 2:

Input: `str = "race a car"`

Output: `false`

Explanation: "raceacar" is not a palindrome.

Example 3:

Input: `str = ""`

Output: `true`

Explanation: `str` is an empty string `""` after removing non-alphanumeric characters. Since an empty string reads the same forward and backward, it is a palindrome.

Constraints:

- a) $1 \leq \text{str.length} \leq 2 * 10^5$
- b) `s` consists only of printable ASCII characters.

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Facebook 15

Adobe 5

Apple 4

Google 4

American Express 2

Spotify 2

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Amazon 10

Microsoft 9

Bloomberg 5

LinkedIn 5

Wayfair 3

Yandex 2

ServiceNow 2

TikTok 2

Infosys 2

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Cisco 3

Goldman Sachs 2

JPMorgan 2

Uber

Zenefits

125. Valid Palindrome - Solution

```

/*
 * @Author : Srinivas Dande
 * @Company: Java Learning Center
 */

class Solution {
    public boolean isPalindrome(String str) {
        str = str.toLowerCase();
        StringBuilder sb=new StringBuilder();
    }
}

```



```
for(int i=0;i<str.length();i++) {  
  
    char ch= str.charAt(i);  
    if( Character.isLetterOrDigit(ch)) {  
        sb.append(ch);  
    }  
  
}  
  
str=sb.toString();  
  
int start = 0;  
int end = str.length() - 1;  
  
while (start < end) {  
    if (str.charAt(start) != str.charAt(end)) {  
        return false;  
    }  
    start++;  
    end--;  
}  
  
return true;  
}  
  
}
```

242. Valid Anagram

Description:

- ✓ Given two strings main and str, return true if t is an anagram of s, and false otherwise.
- ✓ An Anagram is a word or phrase formed by rearranging the letters of a different word or phrase, typically using all the original letters exactly once.

Example 1:

Input: main = "anagram", str = "nagaram"

Output: true

Example 2:

Input: main = "rat", str = "car"

Output: false

Constraints:

- $1 \leq s.length, t.length \leq 5 * 10^4$
- s and t consist of lowercase English letters.

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Bloomberg 19

Amazon 18

Google 2

Goldman Sachs 2

Apple 2

Yahoo 2

Spotify 2

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Facebook 6

Microsoft 6

Affirm 3

Yandex 2

Qualcomm 2

Tesla 2

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

JPMorgan 5

Oracle 4

Cisco 4

Snapchat 3

Adobe 3

Walmart Global Tech 3

BlackRock 3

American Express 3

Grab 2

IBM 2

Visa 2

Dell 2

Uber

Yelp

242. Valid Anagram- Solution

```
/*
 * @Author : Srinivas Dande
 * @Company: Java Learning Center
 */
class Solution {
    public boolean isAnagram(String str1,String str2) {

        if(str1.length()!=str2.length()) {
            return false;
        }

        int count[] = new int[26];

        for (int i = 0; i < str1.length(); i++) {
            count[str1.charAt(i) - 97]++;
            count[str2.charAt(i) - 97]--;
        }

        for (int i = 0; i < count.length; i++) {
            if (count[i] != 0) {
                return false;
            }
        }
        return true;
    }
}
```

387. First Unique Character in a String

Description:

- ✓ Given a string str, find the first non-repeating character in it and return its index.
- ✓ If it does not exist, return -1.

Example 1:

Input: str = "leetcode"

Output: 0

Example 2:

Input: str = "loveleetcode"

Output: 2

Example 3:

Input: str = "aabb"

Output: -1

Constraints:

- $1 \leq \text{str.length} \leq 105$
- str consists of only lowercase English letters.

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Amazon 11

Bloomberg 10

Zillow 5

Paypal 4

Uber 3

Goldman Sachs 2

Adobe 2

Oracle 2

TikTok 2

Infosys 2

Nagarro 2

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Apple **7**

Microsoft **5**

Qualtrics **4**

Walmart Global Tech **3**

Facebook **2**

Yahoo **2**

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Google **11**

Visa **6**

eBay **2**

VMware **2**

Twitter **2**

ServiceNow **2**

387. First Unique Character in a String - Solution

```
/*
 * @Author : Srinivas Dande
 * @Company: Java Learning Center
 */
class Solution {
    public int firstUniqChar(String str) {

        int n=str.length();
        int count[] = new int[26];

        for (int i = 0; i < n; i++) {
            count[str.charAt(i)-97]++;
        }

        for (int i = 0; i < str.length(); i++) {
            if (count[str.charAt(i)-97 ] == 1) {
                return i;
            }
        }
        return -1;
    }
}
```



392. Is Subsequence

Description:

- ✓ Given two strings str and main, return true if str is a subsequence of main, or false otherwise.
- ✓ A subsequence of a string is a new string that is formed from the original string by deleting some (can be none) of the characters without disturbing the relative positions of the remaining characters. (i.e., "ace" is a subsequence of "abcde" while "aec" is not).

Example 1:

Input: s = "abc", t = "ahbgdc"

Output: true

Example 2:

Input: s = "axc", t = "ahbgdc"

Output: false

Constraints:

- a) $0 \leq s.length \leq 100$
- b) $0 \leq t.length \leq 104$
- c) s and t consist only of lowercase English letters.

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Amazon 5

Uber 3

Google 2

Adobe 2

Yandex 2



Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Bloomberg **2**

Apple **2**

Companies

0 - 6 months

6 months - 1 year

1 year - 2 years

Yahoo **3**

Pinterest **2**

Wix

392. Is Subsequence - Solution

```
/*
 * @Author : Srinivas Dande
 * @Company: Java Learning Center
 */
class Solution {
    public boolean isSubsequence(String str,String main ) {

        int m=main.length();
        int n=str.length();

        int i=0;
        int j=0;

        while(i<m && j<n) {
            if(main.charAt(i)==str.charAt(j)) {
                j++;
            }
            i++;
        }
        return (j==n);
    }
}
```