



demo6-rest-server – Handling Exceptions Globally

demo6-rest-server: Files required

1. MyBootApplication.java	Same as Demo5
2. Customer.java	Same as Demo5
3. CustomerController.java	Updated in Demo6
4. MyExceptionHandler.java	Newly Added in Demo6
5. CustomerService.java	Same as Demo5
6. CustomerIDNotFoundException.java	Same as Demo5
7. InvalidPhoneNumberException.java	Same as Demo5
8. CityNotFoundException.java	Same as Demo5
9. MyErrorMessage.java	Same as Demo5
10. application.properties	Same as Demo5
11. pom.xml	Same as Demo5

3. CustomerController.java

```
package com.jlcindia.springboot;

import java.util.ArrayList;
import java.util.List;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.http.HttpHeaders;
import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.RestController;
/*
 * @Author : Srinivas Dande
 * @company : Java Learning Center
 */
@RestController
public class CustomerController {

    @Autowired
    CustomerService customerService;

    @GetMapping("/mycustomer/custId/{custId}")
    public Customer getCustomerByCid(@PathVariable("custId") int custId) {
        System.out.println("CC-getCustomerByCid() - " + custId);

        Customer cust = customerService.getCustomerByCid(custId);
        return cust;
    }
}
```



```
@GetMapping(value = "/mycustomer/phone/{phone}")
public ResponseEntity<Customer> getCustomerByPhone(@PathVariable("phone") long phone) {
    System.out.println("CC-getCustomerByPhone() - " + phone);

    Customer cust = customerService.getCustomerByPhone(phone);
    ResponseEntity<Customer> respEntity =
    new ResponseEntity<Customer>(cust ,HttpHeaders.EMPTY,HttpStatus.OK);

    return respEntity;
}

@GetMapping(value = "/mycustomer/city/{city}")
public ResponseEntity<List<Customer>> getCustomersByCity(@PathVariable("city") String city) {
    System.out.println("CC-getCustomersByCity() - " + city);

    List<Customer> custList =new ArrayList<>();

    custList = customerService.getCustomersByCity(city);

    ResponseEntity<List<Customer>> respEntity =
    new ResponseEntity<List<Customer>>(custList ,HttpHeaders.EMPTY,HttpStatus.OK);

    return respEntity;
}
}
```

4. MyExceptionHandler.java

```
package com.jlcindia.springboot;

import java.time.LocalDateTime;

import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.ControllerAdvice;
import org.springframework.web.bind.annotation.ExceptionHandler;
import org.springframework.web.context.request.WebRequest;
import org.springframework.web.servlet.mvc.method.annotation.ResponseEntityExceptionHandler;
/*
 * @Author : Srinivas Dande
 * @company : Java Learning Center
 */
```



@ControllerAdvice

```
public class MyExceptionHandler extends ResponseEntityExceptionHandler {
```

```
    @ExceptionHandler({ CustomerIDNotFoundException.class })
```

```
    public ResponseEntity<MyErrorMessage> handleCidNotFound() {
```

```
        MyErrorMessage errMsg = new MyErrorMessage();
        errMsg.setMytimestamp(LocalDateTime.now());
        errMsg.setMyerror("Customer Id is Not Available");
        errMsg.setMystatus(HttpStatus.NOT_FOUND.value());
```

```
        return new ResponseEntity<>(errMsg, HttpStatus.NOT_FOUND);
    }
```

```
    @ExceptionHandler({ InvalidPhoneNumberException.class })
```

```
    public ResponseEntity<MyErrorMessage> handlePhoneNotFound(RuntimeException ex,
        WebRequest request) {
```

```
        MyErrorMessage errMsg = new MyErrorMessage();
        errMsg.setMytimestamp(LocalDateTime.now());
        errMsg.setMyerror(" Phone Number Not Found");
        errMsg.setMystatus(HttpStatus.FORBIDDEN.value());
```

```
        return new ResponseEntity<>(errMsg, HttpStatus.FORBIDDEN);
    }
```

```
    @ExceptionHandler({ CityNotFoundException.class })
```

```
    public ResponseEntity<MyErrorMessage> handleCityNotFound(RuntimeException ex, WebRequest
        request) {
```

```
        MyErrorMessage errMsg = new MyErrorMessage();
        errMsg.setMytimestamp(LocalDateTime.now());
        errMsg.setMyerror(" No Customers with given City");
        errMsg.setMystatus(HttpStatus.BAD_REQUEST.value());
```

```
        return new ResponseEntity<>(errMsg, HttpStatus.BAD_REQUEST);
    }
}
```

demo6-rest-client – Calling REST API

demo6-rest-client: Files required

1. Customer.java	Same as Demo5
2. Test1.java	Same as Demo5
3. Test2.java	Same as Demo5
4. Test3.java	Same as Demo5