Status	Finished
Started	Monday, 19 October 2026, 9:18 PM
Completed	Monday, 19 October 2026, 9:23 PM
Duration	4 mins 52 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What does the mode attribute of a file object indicate?

a. The access mode in which the file was opened ✓

b. The size of the file

c. The name of the file

d. The current position of the file cursor

The correct answer is: The access mode in which the file was opened

Question **2**

Correct

Mark 1.00 out of 1.00

Select the correct output of the following code

```
fp.seek(5, 1)
```

a. Move file pointer five characters ahead from the beginning

b.
- Move file pointer five characters behind from the current position.

c.
- Move file pointer five characters ahead from the current position. ✓

d.
- Move file pointer five characters behind ahead from the end of a file.

The correct answer is:

- Move file pointer five characters ahead from the current position.

Question **3**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

- a. 0 ✓
- b. null
- c. 2
- d. 1
- e. garbage

The correct answer is:
0

Question **4**

Correct

Mark 1.00 out of 1.00

Which method is used to sets the position of a file pointer

- a. tell()
- b. seek() ✓
- c. ftell()
- d. fseek()

The correct answer is: seek()

Question **5**

Correct

Mark 1.00 out of 1.00

What does the encoding parameter in the open() function specify?

- a. The encoding format of the file ✓
- b. The buffer size
- c. The size of the file
- d. The mode of the file

The correct answer is: The encoding format of the file

Question **6**

Correct

Mark 1.00 out of 1.00

Select the incorrect file access mode

a. wb+
b. r
c. rw+ ✓
d. ab+

The correct answer is: rw+

Question **7**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. read()
b. readline()
c. readlist()
d. readlines() ✓

The correct answer is: readlines()

Question **8**

Correct

Mark 1.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

a. Prints each line of the file
b. Prints the first 10 characters of the file
c. Prints the entire content of the file ✓
d. Prints an error message

The correct answer is: Prints the entire content of the file

Question **9**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

a. a
b. r+ ✓
c. r
d. w

The correct answer is: r+

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following is data file?

a. none of the given choices
b. Text file
c. Both text and binary file ✓
d. Binary file

The correct answer is: Both text and binary file

Question **11**

Correct

Mark 1.00 out of 1.00

Which of the following methods is used to read a single line from a file?

a. read()
b. readline() ✓
c. readlines()
d. readline(size)

The correct answer is: readline()

Question **12**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for writing in binary format?

a. w
b. r+
c. wb ✓
d. rb

The correct answer is: wb

Question **13**

Correct

Mark 1.00 out of 1.00

What is the use of seek() method in files?

a. none of the mentioned
b. sets the file's current position within the file
c. sets the file's current position at the offset ✓
d. sets the file's previous position at the offset

The correct answer is:
sets the file's current position at the offset

Question **14**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

a. The access mode of the file
b. The file's read/write position
c. The encoding of the file
d. The buffer size for the file operations ✓

The correct answer is: The buffer size for the file operations

Question **15**

Correct

Mark 1.00 out of 1.00

What does the following code do?

```
fo = open("foo.txt", "w")
```

a. Opens an existing file in read mode

b. Creates a new file for writing ✓

c. Appends to an existing file

d. Opens a file in binary mode

The correct answer is: Creates a new file for writing