Status	Finished
Started	Tuesday, 20 October 2026, 8:20 PM
Completed	Tuesday, 20 October 2026, 8:26 PM
Duration	5 mins 56 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

The process of dividing a computer program into separate independent blocks of code with specific functionalities is known as _____.

a. Programming
b. More Programming
c. Modular Programming ✓
d. Step Programming

Question **2**

Correct

Mark 1.00 out of 1.00

Which of the following function definition header is wrong?

a. def div(p1=4, p2, p3): ✓
b. def mul(p1, n1, m1):
c. def sum(n1, n2, n = 3):
d. def scan(p1, p2 = 4, p3 = 5):

Question **3**

Correct

Mark 1.00 out of 1.00

Write the output of : print(min(tuple("computer")))

a. o
b. t
c. u
d. c ✓

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the following function call?

```
def fun1(name, age=20):
   print(name, age)
fun1('Emma', 25)
```

a. Emma 25 ✓

b. Emma 20

c. age

d. name

Question **5**

Correct

Mark 1.00 out of 1.00

Fill in the line of the following Python code for calculating the factorial of a number?

```
def factorial👎 :
    if (n==1 or n==0):
       return 1
    else:
        return ——
num = 5;
print("number : ",num)
print("Factorial : ",factorial(num))
```

a. (n-1)*(n-2)

b. n*(n-1)

c. (n * factorial(n - 1)) ✓

d. fact(n)*fact(n-1)

Question **6**

Correct

Mark 1.00 out of 1.00

Write the output of : print(abs(-45))

a. None of the mentioned
b. 45 ✓
c. 45.0
d. -45

Question **7**

Correct

Mark 1.00 out of 1.00

Which of the following function headers is correct?

a. def fun(a, b, c = 3, d)
b. def fun(a = 2, b, c = 3)
c. def fun(a, b = 2, c = 3) ✓
d. def fun(a = 2, b = 3, c)

Question **8**

Correct

Mark 1.00 out of 1.00

The return statement in function is used to _____.

a. None of the mentioned
b. returns the control to the calling function
c. return value
d. Both return value and returns the control to the calling function ✓

Question **9**

Correct

Mark 1.00 out of 1.00

In a program, a function can be called _____ times.

a. 3
b. Multiple times ✓
c. 5
d. 2

Question **10**

Correct

Mark 1.00 out of 1.00

A function may return multiple values using _____.

a. String
b. Dictionary
c. Tuple ✓
d. List

Question **11**

Correct

Mark 1.00 out of 1.00

Which keyword is used to begin the definition of a function?

a. def ✓
b. Def
c. DEF
d. Define

Question **12**

Correct

Mark 1.00 out of 1.00

What is the output of the following display() function call?

```
def display(**kwargs):
   for i in kwargs:
      print(i)
display(emp="Kelly", salary=9000)
```

a. Kelly
9000

b. ('emp', 'Kelly')
('salary', 9000)

c. TypeError

d. emp ✓
salary

Question **13**

Correct

Mark 1.00 out of 1.00

What will be the output of the following Python code?

```
def sayHello():
   print('Hello World!')
sayHello()
sayHello()
```

a. Hello
Hello

b. 'Hello World!'
'Hello World!'

c. None of the mentioned

d. Hello World! ✓
Hello World!

Question **14**

Correct

Mark 1.00 out of 1.00

A variable that is defined inside any function or a block is known as a _____.

a. inside variable
b. Local variable ✓
c. Global variable
d. Function Variable

Question **15**

Correct

Mark 1.00 out of 1.00

def cal(n1) : What is n1?

a. Keyword
b. Argument
c. Parameter ✓
d. None of the mentioned