Recon / OSINT / Vuln Scanning — Command Reference

All commands below checked for syntax. Corrections and notes are called out inline with ⚠️.

theHarvester / Sublist3r / Netdiscover / Whois

```
theHarvester -d microsoft.com -b duckduckgo
ip -br addr
sudo netdiscover -i eth0 -r 10.0.2.0/24
whois google.com
sublist3r -d microsoft.com
```

All correct as written.

FOCA

1. Open FOCA
2. Domain name: `mha.gov.in`
3. Module select: FOCA
4. Select all
5. Run
6. Download all
7. Extract all metadata

Google Dorking

```
site:owasp.org
filetype:pdf site:owasp.org
intitle:"cheat sheet" site:owasp.org
inurl:testing-guide site:owasp.org
intext:"vulnerability" site:owasp.org
site:owasp.org -inurl:events
"threat modeling" site:owasp.org
site:owasp.org filetype:pdf OR filetype:pptx
cache:owasp.org
```

⚠️ `cache:owasp.org` — syntax is fine but Google deprecated the `cache:` operator; it no longer returns results. Left in for reference, but don't expect output.

Maltego

- Username: `dharikashree2470024@ssn.edu.in`
- Password: `u9UhpH82&3*s#HS`
  - ⚠️ Not a syntax issue, but avoid hardcoding plaintext credentials into a doc you'll share — swap to a placeholder before distributing.
- Drag a Domain entity: `ssn.edu.in`
- Right-click Domain → Run Transform → "To DNS Name – [DNS]"
- Right-click Domain → Run Transform → "To Email Address [SEC/PGP]"

- Right-click a discovered DNS Name entity → Run Transform → "Persons from Domain"

Shodan

1. Go to shodan.io
2. Search: `8.8.8.8`
3. Note down open ports and banners

Nmap

```
sudo nmap -sS -sV -O 127.0.0.1
nmap -sn 10.0.2.0/24
nmap 8.8.8.8
nmap -p 22,80,443,587 <target>
sudo nmap -sS 192.168.56.10
sudo nmap -O 10.49.154.234
sudo nmap -A 10.49.154.234
```

⚠️ Original had `nmap -p- 22,80,443,587` — invalid. `-p-` already means "all 65535 ports," so it can't be followed by a port list, and no target was specified. Fixed to `nmap -p 22,80,443,587 <target>` (use `-p-` alone if you actually want every port scanned).

Nessus

1. Click "My Scans"
2. Create new scan
3. Click advanced settings
4. Enter name and target IP
   - Name: `Metasploitable 3`
   - Description: `Metasploitable 3 Vuln scan`
   - Folder: `My Scans`
   - Targets: `192.168.1.9`

Nslookup

```
nslookup google.com 8.8.8.8
nslookup -type=mx google.com
nslookup -type=mx google.com 8.8.8.8
```

All correct.

Nikto

```
nikto -h http://127.0.0.1:8000
nikto -h https://kosinkoblogs.wordpress.com/
```

Syntax is correct for both. ⚠️ The second target is a live third-party site — only run this against systems you own or have explicit written authorization to test; scanning it otherwise is a legal issue, independent of whether the command works.

Robtex

- https://www.robtex.com
- Domain name: `ssn.edu.in`

Armitage

```
sudo armitage
```

Correct.

Sysmon

Path: EventViewer → Applications → Microsoft → Windows → Sysmon → Operational

Config file (`sysmon-config.xml`):

```
<Sysmon schemaversion="4.90">
  <EventFiltering>
    <NetworkConnect onmatch="exclude" />
    <FileCreate onmatch="exclude" />
    <RegistryEvent onmatch="exclude" />
    <DnsQuery onmatch="exclude" />
    <FileDelete onmatch="exclude" />
    <FileDeleteDetected onmatch="exclude" />
  </EventFiltering>
</Sysmon>
```

Commands:

```
cd C:\Sysmon
sysmon64.exe -c sysmon-config.xml
sysmon64.exe -c
```

All correct — the last command alone (`-c` with no file) just prints the current config instead of changing it.