

# Index

Page numbers in **bold** refer to figures and  
page numbers in *italic* indicate tables.

AALC 150–50 model **350**

Acceleration 124, **468**

Acceleration/frequency toleration limits **369**

Accidents 185

ACVs 13

hovercraft 13, *13*, *14*

Accommodation space requirements 399

ACV

accidents 13

applications 41–5

calculation of transverse stability 163–8,  
166–8

development in UK 9–21

dimensions of *386–7*, *389–90*

dynamic trim 190

factors affecting transverse stability  
168–72

longitudinal motion in regular waves for  
308–22

manœuvrability 206

moving over deep water 190–3

operation modes over ground terrain **122**

over shallow water 194–6

water surface deformation in/beyond air  
cushion over calm water 190–3

weight of *389–90*

Aerodynamic force and moment 221, 223

Aerodynamic momentum drag 96

Aerodynamic profile drag 95–6, *96*

Aerodynamic yawing moment **226**

Air clearance 50, 62, 65

characteristic curves **424**

Air cushion 2, 42

adiabatic stiffness coefficient 348

characteristics 72

characteristics curves 70, **71**

craft, classification 6

flow rate due to mass change rate of 301  
performance

on rigid surface 51

prediction 55–65

pressure distribution 472, **472**

stability 76–83

supported vehicles, *see* ACV

system 282–4, 299–301, 313–17

theory 48–83

early developments 50–5

Air duct 70, **71**, **424**

calculation 410–12

characteristics 78

configuration **413**

loss coefficient *411*

non-dimensional characteristic curves  
345–6

non-dimensional characteristics 350

system 412, **413**

valves 216

Air flow coefficient **64**

Air flow rate 133–4, 339, **340**

coefficient **149**

determination 407–10

distribution effect 339

Air gap **83**, **128**

Air inlet

inclination angle **417**

of integrated lift/propulsion systems **414**

pressure losses **414**

Air jet moment from cushion to atmosphere  
286–7

Air jet propulsion 504–7

Air jet streamlines **54**

- Air leakage 79
  - flow rate of 300, 314–15
  - under SES sidewall **67**
- Air lubrication 2–3, 9, 48
- Air propellers 507–14
  - blade erosion and its mitigation 514–15
  - blade types and efficiency 509–10
  - construction 513
  - diameter/tip speed relationship 511
  - selection **510**, 511
  - weight 513
- Air propulsors 211–14
- Air rudders 217
- Air streamlines **55**
- Air supply to bow skirt area 328
- Aluminium alloy 459
- Amphibious capability 41, 48
- Amphibious hovercraft 1, **3**, 4, **4**, 274
- Anti-plough-in
  - hydrofoils 327
  - requirements 453
- Anti-roll systems 335–6
- Anti-spray plate **335**
- Anti-submarine vessels 41, 42
- AP1.88 15, 20, **21**, 40, 41, 213, 507, 520, **592**, **594**
- AP1.88–400 44
- Aprons 271
- Archimedes' principle 66
- Arctic transport 45
- Axial flow pumps 559
  
- Bag and finger bow seal 247
- Bag and finger bow skirt **153**, 247, 249
- Bag and finger skirt 49, 52, 55, **59**, 62, 71, 129, **238**, 243, 262, **451**
  - equations for static geometry and force analysis 251–5
  - forces acting on **263**
  - model tests 250–1
  - static geometry 250–7
  - supporting forces acting on joints 256–7
- Bag and nozzle skirt
  - chain connection for **237**
  - flexible diaphragm connection **237**
- Bag and pericell skirt 243, **244**, 261
- Bag chord length 251
- Bag cushion pressure ratio **63**, **262**
- Bag pressure 59
- Bag skirt 49
- Bag stern seal 248
  
- Bag stern skirt, geometry and analysis of
  - forces in double or triple 258–60
- Bag to cushion pressure ratio 62, **65**, 251
  - coefficient 60
- Beam seas, differential equations of coupled
  - roll and heave motion of SES in **291**
- Bearings 571
- Bell Aerospace Corporation 25, 29
- Bell-Halter Corporation 29
- Bell Textron Jeff (B) **599**
- Bending 469
- Bending moment 470, **470**, **471**
  - acting on midship section 469–70
  - cushion-borne operation 470
  - hull-borne operation 471
  - transverse 471
- Bernoulli equation 53, 412, 495
- Bernoulli theory 67
- BH.7 14, **15**, 239
- BH.110 29–30, **29**
- Blade element theory 499–500, **501**, 524
- Blade velocity vector diagram **496**
- Bliss, Dennis 11, 233
- Blohm and Voss 40
- Boundary layer thickness 54
- Bow acceleration **307**
- Bow finger tip line 327
- Bow hydrofoils 333–4, **334**
- Bow seal during take off, water contact
  - phenomenon of **105**
- Bow skirt
  - emergence **302**
  - tuck-in 326
- Bow skirt area
  - air supply to 328
  - relative to stern 327
- Bow skirt finger tip **258**
- Bow/stern acceleration, frequency response
  - for **321**
- Bow/stern seal
  - and base-line gap 149
  - during heeling, righting moment of **155**
  - equipment 326–7
  - heave stiffness for 328
  - relative gap **150**
- Bow/stern seal drag 102–3
  - B.A. Kolezaev method 103
  - MARIC method 102
  - Rin-Ichi Marao method 103
- Bow/stern seals 246–9
  - interaction 188

- Bow/stern skirts, height determination 453
- Brødrene Aa 39–40
- British Hovercraft Corporation 10
- Britten-Norman 12
- Cabin 370, 373
  - volume 41–2
- Captured air bubble 2–3, 246
- Cargo vessels 40
- Catamarans 1, 42–3, 113
- Cavitation 522–4, **523**, 531, **537**, 545, 561
  - water jets 556–7
- Cavitation tunnel **552**
- Centrifugal fans 425–9, **507**
  - aerodynamics characteristics **426**
- Centrifugal pumps 558
- CG 359, **359**, 461, 463, 464, 469, 564
- China, ACV and SES development 32–9
- Chong Cheng Shipping Company 35
- Cirrus 39
- Cobblestone effect 322, 323, **324**
- Cockerell, Sir Christopher 3, 7, 9, 48, 233, 275
- Coefficient  $f$  50
- Coefficient of added mass 278
- Coefficient of elongation 347
- Commercial design parameters 378
- Computer program for differential equations of motion 290
- Constant cushion volume 74
- Construction cost per unit seat 398
- Contact forces 441–2
- Continuity equation of flow 282
- Control equipment 208
- Control surfaces 207–17
  - features 216
  - state of the art 216–17, 216
- Control system components 565
- Controllable pitch air propellers (ducted propellers) 211–13
- Coordinate system 297–8, **298**, 308, **309**
- Correction coefficient of wetted surface **109**
- Correction coefficient of wetted surface area of sidewalls **110**
- Couplings 571
- Course-keeping ability
  - and handling 374
  - under quartering or beam winds 375
- Course stability 224–7
  - analysis 225–7
  - dynamic 225
  - static 224–5
  - vertical fins for 208, **209**
  - see also* Stability
- Cushion air
  - compressibility **321**, 322–3
  - flow rate and pressure 71
- Cushion attenuation coefficient vs. craft speed **465**
- Cushion-borne operation
  - bending moment 470
  - in high waves 336–8
- Cushion compartmentation 163–4, 169, **170**
- Cushion depth, damping effect of 323
- Cushion depth/beam ratio 359
- Cushion flow coefficient 401
- Cushion flow rate 334
- Cushion flow rate coefficient 62
- Cushion force 214–16, 222–3, 284
- Cushion geometry 49
- Cushion height **359**
- Cushion height/width ratio versus transverse roll stiffness **360**
- Cushion length/beam ratio 87, **101**, **132**, **150–1**, 330–1, **332**, **357**, 400
- Cushion lift power coefficient 62
- Cushion moment 222–3, 284
- Cushion pressure 41, 50, 59–60, 73, 79, 80, 89
  - analysis of forces acting on fingers under 264
  - and heave amplitude **81**
  - during plough-in 326
  - fluctuations 277, **324**
  - spatial distribution 278
  - trends **401**
- Cushion pressure coefficient 60, 62
- Cushion pressure distribution **472**, 473
  - vs. ship speed **181**
- Cushion pressure/length ratio 89, 132, 149, 400
- Cushion pressure ratio 344
- Cushion static pressure 506, **506**
- Cushion system fans 507
- Cushion wave-making drag **98**
- Cushioncraft CC1 12
- Cushioncraft CC2 12
- Cushioncraft CC5 12, **507**
- Damping coefficient 76–83, 278
  - calculation 77–80
  - experimental methods 80–2

- Damping effect
  - of cushion depth 323
  - on seaworthiness 333–5
- Deck area 41–2
- Deck plates, design load 473
- de Laval, Gustav 2
- Design 46–7
  - concepts 190
  - inertial loads 461–3
  - leading particulars selection prior to **402**
  - loads 469
  - methodology 353–5
  - parameters 354, 377, 378–9
  - checks during design 397–9
  - process 377
  - sequence 377
- Detachable bow/stern seals 249
- Diaphragms 251
  - installation 451
  - of D-shape bags 264–5
- Diesel engines 579, **581**, 588–96
  - cooling systems 590–4
  - exhausts 595
  - lubrication system 595
  - maintenance 610–11
  - number of engines and layout 588–90, **589**
  - operation 607–10
  - relief valves 595
  - vibration 594–5
- Differential air momentum drag from
  - leakage under bow/stern seals 97
- Differential equations of coupled roll and heave motion in beam seas **291**
- Differential equations of longitudinal motion in waves, block diagram **297, 305**
- Differential equations of motion 223–4, 281–90, 304–7, 317–18
  - computer program for 290
  - formation 219–20
  - in regular waves 313
- Dimensions
  - determination 354, 377–404
  - limitations 399
  - of ACV 386–7, 389–90, **403**
- Disc loading **498**
- Displacement, ACV 384–97
- Docking, strength calculation 473
- Drag
  - components, classification 84–5
  - forces 84–134
  - in head seas **338**
  - in waves **338**
  - of non-flush sea-water strainers 116–17
  - of rudders 115–16
  - of shafts (or quill shafts) and boss 116
  - of strut palms 116
  - over calm water 120, 130
  - see also* Hydrodynamic drag; Residual drag; Seal drag; Skirt drag; Total drag; Wave-making drag
- Drag/weight ratio **94**
- Driver technique 185
- D-shape bags 184, **184**, 251
  - diaphragms of 264–5
- DTNSRDC 28
- Duct system characteristic 323–4
- Ducted fans 515–20
  - duct design 518–19
  - fan selection 517
  - stators 518
- Ducted propellers 211–13, 507, 515
- Ducted propulsors 274, 520
- Dynamic motions 273–341, 604
  - historical review 274–6
- Dynamic transverse righting moment of SES 159
- Dynamic trim **156**
  - on cushion over calm water 200–4, **201**
  - over calm water for ACV 308–12
  - prediction over calm water 200–3
- Elastic modulus 347
- Electrical equipment, weight of 396
- Elevons 208–10
- Energy equation 141
- Engine
  - cooling water, hydrodynamic momentum drag due to 115
  - failure modes and effects 606
  - heating for sub-zero temperatures 584–5
  - monitoring and control system **608**
  - operating characteristics 581–2
  - power ranges 579
  - starting 605
  - systems and controls 607
- Equations of motion 217
- Equilibrium equation
  - of forces 265–6
  - static forces 309–10
- Euler number 344
- Extended segment skirts 245, **244**, 260
- External air stream lines 180

- External forces on hull 461–5
- External response 327
- Fan air duct
  - characteristic 323
  - characteristic equation 310
- Fan air inlet/outlet system 413–19
- Fan blade regulation 216
- Fan characteristic equation 142
- Fan characteristics 284
- Fan curve gradient 327
- Fan flow rate 172
- Fan inlet
  - loss coefficient 412
  - pressure recovery coefficient at 412
  - system 413–17
- Fan outlet system, SES 419
- Fan overall pressure 412–13
- Fan speed 148
- Fans
  - aerodynamic characteristics **423**
  - air flow rate 430
  - centrifugal 425–9, **507**
  - cushion system 507
  - efficiency-flow rate characteristics **431**
  - horizontal arrangement 418–19
  - HVAC systems 423
  - impeller diameter 428–9
  - noise reduction 430
  - non-dimensional characteristic curves 345–6
  - non-dimensional characteristics 350
  - off-design operation 422
  - overall pressure-flow rate characteristics **431**
  - overall pressure head 410–13
  - pressure-flow characteristic curve 430
  - selection of type 420–5, **421**
  - by means of specific speed 426–8
  - vertical arrangement 418
  - see also* Ducted fans; Lift fans
- Fast Attack SES 44
- Fast vessels 42
- Fatigue endurance of transmission shafts 569–71
- Finger bow skirt 247
- Finger height ratio 454
- Finger inclination angle 454
- Fins 217
- Flagellation 437
- Flat lift fan 323–4
- Flexible bow seal **135**
- Flexible bow/stern seal 153–4
- Flexible skirt 11, 28, 47–9, 52, 56, 91, **100**, 127, 173, 232, 235
  - advantages 232
  - development 233
- Flow coefficient 407, 408
- Flow continuity equation 78, 141
  - for small perturbations 315–17
- Flow modes in heaving motion 77, **78**
- Flow rate
  - air leakage 300
  - air leakage and cross-flow, small
    - perturbation equation for 314–15
  - coefficient 49, 71–3, 345
  - continuity equation 310–12
  - due to mass change rate of air cushion 301
  - equation 141
  - minimum calm water drag 409–10
- Flow rate–pressure head linear equation with small perturbation 313–14
- Fluttering 437
- Foil-shaped appendages 115
- Footprint pressure 41
- France 40
- Frequency response
  - bow/stern acceleration **321**
  - cushion pressure **293**
  - heave acceleration 292, **319**
  - heave amplitude 318–19, **318**
  - heave motion 77
  - pitch amplitude 319–20, **319**, **333**
  - roll amplitude **293**
  - wave exciting force **320**
  - wave exciting moment **320**
- Froude–Krilov hypothesis 276–7, 296
- Froude number 85, 87, **91**, **92**, **102**, **103**, **109**, **110**, **115**, **177**, **181**, 196, **338**, 348–9
  - and wave profile **189**
- Froude scaling relationship 342
- Fuel and oil, weight of 396
- Fuel consumption 397–8
- Fuel filtering 606
- Fuel system 605
- Gap height 123
- Gas turbines 579, **583**, 596–603, **597**, **602**
  - air intake filtration 601–3, **603**
  - air intake flow requirements 600
  - alarms 605

- inflow distortions 600
- layout and engine selection issues 598–9
- maintenance 610–11
- noise 603
- operation 610
- protection from foreign object damage 600–1
- Gearbox 572–3, **575**
  - power flow diagram **574**
- Generators 595
- Geometrical dimensions 297–8, **298**, 308, **309**
- Germany 40
- Goldstein factor 525, **526**
- Gorkovchanin* 127
- Griffon Hovercraft 25
- GRP 38, **38**, 39, 459
- Guide wheels on land 210–11, **211**
- Habitability requirements 365–74
- Halter Marine Inc. 29
- Harbin Shipbuilding Engineering Institute (HSEI) 32, 48
- HD-1 12
- HD-2 **194**
- Head winds, performance 341
- Heat generation 28
- Heave 273
- Heave acceleration, frequency response **292**, **319**
- Heave amplitude 75, 80
  - and cushion pressure **81**
  - frequency response 318–19, **318**
- Heave attenuation system 335–6
- Heave displacement 81
- Heave frequency 80
- Heave motion 76, **76**, 81, **306**, 341
  - flow modes in 77, **78**
  - frequency response for 77
- Heave position **83**
- Heave stability 80, 83
  - derivatives
    - calculation 77–80
    - experimental methods 80–2
- Heave stiffness for bow/stern seals 328
- Heave velocity 81, **83**
- HEBA high efficiency fan 431–2
- Heeling **138**, **141**
  - angle 361–2
  - moment 361
  - regulation using weight of persons and water (oil) ballast 215
  - restoration moment **145**
  - restoring moment during 223
  - righting arm **147**
  - righting moment of bow/stern seal during **155**
  - with air cushion compartmentation on rigid surface **164**
  - with air cushion compartmentation on water **164**
  - without air cushion compartmentation on water **164**
- High-performance marine vehicles, classification **2**
- High-speed marine vehicle types 1
- HM-2 14–15, 20, 330, 356, **408**
  - bow seal **17**
  - glass reinforced structures under construction **16**
  - stern seal **17**
- HM-5 20
- HM-218 **16**
- HM-221 **18**
- Holland 40
- Horizontal air rudders 208–10
- Hovercraft
  - accidents 13, *13*, *14*
  - classification **6**
  - future 45–6
  - historical background 1–4
  - principal particulars for early Chinese and British **7**
  - see also* ACV; SES
- Hovercraft Development Ltd 10, 11, 275
- Hovering damping 76–83
- Hoverlloyd 16
- Hovermarine Limited 14, 18
- Hull
  - design 185
  - efficiency 544
  - external forces on 461–5
  - strength of *464*
  - structural design 474, *476*
  - weight of 393, 397
- Hull-borne operation, bending moment 471
- Hump drag 132
- Hump transition speed 364
- HVAC 515
- Hydrodynamic coefficients 222
- Hydrodynamic drag 274
  - due to engine cooling water 115
  - see also* Drag

Hydrodynamic forces and moments 221–2  
 acting on sidewalls 285–6, 295, 303  
 acting on skirts **294**, 301–3  
 acting on stern seal 303  
 Hydrodynamic resistance 1, 178  
 Hydrofoil patrol boat (PHM) 32  
 Hydrofoils 42, 43  
 anti-plough-in 327  
 Hydrostatic pressure acting on bottom and  
 sidewalls 473  
 Hyperbolic distribution 89

Ice breaker 45  
 Inducer pumps 559  
 Inflatable diaphragms, tension calculation  
**252**  
 Inner draft 132, **133**  
 Inner/outer water lines **126**  
 Inner/outer water surfaces 188  
 Insulation 370  
 Internal air stream lines 180  
 Internal wave profiles 177  
 Italy 40

Japan 40  
 JEFF(A) 25, 164, 241, 436, 463  
 JEFF(B) 25, 96, 463  
 Jet extensions 49  
 Jet velocity **498**  
 Jetted air rudder 208  
 Jetted bag type skirt 235  
 Jetted extensions **128**  
 Jetted nozzle skirts **236**  
 Jetted skirt 127  
*Jin Sah River* 5, 35

3K-SES 28  
 Kaario, Toivio 3  
 Korea 40

LACV-30 26  
 Laplace transformation 317  
 LCAC 25–6, 43, 241, 507  
 LCAC-001 **207**  
 LCG 99, 130–2, **130**, **131**, 185  
 LEBED 23  
 LHD-4 26  
 Life-saving equipment, weight of 395  
 Lift drag **185**  
 ratio **134**  
 Lift fans 282–4

balancing 429  
 basic data **427**  
 characteristics at small flow rate 429  
 impellor speed and diameter 429  
 installation 430, **430**  
 pressure-flow of 296  
 selection and design 420–32  
 statistics **427**  
 technical issues 429–32  
 Lift power 51, 54–5, 148  
 output coefficient **65**  
 versus air inlet location **415**

Lift system  
 design 406–32  
 distribution of pressure **406**  
 ducting problems 326  
 insufficiency 326  
 layout **406**  
 power 412–13  
 simulated pressure distribution **411**  
 Lifting situation, strength calculation 473  
 Limiting roll angles versus relative cushion  
 height **362**

Limiting stress design 564  
 Liquid load 396–7  
 Load transporters 45  
 Local loading 471–2  
 Longitudinal centre of gravity, *see* LCG  
 Longitudinal metacentric height 356–60  
 Longitudinal motion  
 in regular waves for ACV 308–22  
 in waves 294–307  
 principal parameters **298**  
 Longitudinal stability keel (LSK) 139  
 LSD-1 26

M10 44

Machinery  
 control 604–5, *604–5*  
 space layout 606  
 Manœuvrability 205–31  
 ACV 206  
 basic assumptions and nomenclature 218,  
**218**, **219**  
 differential equations of motion 217–24  
 features of ACV/SES 205–6  
 key factors 205–7  
 on ice 376  
 requirements 374–6  
 MARIC 3, 33–8, 56, 62, 84, 88, 102, 104–6,  
 111, 117, 119, 125, 143, 465–7

- Marine Design & Research Institute of China, *see* MARIC
- Marine propellers
  - blade pitch 529
  - blade sections 521
  - design 520–37
  - efficiency 520
  - example propeller and shaft layouts for SES **533**
  - for SES 535–6
  - installation 521
  - $K_T$  and  $K_Q$  diagrams **530**
  - selection procedure 526–31, **528**
  - types 522
- Market development 17–22
- Materials 28
- Mayer velocity distribution 54
- MCM 31–9, 44
  - detail design and construction 31–2
  - primary design 31
- MCMH **31**, 40
- MCR (Maximum Continuous power Rating) 577
- Medium sized patrol SES 32
- MEKAT 40
- Metacentric height
  - longitudinal 356–60
  - transverse 356–60, 358
- Military applications 43–4
- Military design parameters 378
- Military SES/ACV 32
- Military transport vehicles, time interval from invention to first application 9
- Mine countermeasures 11, 30–9
- Mine sweepers 41
- Mixed flow pumps 558
- Model 711 127, 173
- Model 711–3 138
- Model 711–I 33, **33**, 235, 236
- Model 711–II 34, **34**, 214, **257**, 441
- Model 711–III 34, **34**, 326, 327
- Model 713 189, 327
- Model 716 36
- Model 716–II 37, **37**
- Model 717 **35**, 145, 151, **151**, 188, 189
- Model 717–II **36**, 356
- Model 717–III 356
- Model 717A 156, 158
- Model 717C **121**, 130, **131**, 156, 158, **159**, **160**, 357
- Model 719–II 36
- Model 719 433
- Model 719–II 43, 460
- Model 7202 **35**
- Model 7203 **36**
- Model 7205 **199**
- Model experiments 342–52
- Moment of inertia 463
- Momentum exchange principle diagram **496**
- Momentum theory 97, 493–8, 524, 548–55
- Motion pumping 274
- Motion standards 369
- Motions in waves 273–341
  - characteristic features of ACV and SES 276–8
  - historical review 274–6
  - key craft parameters 278
  - short crested waves 322–4
- MTBO (Mean Time Between Overhaul) 577
- Multi-bag stern skirt 247
- Multi-cell skirt system 165
- Multiple engines 579–81
- MV.PP5 15, **19**, **226**
- MV.PP15 15
- NACA 16 series 524
- NACA 63 series 519
- NACA 66 series 524
- National Research Development Corporation 10
- Needham, C.H. Latimer 11, 232
- Net positive suction head (NPSH) 544, 547, 561–2
- Newton's formula 53
- Noise
  - fans 430
  - gas turbines 603
  - levels 369–72, 370, 372–4, **372**
  - water jets **539**, **540**
- Non-flush sea-water strainers, drag of 116–17
- Norway 39–40
- Nozzles 546–7
  - elevation 547
- Obstacle clearance capability 375, 376
- Oil exploration **22**, 39
- Oil field applications 44–5
- Open loop and segment skirt 243, 261
- Operating modes 136
- Outline design procedure 535
- Overall propulsive efficiency (OPC) 538, 554, 562



- Overturning 173–85, **175**, 182
  - and yawing angles **183**
  - at high speed 177–85
  - at low speed 176
  - in waves 185–6
  - measures for improving resistance to 183–5
  - principal reasons 180–3
  - SR.N6 **186**
- Parabola-shaped sidewalls 114
- Parabolic water planes **114**
- Passenger accommodation 42
- Passenger ferries 44
- Patrol vessels 40
- Payload factor 397
- Payload fraction 384–93
- Peripheral Interface Module (PIM) **609**
- Peripheral jet air cushion 50–1
- Peripheral jet hovercraft 48
- Pitch
  - amplitude, frequency response 319–20, **319**, **333**
  - angle **306**
  - damping 333–4
  - exciting moment **307**
  - motions 340–1
- Pitching 273
- Planing craft 1, 42
- Planing stern seal **154**
- Plate thickness in hull structural design 474, 476
- Platforming 73–4, **74**
  - analysis 74–6
- Pleasure craft 44
- Plenum chamber
  - cushion **8**, **52**
  - on rigid surface 51–2
  - theory 72
- Plough-in 173–85, **174**, 182, **325**
  - at high speed 177–85
  - boundary **181**
  - SR.N6 **186**
  - cushion pressure during 326
  - in following waves for SES 324–8
  - internal reasons 326–7
  - measures for improving resistance to 183–5
  - methods for preventing 327–8
  - principal reasons 180–3
  - progression 178–80, **179**
  - test data 180
  - see also* Anti-plough-in
- Position determination 220–3
- Post-hump speed 374
- Power augmented ram wing (PARWIG) craft 5–9, **6**
- Power consumption
  - in head winds and waves 406
  - per ton-knot 20
- Power loss with increased temperature 584–5
- Power per unit seat 398
- Power plant
  - limitations 399
  - weight of 395–6
- Power transmission 564–73
  - design criteria 564–6
- Power unit selection 577–611
  - design requirements 604–6
- Powering estimation 585–7, **586**, 587
- Pressure coefficient 345, **462**
- Pressure-flow of lift fans **296**
- Pressure head equation 283
- Pressure/length ratio 86, 87
- Propulsion devices, turning tracks for **229**
- Propulsion system 28, 37, **37**, 41, 42
  - design 487–576
  - ACV 487
  - basic theories 492–504
  - methodology 508–9
  - SES 488–92
- PUC-22 **592**
- Puff ports 213–14, **214**, **231**
- Pump
  - characteristics, types and selection 555–6
  - efficiency 559
- Quill shafts, drag due to 116
- Radial flow pumps 558
- Ram air pressure recovery **417**
- Range determination 399
- Recreation design parameters 379
- Reduction drives 572–3
- Relative air gap **65**
- Relative initial static transverse metacentric height 148–9, **148**, **149**, **150**
- Relative sidewall thickness 148–9, **148**
- Relative transverse righting arm **150**
- Remote monitoring 604–5, 604–5
- Residual drag 84–5
  - coefficient of sidewall **115**

- Restoring moment during heeling 223
- Retractable water rudder 210, **210**
- Reversing gear 562–3
- Reynolds law 342
- Reynolds number 100, 104, 344, 345, 349
- Ride characteristics **367**
- Ride control system (RCS) 30, 336, **336**, **337**
- Ride quality 43
- Righting moment of bow/stern seal during heeling **155**
- Rigid body dynamics 277
- Rigid bow seal **135**
- Role parameters 378–9
- Roll amplitude, frequency response curves for **293**
- Rolling 273, **280**, **285**
  - stiffness 359
- Rolling angle and craft speed **178**
- Rolls-Royce ‘Marine Proteus’ gas turbine engines 13
- Rotatable nozzles 562
- Rotating ducted thrusters 213
- Rotating thruster unit **508**
- Rotation derivatives 220–3
- Rudders 208–11
  - drag of 115–16
- Running attitude 156–9, *158*
- Safety factors 473–4, *474*, *475*
- Saunders-Roe Limited 10, 11
- Scaling criteria *351*
  - during static hovering tests 343–8
  - over water 348–52
- Scaling laws 342–52
- Sea Action Group (SAG) 44
- Seakeeping quality 43
- Seal drag 121
  - coefficient **103**
- Seasickness *368*
- Seaspeed 16
- Seaworthiness 90, 273–4, **321**, 328–41, 454
  - effect of principal dimensions 330–3
  - key observations 339–41
  - requirements 364–5, 399
  - scaling conditions 352
- Service speeds 43
- SES
  - applications 41–5
  - dynamic transverse righting moment of 159
  - location of inlets and appendages 188–90
  - plough-in in following waves for 324–8
  - static transverse stability on cushion 137–52
  - transverse dynamic stability 152–63
  - water surface deformation in/beyond air cushion on calm water 197–200, **198**
- SES-100 86
- SES-100A 27, **27**, 28, 30, 85, **85**, 175, 337
- SES-100B **27**, 28
- SES-200 30, *30*, 39, 86, 336, 336
- Shafts and boss, drag due to 116
- Shallow water drag 91
- Shanghai Hu Dong Shipyard 35
- Shaw, R.A. 10
- Shear forces **471**
- Sidewall **109**
  - air leakage **280**, 281–2
  - chines 335
  - configurations **66**
  - depth 333
  - depth ratio 400
  - draft **280**, 281–2
  - geometric configuration 145–8
  - hydrodynamic forces and moments acting on 285–6, 295, 303
  - inner draft 333
  - thickness **66**, **357**
  - thickness ratio 332–3, 402–4
  - wetted surface of **110**
- Sidewall hovercraft 4, **5**
  - development in UK 9–22
- Sidewall water friction drag 104–10
  - B.A. Kolezaev method 109
  - MARIC method 104–6
  - method used in Japan 106–8, **108**
  - NPL method 109
- Sidewall wave-making drag 111–14, **113**
  - B.A. Kolezaev method 114
  - equivalent cushion beam method 111–13
  - Hiroomi Ozawa method 113–14
- Single wall theory 52–5
- Skirt
  - abrasion and corrosion 434
  - abrasion force 441
  - air feed holes 449–50
  - assembly and manufacturing technology 449–51
  - attachments **449**
  - bounce analysis 267–70, **268**, **269**, **270**
  - clearance 79, 82, 171
  - coating **439**, 444–5, *444*

## Skirt (contd)

- components, force acting on **264**
- contact drag 277–8
- damage patterns 433–4
- deformability 455
- deformation **242**
- delamination 433–4, 438
- drag force 441
- dynamic response 271–2
- effect on seaworthiness 328–30
- failure modes 435–6, **435**
- geometric features **451, 452**
- ground interference drag **124**
- hydrodynamic forces acting on **294**, 301–3
- impact force 442
- manufacture flow chart **450**
- observation under water **238**
- pressure drag 101–2
- processing **450**
- service life 433
- shifting installation 215
- shifting system 165
- stiffness 455
- system 184
- tailoring 449–50
- tearing 434
- test boxes 343
- test rig 56–8, **56–9**, 59, 60
- total drag 99
- tuck-in at bow skirt 326
- tuck-under 261–7
- tuck-under boundary 453
- type effect on seaworthiness 329–30
- wave-making drag coefficient **101**
- weight 265–7, 396
- weight per unit area 346, 349–50
- with extended flexible nozzle **236**
- Skirt analysis 232, 452–7
  - forces acting on 262–3
  - forces analysis for deformed fingers **266**
  - hydrodynamic forces acting on skirts
    - running on water **265**
- Skirt bag
  - D-type 184, **184**
  - tension acting on curved sections 262
- Skirt configuration **53**, 134, 165, 233, **233**, 242–5, **244, 245, 249, 250**
  - amphibious ACV 235–42
  - BH.7 **241**
  - design 451–7
  - development 235–49
    - evolution **235**
    - SR.N6 **241**
    - state of the art 235–49
- Skirt design 232, 433–57
  - main issues 234
- Skirt drag 98–103, **124**
- Skirt drag coefficient 134
- Skirt fingers 436, **439**, 441, 442, **442**, 445, 450
  - inward inclination angle 454
- Skirt force (moment) 284
- Skirt friction drag 99–101
- Skirt geometry 453
  - design 323
  - elastic deformation and hysteresis effect 250–1
- Skirt height 328–9, 359
  - and cushion beam ratio 358
  - ratio 400–1
  - statistics **356**
- Skirt joints, selection 447–9, 447, **448**
- Skirt lift apparatus 214–15, **215**
- Skirt loading 437–41, **437**
  - pressure force 437
  - vibration forces 437
- Skirt material 64, 64, 347
  - open weave cloth **443**
  - selection 442–7
  - specific weight 445, **446**
  - tension and tear strength **443**
  - test facilities **440**
  - thickness effect 330
- Skirt/terrain interaction drag 121–3
- SKMR-1 25, 463
- Slamming 1, 466–7
  - forces in waves 364–5
- Slipstream jet velocity **497**
- Small waterplane thin hull vessels (SWATH) 1
- S–N curve 569, **570**
- Speed
  - degradation 330, 331, 341, 364
  - determination 399
  - improvement **332**
- Spray suppression skirts 270–1, **272**, 456–7
- SR.N1 7, 7, 10, 11, 48–9, 507
- SR.N2 11, 13
- SR.N3 11, 12, 13
- SR.N4 11, 12, 13, 14, 16, 17, 239, 330, **330**, 331, **331, 333, 361**, 368, 418, 441, 463, 520
  - drag and thrust curves **119**
  - skirt configuration **240**

- SR.N5 13, 76, 173
- SR.N6 13, 14, **15**, 86, 173, 174, 176, 214, **361**, 418
  - overturning **186**
  - plough-in boundary **186**
- SR.N6-012 185
- Stability 135–86
  - acceptable 137
  - and cushion height
    - ACV 355
    - SES 356
  - coordinate system of craft **167**
  - criteria and standards for stability of SES
    - stability in turns 162
    - stability in waves 162
    - static stability 161–2
  - damage requirements 363
  - design requirements 355–62
  - dynamic stability of ACV travelling over water 173
  - effect of fan flow rate on transverse stability of ACV 172
  - effect of stability skirt clearance on transverse stability 171
  - effect of various parameters on transverse stability 144–51
  - in waves 364
  - internal stability skirts 190
  - longitudinal stability trunks 456
  - requirements 399
    - for large heeling angles 361–2
  - skirt configurations 261
  - standards 355–62
  - static transverse initial stability of ACV 360
  - static transverse stability of ACV **169**
  - static transverse stability on cushion 137–52, **143**
  - static transverse stability without LSK 141–2
  - transverse dynamic stability 152–63
  - transverse stability **358**
    - as function of Froude number **177**
    - during take-off 159–61
    - effect of VCG 171–2
    - factors affecting ACV 168–72
    - for ACV 163–8
    - in waves 161
    - on cushion in motion 154–9
    - with flexible bow/stern seals 154–5
    - with rigid stern seal 155–6
    - without cushion compartmentation 170–1
    - transverse stability moment of heeled SES at speed **160**
    - transverse stability trunks 456
- Standing's formula 197
- Static air cushion characteristics on water surface 66–71
- Static air cushion performance of ACVs on water surface 68–71, **68**, **69**
- Static hovering performance of SES on water 66–8
- Static hovering tests 343–8
- Static thrust 501–4
- Stator systems, design 518
- Steel 459
- Stern bag skirts, geometric parameters **259**
- Stern double planing bag 247
- Stern planing rigid seal 247, 249
- Stern seal **128–9**, **154**
  - hydrodynamic force acting on 303
  - with air bag 248, **248**
- Stern skirt, pressure distribution acting on inner surface **260**
- Streamline
  - analysis 60–2
  - diagram **61**
- Strength calculation 461
- Strength of hull 464
- Strouhal number 346
- Structural design 458–86
  - ACV 459–60
  - current state 460
  - features 458–60
  - hull 474, 476
  - SES 459
- Structural strength
  - analysis, former USSR 467–73
  - calculation 465–7
- Strut palms, drag of 116
- Subcavitating propellers 520, 526
- Subsystem design 354–5
- Supercavitating propellers 522, 531–7
  - outline design procedure 535
- Supports 571
- Surface contact propulsion 574–6
  - design considerations 574–6
- Surface effect ships (SES) 1
- Sway 273
- Swivelling pylons 211, **212**
- Systems 28

- Tacoma Marine Industries 40
- Take-off 124–9, 159–61
  - dynamic stability during 127
  - holes **71**
  - performance 72
  - water contact phenomenon of bow seal during **105**
- TCG 162
- Teeth 271
- Thornycroft, Sir John I. 2
- Thrust
  - deduction **544**
  - in head seas **338**
- Thrust/lift ratio **181**
- Torsion 469
- Torsion load 470, **470**
- Torsional stress 564
- Total drag 85
  - of ACV model 711–IIA **118**
  - of ACV model 7202 **118**
  - over water 117–21
    - ACV 117–19, *117*, **118**
    - SES 119–21
  - skirt 99
- Total system weight 577–9, **578**
- Transmission configuration 582–4
- Transmission shaft
  - design factors 566
  - design load case matrix 568
  - design stresses 566–8
  - fatigue endurance of 569–71
  - sections for analysis **567**
- Transport efficiency 397
- Transverse metacentric height 162, 356–60, 358
- Transverse motions of SES in beam seas 279–94
- Transverse righting moment 160, **295**
- Transverse roll stiffness versus cushion
  - height/width ratio **360**
- Transverse shift of centre of cushion area 165–6, **165**, **166**
- Trim 187–204
  - angle **181**, **182**, **185**
  - calculation 153–4
  - factors influencing 188
  - prediction above hump speed on calm water 203–4
  - regulation using weight of persons and water (oil) ballast 215
- TSL-A **600**, **601**
- Tuck-under **267**
- Turning diameter 374
- Turning performance 227–31
- Turning tracks
  - between bank and non bank turn **230**
  - for propulsion devices **229**
- Twin bag skirt **154**, **451**
- UH-15P **502**
- UK 9–21, 40
- Underwater appendage drag 115–17
- US 25–32
  - amphibious craft 25
  - surface effect ship development 26–30
- USSR (former) 22–5, **22–3**
- Utility applications 44
- Utility craft 45, **590**
- Utility design parameters 378–9
- VA.1 to 3 series 11
- Variable depth sonar (VDS) 32
- Variable-pitch ducted fans **516**
- Variable-pitch propeller hub construction
  - and control system **514**
- VCG 171–2
- Velocity streamlines 501, **502**
- Vertical acceleration 320, **335**, **336**, 365–8, **366**, **367**
- Vertical fins for course stability 208, **209**
- Vertical rudder 208, **209**
- Vessel trim 604
- Vibration 28, 31, **368**, 476–86
  - absorption 478–82
  - acceptable levels **480**
  - analysis 479
  - assessment 485
  - critical operational frequencies **484**
  - damping 370–2
    - design **481**
  - detail design phase 483–5
  - diesel engines 594–5
  - during construction 485
  - exciting force 482
  - high operational speed 477
  - ISO 2372 and ISO 3945 standards 479
  - low natural frequency 476
  - malfunctions caused by 477
  - permissible rules 482
  - preliminary design phase 482–3
  - severe and superharmonic excitation
    - source 476

- tests and trials 486
- water jets **540**
- Vickers 12
- Vortex theory 524–6
- Voyageur* 96
- VT.2 14, **15**
- Waban Aki 45
- Wake factors 544
- Warner, D.K. 3
- Water contact phenomenon of bow seal
  - during take-off **105**
- Water jets 537–64
  - advantages 538
  - cavitation 556–7
  - efficiency **492, 521, 522, 548–54, 549, 551, 557**
  - flush-type inlet 538
  - geometries **541**
  - inlet losses 544–6
  - inlet velocity 560–1
  - inlet with secondary slow speed intake **546**
  - integrated control systems 563–4
  - KaMeWa 522
  - noise **539, 540**
  - overall propulsive efficiency (OPC) 538, 554, 562
  - performance 540–1
  - physical dimensions 540
  - pressure effects around intake 553
  - selection **543, 550, 559–62**
  - steering 562–3
  - thrust vs. craft speed **558**
  - vibration **540**
  - weight vs. inlet diameter 562, **563**
- Water propulsor types **491**
- Water surface deformation **189, 192**
  - at inboard profile **194**
  - HD-2 **194**
  - in/beyond ACV air cushion over calm water 190–6
  - in/beyond SES air cushion on calm water 197–200, **198**
- Water surface profile 192
- Wave amplitude **196–7**
- Wave equation 298–9, 312
- Wave exciting force, frequency response for **320**
- Wave exciting moment, frequency response for **320**
- Wave height **338, 340**
- Wave impact
  - force distribution 472–3
  - loading coefficient **462**
  - pressure 463–5, **464**
- Wave interference 323
- Wave-making drag 86–93, **90, 91, 92, 94, 94, 97**
  - coefficient **88, 89, 94–5**
  - coefficient of slender sidewalls **114**
  - influence of water depth **92**
  - ratio **91**
- Wave-making drag–lift ratio 89
- Wave profile
  - and Froude number **189**
  - beyond cushion, model 7205 **199**
  - in/off cushion due to moving rectangular air cushion **193**
- Wave pumping 274, 278
  - concept 49, 73–6
  - motion 74, 74
  - rate 75–6
- WD-901 37, **37, 38, 189**
- WD-902 **38**
- Weapon systems 32, 42
- Weber number 100, 349
- Weight
  - components 379–80
  - distribution 385, 388
  - equilibrium equation 142
  - of ACV 389–90, **403**
  - of air propellers 513
  - of deck equipment and painting 393–4
  - of electrical equipment 396
  - of equipment 394
  - of fuel and oil 396
  - of hull 393, 397
  - of life-saving equipment 395
  - of metallic structure 393
  - of power plant 395–6
  - of ship systems 395
  - of skirt system 265–7, 346, 349–50, 396
  - of water-jet unit 562, **563**
  - vs. displacement **394**
- Weight classification
  - former USSR 381–2
  - high-speed boats 382–4
  - MARIC 380
  - USSR 381
  - Western countries 382
- Weight estimate 379–84
  - checklist 391–2

- West, A.A. 52–5, 63
- Westland Aircraft Limited 11
- Wetted surface
  - correction coefficient of **109**
  - of sidewalls 104, **106, 107, 110**
- Wetted surface area, correction coefficient **107, 108**
- Wetted surfaces 188
- Whirl speed 568–9
- Wind direction and speed **228**
- Wind tunnel model tests 347
- Wind tunnel tests 343
- Wing in ground effect machines (WIG and PARWIG) 1, 5–9, **6**
- Work boats 45
- XR-1 138
- XR-1A 26, **26**
- XR-1D 30
- XR-5 29
- Yaw 92, **94–5**, 273
- Yawing angles and overturning **183**