

Oracle Database Schema Documentation

This document contains a highly detailed breakdown of the ALERT 4.0 GOVERNMENT system's database schema running on Oracle Database. The system follows a Microservices Architecture. The schema definitions are auto-generated and maintained using Spring Data JPA and Hibernate. Below are the precise `CREATE TABLE` Oracle SQL statements matching the application's entity structures, along with descriptions of their purpose and data stored.

Table: ai_predictions

Service / Module: ai-service

Entity Class: AiPrediction

Description: This table is responsible for storing data related to `AiPrediction` within the ai-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE ai_predictions (  
    PREDICTIONID VARCHAR2(255),  
    INCIDENTID VARCHAR2(255),  
    PREDICTEDSEVERITY VARCHAR2(255),  
    SPREADRADIUSKM VARCHAR2(255),  
    RECOMMENDATIONS VARCHAR2(255),  
    GENERATEDAT TIMESTAMP  
) ;
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
PREDICTIONID	VARCHAR2(255)	String	Stores the predictionId information for AiPrediction.
INCIDENTID	VARCHAR2(255)	String	Stores the incidentId information for AiPrediction.
PREDICTEDSEVERITY	VARCHAR2(255)	String	Stores the predictedSeverity information for AiPrediction.
SPREADRADIUSKM	VARCHAR2(255)	String	Stores the spreadRadiusKm information for AiPrediction.
RECOMMENDATIONS	VARCHAR2(255)	String	Stores the recommendations information for AiPrediction.

GENERATEDAT	TIMESTAMP	LocalDateTime	Stores the generatedAt information for AiPrediction.
-------------	-----------	---------------	--

Table: alerts

Service / Module: alert-service

Entity Class: Alert

Description: This table is responsible for storing data related to `Alert` within the alert-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE alerts (  
    ALERTID VARCHAR2 (255) ,  
    SENDERID VARCHAR2 (255) ,  
    TITLE VARCHAR2 (255) ,  
    DESCRIPTION VARCHAR2 (255) ,  
    SEVERITY VARCHAR2 (255) ,  
    STATUS VARCHAR2 (255) ,  
    TARGETDISTRICT VARCHAR2 (255) ,  
    TARGETTALUK VARCHAR2 (255) ,  
    INCIDENTID VARCHAR2 (255) ,  
    CREATEDAT TIMESTAMP ,  
    VALIDUNTIL TIMESTAMP  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
ALERTID	VARCHAR2 (255)	String	Stores the alertId information for Alert.
SENDERID	VARCHAR2 (255)	String	Stores the senderId information for Alert.
TITLE	VARCHAR2 (255)	String	Stores the title information for Alert.
DESCRIPTION	VARCHAR2 (255)	String	Stores the description information for Alert.
SEVERITY	VARCHAR2 (255)	String	Stores the severity information for Alert.
STATUS	VARCHAR2 (255)	String	Stores the status information for Alert.
TARGETDISTRICT	VARCHAR2 (255)	String	Stores the targetDistrict information for Alert.
TARGETTALUK	VARCHAR2 (255)	String	Stores the targetTaluk information for Alert.

INCIDENTID	VARCHAR2 (255)	String	Stores the incidentId information for Alert.
CREATEDAT	TIMESTAMP	LocalDateTime	Stores the createdAt information for Alert.
VALIDUNTIL	TIMESTAMP	LocalDateTime	Stores the validUntil information for Alert.

Table: analytics_snapshots

Service / Module: analytics-service

Entity Class: AnalyticsSnapshot

Description: This table is responsible for storing data related to AnalyticsSnapshot within the analytics-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE analytics_snapshots (
    SNAPSHOTID VARCHAR2 (255) ,
    SNAPSHOTDATE VARCHAR2 (255) ,
    TOTALACTIVEINCIDENTS NUMBER (10,0) ,
    TOTALALERTSSENT NUMBER (10,0) ,
    TOTALPENDINGAPPROVALS NUMBER (10,0) ,
    TOPAFFECTEDDISTRICT VARCHAR2 (255)
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
SNAPSHOTID	VARCHAR2 (255)	String	Stores the snapshotId information for AnalyticsSnapshot.
SNAPSHOTDATE	VARCHAR2 (255)	LocalDate	Stores the snapshotDate information for AnalyticsSnapshot.
TOTALACTIVEINCIDENTS	NUMBER (10,0)	int	Stores the totalActiveIncidents information for AnalyticsSnapshot.
TOTALALERTSSENT	NUMBER (10,0)	int	Stores the totalAlertsSent information for AnalyticsSnapshot.
TOTALPENDINGAPPROVALS	NUMBER (10,0)	int	Stores the totalPendingApprovals information for AnalyticsSnapshot.
TOPAFFECTEDDISTRICT	VARCHAR2 (255)	String	Stores the topAffectedDistrict information for AnalyticsSnapshot.

Table: approval_workflows

Service / Module: approval-service

Entity Class: ApprovalWorkflow

Description: This table is responsible for storing data related to `ApprovalWorkflow` within the approval-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE approval_workflows (  
    APPROVALID VARCHAR2(255),  
    INCIDENTID VARCHAR2(255),  
    ASSIGNEDCOLLECTORID VARCHAR2(255),  
    STATUS VARCHAR2(255),  
    COMMENTS VARCHAR2(255),  
    CREATEDAT TIMESTAMP,  
    UPDATEDAT TIMESTAMP  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
APPROVALID	VARCHAR2(255)	String	Stores the approvalId information for ApprovalWorkflow.
INCIDENTID	VARCHAR2(255)	String	Stores the incidentId information for ApprovalWorkflow.
ASSIGNEDCOLLECTORID	VARCHAR2(255)	String	Stores the assignedCollectorId information for ApprovalWorkflow.
STATUS	VARCHAR2(255)	String	Stores the status information for ApprovalWorkflow.
COMMENTS	VARCHAR2(255)	String	Stores the comments information for ApprovalWorkflow.
CREATEDAT	TIMESTAMP	LocalDateTime	Stores the createdAt information for ApprovalWorkflow.
UPDATEDAT	TIMESTAMP	LocalDateTime	Stores the updatedAt information for ApprovalWorkflow.

Table: auth_users

Service / Module: auth-service

Entity Class: AuthUser

Description: This table is responsible for storing data related to `AuthUser` within the auth-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE auth_users (  
    USERNAME VARCHAR2(255) PRIMARY KEY,  
    PASSWORD VARCHAR2(255),  
    ROLE VARCHAR2(255)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
USERNAME	VARCHAR2(255)	String	Stores the username information for AuthUser.
PASSWORD	VARCHAR2(255)	String	Stores the password information for AuthUser.
ROLE	VARCHAR2(255)	String	Stores the role information for AuthUser.

Table: incident_reports

Service / Module: incident-service

Entity Class: IncidentReport

Description: This table is responsible for storing data related to `IncidentReport` within the incident-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```

CREATE TABLE incident_reports (
  ID VARCHAR2(255) PRIMARY KEY,
  TITLE VARCHAR2(255),
  CATEGORY VARCHAR2(255),
  SEVERITY VARCHAR2(255),
  STATUS VARCHAR2(255),
  LEVEL VARCHAR2(255),
  DISTRICT VARCHAR2(255),
  TALUK VARCHAR2(255),
  VILLAGE VARCHAR2(255),
  DESCRIPTION VARCHAR2(255),
  REPORTEDBY VARCHAR2(255),
  DATE TIMESTAMP,
  MEDIAIDS VARCHAR2(255),
  UPDATES VARCHAR2(255),
  AISUMMARY VARCHAR2(255),
  AIRECOMMENDATION VARCHAR2(255),
  PHOTOBASE64 VARCHAR2(255)
);

```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
ID	VARCHAR2(255)	String	Stores the id information for IncidentReport.
TITLE	VARCHAR2(255)	String	Stores the title information for IncidentReport.
CATEGORY	VARCHAR2(255)	String	Stores the category information for IncidentReport.
SEVERITY	VARCHAR2(255)	String	Stores the severity information for IncidentReport.
STATUS	VARCHAR2(255)	String	Stores the status information for IncidentReport.
LEVEL	VARCHAR2(255)	String	Stores the level information for IncidentReport.
DISTRICT	VARCHAR2(255)	String	Stores the district information for IncidentReport.
TALUK	VARCHAR2(255)	String	Stores the taluk information for IncidentReport.
VILLAGE	VARCHAR2(255)	String	Stores the village information for IncidentReport.

DESCRIPTION	VARCHAR2 (255)	String	Stores the description information for IncidentReport.
REPORTEDBY	VARCHAR2 (255)	String	Stores the reportedBy information for IncidentReport.
DATE	TIMESTAMP	LocalDateTime	Stores the date information for IncidentReport.
MEDIAIDS	VARCHAR2 (255)	List<String>	Stores the mediaIds information for IncidentReport.
UPDATES	VARCHAR2 (255)	List<String>	Stores the updates information for IncidentReport.
AISUMMARY	VARCHAR2 (255)	String	Stores the aiSummary information for IncidentReport.
AIRECOMMENDATION	VARCHAR2 (255)	String	Stores the aiRecommendation information for IncidentReport.
PHOTOBASE64	VARCHAR2 (255)	String	Stores the photoBase64 information for IncidentReport.

Table: AG_AI_MODEL_REGISTRYS

Service / Module: monolith-legacy

Entity Class: AiModelRegistry

Description: This table is responsible for storing data related to AiModelRegistry within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_AI_MODEL_REGISTRYS (  
    MODELID NUMBER(19,0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
MODELID	NUMBER(19,0)	Long	Stores the modelId information for AiModelRegistry.

Table: AG_AI_PREDICTIONS

Service / Module: monolith-legacy

Entity Class: AiPrediction

Description: This table is responsible for storing data related to AiPrediction within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_AI_PREDICTIONS (  
    PREDICTIONID VARCHAR2 (255)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
PREDICTIONID	VARCHAR2 (255)	String	Stores the predictionId information for AiPrediction.

Table: AG_ALERTS

Service / Module: monolith-legacy

Entity Class: Alert

Description: This table is responsible for storing data related to Alert within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_ALERTS (  
    ALERTID VARCHAR2 (255) ,  
    SENDERID VARCHAR2 (255) ,  
    DISASTERTYPEID NUMBER (19,0) ,  
    TITLE VARCHAR2 (255) ,  
    DESCRIPTION VARCHAR2 (255) ,  
    SEVERITY VARCHAR2 (255) ,  
    STATUS VARCHAR2 (255) ,  
    TARGETLOCATIONTYPE VARCHAR2 (255) ,  
    TARGETLOCATIONID NUMBER (19,0) ,  
    VALIDUNTIL TIMESTAMP  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
			Stores the alertId information for

ALERTID	VARCHAR2 (255)	String	Alert.
SENDERID	VARCHAR2 (255)	String	Stores the senderId information for Alert.
DISASTERTYPEID	NUMBER (19, 0)	Long	Stores the disasterTypeid information for Alert.
TITLE	VARCHAR2 (255)	String	Stores the title information for Alert.
DESCRIPTION	VARCHAR2 (255)	String	Stores the description information for Alert.
SEVERITY	VARCHAR2 (255)	String	Stores the severity information for Alert.
STATUS	VARCHAR2 (255)	String	Stores the status information for Alert.
TARGETLOCATIONTYPE	VARCHAR2 (255)	String	Stores the targetLocationType information for Alert.
TARGETLOCATIONID	NUMBER (19, 0)	Long	Stores the targetLocationId information for Alert.
VALIDUNTIL	TIMESTAMP	LocalDateTime	Stores the validUntil information for Alert.

Table: AG_ALERT_LOCATIONS

Service / Module: monolith-legacy

Entity Class: AlertLocation

Description: This table is responsible for storing data related to `AlertLocation` within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_ALERT_LOCATIONS (  
    ALID NUMBER(19, 0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
ALID	NUMBER (19, 0)	Long	Stores the alid information for AlertLocation.

Table: AG_AUDIT_LOGS

Service / Module: monolith-legacy

Entity Class: AuditLog

Description: This table is responsible for storing data related to `AuditLog` within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_AUDIT_LOGS (  
    LOGID NUMBER(19,0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
LOGID	NUMBER(19,0)	Long	Stores the logId information for AuditLog.

Table: AG_DISASTER_REPORTS

Service / Module: monolith-legacy

Entity Class: DisasterReport

Description: This table is responsible for storing data related to `DisasterReport` within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_DISASTER_REPORTS (  
    REPORTID VARCHAR2(255),  
    REPORTERID VARCHAR2(255),  
    DISASTERTYPEID NUMBER(19,0),  
    DESCRIPTION VARCHAR2(255),  
    LATITUDE VARCHAR2(255),  
    LONGITUDE VARCHAR2(255),  
    VILLAGEID NUMBER(19,0),  
    STATUS VARCHAR2(255)  
);
```

Columns and Data Types

		Java	
--	--	------	--

Column Name	Oracle Data Type	Type	Description
REPORTID	VARCHAR2 (255)	String	Stores the reportId information for DisasterReport.
REPORTERID	VARCHAR2 (255)	String	Stores the reporterId information for DisasterReport.
DISASTERTYPEID	NUMBER (19,0)	Long	Stores the disasterTypeId information for DisasterReport.
DESCRIPTION	VARCHAR2 (255)	String	Stores the description information for DisasterReport.
LATITUDE	VARCHAR2 (255)	String	Stores the latitude information for DisasterReport.
LONGITUDE	VARCHAR2 (255)	String	Stores the longitude information for DisasterReport.
VILLAGEID	NUMBER (19,0)	Long	Stores the villageId information for DisasterReport.
STATUS	VARCHAR2 (255)	String	Stores the status information for DisasterReport.

Table: AG_DISASTER_TYPES

Service / Module: monolith-legacy

Entity Class: DisasterType

Description: This table is responsible for storing data related to DisasterType within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_DISASTER_TYPES (
    DISASTERTYPEID NUMBER (19,0)
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
DISASTERTYPEID	NUMBER (19,0)	Long	Stores the disasterTypeId information for DisasterType.

Table: AG_DISTRICTS

Service / Module: monolith-legacy

Entity Class: District

Description: This table is responsible for storing data related to `District` within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_DISTRICTS (  
    DISTRICTID NUMBER(19,0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
DISTRICTID	NUMBER(19,0)	Long	Stores the districtId information for District.

Table: AG_NOTIFICATIONS

Service / Module: monolith-legacy

Entity Class: Notification

Description: This table is responsible for storing data related to `Notification` within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_NOTIFICATIONS (  
    NOTIFICATIONID NUMBER(19,0) ,  
    USERID VARCHAR2(255) ,  
    ALERTID VARCHAR2(255) ,  
    TITLE VARCHAR2(255) ,  
    MESSAGE VARCHAR2(255) ,  
    STATUS VARCHAR2(255) ,  
    CHANNEL VARCHAR2(255)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
NOTIFICATIONID	NUMBER(19,0)	Long	Stores the notificationId information for Notification.

USERID	VARCHAR2 (255)	String	Stores the userId information for Notification.
ALERTID	VARCHAR2 (255)	String	Stores the alertId information for Notification.
TITLE	VARCHAR2 (255)	String	Stores the title information for Notification.
MESSAGE	VARCHAR2 (255)	String	Stores the message information for Notification.
STATUS	VARCHAR2 (255)	String	Stores the status information for Notification.
CHANNEL	VARCHAR2 (255)	String	Stores the channel information for Notification.

Table: AG_NOTIFICATION_TEMPLATES

Service / Module: monolith-legacy

Entity Class: NotificationTemplate

Description: This table is responsible for storing data related to NotificationTemplate within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_NOTIFICATION_TEMPLATES (
    TEMPLATEID NUMBER(19,0)
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
TEMPLATEID	NUMBER(19,0)	Long	Stores the templateId information for NotificationTemplate.

Table: AG_PERMISSIONS

Service / Module: monolith-legacy

Entity Class: Permission

Description: This table is responsible for storing data related to Permission within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_PERMISSIONS (  
    PERMISSIONID NUMBER(19,0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
PERMISSIONID	NUMBER(19,0)	Long	Stores the permissionId information for Permission.

Table: AG_REPORT_IMAGES

Service / Module: monolith-legacy

Entity Class: ReportImage

Description: This table is responsible for storing data related to `ReportImage` within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_REPORT_IMAGES (  
    IMAGEID VARCHAR2(255)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
IMAGEID	VARCHAR2(255)	String	Stores the imageId information for ReportImage.

Table: AG_REPORT_STATUS_HISTORYS

Service / Module: monolith-legacy

Entity Class: ReportStatusHistory

Description: This table is responsible for storing data related to `ReportStatusHistory` within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_REPORT_STATUS_HISTORYS (  
    HISTORYID NUMBER(19,0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
HISTORYID	NUMBER (19, 0)	Long	Stores the historyId information for ReportStatusHistory.

Table: AG_ROLES

Service / Module: monolith-legacy

Entity Class: Role

Description: This table is responsible for storing data related to Role within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_ROLES (  
    ROLEID NUMBER (19, 0) ,  
    ROLENAME VARCHAR2 (255) ,  
    DESCRIPTION VARCHAR2 (255)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
ROLEID	NUMBER (19, 0)	Long	Stores the roleId information for Role.
ROLENAME	VARCHAR2 (255)	String	Stores the roleName information for Role.
DESCRIPTION	VARCHAR2 (255)	String	Stores the description information for Role.

Table: AG_STATES

Service / Module: monolith-legacy

Entity Class: State

Description: This table is responsible for storing data related to State within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_STATES (  
    STATEID NUMBER (19, 0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
STATEID	NUMBER (19,0)	Long	Stores the stateId information for State.

Table: AG_TALUKS

Service / Module: monolith-legacy

Entity Class: Taluk

Description: This table is responsible for storing data related to Taluk within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_TALUKS (  
    TALUKID NUMBER (19,0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
TALUKID	NUMBER (19,0)	Long	Stores the talukId information for Taluk.

Table: AG_USERS

Service / Module: monolith-legacy

Entity Class: User

Description: This table is responsible for storing data related to User within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_USERS (  
    USERID VARCHAR2 (255) ,  
    EMAIL VARCHAR2 (255) ,  
    PASSWORDHASH VARCHAR2 (255) ,  
    FULLNAME VARCHAR2 (255) ,  
    PHONENUMBER VARCHAR2 (255) ,  
    STATUS VARCHAR2 (255)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
USERID	VARCHAR2 (255)	String	Stores the userId information for User.
EMAIL	VARCHAR2 (255)	String	Stores the email information for User.
PASSWORDHASH	VARCHAR2 (255)	String	Stores the passwordHash information for User.
FULLNAME	VARCHAR2 (255)	String	Stores the fullName information for User.
PHONENUMBER	VARCHAR2 (255)	String	Stores the phoneNumber information for User.
STATUS	VARCHAR2 (255)	String	Stores the status information for User.

Table: AG_USER_SESSIONS

Service / Module: monolith-legacy

Entity Class: `UserSession`

Description: This table is responsible for storing data related to `UserSession` within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_USER_SESSIONS (  
    SESSIONID NUMBER(19,0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
SESSIONID	NUMBER(19,0)	Long	Stores the sessionId information for UserSession.

Table: AG_VILLAGES

Service / Module: monolith-legacy

Entity Class: `Village`

Description: This table is responsible for storing data related to `Village` within the monolith-legacy. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE AG_VILLAGES (  
    VILLAGEID NUMBER(19,0)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
VILLAGEID	NUMBER(19,0)	Long	Stores the villageid information for Village.

Table: notifications

Service / Module: notification-service

Entity Class: Notification

Description: This table is responsible for storing data related to Notification within the notification-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE notifications (  
    NOTIFICATIONID VARCHAR2(255),  
    USERID VARCHAR2(255),  
    TITLE VARCHAR2(255),  
    MESSAGE VARCHAR2(255),  
    STATUS VARCHAR2(255),  
    CHANNEL VARCHAR2(255),  
    CREATEDAT TIMESTAMP  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
NOTIFICATIONID	VARCHAR2(255)	String	Stores the notificationId information for Notification.
USERID	VARCHAR2(255)	String	Stores the userId information for Notification.
TITLE	VARCHAR2(255)	String	Stores the title information for Notification.
MESSAGE	VARCHAR2(255)	String	Stores the message information for Notification.

STATUS	VARCHAR2 (255)	String	Stores the status information for Notification.
CHANNEL	VARCHAR2 (255)	String	Stores the channel information for Notification.
CREATEDAT	TIMESTAMP	LocalDateTime	Stores the createdAt information for Notification.

Table: districts

Service / Module: user-service

Entity Class: `District`

Description: This table is responsible for storing data related to `District` within the user-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE districts (
    NAME VARCHAR2 (255) ,
    TALUKSJSON VARCHAR2 (255)
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
NAME	VARCHAR2 (255)	String	Stores the name information for District.
TALUKSJSON	VARCHAR2 (255)	String	Stores the taluksJson information for District.

Table: employees

Service / Module: user-service

Entity Class: `Employee`

Description: This table is responsible for storing data related to `Employee` within the user-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE employees (  
    USERNAME VARCHAR2(255) PRIMARY KEY,  
    NAME VARCHAR2(255),  
    TITLE VARCHAR2(255),  
    ROLE VARCHAR2(255),  
    STATE VARCHAR2(255),  
    DISTRICT VARCHAR2(255),  
    TALUK VARCHAR2(255),  
    VILLAGE VARCHAR2(255)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
USERNAME	VARCHAR2(255)	String	Stores the username information for Employee.
NAME	VARCHAR2(255)	String	Stores the name information for Employee.
TITLE	VARCHAR2(255)	String	Stores the title information for Employee.
ROLE	VARCHAR2(255)	String	Stores the role information for Employee.
STATE	VARCHAR2(255)	String	Stores the state information for Employee.
DISTRICT	VARCHAR2(255)	String	Stores the district information for Employee.
TALUK	VARCHAR2(255)	String	Stores the taluk information for Employee.
VILLAGE	VARCHAR2(255)	String	Stores the village information for Employee.

Table: resources

Service / Module: user-service

Entity Class: Resource

Description: This table is responsible for storing data related to `Resource` within the user-service. It maintains the primary records essential for system operations such as logging, referencing, and state management.

Oracle SQL Creation Script

```
CREATE TABLE resources (  
    ID VARCHAR2(255) PRIMARY KEY,  
    NAME VARCHAR2(255) ,  
    TYPE VARCHAR2(255) ,  
    LOCATION VARCHAR2(255) ,  
    STATUS VARCHAR2(255) ,  
    ASSIGNEDTO VARCHAR2(255)  
);
```

Columns and Data Types

Column Name	Oracle Data Type	Java Type	Description
ID	VARCHAR2(255)	String	Stores the id information for Resource.
NAME	VARCHAR2(255)	String	Stores the name information for Resource.
TYPE	VARCHAR2(255)	String	Stores the type information for Resource.
LOCATION	VARCHAR2(255)	String	Stores the location information for Resource.
STATUS	VARCHAR2(255)	String	Stores the status information for Resource.
ASSIGNEDTO	VARCHAR2(255)	String	Stores the assignedTo information for Resource.