Status	Finished
Started	Thursday, 29 October 2026, 12:01 AM
Completed	Thursday, 29 October 2026, 12:10 AM
Duration	9 mins 2 secs
Grade	**9.00** out of 10.00 (**90**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Given an integer array `nums`, return *an integer array* `counts` *where* `counts[i]` *is the number of smaller elements to the right of* `nums[i]`.

Example 1:

```
Input: nums = [5,2,6,1]
Output: [2,1,1,0]
Explanation:
To the right of 5 there are 2 smaller elements (2 and 1).
To the right of 2 there is only 1 smaller element (1).
To the right of 6 there is 1 smaller element (1).
To the right of 1 there is 0 smaller element.
```

Example 2:

```
Input: nums = [-1]
Output: [0]
```

Example 3:

```
Input: nums = [-1,-1]
Output: [0,0]
```

Constraints:

- `1 <= nums.length <= 10^5`
- `-10^4 <= nums[i] <= 10^4`

For example:

Test	Result
`print(countSmaller([5,2,6,1]))`	`[2, 1, 1, 0]`
`print(countSmaller([-1]))`	`[0]`

Answer: (penalty regime: 0 %)

Reset answer

```python
def countSmaller(nums: list[int]) -> list[int]:
    n = len(nums)
    counts = [0] * n
    # Store tuples of (value, original_index)
    items = [(num, i) for i, num in enumerate(nums)]

    def merge_sort(arr):
        if len(arr) <= 1:
            return arr

        mid = len(arr) // 2
        left = merge_sort(arr[:mid])
        right = merge_sort(arr[mid:])

        merged = []
        i = j = 0

        while i < len(left) and j < len(right):
            if left[i][0] <= right[j][0]:
                # All elements in right[:j] are strictly smaller than left[i]
                counts[left[i][1]] += j
                merged.append(left[i])
                i += 1
            else:
                merged.append(right[j])
                j += 1

        while i < len(left):
            counts[left[i][1]] += j
            merged.append(left[i])
            i += 1

```

```
        while j < len(right):
            merged.append(right[j])
            j += 1

        return merged

    merge_sort(items)
    return counts
```

	Test	Expected	Got	
✓	print(countSmaller([5,2,6,1]))	[2, 1, 1, 0]	[2, 1, 1, 0]	✓
✓	print(countSmaller([50,20,60,10]))	[2, 1, 1, 0]	[2, 1, 1, 0]	✓
✓	print(countSmaller([-1]))	[0]	[0]	✓
✓	print(countSmaller([-1, -1]))	[0, 0]	[0, 0]	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Given an integer array `nums` sorted in **non-decreasing** order, return *an array of **the squares of each number** sorted in non-decreasing order*.

Example 1:

```
Input: nums = [-4,-1,0,3,10]
Output: [0,1,9,16,100]
Explanation: After squaring, the array becomes [16,1,0,9,100].
After sorting, it becomes [0,1,9,16,100].
```

Example 2:

```
Input: nums = [-7,-3,2,3,11]
Output: [4,9,9,49,121]
```

Constraints:

- `1 <= nums.length <= 10^4`
- `-10^4 <= nums[i] <= 10^4`
- `nums` is sorted in **non-decreasing** order.

For example:

Test	Result
`print(sortedSquares([-4,-1,0,3,10]))`	`[0, 1, 9, 16, 100]`

Answer: (penalty regime: 0 %)

Reset answer

```
def sortedSquares(nums: list[int]) -> list[int]:
    return sorted(x * x for x in nums)
```

	Test	Expected	Got	
✓	`print(sortedSquares([-4,-1,0,3,10]))`	`[0, 1, 9, 16, 100]`	`[0, 1, 9, 16, 100]`	✓
✓	`print(sortedSquares([-7,-3,2,3,11]))`	`[4, 9, 9, 49, 121]`	`[4, 9, 9, 49, 121]`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

To find the frequency of numbers in a list and display in sorted order.

Constraints:

1<=n, arr[i]<=100

Input:

1 68 79 4 90 68 1 4 5

output:

1 2

4 2

5 1

68 2

79 1

90 1

For example:

Input	Result
4 3 5 3 4 5	3 2 4 2 5 2

Answer: (penalty regime: 0 %)

```
from collections import Counter

def frequency_sorted(arr: list[int]) -> None:
    # Count frequencies of each element
    counts = Counter(arr)

    # Sort by the element values (keys) and print
    for number in sorted(counts.keys()):
        print(f"{number} {counts[number]}")

# Reading space-separated input
if __name__ == "__main__":
    import sys
    input_data = sys.stdin.read().split()
    if input_data:
        nums = [int(x) for x in input_data]
        frequency_sorted(nums)
```

	Input	Expected	Got	
✓	4 3 5 3 4 5	3 2 4 2 5 2	3 2 4 2 5 2	✓
✓	12 4 4 4 2 3 5	2 1 3 1 4 3 5 1 12 1	2 1 3 1 4 3 5 1 12 1	✓

	Input	Expected	Got	
✓	5 4 5 4 6 5 7 3	3 1 4 2 5 3 6 1 7 1	3 1 4 2 5 3 6 1 7 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

The problem is that we want to reverse a array in O(N) linear time complexity and we want the algorithm to be in-place as well!
For example: input is [1,2,3,4,5] then the output is [5,4,3,2,1]
Input
5
1 2 3 4 5
Output
5 4 3 2 1

For example:

Input	Result
5 1 2 3 4 5	5 4 3 2 1

Answer: (penalty regime: 0 %)

```
import sys

def reverse_array_in_place(arr: list[int]) -> None:
    left = 0
    right = len(arr) - 1

    # Swap elements from both ends towards the center
    while left < right:
        arr[left], arr[right] = arr[right], arr[left]
        left += 1
        right -= 1

if __name__ == "__main__":
    # Reading competitive programming style input
    input_data = sys.stdin.read().split()
    if input_data:
        n = int(input_data[0])
        nums = [int(x) for x in input_data[1:n + 1]]

        # Reverse in-place
        reverse_array_in_place(nums)

        # Print output space-separated
        print(*nums)
```

	Input	Expected	Got	
✓	5 1 2 3 4 5	5 4 3 2 1	5 4 3 2 1	✓
✓	10 0 2 4 6 8 1 3 5 7 9	9 7 5 3 1 8 6 4 2 0	9 7 5 3 1 8 6 4 2 0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

Given an listof integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

1. List is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted list.
3. Last Element: lastElement, the *last* element in the sorted list.

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

```
Array is sorted in 3 swaps.
```

```
First Element: 1
```

```
Last Element: 6
```

Input Format

The first line contains an integer,n , the size of the list a .
The second line contains n, space-separated integers a[i].

Constraints

· 2<=n<=600

· 1<=a[i]<=$2x10^6$.

Output Format

You must print the following three lines of output:

1. List is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted list.
3. Last Element: lastElement, the *last* element in the sorted list.

Sample Input 0

3

1 2 3

Sample Output 0

List is sorted in 0 swaps.

First Element: 1

Last Element: 3

For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9

Answer: (penalty regime: 0 %)

```
import sys

def count_swaps(a: list[int]) -> None:
    n = len(a)
    num_swaps = 0

    for i in range(n):
        swapped = False
        for j in range(0, n - i - 1):
            if a[j] > a[j + 1]:
```

```
                # Swap adjacent elements
                a[j], a[j + 1] = a[j + 1], a[j]
                num_swaps += 1
                swapped = True

        # If no elements were swapped in this pass, array is already sorted
        if not swapped:
            break

    print(f"List is sorted in {num_swaps} swaps.")
    print(f"First Element: {a[0]}")
    print(f"Last Element: {a[-1]}")

if __name__ == "__main__":
    input_data = sys.stdin.read().split()
    if input_data:
        n = int(input_data[0])
        a = [int(x) for x in input_data[1:n + 1]]
        count_swaps(a)
```

	Input	Expected	Got	
✓	3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3	List is sorted in 3 swaps. First Element: 1 Last Element: 3	✓
✓	5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9	List is sorted in 4 swaps. First Element: 1 Last Element: 9	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00

Bubble Sort is the simplest sorting algorithm that works by repeatedly swapping the adjacent elements if they are in wrong order. You read an list of numbers. You need to arrange the elements in ascending order and print the result. The sorting should be done using bubble sort.

Input Format: The first line reads the number of elements in the array. The second line reads the array elements one by one.

Output Format: The output should be a sorted list.

For example:

Input	Result
6 3 4 8 7 1 2	1 2 3 4 7 8
5 4 5 2 3 1	1 2 3 4 5

Answer: (penalty regime: 0 %)

```
import sys

def bubble_sort(arr: list[int]) -> list[int]:
    n = len(arr)
    for i in range(n):
        swapped = False
        for j in range(0, n - i - 1):
            if arr[j] > arr[j + 1]:
                # Swap adjacent elements if they are in the wrong order
                arr[j], arr[j + 1] = arr[j + 1], arr[j]
                swapped = True

        # Optimization: If no elements were swapped, array is already sorted
        if not swapped:
            break

    return arr

if __name__ == "__main__":
    input_data = sys.stdin.read().split()
    if input_data:
        n = int(input_data[0])
        nums = [int(x) for x in input_data[1:n + 1]]

        sorted_nums = bubble_sort(nums)

        # Print elements separated by spaces
        print(*sorted_nums)
```

	Input	Expected	Got	
✓	6 3 4 8 7 1 2	1 2 3 4 7 8	1 2 3 4 7 8	✓
✓	6 9 18 1 3 4 6	1 3 4 6 9 18	1 3 4 6 9 18	✓
✓	5 4 5 2 3 1	1 2 3 4 5	1 2 3 4 5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **7**

Incorrect

Mark 0.00 out of 1.00

Given an array of integers `arr`, replace each element with its rank.

The rank represents how large the element is. The rank has the following rules:

- Rank is an integer starting from 1.
- The larger the element, the larger the rank. If two elements are equal, their rank must be the same.
- Rank should be as small as possible.

Example 1:

```
Input: arr = [40,10,20,30]
Output: [4,1,2,3]
Explanation: 40 is the largest element. 10 is the smallest. 20 is the second smallest. 30 is the third smallest.
```

Example 2:

```
Input: arr = [100,100,100]
Output: [1,1,1]
Explanation: Same elements share the same rank.
```

Example 3:

```
Input: arr = [37,12,28,9,100,56,80,5,12]
Output: [5,3,4,2,8,6,7,1,3]
```

Constraints:

- `0 <= arr.length <= 10^5`
- `-10^9 <= arr[i] <= 10^9`

For example:

Test	Result
print(arrayRankTransform([40,10,20,30]))	[4, 1, 2, 3]

Answer: (penalty regime: 0 %)

Reset answer

```
def arrayRankTransform(arr: list[int]) -> list[int]:
    if not arr:
        return []

    # Sort unique elements and assign rank
    rank_map = {val: i + 1 for i, val in enumerate(sorted(set(arr)))}

    # Map elements to their rank
    return [rank_map[x] for x in arr]

# Test Runs
print(arrayRankTransform([40, 10, 20, 30]))              # [4, 1, 2, 3]
print(arrayRankTransform([100, 100, 100]))               # [1, 1, 1]
print(arrayRankTransform([37, 12, 28, 9, 100, 56, 80, 5, 12]))  # [5, 3, 4, 2, 8, 6, 7, 1, 3]
print(arrayRankTransform([]))                            # []
```

	Test	Expected	Got	

✗	`print(arrayRankTransform([40,10,20,30]))`	`[4, 1, 2, 3]`	`[4, 1, 2, 3]`
			`[1, 1, 1]`
			`[5, 3, 4, 2, 8, 6, 7, 1, 3]`
			`[]`
			`[4, 1, 2, 3]`
				✗

✓	`print(arrayRankTransform([100,100,100]))`	`[1, 1, 1]`	`[1, 1, 1]`	✓
✓	`print(arrayRankTransform([37,12,28,9,100,56,80,5,12]))`	`[5, 3, 4, 2, 8, 6, 7, 1, 3]`	`[5, 3, 4, 2, 8, 6, 7, 1, 3]`	✓

Your code must pass all tests to earn any marks. Try again.

Show differences

Incorrect

Marks for this submission: 0.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

Given an array of integers `nums`, sort the array in **increasing** order based on the frequency of the values. If multiple values have the same frequency, sort them in **decreasing** order.

Print the *sorted array*.

Example 1:

```
Input:
6
1 1 2 2 2 3

Output:
3 1 1 2 2 2

Explanation: '3' has a frequency of 1, '1' has a frequency of 2, and '2' has a frequency of 3.
```

Example 2:

```
Input:
5
2 3 1 3 2
Output:
1 3 3 2 2
Explanation: '2' and '3' both have a frequency of 2, so they are sorted in decreasing order.
```

Example 3:

```
Input:
9
-1 1 -6 4 5 -6 1 4 1
Output:
5 -1 4 4 -6 -6 1 1 1
```

Constraints:

- `1 <= nums.length <= 100`
- `-100 <= nums[i] <= 100`

For example:

Input	Result
6 1 1 2 2 2 3	3 1 1 2 2 2
5 2 3 1 3 2	1 3 3 2 2

Answer: (penalty regime: 0 %)

```
import sys
from collections import Counter

def frequency_sort(nums: list[int]) -> list[int]:
    counts = Counter(nums)
    # Sort key: (frequency ascending, number value descending)
    nums.sort(key=lambda x: (counts[x], -x))
    return nums

if __name__ == "__main__":
    input_data = sys.stdin.read().split()
    if input_data:
        n = int(input_data[0])
        nums = [int(x) for x in input_data[1:n + 1]]

        sorted_nums = frequency_sort(nums)

        # Print space-separated result
        print(*sorted_nums)
```

	Input	Expected	Got	
✓	6 1 1 2 2 2 3	3 1 1 2 2 2	3 1 1 2 2 2	✓
✓	5 2 3 1 3 2	1 3 3 2 2	1 3 3 2 2	✓
✓	9 -1 1 -6 4 5 -6 1 4 1	5 -1 4 4 -6 -6 1 1 1	5 -1 4 4 -6 -6 1 1 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **9**

Correct

Mark 1.00 out of 1.00

Objective:

Develop a Python program to find the k-th maximum value in a given list of integers. The program should handle various edge cases, including lists with duplicate values, empty lists, and invalid values of k. The k-th maximum value refers to the k-th largest distinct element in the list.

Background:

Finding the k-th maximum value in a list is a common problem in computer science, often encountered in fields like data analysis, competitive programming, and software development. This problem requires an understanding of sorting algorithms, data structures, and efficient problem-solving techniques. By solving this problem, one gains insights into how to handle large datasets and optimize performance in practical applications.

Problem Description:

Given a list of integers, the task is to determine the k-th maximum value in the list. The program should meet the following requirements:

1. **Input:**
    - A list of integers, which can contain both positive and negative values.
    - An integer k, representing the position of the maximum value to find.
2. **Output:**
    - The k-th maximum value in the list.
    - If k is greater than the number of distinct elements in the list or if the list is empty, the program should return an appropriate message indicating the error.

Constraints:

- The list may contain duplicate values.
- The value of k should be a positive integer.
- The list may contain up to 10^6 elements, and each element can be as large as 10^9 in magnitude.

Examples:

Consider the following examples for better understanding:

1. **Example 1:**
    - **Input:** list = [3, 1, 5, 4, 2], k = 2
    - **Output:** 4
    - **Explanation:** The distinct elements in the list are [1, 2, 3, 4, 5]. The 2nd maximum value is 4.
2. **Example 2:**
    - **Input:** list = [7, 7, 7, 7, 7], k = 1
    - **Output:** 7
    - **Explanation:** The distinct elements in the list are [7]. The 1st maximum value is 7.
3. **Example 3:**
    - **Input:** list = [2, 1, 2, 1, 2], k = 3
    - **Output:** -1
    - **Explanation:** The distinct elements in the list are [1, 2]. There is no 3rd maximum value.

For example:

Input	Result
5 3 1 5 4 2 2	4
6 7 7 7 7 7 7 1	7
10 2 1 2 1 2 1 2 1 2 1 3	-1

Answer: (penalty regime: 0 %)

```python
import sys

def find_kth_maximum(nums: list[int], k: int):
    # Handle empty list or invalid k
    if not nums or k <= 0:
        return -1

    # Extract unique elements
    unique_nums = set(nums)

    # If k is larger than the count of distinct elements
    if k > len(unique_nums):
        return -1

    # Sort unique elements in descending order and return the (k-1)-th element
    # Alternatively: sorted(unique_nums)[-k]
    return sorted(unique_nums, reverse=True)[k - 1]

if __name__ == "__main__":
    input_data = sys.stdin.read().split()
    if input_data:
        n = int(input_data[0])
        nums = [int(x) for x in input_data[1:n + 1]]
        k = int(input_data[n + 1])

        result = find_kth_maximum(nums, k)
        print(result)
```

	Input	Expected	Got	
✓	5 3 1 5 4 2 2	4	4	✓
✓	6 7 7 7 7 7 7 1	7	7	✓
✓	10 2 1 2 1 2 1 2 1 2 1 3	-1	-1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Correct

Mark 1.00 out of 1.00

Write a Python program to sort a list of elements using the merge sort algorithm.

For example:

Input	Result
5 6 5 4 3 8	3 4 5 6 8

Answer: (penalty regime: 0 %)

```
import sys

def merge_sort(arr: list[int]) -> list[int]:
    # Base case: a list of length 0 or 1 is already sorted
    if len(arr) <= 1:
        return arr

    # Step 1: Divide the list into two halves
    mid = len(arr) // 2
    left_half = merge_sort(arr[:mid])
    right_half = merge_sort(arr[mid:])

    # Step 2: Merge the two sorted halves
    return merge(left_half, right_half)


def merge(left: list[int], right: list[int]) -> list[int]:
    merged = []
    i = j = 0

    # Compare elements from left and right halves and append the smaller one
    while i < len(left) and j < len(right):
        if left[i] <= right[j]:
            merged.append(left[i])
            i += 1
        else:
            merged.append(right[j])
            j += 1

    # Append any remaining elements from left or right halves
    merged.extend(left[i:])
    merged.extend(right[j:])

    return merged


if __name__ == "__main__":
    # Reading competitive programming style input
    input_data = sys.stdin.read().split()
    if input_data:
        n = int(input_data[0])
        nums = [int(x) for x in input_data[1 : n + 1]]

        sorted_nums = merge_sort(nums)

        # Print the space-separated output
        print(*sorted_nums)
```

	Input	Expected	Got	
✓	5 6 5 4 3 8	3 4 5 6 8	3 4 5 6 8	✓
✓	9 14 46 43 27 57 41 45 21 70	14 21 27 41 43 45 46 57 70	14 21 27 41 43 45 46 57 70	✓

	Input	Expected	Got	
✓	4 86 43 23 49	23 43 49 86	23 43 49 86	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.