

Controls

Separating the look from the behaviour

The killer feature of WPF controls is that the procedural behaviour code is completely separated from its visual tree. Every `Control` has a `Template` dependency property of type `ControlTemplate`. A control template enables the consumer of a control to replace its visual tree with a completely new and arbitrarily complex tree of visuals while keeping the core behaviour of the control intact. Whenever a `Control` is instantiated its `ControlTemplate` is used to generate a tree of visuals that will be used in rendering. The template acts as a blueprint that tells WPF how to create the visual elements needed to render the `Control`. The content of a `ControlTemplate` is of type `VisualTree`.

All `FrameworkElements` in a control template have a relationship back to the control being templated. This relationship is known as the templated parent and is represented by the `TemplatedParent` property.

Templating a standard control


CREATING THE CONTROLTEMPLATE

Listing 1Creating a ControlTemplate

```
<ControlTemplate TargetType="Button">
  <Grid>
    <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
    <Rectangle x:Name="Rectangle2" Width="100" Height="100" Fill="LightBlue"/>
  </Grid>
</ControlTemplate>
```


The ControlTemplate is not the same thing as the actually rendered visuals in the visual tree. It is a blueprint which tells WPF how to create the VisualTree as shown in the diagram below

Figure 1Creating a ControlTemplate



If we add a button whose Template is set to our ControlTemplate it is rendered as follows.

RENDERED 1CREATING A CONTROLTEMPLATE



TRIGGERS AND VISUAL STATE


Listing 2 Triggers and Visual State

```
<ControlTemplate TargetType="Button">
  <Grid>
    <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
    <Rectangle x:Name="Rectangle2" Width="100" Height="100" Fill="LightBlue"/>
  </Grid>
  <ControlTemplate.Triggers>
    <Trigger Property="IsMouseOver" Value="True">
      <Setter TargetName="Rectangle1" Property="Fill" Value="DarkBlue"/>
    </Trigger>
    <Trigger Property="IsPressed" Value="True">
      <Setter Property="RenderTransform">
        <Setter.Value>
          <ScaleTransform ScaleX=".9" ScaleY=".9"/>
        </Setter.Value>
      </Setter>
      <Setter Property="RenderTransformOrigin" Value=".5,.5"/>
    </Trigger>
  </ControlTemplate.Triggers>
</ControlTemplate>
```

Note how we use a special `TargetName` attribute on the triggers setter to target a specific visual element in the control template. This attribute is only used within Templates. A visual element inside a template can take an `x:Name` attribute. This attribute can only be used to access the element from the templates triggers which is somewhat different from its use on elements that form part of the logical tree. The reason being that any particular part of a template could correspond to multiple visuals in the visual tree if the template is applied multiple times.

RENDERED 2TRIGGERS AND VISUALSTATE

Now when the mouse is over the button the fill on the outer rectangle changes to a dark blue colour.



TEMPLATED PARENT


A templated control is considered the templated parent of all the visual elements in its visual tree. Every FrameworkElement has a property called TemplatedParent which enables template elements to access the templated parent. FrameworkElement has a TemplatedParent property that refers to the templated parent.

Listing 3 Templated Parent

```
<ControlTemplate TargetType="Button">
  <Grid>
    <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
    <Rectangle x:Name="Rectangle2" Width="100" Height="100" Fill="LightBlue"/>
    <TextBlock HorizontalAlignment="Center" VerticalAlignment="Center"
      Text="{Binding RelativeSource={RelativeSource TemplatedParent}, Path=Content}"/>
  </Grid>
```

Figure 2Templatd Parent

Notice how each rectangle can reference its templated parent



We can use a special markup extension called TemplateBinding. This makes the xaml more concise, however it has limitations when compared to the full blown Binding markup extension. The limitations are as follows.

```
<ControlTemplate TargetType="Button">
  <Grid>
    <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
    <Rectangle x:Name="Rectangle2" Width="100" Height="100" Fill="LightBlue"/>
    <TextBlock HorizontalAlignment="Center" VerticalAlignment="Center"
      Text="{TemplateBinding Property=Content}" />
  </Grid>
```

RESPECTING CONTENT

A `Button` is a `ContentControl` which means it should render a single piece of content. The manner in which we implemented the `ControlTemplate` in the previous section meant that the window would always render text correctly in a `TextBlock`, however any other type of content would not be correctly rendered. We now consider how to create a `ControlTemplate` for our `Button` that correctly renders its content. The most common way to render `Content` in a `ContentControl` is via an instance of the `ContentPresenter` class. `ContentPresenter` is a `FrameworkElement` designed for rendering heterogenous content. Every WPF `ContentControl` uses an instance of `ContentPresenter` in its default `ControlTemplate`.

Listing 4Respecting Content


```
<Grid>
  <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
  <Rectangle x:Name="Rectangle2" Width="100" Height="100" Fill="LightBlue"/>
  <ContentPresenter HorizontalAlignment="Center" VerticalAlignment="Center"
    Content="{TemplateBinding Property=Content}"/>
</Grid>
```

The `ContentPresenter` has three core `DependencyProperties`.

- ◆ `Content`
- ◆ `ContentTemplate`
- ◆ `ContentTemplateSelector`

Whenever a `ContentPresenter` is inside the `ControlTemplate` of a `ContentControl` these three properties automatically take their values from the properties of the same name in the parent `ContentControl`


Figure 3ContentPresenter Properties



Let us add some text to our Button as content and see how it renders

```
<Button Content="Click Me"/>
```

Figure 4ContentPresenter and string content




How does the ContentPresenter know to convert the Button content string to a TextBlock and set its TextProperty to be the content string? This is one of the rules of the WPF content model which we can summarise as follows.

1. If the content is a UI Element render it as is
1. If the content is a string render it in a TextBlock
2. If the content is a .NET type which has a data template associated with it then use the data template to render it.
3. Otherwise render the standard .NET objects class name in a TextBlock

DATA TEMPLATES AND CONTENT CONTROLS

In this example the window's content is a complex object which we render via a DataTemplate.

Figure 5Control and Data Templates




Listing 5Content and Data Templates

```
<Window.Resources>
  <DataTemplate DataType="{x:Type viewModels:Person}">
    <StackPanel Orientation="Vertical">
      <TextBlock Text="{Binding FirstName}"></TextBlock>
      <TextBlock Text="{Binding SecondName}"></TextBlock>
    </StackPanel>
  </DataTemplate>
</Window.Resources>

<Window.Template>
  <ControlTemplate TargetType="{x:Type templatingStandardControls:_05ContentAndDataBinding}">
    <Border Background="LightBlue">
      <ContentPresenter></ContentPresenter>
    </Border>
  </ControlTemplate>
</Window.Template>
<viewModels:Person FirstName="Kenny" SecondName="Wilson"/>
```

LISTING 6RENDERED WINDOW



CONTENT CONTROL'S CONTENTTEMPLATE

We have already seen that each control has a ControlTemplate that defines the visual tree of that Control. In addition every ContentControl also has a ContentTemplate which defines how its single piece of content is rendered. While the Control.Template dependency property is of type ControlTemplate the ContentTemplate is of type DataTemplate.


DataTemplates and ControlTemplates while similar (both extend the same base class) are intended for different purposes. A control template defines the look of the whole control and tends to be somewhat complex. A data template defines the look of a piece of content within a content control and tends to be simpler. For instance consider the scenario where I want to render a non UIElement object as the content of a button.

The following example is a little contrived but it uses two control templates (one for window and one for button), a content template (for button) and a data template to render the person object. In reality one might use a content template to provide some simpler customisation rather than writing the whole control template from scratch)

Listing 7ContentTemplate

```
<Window.Resources>
  <DataTemplate DataType="{x:Type viewModel:Person}">
    <StackPanel>
      <TextBlock Background="White" Margin="1" Padding="5" Text="{Binding FirstName}"/>
      <TextBlock Background="White" Margin="1" Padding="5" Text="{Binding SecondName}"/>
    </StackPanel>
  </DataTemplate>
  <Style TargetType="Button">
    <Setter Property="Margin" Value="5"/>
    <Setter Property="Padding" Value="5"/>
    <Setter Property="Template" >
      <Setter.Value>
        <ControlTemplate TargetType="Button">
          <Border Background="LightSeaGreen" Padding="5">
            <ContentPresenter/>
          </Border>
        </ControlTemplate>
      </Setter.Value>
    </Setter>
  </Style>
</Window.Resources>
<Window.Template>
  <ControlTemplate
TargetType="{x:Type templatingStandardControls:_06ContentControlAndDataTemplates}">
    <Border Background="{TemplateBinding Background}">
      <ContentPresenter></ContentPresenter>
    </Border>
  </ControlTemplate>
</Window.Template>
<Button Content="{viewModel:PersonMarkup FirstName=Kenny, SecondName=Wilson}">
  <Button.ContentTemplate>
    <DataTemplate>
      <Border Padding="5" Margin="5" Background="LightPink">
        <ContentPresenter Content="{Binding}"></ContentPresenter>
      </Border>
    </DataTemplate>
  </Button.ContentTemplate>
</Button>
```


Figure 6ContentTemplate



Appendices


Creating a Custom Control with control template

In this section we will show how to create a custom control. The control in question is a very simple modeless dialogue box. When made visible the dialogue box simply sits on top of other content rather than the traditional model separate dialogue that comes for free with WPF. Although simple this control highlights the following points.

1. Separation of look and feel from behaviour using a control template
2. How do define the contract between the control and its template

1. Add a project to the solution of type WPF App (.NET Framework)

We call our project 01SeparateLookFromBehaviour



2. Add a MyCustomControl class that extends Control

```
class MyCustomControl : Control
{
}
```

3. Add a static constructor with the following boilerplate

```
class MyCustomControl : Control
{
    static MyCustomControl()
    {
        DefaultStyleKeyProperty.OverrideMetadata(typeof(MyCustomControl),
            new FrameworkPropertyMetadata(typeof(MyCustomControl)));
    }
}
```

4. Add our newly created control as our windows content

When we create our project Visual Studio added a Window1 window for us. We can use this to test our new control by adding it to the window

```
<Window x:Class="SeparateLookFromBehaviour.MainWindow"
        xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation"
        xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
        xmlns:separateLookFromBehaviour="clr-namespace:SeparateLookFromBehaviour"
        Title="MainWindow" Height="350" Width="525">

    <separateLookFromBehaviour:MyCustomControl/>
</Window>
```

Because we have not created any template to define the look our control is essentially lookless.


5. Add a very basic look

Now we can go ahead and add our default control template that defines the look of our control. Move to Themes/Generic.xaml and add the following

```
<ResourceDictionary xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation"
                    xmlns:separateLookFromBehaviour="clr-namespace:SeparateLookFromBehaviour">

    <Style TargetType="separateLookFromBehaviour:MyCustomControl">
        <Setter Property="Template">
            <Setter.Value>
                <ControlTemplate TargetType="separateLookFromBehaviour:MyCustomControl">
                    <Border Background="LightBlue"></Border>
                </ControlTemplate>
            </Setter.Value>
        </Setter>
    </Style>
</ResourceDictionary>
```

We have themed our control. If we compile and go back to our window it looks as follows.



Define a contract between the control and its template

For all but the simplest of controls we need to specify on some level that the template must contain certain elements. We do this via `TemplatePart` attributes on the custom control.

1. Add a `TemplatePart` attribute to the custom control

```
[TemplatePart(Name = "PART_Button", Type = typeof(Button))]  
class MyCustomControl : Control  
{  
    static MyCustomControl()  
    {  
        DefaultStyleKeyProperty.OverrideMetadata(typeof(MyCustomControl),  
            new FrameworkPropertyMetadata(typeof(MyCustomControl)));  
    }  
  
    public override void OnApplyTemplate()  
    {  
        _button = GetTemplateChild("PART_Button") as Button;  
  
        if (_button != null)  
        {  
            _button.Click += (sender, args) =>  
            {  
  
            }  
        }  
    }  
  
    private Button _button;  
}
```

2. Add the required part to the template

```

<ResourceDictionary xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation"
                    xmlns:separateLookFromBehaviour=
                    "clr-namespace:SeparateLookFromBehaviour">

    <Style TargetType="separateLookFromBehaviour:MyCustomControl">
        <Setter Property="Template">
            <Setter.Value>
                <ControlTemplate
                    TargetType="separateLookFromBehaviour:MyCustomControl">
                    <Border Background="LightBlue">
                        <Button Name="PART_Button">Click Me</Button>
                    </Border>
                </ControlTemplate>
            </Setter.Value>
        </Setter>
    </Style>

</ResourceDictionary>

```

Now make sure you can see your handler on the button being hit

Add a Dependency Property

1. Add a static `DependencyProperty` boilerplate as follows

```

using System.Windows;
using System.Windows.Controls;

namespace SeparateLookFromBehaviour
{
    [TemplatePart(Name = "PART_Button", Type = typeof(Button))]
    class MyCustomControl : Control
    {
        public static DependencyProperty MyValueProperty =
            DependencyProperty.Register("MyValue", typeof(double),
                typeof(MyCustomControl),
                new FrameworkPropertyMetadata(OnValueChanged));

        private static void OnValueChanged(DependencyObject dependencyObject,
            DependencyPropertyChangedEventArgs args)
        {
            var myCustomControl = dependencyObject as MyCustomControl;
            if (myCustomControl?._button != null)
                myCustomControl._button.Content = args.NewValue;
        }

        public double MyValue
        {
            get => (double)GetValue(MyValueProperty);
            set => SetValue(MyValueProperty, value);
        }

        static MyCustomControl()
        {
            DefaultStyleKeyProperty.OverrideMetadata(typeof(MyCustomControl),
                new FrameworkPropertyMetadata(typeof(MyCustomControl)));
        }

        public override void OnApplyTemplate()
        {
            _button = GetTemplateChild("PART_Button") as Button;

            if (_button != null)
            {
                _button.Content = MyValue;

                _button.Click += (sender, args) =>
                {
                    MyValue = MyValue * 1.1;
                };
            }

            private Button _button;
        }
    }
}

```

2. Create a simple view model

```

public class ViewModel : INotifyPropertyChanged
{
    private double _someValue;

    public double SomeValue
    {
        get => _someValue;
        set
        {
            _someValue = value;
            PropertyChanged?.Invoke(this, new PropertyChangedEventArgs(
tArgs(nameof(SomeValue))));
        }
    }
    public event PropertyChangedEventHandler PropertyChanged;
}

```

3. Set the ViewModel on the View and bind it to our DP

```

<Window x:Class="SeparateLookFromBehaviour.MainWindow"
        xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation"
        xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
        xmlns:separateLookFromBehaviour="clr-namespace:SeparateLookFromBehaviour"
        Title="MainWindow" Height="350" Width="525">

    <Window.DataContext>
        <separateLookFromBehaviour:ViewModel SomeValue="100"/>
    </Window.DataContext>

    <separateLookFromBehaviour:MyCustomControl MyValue="{Binding SomeValue}"/>
</Window>

```

Controls - Questions

Overview

What defines a control?

Its behaviour

Is a WPF control directly responsible for its visuals?

No. It delegates to an instance of ControlTemplate provided via a DependencyProperty called Template. The template has complete control over the rendering of the control

What is the benefit of this approach?

A consumer of a control to replace its look tree with a completely new and arbitrarily complex tree of visual objects.

One does not need to write a custom control to change the appearance of a control.

How does a ControlTemplate work?

When a control is instantiated its ControlTemplate is used to create a visual tree of elements that will be used to render the control. The ControlTemplate is a blueprint. It is used to generate the visual tree. It is not the visual tree.

When do you need to write a custom control?

You need to provide a new behaviour not provided by existing controls

In what way can one change the appearance of a control?

- 1. Setting properties directly such as foreground*
- 2. With styles*
- 3. With templates*
- 4. Custom controls we can place graphics*

Are all UI elements in WPF controls?

No

What is the base class for the UI elements that don't have behaviour?

FrameworkElement

What are the rules of the WPF Content Model?


1. *If the content is a UIElement then render it*
2. *If the content is a string, render it in a TextBlock*
3. *If the content is a .NET type with an associated data template use that to render it*
4. *Otherwise render the .NET objects class name in a TextBlock*

What are the three core dependency properties of a ContentPresenter?

1. *Content*
2. *ContentTemplate*
3. *ContentTemplateSelector*

Compare and contrast Template and ContentTemplate?

Template is a ControlTemplate and defines the rendering of the control as a whole. ContentTemplate is a data template which renders just the content itself.



```
<Window.Resources>
    <DataTemplate DataType="{x:Type local:Person}">
        <StackPanel>
            <TextBlock Text="{Binding FirstName}"/>
            <TextBlock Text="{Binding LastName}"/>
        </StackPanel>
    </DataTemplate>
</Window.Resources>

<Window.Template>
    <ControlTemplate TargetType="Window">
        <Border Background="LightBlue">
            <ContentPresenter/>
        </Border>
    </ControlTemplate>
</Window.Template>


<local:Person FirstName="Kenneth" LastName="Wilson"/>
```


Control Details

Show how the following piece of xaml is used to create the look of the button?

```
<ControlTemplate TargetType="Button">
  <Grid>
    <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
    <Rectangle x:Name="Rectangle2" Width="100" Height="100" Fill="LightBlue"/>
  </Grid>
</ControlTemplate>
```

Answer



Control Template Triggers

Add two triggers to the below Xaml. The first will set rectangle one to be dark blue when the mouse is over. The second will shrink the button to 90% of previous?

```
<ControlTemplate TargetType="Button">
  <Grid>
    <Rectangle Width="120" Height="120" Fill="Blue"/>
    <Rectangle Width="100" Height="100" Fill="LightBlue"/>
  </Grid>
</ControlTemplate>
```

Answer

```
<ControlTemplate TargetType="Button">
  <Grid>
    <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
    <Rectangle Width="100" Height="100" Fill="LightBlue"/>
  </Grid>
  <ControlTemplate.Triggers>
    <Trigger Property="IsMouseOver" Value="True">
      <Setter TargetName="Rectangle1" Property="Fill" Value="DarkBlue"/>
    </Trigger>
    <Trigger Property="IsPressed" Value="True">
      <Setter Property="RenderTransform">
        <Setter.Value>
          <ScaleTransform ScaleX=".9" ScaleY=".9" ></ScaleTransform>
        </Setter.Value>
      </Setter>
    </Trigger>
  </ControlTemplate.Triggers>
</ControlTemplate>
```

```

        </ControlTemplate.Triggers>
    </ControlTemplate>

```

Templated Parent

What is a templated parent?

All elements in a visual tree created as part of template instantiation have a link back to the control being templated. This is known as the `TemplateParent`.

Add code the following control template such that it renders the parent content in the text block?

```

<ControlTemplate TargetType="Button">
    <Grid>
        <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
        <Rectangle x:Name="Rectangle2" Width="100" Height="100" Fill="LightBlue"/>
        <TextBlock HorizontalAlignment="Center" VerticalAlignment="Center"/>
    </Grid>
    <ControlTemplate.Triggers>
        <Trigger Property="IsMouseOver" Value="True">
            <Setter TargetName="Rectangle1" Property="Fill" Value="DarkBlue"/>
        </Trigger>
        <Trigger Property="IsPressed" Value="True">
            <Setter Property="RenderTransform">
                <Setter.Value>
                    <ScaleTransform ScaleX=".9" ScaleY=".9"/>
                </Setter.Value>
            </Setter>
            <Setter Property="RenderTransformOrigin" Value=".5,.5"/>
        </Trigger>
    </ControlTemplate.Triggers>
</ControlTemplate>

```

Answer

```

<ControlTemplate TargetType="Button">
    <Grid>
        <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
        <Rectangle x:Name="Rectangle2" Width="100" Height="100" Fill="LightBlue"/>
        <TextBlock HorizontalAlignment="Center" VerticalAlignment="Center"
Text="{TemplateBinding Property=Content}"/>
    </Grid>
    <ControlTemplate.Triggers>
        <Trigger Property="IsMouseOver" Value="True">
            <Setter TargetName="Rectangle1" Property="Fill" Value="DarkBlue"/>
        </Trigger>
        <Trigger Property="IsPressed" Value="True">
            <Setter Property="RenderTransform">
                <Setter.Value>
                    <ScaleTransform ScaleX=".9" ScaleY=".9"/>
                </Setter.Value>
            </Setter>
            <Setter Property="RenderTransformOrigin" Value=".5,.5"/>
        </Trigger>
    </ControlTemplate.Triggers>
</ControlTemplate>

```

Same as previous question but do not use the TemplateParent property?

```
<ControlTemplate TargetType="Button">
  <Grid>
    <Rectangle x:Name="Rectangle1" Width="120" Height="120" Fill="Blue"/>
    <Rectangle x:Name="Rectangle2" Width="100" Height="100" Fill="LightBlue"/>
    <TextBlock HorizontalAlignment="Center" VerticalAlignment="Center"
      Text="{Binding RelativeSource={RelativeSource TemplatedParent }, Path=Content}"/>
  </Grid>
  <ControlTemplate.Triggers>

    <Trigger Property="IsMouseOver" Value="True">
      <Setter TargetName="Rectangle1" Property="Fill" Value="DarkBlue"/>
    </Trigger>
    <Trigger Property="IsPressed" Value="True">
      <Setter Property="RenderTransform">
        <Setter.Value>
          <ScaleTransform ScaleX=".9" ScaleY=".9"/>
        </Setter.Value>
      </Setter>
      <Setter Property="RenderTransformOrigin" Value=".5,.5"/>
    </Trigger>
  </ControlTemplate.Triggers>
</ControlTemplate>
```

Content Controls

Create a ControlTemplate for a button which uses two rectangles and respects any content from the templated parent?

```
<UserControl.Resources>
  <Style TargetType="Button">
    <Setter Property="Template">
      <Setter.Value>
        <ControlTemplate TargetType="Button">
          <Grid>
            <Rectangle Width="120" Height="120" Fill="Blue"/>
            <Rectangle Width="100" Height="100" Fill="LightBlue"/>
            <ContentPresenter HorizontalAlignment="Center"
              VerticalAlignment="Center"/>
          </Grid>
        </ControlTemplate>
      </Setter.Value>
    </Setter>
  </Style>
</UserControl.Resources>

<Button>
  <Rectangle Width="40" Height="40" Fill="Aquamarine"/>
</Button>
```

How does this code work when the ContentPresenter has no content set?


```
<UserControl.Resources>
  <Style TargetType="Button">
    <Setter Property="Template">
      <Setter.Value>
        <ControlTemplate TargetType="Button">
          <Grid>
            <Rectangle Width="120" Height="120" Fill="Blue"/>
            <Rectangle Width="100" Height="100" Fill="LightBlue"/>
            <ContentPresenter HorizontalAlignment="Center"
              VerticalAlignment="Center"/>
          </Grid>
        </ControlTemplate>
      </Setter.Value>
    </Setter>
  </Style>
</UserControl.Resources>
```

```

        </ControlTemplate>
    </Setter.Value>
</Setter>
</Style>
</UserControl.Resources>

```

ContentPresenter by default binds its Content, ContentPresenter and ContentPresenter properties to the Templated Parent




What are the rules of the WPF Content Model?

4. *If the content is a UIElement then render it*
5. *If the content is a string, render it in a TextBlock*
6. *If the content is a .NET type with an associated data template use that to render it*
7. *Otherwise render the .NET objects class name in a TextBlock*

Data Template

Write code to do the following



```
<Window.Resources>
    <DataTemplate DataType="{x:Type local:Person}">
        <StackPanel>
            <TextBlock Text="{Binding FirstName}"/>
            <TextBlock Text="{Binding LastName}"/>
        </StackPanel>
    </DataTemplate>
</Window.Resources>

<Window.Template>
    <ControlTemplate TargetType="Window">
        <Border Background="LightBlue">
            <ContentPresenter/>
        </Border>
    </ControlTemplate>
</Window.Template>


<local:Person FirstName="Kenneth" LastName="Wilson"/>
```

Content Controls Content Template

Compare and contrast Template and ContentTemplate?

*Template is a ControlTemplate and defines the rendering of the control as a whole.
ContentTemplate is a data template which renders just the content itself.*

Write code to do the following?




```

<Window.Resources>
    <DataTemplate DataType="{x:Type local:Person}">
        <StackPanel Background="LightBlue">
            <TextBlock Text="{Binding FirstName}"></TextBlock>
            <TextBlock Text="{Binding LastName}"></TextBlock>
        </StackPanel>
    </DataTemplate>
</Window.Resources>

<Window.Template>
    <ControlTemplate TargetType="Window">
        <Border Background="LightSkyBlue" Padding="{TemplateBinding Padding}">
            <ContentPresenter/>
        </Border>
    </ControlTemplate>
</Window.Template>

<Button>
    <Button.Template>
        <ControlTemplate TargetType="Button">
            <Border Background="DarkSeaGreen" Padding="10" Margin="10">
                <ContentPresenter/>
            </Border>
        </ControlTemplate>
    </Button.Template>
    <local:Person FirstName="K" LastName="Wilson"/>
</Button>

```