

Import Some Libraries

```
In [7]: import numpy as np

import pandas as pd
from pandas import Series, DataFrame
from pandas.plotting import scatter_matrix

import matplotlib.pyplot as plt
from pylab import rcParams

import seaborn as sb
```

```
In [8]: %matplotlib inline
rcParams['figure.figsize'] = 5,4
sb.set_style('whitegrid')
```


Read file csv from local computer

```
In [9]: address = 'C:/Users/muham/mtcars.csv'
cars = pd.read_csv(address)
cars.columns = ['car_names', 'mpg', 'cyl', 'disp', 'hp', 'drat', 'wt', 'qsec',
'vs', 'am', 'gear', 'carb']
```

**Using Histogram. With Pandas, we can use (kind='hist').
But with Seaborn, we can use (distplot)**


```
In [32]: cars.index = cars.car_names  
mpg = cars['mpg']  
mpg.plot(kind='hist')
```

Out[32]: <matplotlib.axes._subplots.AxesSubplot at 0x14245d70>



```
In [11]: sb.distplot(mpg)
```


Out[11]: <matplotlib.axes._subplots.AxesSubplot at 0x50d5030>



For Scatter Plot, we can use Pandas with command (kind='scatter'). And for Seaborn, we can use command (regplot) but remember parameters data, and scatter = True


```
In [12]: cars.plot(kind = 'scatter', x='hp', y='mpg', c=['darkgrey'], s=100)
```

```
Out[12]: <matplotlib.axes._subplots.AxesSubplot at 0x512df70>
```



```
In [16]: sb.regplot(data=cars, x='hp', y='mpg', scatter=True)
```


```
Out[16]: <matplotlib.axes._subplots.AxesSubplot at 0x51cc0f0>
```



We can use Seaborn's feature, which is pairplot for data visualization of file or csv

```
In [17]: sb.pairplot(cars)
```

```
Out[17]: <seaborn.axisgrid.PairGrid at 0x51a2730>
```



For Boxplot, we can use .boxplot function by matplotlib

```
In [24]: cars.boxplot(column='mpg', by='cyl')  
cars.boxplot(column='wp', by='am')
```

Out[24]: <matplotlib.axes._subplots.AxesSubplot at 0x14260cd0>

