Experiment No. 9

<u>Aim</u>: Write a program in C demonstrate the concept of page replacement policies for handling page faults eg: FIFO, LRU.


Theory:

FIFO(First In First Out):

- The simplest page-replacement algorithm and work on the basis of first in first out (FIFO). It throws out the pages in the order in which they were brought in.
- The time is associated with each page when it was brought into main memory.
- This algorithm always chooses oldest page for replacement.
- Since replacement is FIFO, a queue can be maintained to hold all the pages in main memory.
- This algorithm doesn't care about which pages are accessed frequently and which are not. However, it is used in windows 2000.

LRU(Least Recently Used):

- The time of page's last use is associated with each page.
- When a page must be replaced, LRU chooses that page that was used farthest back in the past.
- LRU is a good approximation to the optimal algorithm.
- This algorithm looks backward in time while optimal replacement algorithm looks forward in time.
- This policy suggests that replace a page whose last usage is farthest from current time.
- This algorithm can be implemented with some hardware support and is considered to be a good solution for page replacement.



• This algorithm does not suffer through Belady's anomaly.

FIFO Algorithm:

Let capacity be the number of pages that memory can hold. Let set be the current set of pages in memory.

- Start traversing the pages.
 - If set holds less pages than capacity.
 - a) Insert page into the set one by one until the size of set reaches capacity or all page requests are processed.
 - b) Simultaneously maintain the pages in the queue to perform FIFO.
 - c) Increment page fault
 - ii) Else

If current page is present in set, do nothing.

Else

- a) Remove the first page from the queue as it was the first to be entered in the memory
- b) Replace the first page in the queue with the current page in the string.
- c) Store current page in the queue.
- d) Increment page faults.
- 2. Return page faults.

LRU Algorithm:

Let capacity be the number of pages that memory can hold. Let set be the current set of pages in memory.

- Start traversing the pages.
 - If set holds less pages than capacity.
 - a) Insert page into the set one by one until the size of set reaches capacity or all page requests are processed.
 - b) Simultaneously maintain the recent occurred index of each page in a map called indexes.
 - c) Increment page fault
 - ii) Else

If current page is present in set, do nothing.

Shree Rahul Education Society's (Regd.)

SHREE L. R. TIWARI COLLEGE OF ENGINEERING

(Approved by AICTE & DTE, Maharashtra State & Affiliated to University of Mumbai)
NAAC Accredited, NBA Accredited Program, ISO 9001:2015 Certified | DTE Code No.: 3423
Minority Status (Hindi Linguistic)

Else



SHREE L. R. TIWARI COLLEGE OF ENGINEERING

(Approved by AICTE & DTE, Maharashtra State & Affiliated to University of Mumbai)
NAAC Accredited, NBA Accredited Program, ISO 9001:2015 Certified | DTE Code No.: 3423
Minority Status (Hindi Linguistic)

- a) Find the page in the set that was least recently used. We find it using index array. We basically need to replace the page with minimum index.
- b) Replace the found page with current page.
- c) Increment page faults.
- d) Update index of current page.
- 2. Return page faults

Program:

FIFO:

```
#include<stdio.h>
int main()
int reference_string[10], page_faults = 0, m, n, s, pages, frames;
 printf("\nEnter Total Number of Pages:\t");
scanf("%d", &pages);
printf("\nEnter values of Reference String:\n");
 for(m = 0; m < pages; m++)
 scanf("%d", &reference_string[m]);
 printf("\nEnter Total Number of Frames:\t");
 scanf("%d", &frames);
 int temp[frames];
for(m = 0; m < frames; m++)</pre>
 temp[m] = -1;
 for(m = 0; m < pages; m++)
 for(n = 0; n < frames; n++)
 if(reference_string[m] == temp[n]) {
 S++;
 page_faults--;
 page_faults++;
 if((page_faults <= frames) && (s == 0))
 temp[m] = reference_string[m];
 else if(s == 0)
 temp[(page_faults - 1) % frames] = reference_string[m];
 printf("\n");
 for(n = 0; n < frames; n++)
```

Shree Rahul Education Society's (Regd.)



}

SHREE L. R. TIWARI COLLEGE OF ENGINEERING

(Approved by AICTE & DTE, Maharashtra State & Affiliated to University of Mumbai)
NAAC Accredited, NBA Accredited Program, ISO 9001:2015 Certified | DTE Code No.: 3423
Minority Status (Hindi Linguistic)

```
printf("%d\t", temp[n]);
 printf("\nTotal Page Faults:\t%d\n",
page_faults); return 0;
LRU:
#include<stdio.h>
int findLRU(int time[], int n){
int i, minimum = time[0], pos =
0; for(i = 1; i < n; ++i){
if(time[i] < minimum){
minimum =
time[i]; pos = i;
return pos;
int main()
int no_of_frames, no_of_pages, frames[10], pages[30], counter = 0, time[10], flag1, flag2,
i, j, pos, faults = 0;
printf("Enter number of frames: ");
scanf("%d", &no_of_frames);
printf("Enter number of pages: ");
scanf("%d", &no_of_pages);
printf("Enter reference string: ");
for(i = 0; i < no_of_pages; ++i){
scanf("%d", &pages[i]);
for(i = 0; i < no_of_frames; ++i){
frames[i] = -1;
for(i = 0; i < no_of_pages;</pre>
++i){ flag1 = flag2 = 0;
for(j = 0; j < no_of_frames; ++j){}
if(frames[j] == pages[i]){
counter++;
time[j]
counter; flag1 =
flag2
break;}
if(flag1 == 0){
for(j = 0; j < no_of_frames; ++j){}
if(frames[j] == -1){}
counter++;
faults++;
frames[j] = pages[i];
time[j] = counter;
flag2 = 1;
break;
}
```

Shree Rahul Education Society's (Regd.)

SHREE L. R. TIWARI COLLEGE OF ENGINEERING

(Approved by AICTE & DTE, Maharashtra State & Affiliated to University of Mumbai)
NAAC Accredited, NBA Accredited Program, ISO 9001:2015 Certified | DTE Code No.: 3423
Minority Status (Hindi Linguistic)

```
if(flag2 == 0){
pos = findLRU(time, no_of_frames);
counter++;
faults++;
frames[pos] =
pages[i]; time[pos] =
counter;
}
printf("\n");
for(j = 0; j < no_of_frames; ++j){
printf("%d\t", frames[j]);}
}
printf("\n\nTotal Page Faults = %d", faults);
printf("\n");
return 0;
}</pre>
```

Output:

FIFO:

```
nachiketa@nachiketa-VirtualBox:~/Desktop/OSpracs/Prac 9 Q = - □  

nachiketa@nachiketa-VirtualBox:~/Desktop/OSpracs/Prac 9$ gcc fifo.c -o fifo nachiketa@nachiketa-VirtualBox:~/Desktop/OSpracs/Prac 9$ ./fifo

Enter Total Number of Pages: 8

Enter values of Reference String:
2
3
5
7
9
5
1
4
Enter Total Number of Frames: 3

2    -1    -1
2    3    -1
2    3    5
7    9    5
7    9    5
7    9    5
7    9    5
7    9    5
7    9    5
7    9    5
7    9    5
7    9    5
7    9    1
4    9    1
Total Page Faults: 7
nachiketa@nachiketa-VirtualBox:~/Desktop/OSpracs/Prac 9$
```

LRU:

(Approved by AICTE & DTE, Maharashtra State & Affiliated to University of Mumbai)
NAAC Accredited, NBA Accredited Program, ISO 9001:2015 Certified | DTE Code No.: 3423
Minority Status (Hindi Linguistic)

Outcome:

Implemented various Page Replacement Algorithm and evaluated their performance.