



**CFF® ACRYLIC FIBER
TYPE V125-1
MATERIAL CERTIFICATION**

LOT: 70156

DATE: July 24, 2020

GENERAL DESCRIPTION

Chemical Composition: More than 85% Acrylonitrile

Specific Gravity 1.17 +/- 0.05

SPECIFIC PROPERTIES

PULP PROPERTY	TEST METHOD	PROPERTY RANGE	ACTUAL VALUES
Canadian Standard Freeness*	TAPPI T-227	350 - 450 ml	384
Screen Fineness*	TAPPI T-233	10 - 50% (28 mesh)	38.7
Moisture Content	TAPPI T-412	13 - 17%	16.5
Fiber Length, Typical	SR-TFF-004	2.5 – 5.5 mm	3.8
Fiber Length, Maximum	SR-TFF-004	3.5 – 6.5 mm	5.0
Fluff Volume	SR-TFF-005	340 ml minimum	377
Appearance	Visual	Fine White Pulp	OK

* Measured on wet pulp.

J.R. Hagerott

HANDLING / STORAGE

Product shipped in bags with a net weight of 10 +/- 0.2 pounds.

Typical moisture regain is 0 – 2%,

Store in a dry location at ambient conditions.

Shelf life one year.

DISCLAIMER OF WARRANTIES

Sterling makes no warranty of any kind, express or implied, whether of fitness or against infringement or otherwise, except that the materials sold hereunder shall be of merchantable quality and buyer assumes all risk whatsoever as to the result of the use of the materials purchased, whether used singly or in combination with other substances.

Form TF-041

Revised 8/20/2010