

Description

Solutions

Submissions

```
1 class MyStack {
2     private:
3         queue<int> q;
4
5     public:
6         MyStack() {}
7
8         void push(int x) {
9             q.push(x);
10            for (int i = 1; i < q.size();
11                i++) {
12                q.push(q.front());
13                q.pop();
14            }
15
16            int pop() {
17                int res = q.front();
```

Ln 16, Col 16 | Saved

Run

Submit

Testcase

```
1 ["MyStack","push","push","top","|
2 [[],[1],[2],[],[],[[[]]]]
```

Description

Solutions

Submissions

```
18         q.pop();
19         return res;
20     }
21
22     int top() {
23         return q.front();
24     }
25
26     bool empty() {
27         return q.empty();
28     }
29 }
30 };
31
```

```
32 /**
33  * Your MyStack object will be
    instantiated and called as such:
34  * MyStack* obj = new MyStack();
    .. ..
```

Ln 16, Col 16 | Saved

Run

Submit

Testcase

```
1 ["MyStack","push","push","top","|
2 [[],[1],[2],[],[],[ ]]
```

Description

Solutions

Submissions

2 `[[], [1], [2], [], [], []]`

1/8 testcases | Line 1 | Case 1

Result

**Accepted** 3 ms☒ Case 1

Input

`["MyStack", "push", "push", "top", "pop", "empty"]``[[], [1], [2], [], [], []]`

Output

`[null, null, null, 2, 2, false]`

Expected



6.9K



107

